

USE THE BRAINS YOUR IBM WASN'T BORN WITH.

Right at your fingertips in CompuServe's IBM® Forums.

In the **IBM New Users Forum** you'll swap ideas with other new PC users, learn to use Forum features, and pose even basic questions to PC experts.

Our **IBM Junior Forum** gives PCjr® users a reliable source for tips on software, hardware, telecommunications, games and other interests.

In the **IBM Software Forum** you'll trade tips with other IBM PC and AT users on utility software, word processing, DOS and other operating systems.

Visit the **IBM Communications Forum** for advice on the features and compatibility of communications software and hardware, PC Bulletin Boards, micromainframe interfaces and more.

The **IBM Hardware Forum** addresses hardware topics of all types, plus product updates and announcements.

Easy access to free software.

- Download first-rate, non-commercial, usersupported software and utility programs.
- Take advantage of CompuServe's inexpensive weeknight and weekend rates (when Forums are most active, and standard online charges are just 10¢ a minute).
- Go online in most major metropolitan areas with a local phone call.
- And receive a \$25.00 Introductory Usage Credit with purchase of your CompuServe Subscription Kit.

Information you simply can't find anywhere else.

Use the Forum *Message Board* to send and receive electronic messages, and pose specific questions to other IBM and compatible owners.

Join ongoing, real-time discussions in a Forum *Conference*.

Search our unparalleled Forum *Data Libraries* for free software, user tips, transcripts of online conferences and more.

Enjoy other useful services like:

• Popular Computer Magazines—electronic

editions, for your reading pleasure. Including Dr. Dobb's Journal and Computer Language.

• Other CompuServe Forums—supporting LOTUS® products like Symphony™ and 1-2-3.™ Borland International,® Ashton-Tate,® Digital Research,® MicroPro,® Microsoft® and other software. Also Pascal, Basic, C, Forth, Assembly and other programming languages.

All you need is your IBM or IBMcompatible computer and a modem ... or almost any other computer.

To buy your Subscription Kit, see your nearest computer dealer. Suggested retail price is \$39.95. To receive our free brochure, or to order direct, call 800-848-8199 (in Ohio, call 614-457-0802). If you're already a CompuServe subscriber, type GO IBMNET (the IBM Users Network) at any! prompt to see what you've been missing.

CompuServe

Information Services, P.O. Box 20212 5000 Arlington Centre Blvd., Columbus, Ohio 43220

800-848-8199

In Ohio, Call 614-457-0802 An H&R Block Company

Circle no. 237 on reader service card.



Those who insist on C compiler performance are very big on Mark Williams.

And the compiler is just part of our total C Programming System.

These and other powerful utilities now *included* in the C **Programming System:**

· make: compiles only what's necessary from multiple modules, a powerful pro-

- gramming discipline diff: identifies differences between two files
- m4: macroprocessor expression editing and substitution
- egrep: extended pattern search
- · MicroEMACS: full screen editor with source

COMPILER FEATURES

- · Runs under MS-DOS
- Full Kernighan & Ritchie C with recent extensions including void and enum
- Register variables for fast, compact code
- Full UNIX™ compatibility and complete libraries

New!

C for the

Atari ST.

Call for

features

- 8087 Support
- · One-step compiling
- · English error messages
- · ROMable code
- Large and small memory models
- MS-DOS linker compatibility
- · Linker, assembler, archiver
- · Extensive third party library support

csd C SOURCE DEBUGGER

- · Debugs at C source level without assembly
- Separate evaluation, source, program and history windows
- Can execute any C expression
- Capabilities of a C interpreter, but runs in real time
- Set trace points on any statement or variable

Mark Williams' C compiler has earned a place in some very big companies for some very good reasons: it proves the benchmarks right with the speed, code density, consistent performance and expert support required in professional development environments.

But a total development tool shouldn't stop with compiling. Or go on and on with extras that add up and up.

Only Mark Williams' C Programming Systems includes the csd C Source Debugger with true source level debugging to speed your programming job.

And only Mark Williams' new 3.0 version includes utilities like "make" to make quick work of even the largest projects.

From source code to final product, only one takes you all the way: Mark Williams' C Programming System. All for only \$495. Ask about our 60-day money back guarantee when you call

1-800-692-1700 to order today.*

You'll be big on the total C Programming system from Mark Williams, too.

*In Illinois call 312-472-6659.



1430 West Wrightwood Chicago, Illinois 60614

Instant Replay

NEW

Synthetic Intelligence Patent Pending

Generates:

DEMOS, TUTORIALS, PROTOTYPES, PRESENTATIONS, TIMED KEYBOARD MACROS, AND MENU SYSTEMS

Instant Replay memorizes how you ran your program and Instantly generates a Demo Replay. Keystrokes and pause times, inserted prompts, pop-ups and prototypes are all memorized.

Screen Painter for creating 100% user designable pop-ups and Menu Windows. "Excellent, intuitive, easiest-to-use screen generator reviewed" PC Magazine.

Run-Time Screen Scanner and File Scanner for creating Menu systems and presentations.

Screen Grabber so you can edit and include any screen.

Text Editor - fast, full function, with pull-down menus that can be tailored. Memorize it and distribute it as a Demo!

200 Page Manual, 4 diskettes, 60 Day money back guarantee. (Not Copy Protected)

Call or Write. We accept Visa, Amex, Master Card, COD, PO. Dealer Inquiries Welcome.

Instant Replay(tm) \$ 89.95 Demo Diskette Dealer Poster \$ 3.00

ostradamus

Nostradamus Inc. / 5320 South 900 East, Suite 110 SLC, Utah 84117 / Order by phone (801) 261-0769

For IBM PC / XT / AT and True Compatibles

Ask about Programming Libraries

Circle no. 251 on reader service card.

Dr. Dobb's Journal of

FOR THE PROFESSIONAL PROGRAMMER

ARTICLES

Algorithmsfor	•
smooth curves	

ALGORITHMS: Curve Fitting with Cubic Splines by Ian E. Ashdown

Ian presents a program that can connect a set of points with a smooth curve or interpolate a surface between points plotted in three dimensions.

ALGORITHMS: A First-Order Sorting Algorithm by Robert A. McIvor

The radix sort sometimes can perform electronic sorts faster than the exchange-based algorithms usually employed on computers.

Is it really PROLOG? >

Turbo boards

for the IBM PC

Radix sort

REVIEWS

LANGUAGES: Turbo Prolog: The Language by Michael Swaine

Our editor-in-chief examines some of the claims being made. Is it really faster? Is it full PROLOG? Is it a useful tool?

HARDWARE: High-Speed Thrills

by Mike Elkins and Steve King

Installing an accelerator board is a relatively inexpensive way to give an IBM PC, PC/XT, or compatible the throughput of a PC/AT. We benchmarked six of these boards.



About the Cover

36

46

The architectural illustration for this cover was done by Robert H. Frank. The photograph was done by Michael Carr/Pacific Horizons

Directory trees

Memory test

with the 68000 >

C CHEST: Directory Traversal, Trailing 'Zs, and 14 **Horrifying Experiences**

COLUMNS

by Allen Holub

A program that performs a number of functions with directory trees, a utility to let Microsoft's Macro Assembler read 'Z terminated files, and a tale of woe

16-BIT SOFTWARE TOOLBOX: MS-DOS Book, DOS 108 File Handles, and More

by Ray Duncan

by Michael Swaine

Other topics addressed by Ray and his readers include the VDISK-related crashes mentioned in April and problems with resident programs doing file I/O.

THE RIGHT TO ASSEMBLE: The Worm Memory Test 114 by Jan W. Steinman

A self-overlaying test to help diagnose memory errors

This Issue

Many algorithms now used on computers have their roots in mechanical processes. This month, we present two such algorithms; one that replaces the draftsman's spline and one that sorts in an old fashioned (but sometimes faster) way. Michael Swaine offers some thoughts on Borland's latest product, and we present a review of several PC speed boosters. Allen Holub and Ray Duncan provide tasty tidbits. and Jan Steinman brings us a very unusual memory test.

A growing sanity

FORUM		PROGRAMMER': SERVICES	S
by Michael Swaine RUNNING LIGHT by Nick Turner ARCHIVES LETTERS by you SWAINE'S FLAMES: Tiny Star Wars?	6 8 8 10 128	DR. DOBB'S CATALOG: DDJ products—all in one place OF INTEREST: New products of interest ADVERTISER INDEX: Where to find those ads	73 118 126

Next Issue

In October, we'll take a close look at Intel's 80386 chip. What does it really offer, and how do you upgrade from the 80286? We'll also demonstrate some interesting code for the NS320xx chip set.

YOUR
COMPUTER LANGUAGE
IS QUIETLY
BREEDING REAL BATS
IN YOUR
BELFRY.

LANGUAGES THAT ARE CAUSING THE BIGGEST PROGRAMMING BACKLOG IN HISTORY ARE ALSO EATING NICE BIG HOLES IN OUR POCKETS.

Whether it's BASIC, COBOL, Pascal, "C", or a data base manager,

you're being held back.

Held back because the language has frustrating limitations, and the programming environment isn't intuitive enough to keep track of what you're working on.

In the real world, there's pressure to do more impressive work, in less time, and for more clients.

We've been given some incredibly powerful hardware in recent times, but the languages aren't a whole lot

better than they were 20 years ago. So, whatever language you have chosen, by now you feel it's out to get you — because it is.

Sure, no language is perfect, but you have to wonder, "Am I getting

all I deserve?"

And, like money, you'll never

have enough. Pretty dismal, huh?

We thought so, too. So we did something about it. We call it CLARION: You'll call it "incredible."

Distributed on 7 diskettes, CLARION consists of over 200,000 lines of code, taking 3+ years to hone to "world-class" performance. With CLARION you can

write, compile, run and debug complex applications in a New York afternoon.

Even if you're in Savannah. It gives you the power and speed to create screens, windows and reports of such richness and clarity you would never attempt them with any other language. Because *you* would have to

write the code.

With CLARION you simply design the screens using our SCREENER utility and then CLARION writes the source code AND compiles it for you in seconds.

Likewise, you can use REPORTER to create reports.

Remember, only CLARION can recompile and display a screen or report layout for modification.

And with no time wasted. All the power and facilities you need to write great programs, faster than you ever dreamed of.

Programs that are easy to use. Programs that are a pleasure to

And to you that means true satisfaction.

You've coveted those nifty pop-up help windows some major applications feature. But you can't afford the time and energy it takes to write them into your programs.

That's the way it used to be. So we fixed that, too.

CLARION'S HELPER is an interactive utility that let's you design the most effective pop-up help screens that you can imagine. And they're "context sensitive." meaning you can have help for every field in your application.

Unlike the other micro languages, CLARION provides declarations, procedures, and functions to process

dates, strings, screens, reports, indexed files, DOS files and memory tables.

CLARION

Imagine making source program changes with the CLARION EDI-TOR. A single keystroke terminates the EDITOR, loads the COM-PILER, compiles the program, loads the PROCESSOR and executes the program. It's that easy!

Our data management capabilities are phenomenal. CLARION files permit any number of composite keys which are updated dynami-

cally.

A file may have as many keys as it needs. Each key may be com-posed of any fields in any order. And key files are updated when-ever the value of the key changes. Like SCREENER and RE-

PORTER, CLARION'S FILER utility also has a piece of the CLARION COMPILER. To create a new file, you name the Source Module. Then you name the Statement Label of a file structure within it.

FILER will also automatically rebuild existing files to match a changed file structure. It creates a new record for every existing record, copying the existing fields and

initializing new ones.

Sounds pretty complicated, huh?
Not with CLARION's documentation and on-line help screens. If you are currently competent in BASIC, Pascal or "C" you can be writing CLARION applications in a day. In two days you won't believe the eloquence of your CLARION programs.
Okay, now for the best part of all. You can say it in CLARION

for \$295.00-plus shipping and handling. All you need is an IBM® PC, XT,

AT or true compatible, with 320 KB of memory, a hard disk drive, and a parallel port. And we'll allow a full 30 day evaluation period. If you're not satisfied with

CLARION, simply return it in its original condition for a full refund.

If you're not quite ready to take advantage of this no-risk opportunity, ask for our detailed 16 page color brochure. It vividly illustrates the elegance of CLARION. Consider it a preview of programming in the fast lane.

Either way, the 800 call's a freebie.

Dept. A2ST/4

SAY IT IN







BARRINGTON SYSTEMS, INC. 150 EAST SAMPLE ROAD POMPANO BEACH, FLORIDA 33064 305/785-4555

EDITORIAL

ometimes Next Big Thing is a neglected old thing.

When I was a graduate student I took all the AI classes and seminars I could. In a class taught by Gene Freuder, who had just arrived from MIT where he had studied under Patrick Henry

Winston, I wrote an expert system for draw poker. At that time, expert systems interested me, but not as much as the challenge, posed by another of my professors, Doug Hofstadter, of writing a program that could generate analogies, a problem in the area of machine learning. My expert system worked, after a fashion, and I never got anywhere with the machine learning program. Looking back over the past few years, it may seem that the same could be said for the entire field of AI: expert systems work; machine learning never got started.

I once believed that, but now I think I was wrong. Research in machine learning has certainly taken a back seat to expert systems work since my graduate school days. The results are evident: By focusing on narrow problem areas and domain-specific knowledge, workers in expert systems have created some very powerful practical tools and turned a technique into an industry. The Business section of the July 7, 1986, San Jose, California, San Jose Mercury News, amid grumblings about the industrywide slump in software, computers, and electronics, noted that one expert systems company, Teknowledge, was doing spectacularly well.

Machine learning never makes it into the Mercury News; nevertheless, research in machine learning has continued quietly over the yearsand not without results. There are, for example, programs whose performance improves with experience



and programs that develop new problemsolving heuristics. There are programs that produce interesting analogies.

I hope that machine learning is about to capture the imaginations of programmers and venture capitalists. The potential

benefits from work in machine learning are, I believe, far greater than the benefits of expert systems work. Understanding natural language, for example, requires the ability to learn new concepts rather than requiring a body of expert knowledge. And by the very nature of the learning process, it seems that any learning program would have to be general in application, suggesting that we would only need one. Given one, we could clone it.

Also by the nature of the learning process, the performance of learning programs will probably be unreliable, and this may force us to start looking at programs in a different way. Induction and generalization seem incompatible with the provability and reliability necessary for Star Wars-type projects. Making mistakes may well be an inextricable component of learning. We may one day find ourselves praising programs for their efforts as much as for their results.

The review of PC speed-up boards in this issue was completed before we knew of this manufacturer of a comparable board:

STD (Seattle Telecom & Data Inc.) 2637 151st Pl. NE Redmond, WA 98052 (206) 883-8440

Michael Swams

Michael Swaine editor-in-chief

Dr. Dobb's Journal of

Editorial

Editor-in-Chief Michael Swaine Editor Nick Turner Managing Editor Vince Leone

Assistant Editor Sara Noah Ruddy Technical Editor Allen Holub Contributing Editors Ray Duncan

Michael Ham Allen Holub

Namir Shammas Copy Editor Rhoda Simmons Electronic Editor Levi Thomas

Production Production Manager Bob Wynne Art Director Michael Hollister Assoc. Art Director Alida Hinton Typesetter Jean Aring

Cover Artist Robert H. Frank Newsstand Sales Mgr. Stephanie Barber

Circulation Director Maureen Kaminski Book Marketing Mgr. Jane Sharninghouse Circulation Assistant Kathleen Shay Administration

Finance Manager Treva Rafalski Business Manager Betty Trickett Accounts Payable Supv. Mayda Lopez-Quintana Accts. Pay. Coordinator Kathy Robinson Accounts Payable Asst. Karen Green

Accounts Receivable Mgr. Laura Di Lazzaro Accts. Receivable Asst. Denise Giannini Adm. Coordinator Kobi Morgan **Advertising Director** Robert Horton (415) 366-3600

Account Managers Michele Beaty (317) 875-8093 Lisa Boudreau (415) 366-3600 Gary George (404) 897-1923 Michael Wiener (415) 366-3600 Cynthia Zuck (718) 499-9333

Promotions/Srvcs.Mgr. Anna Kittleson Advertising Coordinator Michelle A. Davié

M&T Publishing, Inc.

Chairman of the Board Otmar Weber Director C.F. von Quadt President and Publisher Laird Foshay

Dr. Dobb's Journal of Software Tools (USPS 307690) is published monthly by M&T Publishing, Inc., 501 Galveston Dr., Redwood City, CA 94063; (415) 366-3600. Second-class postage paid at Redwood City and at additional entry points.

Article Submissions: Send manuscripts and disk (with article and listings) to the Assistant Editor.

Address Correction Requested: Postmaster: Send Form 3579 to Dr. Dobb's Journal, P.O. Box 27809, San Diego, CA 92128 ISSN 0888-3076

Customer Service: For subscription problems call: outside CA (800) 321-3333; within CA (619) 485-9623 or 566-6947. For order problems call (415) 366-3600.

Subscription Rates: \$29.97 per year, U.S. Foreign rates: \$63.97, air; \$51.97, surface. Foreign subscriptions must be prepaid in U.S. dollars, drawn on a U.S. bank. For foreign subscriptions, TELEX: 752-351.

Foreign Newsstand Distributor: Worldwide Media Service, Inc., 386 Park Ave. South, New York, NY 10016; (212) 686-1520 TELEX: 620430 (WUI).

Entire contents copyright \$ 1986 by M&T (ABC Publishing, Inc.; unless otherwise noted on specific articles. All rights reserved.

People's Computer Company

Dr. Dobb's Journal of Software Tools is published by M&T Publishing, Inc. under license from People's Computer Company, 2682 Bishop Dr., Suite 107, San Ramon, CA 94583, a nonprofit corporation.



The C for Microcomputers

PC-DOS, MS-DOS, CP/M-86, Macintosh, Amiga, Apple II, CP/M-80, Radio Shack, Commodore, XENIX, ROM, and Cross Development systems

MS-DOS, PC-DOS, CP/M-86, XENIX, 8086/80x86 ROM

Manx Aztec C86

"A compiler that has many strengths ... quite valuable for serious work"

Computer Language review, February 1985

Great Code: Manx Aztec C86 generates fast executing compact code. The benchmark results below are from a study conducted by Manx. The Dhrystone benchmark (CACM 10/84 27:10 p1018) measures performance for a systems software instruction mix. The results are without register variables. With register variables, Manx, Microsoft, and Mark Williams run proportionately faster, Lattice and Computer Innovations show no improvement.

	Execution Time	Code Size	Compile/ Link Time
Dhrystone Benchmark			
Manx Aztec C86 3.3	34 secs	5,760	93 secs
Microsoft C 3.0	34 secs	7,146	119 secs
Optimized C86 2.20J	53 secs	11,009	172 secs
Mark Williams 2.0	56 secs	12,980	113 secs
Lattice 2.14	89 secs	20,404	117 secs

Great Features: Manx Aztec C86 is bundled with a powerful array of well documented productivity tools, library routines and features.

Optimized C compiler
AS86 Macro Assembler
80186/80286 Support
8087/80287 Sensing Lib
Extensive UNIX Library
Large Memory Model
Z (vi) Source Editor -c
ROM Support Package -c
Library Source Code -c
MAKE, DIFF, and GREP -c
One year of updates -c

Symbolic Debugger LN86 Overlay Linker Librarian Profiler DOS, Screen, & Graphics Lib Intel Object Option CP/M-86 Library -c INTEL HEX Utility -c Mixed memory models -c Source Debugger -c CP/M-86 Library -c

Manx offers two commercial development systems, Aztec C86-c and Aztec C86-d. Items marked -c are special features of the Aztec C86-c system.

Aztec C86-c Commercial System \$499
Aztec C86-d Developer's System \$299
Aztec C86-p Personal System \$199
Aztec C86-a Apprentice System \$49

All systems are upgradable by paying the difference in price plus \$10.

Third Party Software: There are a number of high quality support packages for Manx Aztec C86 for screen management, graphics, database management, and software development.

C-tree \$395 | Greenleaf \$185 |
PHACT \$250 | PC-lint \$98 |
HALO \$250 | Amber Windows \$59 |
WindScreen \$149 | FirsTime \$295 |
SunScreen \$99 | C Util Lib \$185 |
PANEL \$295 | Plink-86 \$395 |

MACINTOSH, AMIGA, XENIX, CP/M-68K, 68k ROM

Manx Aztec C68k

"Library handling is very flexible ... documentation is excellent ... the shell a pleasure to work in ... blows away the competition for pure compile speed ... an excellent effort."

Computer Language review, April 1985

Aztec C68k is the most widely used commercial C compiler for the Macintosh. Its quality, performance, and completeness place Manx Aztec C68k in a position beyond comparison. It is available in several upgradable versions.

Optimized C Macro Assembler Overlay Linker Resource Compiler Debuggers Librarian Source Editor MacRam Disk -c Library Source -c Creates Clickable Applications Mouse Enhanced SHELL Easy Access to Mac Toolbox UNIX Library Functions Terminal Emulator (Source) Clear Detailed Documentation C-Stuff Library UniTools (vi,make,diff,grep) -c

One Year of Updates -c

Items marked -c are available only in the Manx Aztec C86-c system. Other features are in both the Aztec C86-d and Aztec C86-c systems.

Aztec C68k-c Commercial System	\$499
Aztec C68d-d Developer's System	\$299
Aztec C68k-p Personal System	\$199
C-tree database (source)	\$399
AMIGA, CP/M-68k, 68k LINTY	0011

Apple II, Commodore, 65xx, 65C02 ROM

Manx Aztec C65

"The AZTEC C system is one of the finest software packages I have seen"

NIBBLE review, July 1984

A vast amount of business, consumer, and educational software is implemented in Manx Aztec C65. The quality and comprehensiveness of this system is competitive with 16 bit C systems. The system includes a full optimized C compiler, 6502 assembler, linkage editor, UNIX library, screen and graphics libraries, shell, and much more. The Apple II version runs under DOS 3.3, and ProDOS, Cross versions are available.

The Aztec C65-c/128 Commodore system runs under the C128 CP/M environment and generates programs for the C64, C128, and CP/M environments. Call for prices and availability of Apprentice, Personal and Developer versions for the Commodore 64 and 128 machines.

Aztec C65-c ProDOS & DOS 3.3 \$399
Aztec C65-d Apple DOS 3.3 \$199
Aztec C65-p Apple Personal system \$99
Aztec C65-a for learning C \$49
Aztec C65-c/128 C64, C128, CP/M \$399

Distribution of Manx Aztec C

In the USA, Manx Software Systems is the sole and exclusive distributor of Aztec C. Any telephone or mail order sales other than through Manx are unauthorized.

Manx Cross Development Systems

Cross developed programs are edited, compiled, assembled, and linked on one machine (the HOST) and transferred to another machine (the TARGET) for execution. This method is useful where the target machine is slower or more limited than the HOST, Manx cross compilers are used heavily to develop software for business, consumer, scientific, industrial, research, and educational applications.

HOSTS: VAX UNIX (\$3000), PDP-11 UNIX (\$2000), MS-DOS (\$750), CP/M (\$750), MACINTOSH (\$750), CP/M-68k (\$750), XENIX (\$750).

TARGETS: MS-DOS, CP/M-86, Macintosh, CP/M-68k, CP/M-80, TRS-80 3 & 4, Apple II, Commodore C64, 8086/80x86 ROM, 68xxx ROM, 8080/8085/Z80 ROM, 65xx ROM.

The first TARGET is included in the price of the HOST system. Additional TARGETS are \$300 to \$500 (non VAX) or \$1000 (VAX).

Call Manx for information on cross development to the 68000, 65816, Amiga, Cl28, CP/M-68K, VRTX, and others.

CP/M, Radio Shack, 8080/8085/Z80 ROM

Manx Aztec CII

"Tve had a lot of experience with different C compilers, but the Aztec C80 Compiler and Professional Development System is the best I've seen."

80-Micro, December, 1984, John B. Harrell III

Aztec C II-c (CP/M & ROM)	\$349
Aztec C II-d (CP/M)	\$199
C-tree database (source)	\$399
Aztec C80-c (TRS-80 3 & 4)	\$299
Aztec C80-d (TRS-80 3 & 4)	\$199

How To Become an Aztec C User

To become an Aztec C user call 1-800-221-0440 or call 1-800-832-9273 (800-TEC WARE). In NJ or outside the USA call 201-530-7997. Orders can also be telexed to 4995812.

Payment can be by check, COD, American Express, VISA, Master Card, or Net 30 to qualified customers.

Orders can also be mailed to Manx Software Systems, Box 55, Shrewsbury, NJ 07701.

How To Get More Information

To get more information on Manx Aztec C and related products, call 1-800-221-0440, or 201-530-7997, or write to Manx Software Systems.

30 Day Guarantee

Any Manx Aztec C development system can be returned within 30 days for a refund if it fails to meet your needs. The only restrictions are that the original purchase must be directly from Manx, shipped within the USA, and the package must be in resalable condition. Returned items must be received by Manx within 30 days. A small restocking fee may be required.

Discounts

There are special discounts available to professors, students, and consultants. A discount is also available on a "trade in" basis for users of competing systems. Call for information.



To order or for information call:

800-221-0440

RUNNING LIGHT


A new sanity seems to be infecting a growing number of computer-related companies. Could it be that our industry is becoming customer driven? Here are some examples of this new and encouraging trend:

Copy protection, long a hotly debated issue between customers and software makers, is finally being abandoned as more and more customers spurn protected software. For many years it's been difficult to find major software packages that weren't bound up in all sorts of cryptic ways. Now, with only a few exceptions, every important program is available in an unprotected form. This has been a rapid process. Why didn't it happen sooner?

The industry seems to be concerned about creating a completely machine-independent standard for the new CD-ROM technology. Everyone seems hesitant to produce any real products until there is a standard that can be applied across *all* products. We applaud this. Why didn't this kind of cooperative effort go into floppy-disk formats?

Other standards seem to be emerging as well. For example, the Post-Script page-description language, developed by Adobe Systems for Apple's LaserWriter, is now supported by a new series of plug-compatible printers from Texas Instruments. This is a credit to both Apple and TI (and Adobe, of course). Other makers of page-output products have indicated their intentions to support PostScript.

Living Videotext recently made public the file-storage format for its ThinkTank series of idea-processor programs. The response from programmers was immediate and enthusiastic. We predict we'll soon see other products that are compatible



with ThinkTank.

Even venerable Apple Computer is finally going to produce a Macintosh with slots. What is this world coming to?

We think the industry is finally becoming respectable. Now that there are enough customers so that a small

percentage of the market share can mean a large change in dollar volume, the customer's feelings about a product are suddenly important. We encourage you to let your feelings be known. Now that companies are finally starting to respond in a big way, your voice can make a difference.

This month's hint for writers concerns communication—from us to you and back. First, we want to remind you of how important it is to include a phone number with every letter, manuscript, outline, or proposal that you send us. Often we save several weeks of correspondence by calling you directly and discussing your idea over the phone.

We have a set of form letters that we send out at various times during the article editing process. If you send us a manuscript, you will definitely get some sort of a reply within a few weeks. If your article is not rejected right away, it will be put into a file for consideration. It may spend as much as a month in there before it gets assigned or rejected. If you have sent a manuscript into *DDJ* and you haven't heard from us in a while, feel free to call me. I'll be happy to look it up and let you know what's happening.

nit Ju

Nick Turner editor

ARCHIVES

The Safe Bet

"Nineteen eighty-one will bring the advent of 16-bit microcomputer systems. [T]here will be a shift toward very large companies in the microcomputer market...."—Bill Gates, InfoWorld, January 19, 1981.

"Microsoft played a significant role as a consultant to IBM in the development of its hardware...."—Paul Freiberger, InfoWorld, October 5, 1981.

"People have been dazzled by the stuff that's gone on at Xerox PARC for years.... With good bit-mapped graphics and 16-bit machines on real production equipment, we can perform some of those same pieces of magic."—Bill Gates, InfoWorld, January 11, 1982.

"Insiders suggest that Apple had to go to Microsoft to get some of the [Lisa software] done. Why Microsoft? Apparently Microsoft has a couple of ex-Xerox PARC Smalltalk programmers."—John Dvorak, InfoWorld, January 31, 1983.

"There should also be some really usable portable computers using liquid-crystal displays of at least 8 lines by 40 characters."—Bill Gates, InfoWorld, January 10,

"Microsoft... developed all the software for the Model 100."—Scott Mace, InfoWorld. April 11, 1983.

"Most predictions [are] inside information in the guise of prognostication."—John Dvorak, InfoWorld, January 10, 1983.

Ten Years Ago in DDJ

"Hellman and Diffie hold that the [56-bit DES] key is not all that secure, that such a key could be broken in a day by anyone with enough money to build the trial-and-error machinery to search the 100 million billion keys... not too much for a government agency, say, the NSA or CIA."—DDJ, September 1976.

"Motorola is reliably rumored to be working on their 6809, which supposedly will give Zilog's Z80 some stiff competition. More details when we have 'em."—DDJ, September 1976.

"For non-Apple systems: source and object code supplied [for a 6502 disassembler] occupies pages 8 and 9. All code is on page 8, tables on page 9. These tables may be relocated at will...code may also be relocated. Be careful if you use pages 0 or 1. Page 1 is the subroutine return stack...." Steve Wozniak, DDJ, September, 1976.

"I wish to express a certain disgruntlement with some of the gargoyles that have been erected on the cathedral of LISP."

—John McCarthy, DDJ, September, 1976.

"I enclose my ... string immediate-output subroutine for 6502-based systems." —Chris Espinosa, DDJ, September, 1976.



DATALIGHT C DELIVERS

ANCE

DATALIGHT C \$60 ■ THE DEVELOPER'S KIT \$99

The DATALIGHT C Compiler is a performer through and through. From the UNIX System 5 language with the latest ANSI extensions (prototyping), to the top compile speed, with the understandable error interface, on to the tight/fast code - the Performer shines. Performance comes in two sizes: THE DATALIGHT C Compiler, and the DEVELOPER'S KIT.

DATALIGHT C provides you with a full range of features, like full 8087 and software floating point, a UNIX-style MAKE program, onestep compile/link, and UNIX-like tools in source form. You also get automatic .COM file generation, MS-DOS compatible object files, third-party library/debugger support, and much more.

The DEVELOPER'S KIT provides the extra features required by the serious programmer. The DEVEL-OPER'S KIT allows you to build programs as BIG as the memory in your PC. You can also tailor your applications to your special PC or ROM-based needs using the startup and library source provided.

And what do our users think? They love us! In fact, the ones who

own higher-priced compilers love us the most because they know what PERFORMANCE really is!

"This is a sharp compiler! . . . what is impressive is that DATALIGHT not only stole the compile time show completely, but had the fastest Fibonacci executable time and had excellent object file sizes to boot!" Chris Skelly

COMPUTER LANGUAGE

"I have and actively use Microsoft C version 3.0, Mark Williams C, and Lattice version 3.0, in addition to your compiler. Of all the compilers that I have used yours really stands out as the best package."

Matthew Brandt TANGENT TECHNOLOGIES

Of all the MS-DOS C compilers available, we have chosen DATA-LIGHT for all our development."

Keven Smith Drew Gileson TRAVELING SOFTWARE

So why wait? You can have the Performer, a 30-day money-back guarantee, and the call is on us. So order now!

DATALIGHT C (Ver 2.10)

- Full UNIX System 5 C Compiler with ANSI extensions.
- Fast/tight code.
- 8087 & software floating point.
- Full UNIX compatible library.
- MAKE program with macros, dependency checking, and MS-DOS internal commands.
- DLC one-step compile/link program.
- Tools in source (diff, cat, pr, wc, rm).
- Powerful utilities in source form.
- Compatible with MS-DOS linker.

DEVELOPER'S KIT (Ver 2.10)

- All features of DATALIGHT C!
- Third-party library support.
- Multiple memory model support
 - Small 64k code 64k data
 - Data
 - 64k code 1Meg data
 - Program lMegcode 64k data Large lMegcode lMeg data
- Complete SOURCE CODE for libraries.
- Complete SOURCE CODE for startup routine.
- ROMable code.

MS-DOS is a trademark of Microsoft. UNIX is a trademark of Bell Labs. Lattice C is a trademark of Lattice Inc.

KENMORE, WA 98028 (206) 367-1803 ORDER NOW! 30-DAY MONEY-BACK GUARANTEE. YES, I WANT THE PERFORMER!!! By phone call 1-800-628-2828 — Ext. 571 (Orders only) Technical Information (206) 367-1803 I want _____ copies of DATALIGHT C (\$60) I want _____ copies of the DEVELOPER'S KIT (\$99) Add \$5 for shipping in US/\$15 outside US. C.O.D. (add \$2.50) NAME ADDRESS CITY _ STATE ___ CARD# EXPIRATION DATE _ P.O. # (attach copy) Circle no. 203 on reader service card.

LETTERS



The Right to Optimize

Dear DDJ, Richard Campbell's March column on NS32016 square root calculations prompted me to implement his algorithm on my 68000 system and do some comparative measurements. My system is a 68000 board hooked to an Apple II computer running at an effective clock rate of approximately 8.1 MHz. (The nominal clock rate of 12.5 MHz is slowed down by one additional wait cycle on every bus

transfer and a software D-

RAM refresh scheme.)

Unfortunately, I do not have a C compiler for my board, so I had to resort to rewriting Mr. Campbell's program for what I have available, which is a UCSD p-code System adapted from Apple Pascal to the 68000. One of the limitations of this system is that it handles only 16-bit signed integers, so I had to use some routines of my own to support 32-bit integer arithmetic in order to stay compatible with Mr. Campbell's benchmarks, which used a loop from 0 to 60,000 to time the square root routines.

As the Pascal compiler produces p-code object programs, I wrote the square root routine in 68000 assembly language and linked it as an external procedure to the surrounding Pascal program [Listing One, page 56]. For performance measure-


ments, I used a system time procedure with a resolution of 1/60th of a second and, like Mr. Campbell in his article, a loop performing 60,001 calls to the square root routine with arguments ranging from 0 through 60,000. To derive the time it takes for the square root routine to execute, I measured the execution time of the Pascal program and then subtracted from it the execution time of the same program linked to a routine that skips the calculation of the square root: the latter time therefore represents the overhead for the loop and the procedure call mechanism, which has nothing to do with the square root algorithm itself.


Using the routine that mimics Mr. Campbell's compiler-generated code [Listing Two, page 56], the program executes in 16.73 (+/-0.02) seconds on my system (without printing or counting shifts and divisions) and the empty shell program needs 12.08 seconds. Calculating 60,001 square roots, therefore, takes 4.65 seconds, for an average of 77.5 microseconds per square root. To answer Mr. Campbell's question about whether hand optimizing the assembly code is worth it, I did just that. Using the same measuring procedure as above, the optimized code [Listing Three, page 56] needed 3.90 seconds to perform the 60,001 square root calculations (without overhead), for an average of 65 microseconds per square root-a speedup of about 16 percent. In my book, that is well worth the little trouble it takes to optimize the routine, especially if it is used often.

To find out by how much Mr. Campbell's algorithm is faster than the algorithm mentioned by Jim Cathey, I also performed the measurements for a program using that algorithm to calculate the square root [Listing Four, page 58]. Without overhead, Mr. Cathey's algorithm took 8.66 seconds to perform the 60,001 square roots, or an average of 144 microseconds per square root; it is therefore almost twice as slow as the unoptimized code for Mr. Campbell's algorithm.

To compare my results for the MC68000 with the published ones for a 6-MHz NS32016, they should be multiplied by a factor of 1.60 (9.6 MHz/6 MHz) to get timings equivalent to a 6-MHz 68000. If this is done, the time to calculate a square root using the unoptimized code becomes 124 microseconds, the optimized version needs 104 microseconds, and the square root calculation using bit shifting needs 231 microseconds. This clearly disproves Mr. Campbell's statements about the superiority of the NS32016.

Regarding Mr. Campbell's comments about the bit-shifting algorithm "hitting the NS32016 below the belt," I can only say that Mr. Cathey's algorithm was not specifically designed to do that but is rather a general-purpose algorithm that merely points out certain weaknesses in the NS32016's design. In my opinion, the MC680XX family is clearly superior to the microprocessors of the NS320XX family; everything you can do with a NS32016, you can also do on a 68000-often more easily,





When Will It Dawn On You?

XTC® is a PC programmer's dream come true. Just ask the thousands of programmers who've already awakened to the extraordinary features of this world class editor, designed for the IBM PC and true compatibles.

Features like XTC's interpretive macro language that lets you code macros on the fly. And fine-grained multitasking so you can run macros in the background while you continue editing.

Of course, XTC also lets you code macros in a high level language. And with the macro compiler you can write macros to check syntax in real time and translate source code from one language to another.

What's more, DOS compilers, linkers and utilities will run inside XTC so you don't have to leave the editor to compile and test run your programs.

If that's not enough, XTC has multiple large windows, 20 text buffers, and a host of other powerful features no other editor can offer.

In brief, you'll find little to compare with the power, flexibility, and advanced features that make XTC outshine the competition every time.

So if you're still dreaming about the ultimate editor, wake up. It could be right before your eyes.

XTC. From Wendin. Only \$99.



© Copyright 1986 Wendin, Inc.

MS is a trademark of Microsoft, PC-DOS is a trademark of IBM; UNIX is a trademark of AT&T; VAX/VMS is a registered trademark of Digital Equipment The people who make quality software tools affordable.

Wendin and XTC are registered trademarks of Wendin, Inc. PCUNIX, PCVMS, Operating System Toolbox, and Personal Operating System are trademarks of Wendin Inc.

Circle no. 112 on reader service card.

Ask about our other products for the IBM PC and true compatibles.

PCVMSTM

Multitasking, multiuser version of DEC's powerful VAX/VMS operating system. Runs most MS-DOS programs.

PCUNIXTM

True multitasking, multiuser operating system similar to AT&T's popular UNIX® operating system.

OPERATING SYSTEM TOOLBOX™

Complete software construction set that lets you build your own multitasking, multiuser operating systems.

All products priced at \$99 with source code included.

ORDER HOTLINE (509) 235-8088 (MON.-FRI., 8-5 PACIFIC TIME)







DEALER INQUIRIES WELCOME

Foreign orders inquire about shipping. Domestic orders add \$5.00/1st item, \$1.00 each additional item for shipping, handling, and insurance. Washington residents add 7.8% sales tax.

LETTERS

(continued from page 10)

usually faster, and then some, as illustrated above.

Other than that, I agree with Mr. Campbell's conclusion that many bit-level tricks of the 8-bit era are outdated and should be replaced by newer and faster algorithms more appropriate for 16/32-bit processors. I hope to find exactly such articles in future issues of *DDJ*.

Thomas Wieland 8676 Anthony, #5 Pierrefonds, PQ H84 2B6 Canada

moveq #0,d0 move.b (pseudopc)+,d0 add.w d0,d0 move.w 0(opptr,d0.w),a0 imp (a0) Dear *DDJ*,

8080 Simulator

Hats off to Jim Cathey for such a nice and useful piece of MC68000 code. [See "COM: An 8080 Simulator for the MC68000," January 1986.] After I had typed in the code (only one typo and an easy to find one at that), I couldn't resist adding Z80 relative jumps and djnz [Listing Five, page 58].

In an attempt to improve on the simulator's speed, and remembering an old trick from FORTH compiler writing days, I expanded mloop, which I duly dubbed NEXT, at the end of

* d0 <-- offset into word table

* d0 max is \$ff << 1 (\$1fe)

* clr hi word

* exec opcode

* fetch next opcode

every opcode simulation, thereby gaining eight t-cycles per simulated 8080 instruction as well as freeing a6 for other purposes (I promptly used it to point to pseudo-HL).

If your system is configured with CP/M-68K above the TPA in such a way that the simulator runs below \$8000, you can even go a step further by having a jump table (optabl) in the shape of dc.ws and a NEXT that looks like that shown in Table 1, left.

Together with various minor alterations too voluminous to present here, this last modification sped up the simulator to such an extent that it now runs slightly faster than SoftDesign's Z80 emulator, alas without providing full Z80 support. As many CP/M-80 programs don't use the extra Z80 instructions anyway, this restriction is seldom felt.

In order to spare other CP/M-68K users a set of blistered fingers, I will gladly copy the source for anyone who provides a formatted 8-inch or 51/4-inch floppy disk (please give fcb and skew details if not 8-inch SSSD).

Edmund Ramm Postfach 38 D-2358 Kaltenkirchen West Germany

ASMLIB

Table 1: Improved NEXT routine for 8080 simulator

Assembly Language Programming Library for the IBM PC/XT/AT or compatible DOS systems.

ASMLIB gives the Assembly Language programmer 190+ assembly functions which do

- Graphics functions draw CIRCLES, ARCS, ELLIPSES, LINES, and plots POINTS on the Color Adapter, Enhanced Graphic Adapter, and the Herc. Monochrome Card. Functions also allow PAINTING, IMAGE SAVES and RESTORES, and SCROLLING.
- Text Windows Up to 64 text windows may be defined, outlined, overlapped, moved, and can be grouped onto 256 logical display pages.
- Floating Point Arithmetic and Trigonometry functions for the MS and IEEE (8087) floating point formats (both 4 and 8 byte precision), and the 8087 (80287) can be utilized automatically if installed into the target system.
- ASCII String/Numeric conversion routines provide a user interface to the math functions. ASFORMAT function allows numeric values to be formatted utilizing commas, dollar signs, left or right justified, etc. (i.e. BASIC's PRINT USING).
- Mouse Support ASMLIB provides support for any mouse device which adheres to the MS Mouse software standard.
- Dynamic Memory support can utilize all available memory (up to 640k). Blocks of memory can be allocated, changed, moved, and killed.
- Console I/O, Disk I/O with file copy routines, Asynchronous Communications, Printer Support, ASCII String support, Sound generation, plus much more.

ASMLIB is supplied with complete MASM source code on 3 DOS diskettes along with a 215+ page reference manual.

- ALL FOR ONLY -\$149.00

For ordering or info please call:

BC Associates 13073 Springdale St., Suite 134 Westminster, CA 92683 (714) 741-3015

Phone COD orders accepted - ORDER YOURS TODAY!!!

Corrections

Dear DDJ.

The C implementation of Bresenham's line-drawing algorithm that appeared in the May 1986 issue contains several errors. [See "Simple Plots with the Enhanced Graphics Adapter" by Nabajyoti Barkakati.] These errors cause the routine v_draw to fail in the first and third quadrants. I have enclosed a corrected version, c_draw [Listing Six, page 62].

In v_draw, a statement

on line 75 is missing altogether. This causes the routine to break in a not so subtle manner: I assume the omission is a misprint. However, initialization of the decision variable d (lines 34 and 80) is incomplete, resulting in somewhat more obscure problems. The value to which dmust be initialized depends upon whether the line slope is positive or negative. If the initialization is handled incorrectly, symmetry is destroyed and endpoint overrun errors are introduced. These problems may not show up unless the routine is tested at all the boundary conditions.

The line-drawing routine runs rather slowly when the BIOS point-plotting routine is used, even on an IBM PC/AT. Possibly the use of Bruce Smith's assembly-language point-plotting algorithm, published in the January 1985 16-Bit Software Toolbox, would speed things up.

Joseph N. Mente Titanic CodeWorks 916 Olive Rd. Homewood, IL 60430

Listing One of Everett Carter's article, "Forth Goes to Sea," (July 1986) was truncated. The rest of the listing begins on page 50.

DDJ

(Listings begin on page 56.)

TAKE THE NEX OGICAL STEP

\$89 Price

- Separate Compilation
- Native Code Generation
- Large Memory Model Support
- Multitasking
- Powerful Debugging Tools
- Comprehensive Module Library
- Available for the PC and the VAX

Move up to LOGITECH MODULA-2/86. Whether you're a single programmer or part of a team, with LOGITECH MODULA-2/86 you'll decrease your overall development cycle and produce more reliable, more maintainable code. Build your program using our extensive library modules, your own modules or those from a growing list of available third-party software vendors. If you're a Turbo Pascal user you can even take your existing code along with you with the help of our new Translator!

NEW & IMPROVED!

Turbo Pascal to **Modula-2 Translator**

Now it's even easier for Turbo users to step up to Modula-2/86. Our improved Translator changes your Turbo source code into Modula-2/86 source, solving all the incompatibilities, and translating the function calls of Turbo into Modula-2/86 procedures. Implements the complete Turbo library!

LOGITECH MODULA-2/86

Complete with Editor, Run Time System. Linker, 8087 Software Emulation, Binary Coded Decimal (BCD) Module, Logitech's comprehensive library, Utility to generate standard .EXE files. AND more!

- LOGITECH MODULA-2/86 with 8087 Support \$129
- LOGITECH MODULA 2/86 PLUS \$189 For machines with 512K of RAM. Takes advantage of larger memory to increase compilation speed by 50%.

Turbo Pascal is a registered trademark of Borland

To place an order call our special 10DULA-2/86

RUN TIME DEBUGGER

(Source level!)

The ultimate professional's tool! Display source code, data, procedure call chain and raw memory. Set break points, assign values to variables, pinpoint bugs in your source.

UTILITIES PACKAGE

Features a post-mortem debugger (PMD). If your program crashes at run time the PMD freezes the situation so you can pinpoint, in the source, the cause of the error and the status of the data. Also includes a disassembler, cross reference utility and ver-

LIBRARY SOURCES

s99 Source code for our major library modules

WINDOW PACKAGE

Now you can build true windowing into your Modula-2 code. Powerful, though only 15K in size. Features virtual screens, color support, overlapping windows and a variety of borders.

MAKE UTILITY

Automatically selects modules affected by code changes to minimize recompilation and relinking. Even figures out dependencies for you!

CROSS RUN TIME DEBUGGER AND ROM PACKAGE

Now available at an introductory price!

sion that allows conditional compilation.

is now available for customization or exemplification.

\$29

\$49

\$199

In California: 800-552-8885 I want to move up to LOGITECH MODULA-2/86! Here's the configuration I'd like: ☐ Logitech Modula-2/86 889 with 8087 support \$129 ☐ Plus Package \$189 Turbo to Modula Translator \$49 ☐ Run Time Debugger \$69 ☐ Utilities Package \$49 Library Sources 899 ☐ Window Package \$49 ☐ Make Utility \$29 ROM Package \$199 Total Enclosed □ Visa □ Mastercard □ Check Enclosed Card Number Expiration Date Signature Address City, State

NEW, improved Turbo Pascal to Modula-2

Translator!

Call for information about our VAX/VMS

toll free number:

800-231-7717

version, Site License, University Discounts,

Dealer & Distributor pricing.

Logitech, Inc. 805 Veterans Blvd. Redwood City, CA 94063 Telephone 415-365-9852 For European pricing please contact: Logitech SA Box 32, CH-1143 Apples, Switzerland Telephone 41-21-774545

C CHEST

Directory Traversal, Trailing ^Zs, and Horrifying Experiences

Directory Traversal

his month I'm going to look at another sort of tree-a directory tree. The program presented here does several things, depending on how it's invoked. If the program is named whereis.exe, then the command whereis < fname > will search the entire directory tree for a file called fname, printing the full path name of the file when it's found. Wildcard characters are recognized in the name (as in whereis *.c). Be careful if you're running this program under the shell. You'll have to escape the wildcards to prevent the shell from expanding them (whereis "*.c" or whereis *.c).

By renaming the same program to dtree.exe, several functions are added. The basic command syntax is:


$$\frac{\text{dtree [root]}[-f < \text{name}>][-s][-d]}{[-e \text{ cmd arg }...]}$$

The root indicates where to begin the directory traversal. If it's not specified, then / is used. Thus, *dtree* (with no arguments) descends recursively through the entire directory tree, starting from the root directory, printing a list of all the directories on your disk. *Dtree* < *dname*> prints a list of all directories at or below < *dname*> in the directory tree. So *dtree* / works in the same way as

by Allen Holub

dtree without arguments does. Dtree /src prints a list of all subdirectories below /src (including the subdirectories of the subdirectories). Table 1, page 16, shows a sample output from my own disk.

The -d command-line switch causes a graphic representation of the directory tree to be printed rather than a simple list of the names. If -s is specified too, short names are used in-



stead of the full path name. An example is given in Table 2, page 16. When the program's output is redirected to a file, it's printed as shown (with plus signs and dashes). If output goes to *stdout*, the IBM box-drawing characters are used so that you have a prettier picture on the screen.

The -e switch is used to execute commands. All command-line arguments that follow -e are taken as a command that will be executed from each directory as it's visited. A space must follow the e. For example:

$$dtree / -e ls -l$$

prints a list of every file in every directory on the disk using the ls long format (that is, because the -l follows the -e on the command line, it's passed to ls rather than being interpreted by dtree). The directory name is printed too (just before the command is executed). If you need to execute either a batch file or a command that's part of the shell, you have to invoke the shell explicitly. Examples are:

dtree . —e sh cp "*.c" a:

The first example does the same as

The first example does the same as dtree - e ls does except that the dir command (that's internal to COMMAND.COM) is used. The second example executes an MS-DOS batch file; the arguments following the file name are passed to the batch file. The third

example does the same, but my own shell (as distributed by *DDJ*) is used rather than COMMAND.COM. The last example backs up all .c files in an entire system—that is, it copies all .c files in the current directory and any subdirectories to the a: drive. The explicit invocation of the shell is necessary because wildcard expansion must be done in each directory as it's visited, and this expansion is done by the shell, not by *cp*. Had you said:

dtree. -e cp *.c a:

the *.c would have been expanded by the shell to all files in the current directory that end in .c. Dtree would copy these and then descend to a subdirectory and try to find files having the same names as the ones in the parent (because the *.c is expanded by the shell before dtree ever sees the command line).

The switch -f < name > (no space between f and < name >) causes the program to search for the file called < name >. So dtree / -f < name > does the same thing as where is < name > does. Using dtree rather than where is has two advantages. First, dtree can start the search at any directory, but where is always starts at the root. So:

dtree /src -ffoo.c

finds foo.c only if it exists at or below /src in the directory tree. The second advantage comes from using —f and —e together on a single command line. Here, the command is executed only if the file is found. For example, if you're running under sh (rather than COMMAND.COM) using the rm program provided with the /util package to remove files:

dtree / -ffoo -e rm foo

Finds all occurrences of the file foo

QUITDOING GRUNT WORK.

Let Greenleaf do it for you and set you free.

C Program developers, stop slaving!

Greenleaf libraries have the functions you need — already perfected and in use by winning program developers in major corporations such as IBM, EDS and GM.

Between our Greenleaf Functions and Greenleaf Comm Library, we have over 340 functions on the shelf. Each one can save you time and effort. Money, too.

Many C programmers have told us that, even if they only use one or two functions, our products easily pay for themselves:

The Greenleaf Functions

The most complete and mature C language function library for the IBM PC, XT, AT and close compatibles. Our version 3.0 includes over 225 functions — DOS, disk, video, color text and graphics, string, time/date, keyboard, new disk status and Ctr1-Break control functions plus many more!

The Greenleaf Comm Library

Our 2.0 version is the hottest communications facility of its kind. Over 120 all new functions — ring buffered, interrupt-driven asynchronous communications.

Call Toll Free

1-800-523-9830

In Texas and Alaska, call

214-446-8641





GREENLEAF

Software

Greenleaf Software, Inc. 1411 LeMay Drive Suite 101 Carrollton, TX 75007 If you need more than 2 ports, only Greenleaf gives you the total solution — boards, software, and complete instructions that enable you to build a 16-port communication system.

And no matter how many ports you have, it's virtually impossible to lose information with multiple file transfers. XMODEM, XON/XOFF and Hayes modem controls are featured.

We support all popular C compilers for MS DOS: Lattice, Microsoft, Computer Innovations, Wizard, Aztec, DeSmet and Mark Williams.

Order today!

Order a Greenleaf C library now. See your dealer or call 1-800-523-9830. Specify compiler when ordering. Add \$8 for UPS second day air, or \$5 for ground. Texas residents, add sales tax. Mastercard, VISA, P.O., check, COD. In stock, shipped next day.

Greenleaf

Comm Library v2.0 \$185 Greenleaf Functions v3.0 \$185 Digiboard Comm/4-II \$315 Digiboard Comm/8-II \$515

We also sell compilers, books and combination packages.

Circle no. 97 on reader service card.

C CHEST

(continued from page 14)

on the disk and deletes them, and:

```
dtree /src/trees "-f*.bak" -e
sh -c rm "*.bak
```

deletes all .bak files in the /src/trees directory (and any subdirectories of /src/trees). The -f argument has to be quoted to prevent the shell from expanding it /dtree expands the wild-cards itself and -f can take only one

```
/src
/src/getargs
/src/grep
/src/nr
/src/nr/hyphen
/src/red
/src/shell
/src/shell/util
/src/shell/util2
/src/sm
/src/small-c
/src/sml-tool
/src/tools
/src/tools/doc
/src/tools/lattice
/src/tools/old
/src/tools/trees
/src/tools/trees/old
 /src/util
```

Table 1: Output from dtree /src

```
src
+----getargs
+----grep
+----nr
        +----hyphen
+ ----red
+----shell
        +----util
        +----util2
+----sm
+----small-c
 +----sml-tool
 +----tools
        +----doc
        +----lattice
         +----old
         +----trees
                +----old
 +----util
```

Table 2: Output from dtree / src -d-s>file

argument). Similarly, rm doesn't expand wildcards so you must invoke a shell to do it. The *.bak has to be quoted so that the subshell will do the expansion instead of the current shell.

Because the *delete* and *copy* functions are built into COMMAND.COM, you can say:

```
dtree /src -f*.bak -e command /c copy *.c a:
```

to do the equivalent operation from outside the shell. You don't have to quote any arguments because COMMAND.COM won't expand them; *copy*, on the other hand, will.

Dtree.c

The source for *dtree()* is in Listing One (page 62). The modus operandi of the program is determined in *main()* on lines 380—394. *Main()* examines argv[0] to see by what name it was invoked. If *whereis* is used, the *if* clause is executed; if anything other than *whereis* is used, then the *else* clause is executed. Note that argv[0] isn't supported by DOS, Version 2.x, so this automatic configuration will work only if you're using DOS 3.x or if you're running the shell (the *reargv()* function will give you access to argv[0]).

The main() routine also determines which character set to use for tree printing (on line 397). It does this in the same way as does the print routine I discussed last month. The same limitations apply, too (that is, graphics are used unless standard output is redirected to a file). The signal() call on line 405 is necessary because the traversal algorithm actually changes the current directory as it traverses. The signal() call sets up the interrupt system so that when a ^C is encountered, the current directory will be set back to whatever directory you started from when the program booted. The actual resetting is done in onintr() on lines 361-366.

Dtree() can't use getargs because it uses a position-dependent command-line switch (-e). So the program's arguments are processed by hand in doargs() on lines 270-332. It works pretty much the same as getargs() does, setting global variables to correspond to encountered command-line switches and compressing argy to remove all command-line switches.

Note that all argv entries following -e on the command line aren't analyzed (that's the test for Args on line 295; Args is NULL if a -e hasn't been found).

The basic traversal algorithm is done by prnt() (on lines 174–232). It uses a modified version of the preorder tree-printing algorithm that I discussed two months ago, so I won't cover that material again. However, instead of using a basic tree-traversal algorithm:

trav(root)

```
{
    print(root);
    trav(left);
    trav(right);
}
which can be restated for multiway
tree traversal as:

trav(root)
{
    print(root);
    for(each child)
        trav(child);
}

dtree uses:

trav(current directory)
{
    print(current directory's name);
    get list of all subdirectories;
    for(each subdirectory)
        trav(subdirectory);
}
```

The code on lines 188-192 just prints vertical bars in the appropriate places, provided you're printing a picture of the tree (that is, -d is specified on the command line, causing Draw to be true). If you're searching for a file, the if statement on lines 194-198 is executed. The directory name is not printed. Rather, if the file exists, you execute the command tail. Execute() won't do anything if -eisn't found on the command line. If you're not looking for a specific file, the else clause on lines 199-203 prints the current directory name and then executes the command tail.

Prnt() gets the list of subdirectories using the same dir() subroutine that's used by the shell (the code for all these routines and for the mydir.h file that's #included on line 4 are in

Are you getting the

Do you believe
Turbo Pascal
is a serious
programming
language and not
just a toy? Would you like to
improve your skills and
master the power and ease of
Turbo Pascal
programming? Then M&T
has a publication for you:
Turbo Tech Report.

This bimonthly newsletter/disk publication is written in the *Dr. Dobb's Journal* tradition, delivering high-quality technical reviews, in-

depth articles, tips and tricks, and Turbo Pascal utilities, libraries, and source code on disk. Editor Namir Clement Shammas is dedicated to bringing you the best in Turbo programming, insight, commentary and gossip.

for \$99 a year!

Subsc. price of the price of

Each valuable issue will include:

• Reviews of Turbo Pascal-related products. You'll read about the latest Turbo Pascal third party software

like Blaise Computing's new Turbo
Power Tools.

In-depth articles on

• In-depth articles on expanding your Turbo Pascal programming skills—on topics like 3D graphics, screen utilities, and memory resident programs.

developments,

• Applications developed by other Turbo users and public domain Turbo Pascal software programs on disk. If you're an expert Turbo

with 6 newsletters
for \$99 a year!

Pascal programmer or a novice interested in expanding your Turbo skills, you need Turbo Tech Report.

Subscribe today at the special introductory price of just \$99—that's 33% off the regular price of \$150.

To order by credit card, call toll free 1-800-528-6050 ext. 4001 and ask for item 300. Or mail the attached coupon with your payment to *Turbo Tech Report*, 510 Galveston Drive, Redwood City, CA 94063.

Turbo Pascal is a trademark of Borland International Inc. Turbo Power Tools is a trademark of Blaise Computing Inc.

Introducing Turbo Tech

Report, the newsletter

for Turbo Pascal

programmers. 6 disks

C CHEST

(continued from page 16)

the March 1986 C Chest. *Mk_dir()* creates a *DIRECTORY* structure on line 205. This structure is initialized on lines 211–215 so that *dir()* will get a sorted list of subdirectories, using the full path name of each directory in the list. *Dir()* itself is called on line 219; the recursive traversal of each subdirectory is done by the *while* loop on lines 221–225; and memory used by the the *DIRECTORY* structure is freed on line 230 [with the *del*

_dir() call].

Find() (on lines 137–170) uses the same directory routines to look for a file. It will expand any wildcard characters in the file spec and print the whole list of matching files. The remainder of the code you've already seen, either last month or the month before, so I won't cover it again here.

Fixing ^Z-Terminated Files

Back in May, Ray Duncan mentioned a problem with ^Z-terminated files being read by the Microsoft Macro Assembler, Version 4.0 (16-Bit Software Toolbox, p.109). The include function ignores the end-of-file mark (^Z) and uses the file size, so it will kick out error messages if you create a file with any editor that terminates its files with 'Zs rather than just making the files the correct length. Mince, Vedit, and WordStar (in document mode) are three of these editors. You often see this sort of padding in programs that were originally written for CP/M or MS-DOS, Version 1 (where 'Z is the only way to end a file). Microsoft has been trying to get rid of the 'Z end-of-file marker since it introduced Version 2 of MS-DOS, and I guess it's finally playing hardball.

This 'Z problem is responsible for a lot of weird behavior on the part of the shell, too. The formatted I/O routines in Version 3.0 of the Microsoft C compiler get hopelessly confused when they try to read a 'Z-terminated file. So if you try to execute a Vedit-created batch file from the shell, strange things start happening (characters mysteriously appear and disappear, error messages such as "stdout: no room left on device" are printed, and so on).


Unfortunately, the fix that Ray gave in his column (enter, write, and then exit from EDLIN) doesn't seem to work all the time (or so say friends who've tried it), and it turns out to be almost impossible to fix this problem in Microsoft-compiled programs without going to unformatted binary input (that is, open(), read(), and so on). So I wrote a utility called fix to deal with it (see Listing Two, page 68).

Fix removes all trailing ^Zs from a text file (actually it truncates the file at the first ^Z it finds). Usage is:

fix file [file . . .]

where the command line holds a list of files to fix. The program renames the files specified on the input line to xxx.bak, where xxx is the original root part of the file name. It then overwrites the original file, removing the trailing 'Zs.

The program is very short and pretty much self-explanatory. Note that the *ctlc()* and *reargv()* calls on lines 54 and 55 are useful only if you're running under the shell and they're supplied along with the shell.



FEATURES:

- ➤ Optional strong type checking
- Overloading of function names and operators
- Optional guaranteed initialization of data structures
- ▶ Data abstraction
- Dynamic typing (virtual functions)
- Optional user-defined implicit type conversion

The only commercially-available C++ customized to operate on PC's, micros, minis, and mainframes with popular C compilers, including:

LATTICE MICROSOFT DEC C GREEN HILLS WIZARD WHITESMITH'S

- Works with your present C Compiler
- Functions as a Preprocessor Translator handles regular C code with no changes
- Type-checking and other features are optional you can turn them off
- Already thousands of users at commercial sites
- Complete documentation: <u>C++, A User's Guide</u>
 by Bjarne Stroustrup of AT&T (Addison-Wesley, 1986)

We Specialize In: Cross/Native Compilers: C, Pascal, FORTRAN, Ada, LISP—Assemblers/Linkers — Symbolic Debuggers — Simulators — Interpreters — Profilers — OA Tools — Design Tools — Common Tools, — OS Kernels — Editors — VAX & PC Attached Processors and more WeSupport: 680xx, 60x6, 320xx, 68xx, 80xx; Clipper, and dozens more

—A DIVISION OF XEL

60 Aberdeen Ave., Cambridge, MA 02138 (617) 491-4180

Designer C++ is a trademark of XEL. Inc. Ada is a trademark of the U.S. Government (Ada Joint Program Office)

First "language specific" DBMS written exclusively for Capplications is also royalty free

"db_VISTA™ lets you easily build complex databases with many interconnected record types..." Dave Schmitt, President, Lattice, Inc.

Designed exclusively for C, db_VISTA™ is a language specific database management system. Both single and multi-user versions let you take full advantage of C, through ease of use, transportability and

Every Line of Code Written in C for C Programmers

All functions use C conventions so you will find db_VISTA easy to learn. db_VISTA operates on most popular computers, and because it is written in C it can easily be ported to most computers.

Royalty-Free, You Only Pay Once

Whether you're developing applications for a few customers, or for thousands, the price of db_VISTA is the same. If you are currently paying royalties for a competitor's database, consider switching to db_VISTA and say goodbye to royalties. To help you make the change over to db_ VISTA, ASCII file transfer utilities are included. dBASE file transfer utilities are available as an option.

More from your database applications with source code

Source code includes all db_VISTA libraries and utilities.

- 1. Recompile our run-time libraries utilizing non-standard compiler options.
- 2. Create a debugging library including a function traceback by activating preprocessor commands embedded in the source code.

Multi-user and LAN capability

Information often needs to be shared. db_VISTA has multi-user capability and supports simultaneous users in either multi-tasking or local area networking environments, allowing the same C applications to run under UNIX and MS-DOS.

Faster execution without data redundancy

Less data redundancy means reducing disk storage requirements and maximizing data access performance. A customer evaluating a leading competitor's product prior to purchasing db_VISTA benchmarked db_VISTA's retrieval time to be 276% faster than a leading competitor.

Complete documentation included

User manual contains 193 pages, 8 diagrams, 10 tables, appendices, an extensive index, plus a database application example. 9 chapters with complete instructions.

db_QUERY™lets you ask more of your database

db_QUERY is a linkable, SQL-based ad hoc query and report writing facility. It's also royalty-free.

Circle no. 206 on reader service card.

30-Day Money-Back Guarantee

We wish to give you the opportunity to try db_VISTA for 30 days in your development environment and if not satisfied return it for a full refund.

Price Schedule

	db_VISTA	db_QUERY
Single-user	\$195	\$195
Single-user with Source	\$495	\$495
Multi-user	\$495	\$495
Multi-user with Source	\$990	\$990

FREE 60 Days Application Development Support All software Not Copy Protected

Call Toll-Free Today!

To order or for information, call TOLL-FREE at 1-800-843-3313, then at the tone touch 700-992 or call 206-747-5570.

VISA and MASTERCARD Accepted

Read what others say about db_VISTA

"If you are looking for a sophisticated C programmers database, db_VISTA is it. In either a single or multi-user environment, db_VISTA lets you easily build complex databases with many interconnected record types. The multi-user implementation handles data efficiently with a LAN and Raima's customer support and documentation is excellent. Source code availability and a royalty-free run-time is a big plus.

Dave Schmitt, President Lattice, Inc.

"Not 'yet another user-friendly database," it is a DBMS aimed at the technical C programmer instead of the non-technical end-user."

Hal Schoolcraft, Data Based Advisor March, 1985

"On the whole, I have found db_VISTA easy to use, very fast with a key find, and powerful enough for any DBMS use I can imagine on a microcomputer'.

Michael Wilson, Computer Language September, 1985

db_VISTA Version 2.11 Database Management System for C

Database Record and File Sizes

- Maximum record length limited only by accessible RAM
- Maximum records per file is 16,777,215
- No limit on number of records or set types
- Maximum file size limited only by available disk storage ◆ Maximum of 255 index and data files

Keys and Sets

- Key length maximum 246 bytes
- No limit on maximum number of key fields per record—any or all fields may be keys with the option of making each key unique or duplicate
- No limit on maximum number of fields per record, sets per database, or sort fields per set
- No limit on maximum number of member record types per set

- Database definition language processor Interactive database access utility
- Database consistency check utility
- Database initialization utility Multi-user file locks clear utility
- Key file build utility
- Data field alignment check utility • Database dictionary print utility
- · Key file dump utility
- ASCII file import and export utility

- Multi-user support allows flexibility to run on a local area network
- File structure is based on the B-tree indexing method and the network database model
- Run-time size, variable-will run in as little as 64K, recommended RAM size is
- Transaction processing assures multiuser database consistency
- File locking support provides read and write locks on shared databases
- SQL-based db_QUERY is linkable • File transfer utilities included for ASCII, dBASE optional

Operating System & Compiler Support

- Operating system's MS-DOS, PC-DOS, Unix, Xenix, Macintosh and Amiga
- · C compiler's Lattice, Microsoft, DeSmet, Aztec, Computer Innovations, Xenix and

Independent Benchmark Results

Eleven key retrieval tests on sequentially and randomly created key files. Benchmark procedure adapted from "Benchmarking Database Systems: A Systematic Approach" by Bitton, DeWitt, and Turbyfill, December, 1983.

Total Retrieval Time of 11 Tests db VISTA

:671.24 Leading Competitor



12201 S.E. Tenth Street Bellevue, WA 98005 USA (206) 747-5570 Telex: 9103330300 BCN RIVERTON 1 (800) 843-3313 at the tone touch 700-992





C CHEST

(continued from page 18)

Don't include these calls if you're using COMMAND.COM.

A Tale of Woe

My friend Bill Wong, who lives across the street, has gallantly volunteered to beta test the shell as I bring up the new version. He was having problems with it the other day, and we thought these problems might be DOSrelated (he's running Version 3.0 rather than 3.1), so we decided to upgrade the DOS version on his hard disk. Earlier versions of DOS (pre-3.1) made it impossible to create a system disk except by formatting the disk with the /s flag set (copy won't copy system files). This, of course, forced you to back up, format, and then restore your entire hard disk to install a new version of DOS. Version 3.1 comes with a utility called sys that can transfer a system to a hard disk, but I had forgotten that this utility existed.

So. I tried to install the new DOS version on Bill's disk by removing the hidden and system attributes from IBMBIO.COM and IBMDOS.COM and then copying them over to the hard disk in the normal way. I've a program (called chmod) that can change these attributes (attrib can change only the read-only attribute). Files successfully transferred, I pressed Ctl-Alt-Del, and to my horror, the system wouldn't boot. It didn't even print an error message—it just hung. "Oh God," I said to myself, "I've destroyed Bill's hard disk." Fortunately, things weren't quite that bad. The system booted from the floppy with no trouble. We could at least get the thing running again to try to find out what the problem was.

To make a long story short, we fooled around for more than an hour, trying everything we could think of (including running the sys program, now rediscovered by us). Nothing worked. No amount of copying fixed anything. Changing attributes didn't help. Sys said that it had transferred the system, but it still wouldn't boot from the hard disk. So, in desperation we deleted the entire root directory (including the system files) and tried to run sys again. Now it started giving us "No room for system on destination disk" error mes-

sages. The disk was only two-thirds full, so there was obviously some other problem.

Finally I threw in the towel and decided to call Microsoft. It told me that it does not support end-users of DOS and that I'd have to call IBM. IBM told me that it does not support end-users of DOS and that I'd have to call the store that sold me the computer. ComputerLand told me that it had no idea what the problem was, though it could guess. The person I talked to suggested reading the DOS Technical Reference. So, it seems there is no technical support available for MS-DOS—from anyone.

I dug out the Technical Reference and actually did find something there. It was even in the index (under system reset). When MS-DOS boots: "The boot record then checks the root directory to assure that the first two files are IBMBIO.COM and IBMDOS .COM. These two files must be the first two files, and they must be in that order (IBMBIO.COM first, with its sectors in continuous order)." So, my theory is that when you open a file for overwrite, DOS frees up the associated FAT entries and directory space. That is, it doesn't just overwrite an existing file with new data; it throws away the existing file and then starts from scratch, putting the copy wherever it feels like. So the two boot files ended up in the wrong place. Meanwhile all our thrashing around on the disk ended up putting something into the sectors that IBMBIO.COM wanted to occupy. This explains sys' inappropriate error message. There's plenty of room on the disk, but there's probably no room on track 0. I still don't understand why sys told us that the system had been transferred successfully the first few times we tried to use it. I suspect this has something to do with directory entries for IBMBIO.COM and IBMDOS.COM already existing but pointing at the wrong place on the disk. It seems to me that sys should check for things such as that. It obviously doesn't. I also don't understand, if the positions of IBM-BIO.COM and IBMDOS.COM on the disk are so important, why you can delete them at all. To my mind they shouldn't even be in the directory system because you can't treat them like you can any other file.

I'm sure there's a lesson to be

learned from all this, but I'm not sure what it is. Your only recourse is to back up, reformat the hard disk, and restore. Looked at in a truly Polyanna fashion, at least disk accesses will speed up because all the file fragmentation will be eliminated.

To add injury to insult, bringing up Version 3.1 didn't fix the problem with the shell (which turned out to be the ^Z problem that I described earlier). Aren't computers wonderful?

Availability

The listings from this month are all available on CompuServe (type go ddj). The chmod program, used to change file attributes, is now distributed by DDJ as part of Version 1.1 of the /util package. This package also includes the rm and cp utilities used in the examples. If you have an earlier version, you can get an upgrade from DDJ for \$6. The fix program is distributed with Version 2.0 of the shell (available from DDJ, upgrades are \$6, too) and is also available on CompuServe. The directory-related routines used by dtree.c are also part of the shell. They were originally published in this column in March 1986 (the listing begins on page 56 of that issue). Note that the mydir.h file on the shell distribution disk is called dir.h in that listing.

An IBM PC-compatible disk containing the complete sources for dtree.c and fix.c (including the directory routines) is available for \$25 from Software Engineering Consultants, P.O. Box 5679, Berkeley, CA 94705.

DDJ

(Listings begin on page 62.)


Vote for your favorite feature/article. Circle Reader Service **No. 1**.

Ready for the Ultimate?

DVANCED MS-DOS®. If you're a seasoned assembly-language or C programmer, familiar with Intel's 8086/8088/80286

microprocessors, you want detailed information on MS-DOS® that speaks to your level of experience. Here, from Microsoft Press and Ray Duncan, is the kind of high-level, advanced information you need to write robust,


high-performance MS-DOS® applications. Now you can explore each of the MS-DOS® functions and special features in detail, comparing and contrasting the various versions along the way. Scores of detailed programming examples — isolated code fragments and complete utility programs — illustrate each feature. And a wealth of reference information on all the functions and interrupts, error



codes, IBM ROM-BIOS, and the Lotus/Intel/Microsoft Expanded Memory Manager awaits you. ADVANCED MS-DOS®— let your experience shine. \$22.95. Available wherever books and software are sold. Microsoft Press, 16011 NE 36th Way, Box 97017, Redmond, Washington 98073-9717


MICROSOFT.
PRESS

NOBODY ELSE HAS MADE THE CONNECTION.



There's only one way to link the extensive resources of Intel's microprocessor development system with the power of a DEC VAX* and the affordability of the IBM* PC.

And that's via our enhanced version



of OpenNET™ for the development lab.

Thanks to this open architecture network, engineers can have immediate, and transparent, access to other team members' work.

Plus you have the ability to add special-purpose hardware to make those teams more productive.

For example, by connecting our high-performance file server, the Network Resource Manager, you can off-load file management and job distribution from the shoulders of your design team. On the off chance nobody wants to spend his time chasing down floppy disks.

And then you can hook up an 80286-based Compilengine to off-load compute-bound compilations from VAXs and workstations. Leaving them, and their human partners, more time for interactive tasks.

Equally important, the network maximizes the value of your existing development

VAX is a registered trademark of Digital Equipment Corporation. IBM is a registered trademark of International Business Machines Corp. OpenNET is a trademark of Intel Corporation. Microsoft is a registered trademark of Microsoft Corporation. © 1986 Intel Corporation.

hardware while minimizing your outlay for new equipment.

That's because
OpenNET adheres very
rigidly to some very
flexible standards.
Standards like Ethernet/
IEEE 802.3. And the
ISO message delivery and
Intel/IBM/Microsoft*
Network File Access
protocols.

All of which means existing development hosts, languages and tools, including ICE, are instantly compatible with the latest ones. So you can avoid obsoleting one set of tools just to use another.

We'll even take full responsibility for servicing and supporting your network. Anywhere in the world.

Sound like we've got things together? Then call us at (800) 548-4725.

Ask to meet with one of our experienced network engineers. We'll see you make all the right connections.



Curve Fitting with Cubic Splines

by Ian E. Ashdown

Before computer-aided drafting workstations completely replace the draftsman's pencil and paper, let's examine one of the draftsman's tools: the

The program can generate a curve for a thousand or more data points.

spline. Presented with data in the form of points on an x-y plane, the draftsman uses a spline—a flexible strip of metal or plastic—to draw a smooth curve between them.

The technique is very simple. After plotting the data on a sheet of paper, an appropriately sized spline is held in place at these points (referred to as "knots") with weights or pins. The draftsman then traces the curve formed by the spline. For any given set of knots, the curve generated is independent of the spline chosen and is thus exactly reproducible.

From mechanical engineering, elementary beam theory shows that if the spline is not too severely stressed, it will conform to a curve described by a set of cubic polynomial equations, one between each pair of adjacent knots. Adjacent polynomials meet at their common endpoints (the knots), and their slopes and rates of curvature at these points are equal. Stated in mathematical terms, these polynomials join continuously at the knots with continuous first and second derivatives.

Knowing this, you can develop a mathematical model of the draftsman's splines and from this model construct a computer program for interpolating a smooth curve between a set of knots. With a bit of care in choosing algorithms, such a program can quickly and accurately generate a curve for a thousand or more data points on the smallest of personal computers. It can even be adapt-

byHeart Software, 620 Ballantree Rd., West Vancouver, BC V7S 1W3, Canada ed to interpolate a smooth surface between points plotted in three dimensions.

Developing the model involves basic calculus and matrix theory. If you are unfamiliar with such

mathematics, rest assured that the resultant algorithms are very easy to program and using a cubic spline program requires no understanding of the underlying mathematical theory. Give the program a set of knots, and it will dutifully interpolate a smooth curve in all (well, almost) cases


Why then discuss the mathematics of cubic splines at all? There are two answers. One is that seeing how the algorithms are developed gives you the confidence to use them. The other is that there may be cases in which the algorithms will not perform exactly as desired. Knowing their theory may enable you to create a modified algorithm to fit the problem at hand.

A Simple Explanation

Some of the math involved in spline calculations may be a bit daunting if you haven't had training in calculus and matrix mathematics. For those who want to get the gist of it without getting tangled up in equations, here's a short summary.

Because a spline is really nothing more than the graphs of a set of contiguous (endpoint-adjacent) cubic equations, all you need to know to draw it are the parameters of each of the equations. Naturally, there will be one such equation for each segment of the spline.

Because you know that the endpoints of each segment will coincide with the endpoints of the adjacent ones, and you know that the slopes of both curves will be the same at the joining points, it is possible to derive the equations



of the segment curves because, for any set of two points and two slopes, there is one and only one cubic curve segment that passes through the two points with the given slopes. Because each segment of the spline shares the same slope at its endpoints as its neighbors, you know that its first derivative (slope) will be the same at that point. Because the curves are the graphs of cubic polynomials, you know their second derivatives (change in slope) will be straight lines. Because (from the definition of the spline curve) the slope changes smoothly over the length of the curve, you know that the graph of the second derivatives of the spline equations will consist of a series of straight lines joined together at their endpoints.

A Rigorous Explanation

Beginning in this section, the math will get quite involved. If you're not into heavy math, you might want to skip down to the sections on the actual algorithms or you might want to skim through the math sections. It's not necessary to have a full understanding of the math in order to make the spline program work properly, but it helps.

Starting with a set of data points (the knots) stated as ordered horizontal coordinates x[i] ($i=1,\ldots,n$) and corresponding vertical coordinates y[i], define the curve-to-be as the composite function:

$$y(x) = f[i](x)$$
 for $x[i] \le x < x[i+1]$; $i = 1, ..., n-2$;
and $x[n-1] \le x < x[n]$

where each function f[i](x) is a cubic polynomial of the form:

$$f[i](x) = ax^3 + bx^2 + cx + d$$

where a, b, c, and d are constants. In other words, y(x) is really a set of functions, each of which is defined over an interval between two adjacent knots at (x[i], y[i]) and (x[i+1], y[i+1]).

Furthermore, let's define y'[i] and y''[i] as the first and second derivatives of y(x) at x = x[i]. Knowing that the set of functions f[i](x) must join at their endpoints (the knots of the spline) and also that their first and second derivatives are continuous at these points, you have the following continuity conditions:

$$\begin{array}{lll} f[i](x[i]) = y[i] & i = 1, \dots, n-1 \\ f[i-1](x[i]) = y[i] & i = 2, \dots, n \\ f'[i-1](x[i]) = f'[i](x[i]) & i = 2, \dots, n-1 \\ f''[i-1](x[i]) = f''[i](x[i]) & i = 2, \dots, n-1 \end{array}$$

Because each function f[i](x) is a cubic polynomial, it follows that its second derivative is a linear function (a straight line) between its endpoints. If you define:

$$h[i] = x[i+1] - x[i]$$

then linear interpolation gives you:

$$f''[i](x) = \frac{y''[i] * (x[i+1] - x) + y''[i+1] * (x - x[i])}{h[i]}$$

Integrating this equation twice and selecting the constants of integration such that the continuity conditions are satisfied, you can derive the interpolation equation shown in Table 1, page 26.

Remember this equation—you'll use it later to interpolate the curve defined by y(x) between the given knots. But first you need to calculate the unknown coefficients y''[i] for all i between 1 and n.

Differentiating and evaluating the interpolation equation for x[i] yields:

$$f'[i](x[i]) = \frac{y[i+1] - y[i]}{h[i]} - \frac{h[i]}{6} * (2 * y''[i] + y''[i+1])$$

$$f[i](x) = \frac{y[i] * (x[i+1] - x) + y[i+1] * (x - x[i])}{h[i]} - \frac{h[i]^{2} *}{6} \left(y''[i] * \left(\frac{(x[i+1] - x)}{h[i]} - \frac{x[i+1] - x}{h[i]} \right)^{3} \right) + y''[i+1] * \left(\frac{(x - x[i])}{h[i]} - \frac{x - x[i]}{h[i]} \right)^{3} \right) \right)$$

$$for i = 1, ..., n$$

Table 1: Interpolation equation

CUBIC SPLINES

(continued from page 25)

and

$$f'[i-1](x[i]) = \frac{y[i] - y[i-1]}{h[i-1]} + \frac{h[i-1]}{6} * (y''[i-1] + 2 * y''[i])$$

Because the first derivatives of the functions at their endpoints are continuous, these two equations are equivalent. You can rearrange the terms of their right-hand sides to get:

$$h[i-1] * y''[i-1] + 2 * (h[i-1] + h[i]) * y''[i] + h[i] * y''[i+1]$$

$$= 6* \left(\frac{y[i+1] - y[i]}{h[i]} - \frac{y[i] - y[i-1]}{h[i-1]} \right)$$

for i = 2, ..., n-1.

Expressed in matrix form, the above equations show an

Table 2: $f'[i](\times [i])$ and $f'[i-1](\times [i])$ expressed in matrix form for n=6

Table 3: Matrix form of nonperiodic spline function

interesting diagonal symmetry that you can take good advantage of later. Using n=6 as an example, they look like those shown in Table 2, page 26.

A Variety of End Conditions

So far, you have n unknowns y''[i] but only n-2 conditions as expressed by the above equations. Two more conditions are required to obtain a unique solution for your curve y(x). Several variations are possible; I'll look at two of the more useful ones here.

The first is to specify that:

$$y''[1] = j * y''[2]$$

and
 $y''[n] = k * y''[n-1]$

where j and k are arbitrary constants. With a bit of matrix manipulation, you get the equations shown in Table 3, page 26.

If the values of j and k are zero, you have y''[1] = y''[n] = 0. This is equivalent to a spline whose ends are not constrained beyond the end knots and is known as the "natural" cubic spline. A nonzero value for j or k is equivalent to bending an end of the draftsman's spline and will affect all of the interior cubic polynomial functions. The effect on the interior polynomials, however, rapidly decreases as you move away from the endpoints.

For some sets of knots, a nonzero value of j or k will result in a smoother interpolating curve at its corresponding end. A value of 0.5 is often appropriate. Be forewarned, however, that for some negative values the curve will be discontinuous. As it approaches these values, the end of the curve begins to oscillate, the peaks becoming larger and larger until they reach infinity at the exact values.

The above set of linear equations can be solved using Gaussian elimination. You must be careful, however. In

/* Reduce matrix to upper triangular form */

for i=2 to i=n-2begin c[i+1]=c[i+1]-h[i]*h[i]/c[i] d[i+1]=d[i+1]-d[i]*h[i]/c[i]end

/* Solve using back substitution */ y''[n-1]=d[n-1]/c[n-1]for i=n-2 to i=2begin y''[i]=(d[i]-h[i]*y''[i+1])/c[i]end y''[1]=j*y''[2] /* End conditions */ y''[n]=k*y''[n-1]

Table 4: Algorithm 1: Nonperiodic spline coefficient determination

AT LAST: Professional Typesetting Capability For PC Users

With $\mathbf{PCTEX}^{\scriptscriptstyle\mathsf{TM}}$ — the best-selling full implementation of Professor Don Knuth's revolutionary typesetting program TEX .

FINEST Typeset Quality Printing From:
dot matrix laser phototypesetter

$$\sum_{i=1}^{\infty} \frac{1}{i} \quad \begin{pmatrix} a_{11} & \dots & a_{1n} \\ a_{21} & \dots & a_{2n} \\ \vdots & \ddots & \vdots \\ a_{m1} & \dots & a_{mn} \end{pmatrix} \quad \int_{-\infty}^{\infty} e^{-x^2} dx$$

WIDEST Range Of Output Device Drivers:

- Epson FX, LQ
- HP LaserJet*
- Toshiba
- Apple LaserWriter
- Corona LP-300*
- APS-5 phototypesetter
- Screen preview, with EGA or Hercules card

MOST COMPLETE Product Offering:

PC TEX (not copy protected) includes the following:

- Our specially written *PCTEX Manual*, which enables you to start using TEX right away.
- Custom "macro packages" that provide formats for letters, manuals, technical documents, etc.
- The LATEX document preparation system, a full-featured macro package for preparing articles, books, reports, etc., and LATEX User's Manual.
- AMS-TEX, developed by the Amer. Math. Society for professional mathematical typesetting.

Site licenses, volume discounts, and interfaces to PC Paintbrush, PC Palette, FancyFont and Fontrix are also available.

PRICED FROM ONLY \$249.00!

(Printer drivers and interfaces additional.)



Laser printer, fonts & software from \$2995.00

For IBM PC/XT, AT or compatible, DOS 2.0 or higher, and 512K RAM. Hard disk required for printer drivers and fonts. *HP LaserJet and Corona require additional interface boards.

For more information call or write: Personal T_EX, Inc.

20 Sunnyside, Suite H, Mill Valley, CA 94941 (415) 388-8853

This ad, with space for the photograph, produced by PC TeX. Typeset on the Epson FX80, the Corona LP-300 laser printer, and the Autologic APS-5 phototypesetter.

 $T_{\hbox{\footnotesize EX}}$ is a trademark of the American Mathematical Society. Manufacturers' product names are trademarks of individual manufacturers.

(continued from page 27)

its most general form, this method can require prodigious amounts of memory and millions of floating-point computations. Given 1,000 unknowns, Gaussian elimination needs storage for more than 1 million floating-point numbers and performs some 334 million multiplications and divisions! The loss of accuracy because of so many calculations can render the results meaningless.

Fortunately, the coefficient matrix described here is very sparse and symmetrical. The nonzero elements can be stored in a few linear arrays and the remainder ignored. By observing how Gaussian elimination solves the equations, you can modify the method to eliminate operations involving multiplication by and addition of zero. The result is Algorithm 1 (Table 4, page 27), which has very reasonable memory requirements and execution times—a cubic spline problem with 1,000 knots can be solved quickly on most personal computers, even those with less than 64K of memory!

In practice, array $y''[\]$ would be used initially to store the elements of array d[\]. Then, as the elements of $y''[\]$ are solved during back substitution, they overlay the values of d[\]. To implement this space-saving technique in Algorithm 1, change every instance of d[\] to $y''[\]$.

The second variation is more interesting and comes from the need to interpolate data extracted from periodic phenomena. If you plot any periodic data in polar coordinates, a smooth curve between them forms a closed curve, with the endpoints of the curve meeting. Plotting the same data in rectilinear coordinates with the horizontal coordinates expressed over 360 degrees, it's easy to see that you can model the curve with a cubic spline function.

Because the curve is periodic, the endpoint vertical coordinates are by definition equal. In other words, y[1] =

y[n]. You need to specify the end conditions such that the first and second derivatives of the curve are continuous with respect to each other at these points. Stated in mathematical terms, y'[1] = y'[n] and y''[1] = y''[n].

The second derivatives are easy—they can be expressed directly in matrix form. To use the first derivatives of y(x) at the endpoints, you need an equation that relates them to y(x) and its second derivative. Going back to the derivations for f'[i](x[i]) and f'[i-1](x[i]) and evaluating them for x[1] and x[n] respectively, you have:

$$f'[1](x[1]) = \frac{y[2] - y[1]}{h[1]} - \frac{h[1]}{6} * (2 * y''[i] + y''[2])$$

and

$$f'[n-1](x[n]) = \frac{y[n] - y[n-1]}{h[n-1]} + \frac{h[n-1]}{6} * (y''[n-1] + 2*y''[n])$$

But y'[1] = y'[n], so:

$$6* \left(\frac{y[2]-y[1]}{h[1]} - \frac{y[n]-y[n-1]}{h[n-1]}\right) =$$

$$h[n-1]^*(y''[n-1]+2^*y''[n]) + h[1]^*(2^*y''[1]+y''[2])$$

Again with some matrix manipulation, you get the equations shown in Table 5, below. These equations can be solved efficiently and quickly with another modified version of Gaussian elimination, as shown in Table 6, page 30.

Other end conditions are possible. You can, for example, specify the slope of the spline at its endpoints by specifying the first derivatives at y[1] and y[n]. You can

$$\begin{bmatrix} c[2] & h[2] & 0 & \dots & 0 & h[1] \\ h[2] & c[3] & h[3] & \dots & 0 & 0 \\ 0 & h[3] & c[4] & \dots & 0 & 0 \\ \dots & \dots & \dots & \dots & \dots & \dots \\ 0 & 0 & \dots & h[n-2] & c[n-1] & h[n-1] \\ h[1] & 0 & \dots & 0 & h[n-1] & c[n] \end{bmatrix} = \begin{bmatrix} y^*[2] \\ y^*[3] \\ y^*[4] \\ \dots \\ y^*[n-1] \\ y^*[n] \end{bmatrix} = \begin{bmatrix} d[2] \\ d[3] \\ d[4] \\ \dots \\ y^*[n-1] \\ y^*[n] \end{bmatrix}$$
 where
$$c[i] = 2 \cdot (h[i-1] + h[i]) \text{ for } i = 2, \dots, n-1$$

$$c[n] = 2 \cdot (h[1] + h[n-1])$$

$$d[i] = 6 \cdot \left(\frac{y[i+1] - y[i]}{h[i]} - \frac{y[i] - y[i-1]}{h[n-1]} \right) \text{ for } i = 2, \dots, n-1$$

$$d[n] = 6 \cdot \left(\frac{y[2] - y[1]}{h[1]} - \frac{y[n] - y[n-1]}{h[n-1]} \right)$$

Table 5: Matrix form of periodic spline function

HAUPAU

Is Getting A Fast Reputation.



ing a fast reputation with their 87 Math Pak, the combination of an 87 chip and 87 Software Pak that's been accelerating PC math since 1982.

Next came their racy 287 FAST/5, a math coprocessor module with its own 5MHz clock, speeding up PC/AT math by 25%. (Pictured above.)

Now, Hauppauge Unveils the 287 FAST/10...

Our newest math coprocessor for the PC/AT, the 287 FAST/10 moves out at 8MHz-more than doubling the speed of each floating point math operation. The FAST/10 accelerates AutoCad, 1-2-3, Symphony, Turbo Pascal, Framework and more. The FAST/10 also runs in PC/AT compatibles including the Compaq Deskpro 286, Sperry PC/IT and most 286 accelerator boards.

... And the 87 Software Pak Version 6.0

Designed to steal the heart of programmers, the 87 Software Pak supports IBM's BASIC Compiler 1.0 and 2.0, and Microsoft's QuickBASIC, executing math-intensive programs up to 20 times faster! The 87 Software Pak also performs FFT's and Matrix operations. For example, a PC (or PC/XT) with an 87 Chip and 87 Software Pak can perform a 512-point complex FFT in just 1.1 seconds. What's more, a PC/AT with a FAST/10 inverts a 25 by 25 element matrix in under 1 second.

Circle no. 274 on reader service card.

(Pronounced "Ha-pog")

HAUPPAUGE Math Coprocessors 287 FAST/10 10MHz math coprocessor for PC/AT and compatibles.....\$469 287 FAST/8 8MHz math coprocessor for PC/AT and compatibles\$379 287 Chip PC/AT math coprocessor-runs at 4MHz in the old model IBM PC/AT and 5.33 MHz in the new

model PC/AT\$219 87 Chip Math coprocessor for IBM PC, PC/XT and compatibles.....\$129 87-2 Chip Math coprocessor for 8MHz PC compatibles...\$195 HAUPPAUGE Math Coprocessor Paks 87 Math Pak V.6.0 87 chip and math coprocessor software support for IBM BASIC Compiler 1.0, 2.0 and Microsoft's QuickBASIC. Plus, Matrix and FFT support, one year of free updates, complete source code and "8087 Applications and page 12.7. Programming"\$279 87 Software Pak V.6.0 Math coprocessor software support as in the 87 Math Pak, but without 87 chip\$180 With any Hauppauge math coprocessor\$150 Recalc + Math coprocessor support for 1-2-3 version 1A .. \$ 95 With any Hauppauge math coprocessor \$ 49 HFT + Complete Hayes Fourier Transform Package\$125 With any Hauppauge math coprocessor \$ 79

The 287 FAST/8 Doubles Your PC/AT's Math Speed! Help your PC/AT get a fast reputation with Hauppauge's new 287 FAST/8. Call today, or contact your local computer dealer to learn more about Hauppauge's racy product line. And ask for "87 Q & A," our free booklet on math coprocessors.

Hauppauge Computer Works, Inc. 358 Veterans Memorial Highway, Suite MSI, Commack, New York, USA 11725 516-360-3827 • TELEX: 262939-HCW

(continued from page 28)

also specify a linear combination of first and second derivatives at the endpoints. The two examples presented here, however, will generally prove the most useful for interpolative curve fitting.

Specifying the end conditions and solving the appropriate set of linear equations gives you the coefficients you need to solve your interpolation equation. (Note that this equation remains the same no matter what end conditions have been specified.) For any given value of x within the range of values spanned by the knots, you need only determine the two knots between which the value lies. This gives you the value of i to insert in the interpolation equation and with it the appropriate coefficients y''[i] and

```
/* Initialize array e[] as nth column of matrix M[][] */
e[2] = h[1]
for i = 3 to i = n-2
   begin
       e[i] = 0
e[n-1] = h[n-1]
e[n] = c[n]
/* Initialize variable f as matrix element M[n][1] */
f = h[1]
/* Reduce matrix to upper triangular form */
 for i = 2 to i = n-2
    begin
        c[i+1] = c[i+1] - h[i] * h[i]/c[i]
        d[i+1] = d[i+1] - d[i] * h[i]/c[i]
        e[i+1] = e[i+1] - e[i] * h[i]/c[i]
        d[n] = d[n] - d[i] * f/c[i]
        e[n] = e[n] - e[i] * f/c[i]
        f = -f * h[i]/c[i] /* Now matrix element M[n][i] */
    f = f + h[n-1] /* Now matrix element M[n][n-1] */
     d[n] = d[n] - d[n-1] * f/c[n-1]
     e[n] = e[n] - e[n-1] * f/c[n-1]
 /* Solve using back substitution */
 y''[n] = d[n]/e[n]
 y''[n-1] = (d[n-1] - e[n-1] * y''[n])/c[n-1]
 for i = n-2 to i = 2
     begin
        y''[i] = (d[i] - h[i] * y''[i+1] - e[i] * y''[n])/c[i]
  y''[1] = y''[n] /* End condition */
```

Table 6: Algorithm 2: Periodic spline coefficient determination

y"[i+1] to use in solving for the corresponding y coordinate.

What about the related problem of fitting a smooth surface to data plotted in three dimensions? If the data is regularly spaced in two of those dimensions (say the x-y plane), you can calculate a family of curves in parallel x-z planes. Each curve is the intersection of the x-z plane with the surface. Then, for any perpendicular y-z plane, your knots are the intersection of the x-z plane curves with the y-z plane. From these, you can calculate the intersection of your surface with the y-z plane. With this method, you can determine any point on the surface uniquely.

Final Words

I could have demonstrated the above algorithms using a small BASIC program; however, the Unix operating system offers a utility called spline that is much more comprehensive. Heeding once again Richard Stallman's call ("The GNU Manifesto," DDJ, March 1985) for placing Unix in the public domain ("FGREP," DDJ, September 1985, was my previous response), the accompanying "demonstration" program (SPLINE.C) is a full emulation of the Unix spline utility. (See Listing One, page 72.)

If you would rather not spend an evening or two entering and (inevitably) debugging SPLINE.C, you can purchase machine-readable versions for \$35 from byHeart Software, 620 Ballantree Rd., West Vancouver, BC V7S 1W3, Canada. Supported disk formats are CP/M 8-inch SSSD and MS-DOS (2.x) 51/4-inch DSDD. Included on the disk are the source code in C for SPLINE.C and FGREP.C, their executable programs, and the text from this article and "Parallel Pattern Matching and FGREP" (DDJ, September 1985).

Cubic splines are an elegant solution to the problem of fitting curves to a set of given points in an x-y plane. An understanding of the mathematics used to develop them is not essential. The simplicity and efficiency of the algorithms involved should encourage anyone interested in graphics or data analysis to add cubic splines to their software toolboxes.

Bibliography

Bell Telephone Laboratories. *UNIX Programmer's Manual*, vol. 1. New York: Holt, Rinehart & Winston, 1983. 145. Forsythe, George; Malcolm, Michael; and Moler, Cleve. *Computer Methods for Mathematical Computations*. Englewood Cliffs, N.J.: Prentice-Hall, 1977. 70—83. Hamming, R. W. *Numerical Methods for Scientists and Engineers*. 2d ed. New York: McGraw-Hill, 1973. 349—355. Hildebrand, F. B. *Introduction to Numerical Analysis*. New York: McGraw-Hill, 1974. 478—494.

DDJ

(Listing begins on page 72.)

Vote for your favorite feature/article. Circle Reader Service No. 2.



ANOTHER PLUS FROM BLAISE COMPUTING

The best just got better! Turbo POWER TOOLS, acclaimed as the best programmer support package for Turbo Pascal, now has

even more functions, more detailed documentation and more sample programs.

NO SECRETS

Turbo POWER TOOLS PLUS is crafted so that the source is efficient, readable and easy to modify. We don't keep secrets! We tell you exactly how windows are managed, how interrupt service routines can be written in Turbo Pascal, and how to write memory resident programs that can even access the disk. Maybe you've heard of some undocumented DOS features that resident programs use to weave their magic. Turbo POWER TOOLS PLUS documents these features and lets you make your own magic!

Here's just part of the PLUS in Turbo POWER TOOLS PLUS:

- WINDOWS that are stackable, removable, with optional borders and a cursor memory.
- FAST DIRECT VIDEO ACCESS for efficiency.
- SCREEN HANDLING including multiple monitor and EGA 43-line
- POP-UP MENUS which are flexible, efficient and easy to use, giving your applications that polished look.
- INTERRUPT SERVICE ROUTINES that can be written in Turbo Pascal without the need for assembly language or inline code.

Power Tools Plus[™] Window Routines. Memory Resident Routines.

◆ INTERVENTION CODE lets you develop memory resident applications that can take full advantage of DOS capabilities. With simple procedure calls, you can "schedule" a Turbo Pascal procedure to execute either when a "hot key" is pressed, or at a specified time.

PROGRAM CONTROL ROUTINES allow you to run other programs from Turbo Pascal, and even execute DOS

▶ MEMORY MANAGEMENT allows you to monitor, allocate and free DOScontrolled memory.

DIRECTORY AND FILE HAN-DLING support to let you take advantage of the newer featu including networking.

STRING procedures allowing powerful translation and conversion capabilities.

 FULL SOURCE CODE for all included routines, sample programs and utilities.

DOCUMENTATION. TECHNICAL SUPPORT and attention to detail that

Routinely.

Another quality product from Blaise Computing: Turbo ASYNCH PLUS"

\$99.95.

have distinguished

Blaise Computing

Turbo POWER TOOLS PLUS sup-

ports Turbo Pascal

Version 2.0 and

later and is just

over the years.

A new package which provides the crucial core of hardware interrupt support needed to build applications that communicate. ASYNCH PLUS offers simultaneous buffered input and output to both COM ports at speeds up to 9600 baud. The XON/XOFF protocol is supported. Now it also includes the "XMODEM" file-transfer protocol and support for Hayes compatible modems.

The underlying functions of Turbo ASYNCH PLUS are carefully crafted in assembler for efficiency and drive the UART and programmable interrupt controller chips directly. These functions, installed as a runtime resident system, require just 3.2K bytes. The high level function are all written in Turbo Pascal in the same style and format as Turbo POWER TOOLS PLUS. All source code is included for just

BLAISE COMPUTING INC.

2560 Ninth Street, Suite 316 Berkeley, CA 94710 (415) 540-5441

Circle no. 159 on reader service card.

res of DOS	ORDER TOLL-FREE 800-227-8087
	Calif. residents call (415) 540-5441
	for
	Enclosed is \$
Fare cond n	ne the PLUS I need! Enclosed is \$ for pure the PLUS I need! Turbo ASYNCH PLUS T
YES, send	ne the PLUS I need! Enclosed is \$_\text{WER TOOLS PLUS} \subseteq \text{Turbo ASYNCH PLUS} \subseteq \text{WER TOOLS PLUS} \subseteq \text{Turbo ASYNCH PLUS} \subseteq CA residents add 6\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Turboro	me the PLUS I need: ☐ Turbo ASYNCH PLOS DWER TOOLS PLUS ☐ Turbo ASYNCH PLOS DWER TOOLS PLUS ☐ Turbo ASYNCH PLOS DWER TOOLS PLUS ☐ Turbo ASYNCH PLOS WELL STORT OF THE TOOLS OF THE PLOS O
OTHER	rders add \$10.00 for 1000
domestic	WER TOOLS PLOS (CA residents add 6½% Sales Tax (CA residents add 6½% Sales Tax rders add \$10.00 for Federal Express shipping.) Phone: ()
Mame'	
Name.	Address: State: Zip:
Shipping	Address: Zip:
	StateExp. Date:
City: —	
VISA or	MC #:

Reprinted from PC Magazine, June 10, 1986 Copyright © 1986 Ziff-Davis Publishing Company

A General First-Order Sorting Algorithm

ost widely used sorting algorithms, such as the Shell sort and quicksort, require a sorting time approximately proportional to $nlog_2n$, where n is the number of sort keys, whereas the bubble sort requires a time proportional to n^2 . Often it is stated erroneously that it has been proved that no sorting algorithm can improve on an $nlog_2n$ time. The proof refers only to algorithms based on exchanges, however, as Knuth states clearly in volume 3 of his series *The Art of Computer Programming*.

There is a sort algorithm called the radix sort that is not based on exchanges. This sort has been known and used since long before the time of electronic computers and was generally used for sorting punched cards, but it does not seem to have been widely adapted for computer use. The time required to do such a sort is proportional to n.

In seeking a reason for the slighting of this algorithm, which I have used successfully on a variety of computers for about 20 years, I have come to the following conclusion. There must be an intuitive feeling on the part of programmers that, whereas sorts requiring time kin will always be faster than those requiring k2n log2n when the value of n is sufficiently great (where k1 and k2 are arbitrary constants), for practical values of n that fit into a computer's RAM, k1 is sufficiently greater than k2 to nullify the advantage. As I will demonstrate, this assumption is invalid in many cases.

Robert A. McIvor, 3100 Carling Ave., Apt. 920, Nepean, ON K2B 6J6, Canada by Robert A. McIvor

This linear-time sort was once used on punched cards.

How the Radix Sort Works

The basis of the radix sort algorithm is to divide the sort keys into two lists, with their placement in a list being dependent on whether the least significant bit is set or not. The two lists are then concatenated with the list in which the bit is not set placed first. This step is repeated for each bit in each sort key, working from the least significant end to the most significant end. When this procedure is complete, the file is sorted.

The chief disadvantage of this method when compared to exchange sorts is that the time required for completion has the same dependence on the number of bytes in the key as it does for the number of keys—that is, it takes the same time to sort 10,000 1-byte records and 1,000 10-byte records. Exchange sorts, on the other hand, are much less dependent on key length than on the number of keys because it is usually unnecessary to compare every byte in two keys to determine which is the greater.

Another possible disadvantage of the algorithm as presented here (a sort algorithm for linked lists) is the additional space overhead required. Each key must have an additional 2-4 bytes allotted for a pointer address. Although this is perhaps unreasonable for 1-byte sort keys, the

disadvantage becomes less and less significant with longer sort keys. Furthermore, if the data to be sorted is already in a linked list, no additional space is required. For sorts in which keys must be extracted from a record and manipulated to perform special sorts, such as sorting signed numbers, sorting in reverse order, or sorting in a special collation order, forming a linked list of the sort keys does not usually entail much additional effort.

The Test Programs

Listing One, page 86, is the radix sort as coded for the Macintosh in Aztec C. The include files are needed to provide the definitions of Random() and TickCount() used in the timing routine. The routine MaxApplZone() provides space in the application heap for the sort keys. It must be called before anything else, and the lmalloc must be given a noncalculated number or the exit branch of insufficient space is taken. Also, the call seems to be required in the routine in which the allocation occurs. RAM disks and cache programs for the Macintosh may have adjusted the application heap, leaving no space for allocation. Allocation is necessary for record counts in the thousands because the space permitted for data declared in the program is limited. KEYSIZ (the size of the sort key) is declared at compile time to avoid editing for each change.

The sort program is passed the key size and the pointer to the first record. Two additional pointers (first and last) follow the two lists created at each pass, whose heads are given by the pointers start and start2. The pointer temp follows the combined list during each pass. Each bit from

of Record	is						Bytes in h	(ey				
	1 -	2	3	4	5	6	7	8	9	10	11	12
1000	19	37	56	74	92	112	130	149	168	186	205	223
2000	37	74	111	148	185	223	260	297	335	372	409	443
3000	56	111	166	222	277	334	390	446	502	557	613	663
4000	74	148	221	295	369	446	520	594	670	743	818	885
5000	93	185	278	369	462	557	650	743	835	929	1022	1107
6000	112	222	333	443	554	669	780	892	1002	1115	1225	1328
7000	131	259	388	517	646	780	910	1040	1170	1301	1430	1549
8000	149	296	444	590	739	891	1040	1189	1336	1486	1634	1770
9000	167	333	500	665	831	1002	1170	1337	1504	1671	1838	1992
10000	186	370	554	739	923	1114	1300	1485	1672	1856	2042	
Times are	in 60ths	of a secon	nd.					1 100	1012	1030	2042	2213

Table 1: Execution times of radix sort on Macintosh

Number												
of Record	ds						Bytes in I	(ev				
	1	2	3	4	5	6	7	8	9	10		
1000	104	129	146	162	176	203	205	229	254	250	11	12
2000	256	321	344	389	446	509	502	515	599	584	240	290
3000	388	537	562	623	717	783	822	848	933	1034	617	685
4000	570	775	857	966	1136	1245	1185	1255	1475	1464	069	095
5000	778	957	1149	1228	1516	1554	1549	1630	1909	1929	1571	1685
6000	930	1240	333	1462	1788	1902	1936	1942	2205	2410	2112	2148
7000	1044	1547	1645	1774	2034	2287	2471	2437	2771	3062	2552	2762
8000	1347	930	2111	2429	2806	2859	2975	3087	3616		3170	3295
9000	1511	2069	2212	2483	3008	3257	3057	3270	3856	3625	3855	4240
10000	1736	2400	2639	2899	3544	3648	3845	4270	4668	4111 4695	4482 4688	4563 5216

Table 2: Execution times of Shell sort on Macintosh

Key Count					Sort Key	Length in	Bytes				
1000	1 26.7 5.4	30.3 10.8	3 33.2 16.2	4 34.6 21.6	5 37.2 27.0	6 39.8 32.4	7 42.5 37.8	8 46.0 43.2	9 47.5 48.6	10 48.1	
2000	60.7 10.8	68.2 21.6	81.2 32.4	85.4 43.2	94.4 54.0	101.0 64.8	105.0 75.6	118.0 86.4	118.0	54.0 118.2	
3000	92.1 16.2	132.0 32.4				04.0	73.0	00.4	97.2	108.0 198.0	
4000	138.0 21.6	188.0 43.2								162.0	
5000	188.0 27.0	267.0 54.0									
6000	239.0 32.4										
7000	264.0 37.8										
8000	328.0 43.2										
9000	406.0 48.6										
10000	438.0 54.0										
11000	459.0	alculated)									
2000	535.0	alculated)									

Table 3: Comparative sort time in seconds for Shell sort and radix sort on Z80

SORTING ALGORITHM (continued from page 32)

least to most significant is isolated in turn, and the byte is added to the *first* and *last* lists depending on whether it is 0 or 1. When the end of the *temp* list is reached, the *last* list is terminated with a 0 pointer, and the last member of the *first* list is pointed to the head of the *last* list (*start2*). When all bits have been traversed, the pointer *start*, which points to the head of the sorted list, is returned. In addition, checks are made for empty lists, and the appropriate action is taken.

I compared the radix sort algorithm times with those obtained from the Shell sort algorithm given on page 116 of *The C Programming Language* by Kernighan and Ritchie. I've provided a listing of my version of the Shell sort for comparison (Listing Two, page 87). The initialization, of course, is different for the Macintosh.

Some Test Results

In both the radix and the Shell sorts, a random function was used to pro-

vide data for sorting. The times for the radix sort, unlike those for the Shell sort, are data independent. Tables 1 and 2, page 33, show the sort times for the radix and Shell sorts on a 512K Macintosh.

I also programmed the algorithms in BDS C for a Z80 computer running at 2 MHz. In both cases the radix sort is superior for sort keys shorter than 12 bytes when the number of records exceeds 1,000. For 10,000 1-byte records, the radix sort is more than nine times faster. The crossover point for 12-byte keys occurs at approximately 500 records, and for keys of 7 bytes or less, the crossover is at 100 or fewer records. Table 3, page 33, shows the results for the Z80 system.

The execution time of the radix sort for the Z80 system can be expressed by the formula (5.4×10^{-3}) mn seconds, where m is the number of bytes in the sort key and n the number of keys to be sorted. The Macintosh execution time was (3.11×10^{-4}) mn seconds—more than 17 times faster. The ratio of times for the Shell sort was similar.

The radix sort algorithm was also coded in Z80 assembly language. The run times are approximately six times faster—the measured time for the radix sort was (9.1×10⁻⁴)mn seconds at 2 MHz.

You might think that by masking two bits at a time and dividing the keys into four lists, an additional time savings of about 50 percent would be achieved. In fact, the saving is only about 17 percent because of the increased overhead in the inner loop.

Bibliography

Kernighan, Brian W., and Dennis M. Ritchie. *The C Programming Language*. Englewood Cliffs, N.J.: Prentice-Hall, 1978.

Knuth, Donald. The Art of Computer Programming, Volume 3. Sorting and Searching. Reading, Mass.: Addison-Wesley, 1969.

DDJ

(Listings begin on page 86.)

Vote for your favorite feature/article. Circle Reader Service No. 3.

FOR CHIN

WINDOWS FOR DATATM

DATA THE HELP

DATA ENTRY

Windows for Data does the hard jobs that others can't — we guarantee it. Makes standard display and entry tasks

DATA ENTRY: The most complete and flexible data entry system on the market. Pop-up data-entry windows; field types for all C data types, plus decimals, dates, and times; auto conversion to and from strings for all field types; system and user-supplied validation functions; range-checking; scrollable context-sensitive help; required and must-fill fields; programmer-definable edit keys, field types, and field masks. Read field by field or auto-read all fields. Branch and nest window forms. Virtually every capability of WFD can be modified to meet special needs.

easy. Reliable. Compact. Portable.

WINDOWS: WFD is built upon and includes Windows for C, the windowing system rated #1 in PC Tech Journal (William Hunt, July 1985). WFC now has more features than ever, including automatic full compatibility with Microsoft Windows and TopView.

UNPRECEDENTED FLEXIBILITY

WINDOWS



As many possibilities as Vermont in June.

MENUS: Build multi-level menus in the format of Lotus 1-2-3, Macintosh, or a style of your own choosing.

HELP: Build context-sensitive or menudriven help systems. Display text in pop-up, scrollable windows.

UNIX, DOS, OR BOTH

WFC and WFD provide source code compatibility between PCDOS and UNIX.

OUR CHALLENGE AND GUARANTEE

If you have an application where no other tool can do the job, try **Windows for Data**. If it doesn't help you solve your problem, RETURN FOR A FULL REFUND. YOU MUST BE SATISFIED.

WINDOWS WINDOWS FOR DATA FOR C

PC DOS* \$295 \$195 XENIX-286 \$595 \$395 UNIX CALL CALL

Call for **FREE Demo diskette**.
*All popular C compilers; no royalties.



21 Elm Ave. Richford, VT 05476 **802-848-7738**, ext. 31.

MasterCard & Visa Accepted. Shipping \$3.50 VT residents add 4% tax.

NEW!!

TURBO

SCREEN/APPLICATION GENERATOR

Give your application a Turbo Boost with the Most Advanced Turbo Pascal Environment Available. Have Turbo Master generate your screen, file handling and menu Programs. For \$99.95 receive 6 Floppy Disks & Manual.

TURBO ISAM MASTER

Generates 'Ready to Run' Turbo Programs Using BORLAND'S Turbo Pascals Database TOOLBOX or optional SOFTCRAFT'S BTRIEVE.

With a few key strokes you can generate the following Pascal programs/includes files. Automatically interfaces to Turbo Screen Master.

- MASTER DATABASE PROGRAM Generates Pascal Program Code for the following functions
- -Add a Record Allows both duplicate & unique only keys. Change the up to 48 fields comprising the primary key and the up to 7 secondary keys at any time during input, and the validity of the keys are checked and the ISAM key files are automatically adjusted.
- -Delete a Record Shows the record to be deleted on the screen and allows you to change your mind about deleting, and then adjusts the keys files automatically for the up to 8 keys. The disk space is reused automatically by the programs.
- -Edit a Record with a key change allowed. -Search Database by Key - The ability to display the keys on the screen or printer in sorted order.
- DATA BASE RECOVERY PROGRAM. This program recovers your database if it corrupted by a power outage or certain hardware failures.
- MULTIPLE ISAM FILES Can be used at the same time in a single program. The generator also produces context sensitive instructions on how to integrate the generated program into your main program.
- **DOCUMENTATION** Print screens and ISAM specifications. Also inline program documentation is generated.

TURBO MENU MASTER

GENERATES 'Ready to Run' Turbo Programs with Dedicated Screens or Windows.

FEATURES: Has Menu Data Base so it's easy to modify menus.

PROVIDES SELECTION BY:

- -Press of a number
- -Press of a function key
- -Press the high lighted letter
- -Use the arrow keys

ADAPTIVE SCREEN COLORS - Different screen colors are automatically used for color or monochrome display. This allows you to provide a better interface for the user.

INTERACTIVE MENU BUILDER

- -Allows for the automatic entry and reorder of selections
- -Offers easy color selection
- -Allows for choice of procedure, chain, execute or comment code generation for each selection
- -Has startup Menu that YOU design.
- -Provides for the integrated Display and control of the Key Lock Status.

URBO RESIDENT SCREEN CAPTURE

hich allows you to capture Text creens from any running program.

TURBO SCREEN MASTER

GENERATES 'Ready to Run' Mulit-screen programs with advanced field definition.

- USER SPECIFIED PROCEDURES can be called before and after data entry for each field. This allows SCREEN GENERATION THAT IS INDEPENDENT OF USER INSERTED PRO-GRAM STATEMENTS.
- YOU CAN CUSTOM PROGRAM special field edits and processes which Screen Master automatically includes into the screen program. This allows for "On the Fly FUNCTION KEY AND WINDOW ROUTINES.
- **RECORD FORMATS** and initialization routines for Structures and Arrays are automatically generated.
- CAN SPECIFY a Protected Field to be automatically redisplayed if its value changes.
- TYPES INCLUDE Strings, Yes/No, Time, Male/Female and Numbers.
- FIELDS CAN BE STORED (declared) as Boolean, Integer, Real, Character, or String.

2000年,1000年	MENTAL STREET	The state of the s
COMPARISON WITH OTHER PRODUCTS	TURBO SCREEN MASTER	SCREEN SCULPTURE Ver - 1.01
Full support for structures, arrays and Declarations specifications Full support for user written pro- cedures, function keys & help	YES	NO
screens	YES	NO
Etch-A-Sketch Border Drawings	YES	NO
Point and Paint color interaction	YES	YES
Border color control	YES	NO
User defined valid character sets	YES	NO
Display of Caps/Num Lock Status Optional realtime initialization of	YES	NO
data/time	YES	NO

TURBO RESIDENT ISAM

Replaces Borland's Toolbox ISAM method

- Eliminates 8k of code space that Borland's Turbo Toolbox ISAM requires in your program.
- Puts the Key Buffer Data Area outside of your program's data space.
- Speeds Compling
- Eliminates errors caused by inconsistant ISAM specifications between ISAM files.
- Increases program loading time.
- Reduces object program size.
- Offers SUPER-FAST record creation and lookup. For example, it can CREATE over 20 single key records PER SECOND on an IBM AT running at a 9 meg clock rate.

OUR USERS REPORT

- "Since Fall of 85, I have generated over 300 program modules with it and find it to be just what I needed. Most of all the modules represent 5000 to 8000 lines of Pascal Code" Oner Systems
- "By being able to produce a 21 screen and menu control demo so quickly helped me obtain the contract.'
- "Speeded up my screen development by 6 times" Elexor Associates.
- "Has many of the features of the Super Mini development tools costing \$10,000." Applied Micro Systems.
- "We developed 3 Vertical Market Applications in the 6 months we had your system." Absolute

******* *BTRIEVE INTERFACE MODULE

- ¥ Allows full multiuser record locking and ★
- ¥ Automatic file recovery for the industry's ★
- ¥ most popular LANs. Works with the in-★
- * for multiuser LAN's (optional). * Requires Btrieve by SoftCraft, Inc.
- ***********

TURBO MASTER TOOLS

The Turbo Toolkit Master includes procedures for full control over all screen attributes, advanced string functions, automatic control of multiple help screens, saving and retrieving screens to RAM buffers, Caps/Num/Scroll/Lock control procedures, and report procedures.

RISK FREE TRIAL

Try the demo package included for 30 days. If not pleased return for a full refund.

Credit Card Orders Call:

1-800-821-9503 In Florida (800) 342-0137

For Other Information Call (305) 892-5686

NO ROYALTIES on Generated Programs

VEC	ENICI	OSED	10
1 - 0.	EINCI	USELL	

- **Turbo Master Tools**
- Turbo Menu Master
- Turbo Screen Master \$995 **Turbo ISAM Master**
- Turbo Screen Capture
- Resident ISAM

Systems Requires: IBM PC,XT,AT or 100% Compatible -246K MS DOS 2.0 or Higher, Turbo Pascal 3.0 - 2 DD/DS

US orders add \$7.50 S&H

All foreign orders add \$15 per product ordered.

Name: _Phone: __

Shipping Address:

City:

VISA or MC #: _

Exp. Date _

C.O.D.'s will be accepted. Outside USA: make payment by bank draft, payable in US dollars drawn on a US bank.

Turbo Pascal & Turbo Database Toolbox are trademarks of Borland International, IBM is a trademark of International Business Machines, MS-DOS is a trademark of Microsoft. Btrieve is a trademark of Softcraft, Inc. Screen Sculpture is a trademark of softcraft of the Software Bottling Co. of New York. © 1985 Hawaiian Village Com-

HAWAIIAN VILLAGE COMPUTER SOFTWARE

1109 Pennsylvania Ave., St. Cloud, Florida 32769

Turbo Prolog: The Language

true. I had to believe it.

A software developer of my acquaintance had designed an AI product and was searching for the best development environment for its implementation. Having worked with *PROLOG*, he knew he wanted to use it, if he could only find an implementation that met his needs. Bor-

he story was too good to be

PROLOG compiler—not an interpreter, but a compiler—and would be selling it for less than \$100. Even though price was not his biggest concern, he felt he owed it to prudence to check this out. He called Borland.

land, he heard, had acquired a fast

Because he had a product in the works, the developer's questions were specific and technical, just as, because Borland had not yet released the product and had not developed it in-house, the answers he got initially were vague and unsatisfying. Persevering, he finally penetrated deep within the company to one programmer who really knew the product, the in-house expert. Although the programmer was knowledgeable and forthright, some of his answers surprised the developer, who consequently posed even more probing questions about the features and capabilities of the implementation, eliciting even more—to the developer surprising answers. Finally, the programmer blurted out, "Well, you know it's not PROLOG; it's Turbo Prolog.

Apocryphal, no doubt. One of the goals of this review will be to decide what poetic truth there may be in the story.

Michael Swaine, 501 Galveston Dr., Redwood City, CA 94063.

by Michael Swaine

The cut operator is the feature PROLOG most needs to lose.

"Core" PROLOG

PROLOG is a declarative as opposed to an imperative language, meaning that a program consists of a set of statements of fact rather than of a list of instructions. The language itself has the ability to do some of what in other languages is the programmer's job because PROLOG embodies an inference engine based on the techniques of resolution and unification. Resolution as a language basis is known to be logically complete in the sense that it can generate any of the logical implications of the facts and rules in a knowledge base. The imperative mode, the flow of control, and the logical inference process in a PROLOG program are all handled on an application-independent basis by the interpreter-or, now that PRO-LOG compilers are coming into being, at any rate not by the programmer. In principle, the programmer simply throws statements at PROLOG, and PROLOG deduces what is deducible (prompted by questions, referred to in PROLOG as goals).

If the above description makes the programmer's job sound too simple, note that the statements can be contingencies on variables, such as these two statements:

grandfather(X,G):-

father(P,G), mother(X,P).
grandfather(X,G):father(P,G), father(X,P).

which state that the grandfather relationship holds between entities X and G if the father relationship holds between P and G and the mother relationship holds between X and Y, or if the father relationship holds between Y and Y are rules, together with a database of facts such as the following about parents and their children:

mother(john, rita). father(jacob, eli). father(rita, luigi). father(john, jacob).

permit automatic deduction of implications, as in the following dialogue:

you: grandfather(john,G)

program: G = eliprogram: G = luigi

in which you ask for and receive the names of John's grandparents.

Despite the curious fact that the order of statements (for example, the order of the four statements about parenthood above) is often irrelevant to the successful execution of PROLOG programs, it is quite relevant to their efficient execution, and a PROLOG programmer has to expend some effort structuring programs for efficiency.

For a solid presentation of PROLOG, you should read *Programming in Prolog*, second edition, by W. F. Clocksin and C. F. Mellish. A good introduction for programmers is Dave Cortesi's "Tour of PROLOG" (DDJ, March 1985). Details of these and other sources are

listed at the end of this review.

What you won't find anywhere is the official definition of the language. Not only is there no such thing as standard PROLOG, but it's also not even clear that PROLOG is a language by evervone's definition. The closest thing we have to an official, broadly accepted definition is Clocksin and Mellish's "core" PROLOG. Clocksin and Mellish. though, are more descriptive than prescriptive regarding linguistic diversity and even seem to acknowledge that PROLOG may be less important as a language in itself than for the more powerful languages that will be developed in it or from it. PROLOG, they say in the preface to the second edition of their book, "is now seen as a potential basis for an important new generation of programming languages and systems."

PROLOG as it now stands has some deficiencies, and we have reason to look forward to that new generation of programming languages. For one thing, one of the few mechanisms for limiting explicitly the search space for solutions is the fairly awkward and implicit technique of ordering clauses and conjuncts. Another mechanism is the *cut* operator, which Clocksin and Mellish identify as the feature PROLOG most needs to lose.

Then there are the limitations of resolution, as discussed by Michael R. Genesereth and Matthew L. Ginsberg ("Logic Programming," Communications of the ACM, September 1985). A good logic programming system, they point out, needs to be able to "draw conclusions from uncertain data, reason analogically, and generalize its knowledge appropriately." That's not resolution, and it's not PROLOG.

What is PROLOG, officially? On page 111 of their book, Clocksin and Mellish erect a "core" PROLOG, built of the features most often found in existing implementations, on top of "pure" PROLOG; the built-in predicates many people regard as an integral part of the language proper are in fact part of the patchwork core, not the pure essence. The body of PROLOG explicitly put forth in Clocksin and Mellish is not a full language, and implementers have extended it as they saw fit. Finally, although Clocksin and Mellish have nevertheless cobbled together some sort of average implementation in their core PROLOG, a separate strand of development is represented by micro-PROLOG, a version with a radically different syntax, described in *micro-PROLOG: Programming in Logic* by K. L. Clark and F. G. McCabe.

Despite the limitations of resolution and the lack of definition of the PROLOG language, powerful and efficient implementations of PROLOG have been developed in Europe, Australia, Japan, and the United States. Several PC-based PROLOGs now exist (see the box below), one of the most interesting of which, at least in terms of claims being made about its speed, is Borland's Turbo Prolog. Judging by the discussions on *DDJ*'s CompuServe forum, there is much difference of opinion about the product.

Because there is no clear standard against which to weigh Turbo Prolog, and because vendors of other personal-computer-based PROLOG implementations seem to have had something else in mind when they developed their products, it makes sense to look at Turbo Prolog in isolation; DDJ does, however, plan to follow up on this review with a comparative review of PROLOG implementations. This review focuses on Borland's Turbo Prolog from

several directions: as an implementation of PROLOG, using Clocksin and Mellish core PROLOG as a soft standard; as a language and software development environment in its own right; as a learning environment; and as a phenomenon in the world of software tools. On the way, it addresses some of the claims being made about Turbo Prolog.

Claim 1: Not Full PROLOG

Turbo Prolog is not full PROLOG.

You hear this claim often, most often from PROLOG purists and Borland competitors. It's certainly true, even by a fairly flexible definition of the language, that Turbo Prolog lacks some of the requisite elements of a full PROLOG implementation. The left column of Table 1, page 38, shows the major features of core PROLOG that are missing in Turbo Prolog. Many syntactical differences are left out of the table; Turbo Prolog largely ignores core PROLOG I/O, substituting its own rich collection of I/O primitives, screen-handling functions, and graphics commands. The Borland syntax is eclectic.

Turbo Prolog does, however, provide the bulk of what makes up core PROLOG. (Henceforth I'll drop the word *core*, but keep in mind that I

MS-DOS PROLOG Implementations

Ada PROLOG Automated Design Associates 1570 Arran Way Dresher, PA 19025 (215) 646-4894

Arity/PROLOG Arity Corp. 336 Baker Ave. Concord, MA 07142

Turbo Prolog Borland International 4585 Scotts Valley Dr. Scotts Valley, CA 95066 (408) 438-8400

PROLOG/i and PROLOG/m Chalcedony Software 5580 La Jolla Blvd., #126B La Jolla, CA 92037 (619) 483-8513 PROLOG1 and PROLOG2 Expert Systems International 1150 First Ave. King of Prussia, PA 19406 (215) 337-2300

MPROLOG P500 Logicware 5000 Birch St. Newport Beach, CA 9260 (714) 476-3634

LPA Micro-PROLOG Professional Programming Logic Systems 31 Crescent Dr. Milford, CT 06460 (203) 877-7988

PROLOG-86 Solution Systems 335B Washington St. Norwell, MA 02061 (617) 659-1571

TURBO PROLOG (continued from page 37)

mean this soft standard when I refer to PROLOG.) Turbo Prolog is a declarative language built around a resolution-based inference engine. The implementation uses recursion and backtracking and supports the usual PROLOG flow-of-control tools of cut and fail and the explicit ordering of clauses and conjuncts to control program flow. Turbo Prolog also allows the programmer additional control via a compiler directive that checks for possible nondeterministic clauses. It supports, with some exceptions and extensions, Clocksin and Mellish syntax.

Perhaps the greatest shortcoming of Turbo Prolog as an implementation of PROLOG is the lack of what might be called "metalinguistic" functions and operators. Some of these supplied in PROLOG are arg, functor, name, op, clause, and call and the univ operator. In general, these functions allow the PROLOG program to examine itself, to operate on code as data, and to construct new clauses and goals undreamt of by the programmer.

Of these, some are less important than others; op allows extension of the operators of the language so that, for example, you could define ^to be the exponentiation operator that Borland didn't supply. This function is a handy tool, allowing the programmer to define the arity and structure (for example, two-argument infix) for new operators. But as Clocksin and Mellish point out, this capability is ultimately nothing more than a device for prettying up I/O; it adds no additional computational power.

Also, to some extent the metalinguistic predicates and operators are interchangeable or can be defined in terms of one another. You don't absolutely need the *univ* operator if you have both *functor* and *arg*, and vice versa. But either the *univ* operator or the combination of *functor* and *arg* is needed to map data structures and clauses (code elements) into one another so that in PROLOG code is truly data.

As an example of the power of these metalinguistic constructs, consider the following metainterpreter for PROLOG, adapted from Henryk Jan Komorowski and Shigeo Omori's article "A Model and an Implementation of a Logic Programming Environment," in the Proceedings of the ACM SIGPLAN 85 Symposium on Language Issues in Programming Environments. This code is also adapted from Clocksin and Mellish.

prove(true) :- !.
prove(P, <morePs>) : prove(P), prove(<morePs>).
prove(P) : clause(P, Body), prove(Body).

These clauses mean succeed when the argument is true; to prove a conjunction, prove the first clause, then prove the rest; and to prove one thing, find a clause in the database with that thing as its head and prove the body of the clause. This metainterpreter allows the programmer to redefine the action of the PROLOG interpreter, and it's the function clause, with its ability to examine code as data, that permits this.

This predicate *prove* is a simple version of the PROLOG *call*. The Turbo Prolog manual (p. 151) also defines an interpreter (called *call*) that uses Turbo Prolog's call-by-reference capability. The listing (unfortunately complicated by several typographical errors) suggests how you might build the missing metalinguistic elements.

Nevertheless, the claim that Turbo Prolog is not full PROLOG is justified, and that places limits on what you can do with it. Complex applications developed under existing PROLOG versions may require significant rethinking before they can be ported to Turbo. On the other hand, Turbo Prolog does provide something that other PROLOGs may not in its support of DOS calls and machine-language functions. This low-level support suggests that anything missing from the compiler can be supplied—if you're willing to write it yourself.

What may prove to be as great a hindrance to experienced PROLOG programmers using Turbo Prolog, though, are the features the language has that, from a purist's point of view, it shouldn't have. These features are also the greatest advantage Turbo Prolog might claim over more faithful implementations.

Claim 2: New Language

Turbo Prolog is not PROLOG at all but

Features in "core" PROLOG and not in Turbo Prolog

"metalinguistic" features: =.. (univ), arg, call, clause, functor, gensym, name, op. I/O: get0, get, put, read, tab, display, tell, telling, told, user, see, seeing, seen, reconsult.

Features in Turbo Prolog and not in "core" PROLOG

arithmetic: bitand, bitnot, bitxor, bitor, bitleft, bitright.

I/O: readIn, readchar, readint, readreal, readterm, writedevice, writef, about a dozen file functions, and a wealth of screen handling functions.

string handling and type conversion: about a dozen functions.

system access: bios, system, membyte, memword, portbyte, ptr_dword, storage, date, time.

Table 1: Major feature differences between "core" PROLOG and Turbo Prolog

goal
makewindow(1,7,7,"Source",0,0,20,35),
write("Which file to copy?"),
cursor(3,8),readln(X),
makewindow(2,7,7,"Destination",0,40,20,35),
write("What name for the copy?"),
cursor(3,8),readln(Y),
concat(X,"",X1),concat(X1,Y,Z),
concat("copy",Z,W),
makewindow(3,7,7,"Process",14,15,8,50),
write("Copying",X," to ",Y), cursor(2,3),
system(W).

Table 2: A Borland routine that gives users a window to DOS

Now available worldwide:

Prospero's professional language compilers for PCs and STs

PRO PASCAL & PRO FORTRAN-77:

FOR IBM PCs, XTs, ATs & COMPATIBLES, & ALL OTHER MS-DOS MACHINES. ALSO FOR ATARI ST, SINCLAIR QL

USE THE LANGUAGES THE PROFESSIONALS USE: PASCAL AND FORTRAN.

C is high on performance but low on safety, structure, portability and maintainability. Pascal is excellent for education and for longterm projects. Fortran gives you access to hundreds of existing programs - and uses established programming skills!

ISO-PASCAL

Pro Pascal is validated to ISO 7185 / ANSI 770X3.97 Class A (no errors) on the Z80 processor under CP/M and the 8088 processor under PC-DOS. This provides a guarantee that the compiler is complete and works perfectly.

FORTRAN-77

Pro Fortran-77 is a full implementation of ANSI Fortran-77 with no omissions and many useful extensions. Validation is imminent.

Prospero Compilers Work!

No known bugs when we ship - so you don't have to program around the holes.

"Lazy I/O" for interactive use.


Good Housekeeping

All files closed on exit from procedure

Hand-coded library

Produces compact and efficient programs.

- · software developers
- · universities and colleges
- · government and industry
- · students of computing
- · development of personal skills
- solving technical problems
- · training institutions



16 digit accuracy

Single and double precision IEEE format arithmetic gives 7 or 16 digit precision.

50,000 Lines Big

Compiles big programs >50,000 lines... >5,000 identifiers...Separate compilation to build libraries and massive program suites.

Jumbo

New Jumbo memory model with Pro Fortran-77 gives unrestricted access to all 640K under MS-DOS.

Compilers include

- · compiler
- · linker
- · run-time libraries
- · librarian
- · X-ref program
- · sample programs
- · 200+ page manual

Full GEM AES and VDI bindings supplied with Atari products and (on request) with Pro Pascal for MS-DOS.

Amstrad & Z80

Pro Pascal and Pro Fortran-66 are available for Z80 machines.

Symbolic debugger

16 bit versions include Probe - a superb symbolic debugger. You can view fully compiled code as source, backtrack, display and change variables using source names, check the calling stack, and break anywhere. Pro Fortran-77 version can also Debug and produce execution profiles.

Pascal «—» Fortran

Interlinkable code means you can use the best of both languages. Ask for details.

We Specialize

At Prospero we specialize in writing language compilers. We produce the best possible compilers, conforming to the appropriate standard, and giving programmers a secure base on which to build.

Quote: "Pro Pascal is not only ISOvalidated, it is also a superb-quality and very full software development tool." Personal Computer World Nov 1985



Circle no. 160 on reader service card.

Prospero compilers are used at more than 6000 sites around the world.

It's easy to order!

Credit card holders phone 011-441-741-8531. Mastercard, Visa, Diners & Amex accepted. Prospero's compilers are also available from good software dealers and distributors worldwide.

Reviews & Info

Call 011-441-741 8531 or write in for a free info pack with datasheets and magazine

New: Pro Fortran-77 for MS-DOS will be available in August/September 86.

Software distributors

Contact us for our Worldwide Distribution Guide.

US Distributors:

PC Brand 212-410-4001

Software Consulting

215-837-8484

Atari: Apex Resources 617-232-9686

Oreman Sales 504-468-2001

QL: A+ Computer Resources

603-357-1800

Quantum 201-328-8846

Call for worldwide distributor list

Prospero Software

LANGUAGES FOR MICROCOMPUTER PROFESSIONALS 190 CASTELNAU, LONDON SW13 9DH, ENGLAND TEL 01-741 8531 TELEX 8814396

Mail order service

Send this coupon with check to Prospero Software Ltd, 190 Castelnau, London SW13 9DH, England. Add \$5 shipping and allow 28 days for delivery.

Please supply (enter number required):

- Pro Fortran-77 for Atari ST at \$149
 - Pro Pascal for Atari ST at \$149
- Pro Fortran-77 for Sinclair QL at \$129
- Pro Pascal for Sinclair QL at \$129 Pro Fortran-77 for MS-DOS at \$495
- Pro Pascal for MS-DOS at \$390
- Pro Pascal for CP/M-86 at \$390

Special offer till 10/1/86: both Atari compilers for \$269

I enclose payment of \$

State/ Zip.....

Telephone No.... In case of query call 011-441-741 8531 or telex 8814396. Tick product name if you just require information!

TURBO PROLOG

(continued from page 38)

a new language.

"It's not PROLOG; it's Turbo Prolog."—apocryphal Borland programmer.

The right-hand column of Table 1 points out another way in which Borland's compiler deviates from PRO-LOG: by extending it and by being in some senses a richer language. Turbo Prolog allows access to memory, I/O ports, and BIOS routines via a bios predicate and to DOS via a predicate called system. Using the system predicate and the strong display facilities of Turbo Prolog, the programmer can easily give the user a window to DOS. The program shown in Table 2, page 38, is a Borland-supplied, window-oriented, file copy routine that shows the system predicate in action. As you see, it is virtually devoid of any PROLOG declarative flavor.

Because Turbo Prolog is compiled, certain features Clocksin and Mellish describe, such as *trace*, are imple-

mented in Turbo as compiler directives. Turbo Prolog also has some compiler directives expressly conceived to help assess efficiency of program structure in PROLOG, such as check_determ, check_cmpio, nowarnings, and diagnostics. These tools, which do such things as eliminating tail recursions and flagging possibly nondeterministic clauses, are needed in a language that provides as few explicit controls on program flow as does PROLOG. Turbo Prolog also maintains the programmer's variable names for postcompilation editing of source code.

You can, according to Borland (I haven't tested this), incorporate in your Turbo Prolog programs subroutines written in 8088 assembly language, FORTRAN, C, or Pascal (but not Turbo Pascal, yet). That alone won't make the routines PROLOG-like, of course. If you want to write components in some other language and have them perform PROLOG purposes, you may have to work a little: a single three-argument predicate

could conceivably require nine separate routines if implemented in assembly language because each permutation of instantiated and uninstantiated arguments could require different action.

Some of Turbo Prolog's deviations from PROLOG style—for example, Turbo Prolog's strict data typing—force rethinking of program logic. You could argue that strict data typing violates PROLOG design and limits usefulness and portability. Borland's manual defends the practice in terms of creating a more secure program development environment and reducing space requirements for the language.

There are other arguments for using some kind of data typing in PRO-LOG: Daniel Brand's article "On Typing in Prolog," in the January 1986 ACM SIGPLAN Notices presents arguments for at least one model of typed PROLOG. Brand claims his model has the advantages of improved program readability, reduced computation time because of fewer and shorter clauses and reduced search space, and reduced need for the cut operator. It requires an enhanced unification algorithm that checks data types before unifying clauses. This slows things down a little, but Brand thinks the cumulative effect is faster code. Turbo Prolog's approach is different but shares some of these advantages.

A related limitation of Turbo Prolog is the constraint that you can only assert facts, not rules, and this also retricts the product's usefulness.

Is Turbo Prolog truly PROLOG? If you need the full metalinguistic power of the core predicates that Clocksin and Mellish sketch out in Chapter 6 of their book, or if you will be porting a complex existing PROLOG system to the PC—no. Otherwise, consider this just a particularly deviant dialect among other deviations. The reason for Turbo Prolog's deviations from Clocksin and Mellish is clear: the programmers wanted to make it fast.

Claim 3: Faster

Turbo Prolog is faster than the Japanese fifth-generation language systems.

This claim comes from the Turbo Prolog manual (p. 4): "Turbo Prolog runs on a computer costing about

MS-DOS, UNIX, APPLE MAG, GP/M, NETWORKS and MORE. ONE G-Gree ISAM DOES THEM ALL!

The creator of Access Manager™ brings you the most powerful C source code, B+ Tree file handler: C-tree™

- multi-key ISAM and low-level B+ Tree routines
- complete C source code written to K&R standards
- single-user, network and multi-tasking capabilities
- fixed and variable record length data files
- virtually opened files accommodate limited file descriptors
- no royalties on application programs

8395 COMPLETE

Specify diskette format:


- 51/4" MS-DOS
- 8" CP/M
- 31/2" Mac
- 8" RT-11



For VISA, MC and COD orders call (314) 445-6833
FairCom
2606 Johnson Drive
Columbia, MO 65203

The following are trademarks: c-tree and the circular disk logo—FairCom; MS—Microsoft Inc.; CP/M and Access Manager—Digital Research Inc.; Unix—AT&T; Apple—Apple Computer Co.

Circle no. 93 on reader service card.



"It's Microsoft C, and I can get it to you the day after tomorrow."

> Bruce Lynch, President The Programmer's Shop

Informed buying shouldn't take longer and cost more. Bill doesn't buy his software on the spur of the moment. Nor does he make a purchase without evaluating a ton of packages. But he refuses to make a full-time job of it.


So he lets us do a lot of the groundwork for him. The Programmer's Shop offers Bill over 62 programming language implementations and 174 support programs, all from the same source. But we also give him informed product evaluations and recommendations based on his particular needs. And we offer a quarterly insider's newsletter on programming and industry trends, new tools and techniques.

It's nothing that we don't do for all of our 10,000 customers. We recommend evaluating software by getting detailed information from several different sources, including unbiased reports and reviews.

Is Microsoft C the best on the market? For Bill, sure. He wanted its tight code and needed its UNIX System V compatibility. And now Microsoft C Version 4.00 includes Microsoft CodeView,™ a source-level windowing debugger. Bill also liked the idea that we carry over 37 compatible support products for it. Including support libraries like CTree, Halo, Panel and PforCe. In the process, Bill learned quite a bit about C compilers.

C for yourself. Bill helped us compile a 16-page report of the objective opinions of 4 magazines, 14 users and 3 industry analysts: The C Test.

As an unbiased evaluation by users and professionals alike, The C Test is one of the most comprehensive and informative reports currently available on C development tools. It's only available from The Programmer's Shop. And it's yours free for the asking. Here's what you'll find in it:



Benchmark Source Code
 Magazine Reviews

Users' Feedback
 Performance Benchmarks

User Study and Profiles
 Test Drive Survey Results

37 Compatible Products

The C Test will give you the satisfaction of knowing you made the right choice from among all of the alternatives.

Call us for more than a bargain. Call us for advice. The Programmer's Shop specializes in making life easier, more informed and less expensive for people like Bill Davidsen. And you. We've become a success by giving the best advice for free and selling the best software for less.

Call us now with any question about your next software purchase. Given your needs and budget, we'll tell you

what we suggest. Free.

To order Microsoft C (\$319) or for your free copy of The C Test, simply call the toll-free number below:

1-800-421-8006. In Massachusetts, call 1-800-442-8070.

MICR⊕SOFT. C Compiler Version 4.00

MICROSOFT C COMPILER

 Produces fast executables and optimized code including elimination of common sub-expressions. NEW!

Implements register variables.

- Small, Medium and Large Memory model libraries.
 Compact and HUGE memory model libraries. NEW!
 Can mix models with NEAR, FAR and the new HUGE pointers.
 Library routines implement most of UNIX™ System V C library.
 Start-up source code to help create ROMable code. NEW!
 Full proposed ANIX C library contact (waster head). NEW!
- Full proposed ANSI C library support (except clock). NEW!
 Link your C routines with Microsoft FORTRAN (version 3.3 or higher), Microsoft Pascal (version 3.3 or higher) or Microsoft Macro Assembler.
- Microsoft Windows support and MS-DOS 3.1 networking support.

MICROSOFT PROGRAM MAINTENANCE UTILITY. NEW!

- Rebuilds your applications after your source files have changed.
- Supports macro definitions and inference rules.

OTHER UTILITIES.

- Library Manager.
- Overlay Linker.
- EXE File Compression Utility. EXE File Header Utility.

MICROSOFT CodeView WINDOW-ORIENTED SOURCE-LEVEL DEBUGGER. NEW!

- Watch the values of your local and global variables and expressions as you debug.
- Set conditional breakpoints on variables, expressions or memory; trace and single step.
- Watch CPU registers and flags as you execute.
- Debug using your original source code, the resulting disassembly or both intermingled.

Microsoft C comes with a 30-day money-back guarantee from The Programmer's Shop.

UNIX System V is a trademark of AT&T Bell Laboratories. CTree is a trademark of FairCom. Halo is a trademark of Media Cybernetics. Panel is a trademark of Roundhill Computer Systems. PforCe is a trademark of Phoenix Software.

Microsoft is a registered trademark and CodeView is a trademark of Microsoft Corporation.

THE PROGRAMMER'S S

THE C TEST

The programmer's complete source for software, services and answers.

128 Rockland Street, Hanover, MA 02339 (617)826-7531 (continued from page 40)

\$2000, yet, in a comparison made in 1984 using an earlier version of the system, it produced programs that executed faster than those produced by the prototype of the Japanese Fifth Generation computer." And from the March 3 press release, Turbo Prolog "outperforms other existing PROLOG language tools by factors of up to 10,000."

The developers of the compiler that Borland is marketing in the United States as Turbo Prolog sacrificed power and portability for speed. How much speed did they buy?

The speed of AI languages is measured in LIPS (logical instructions per second). It's reasonable that a fifthgeneration language should have a different unit for measuring performance from that used in evaluating third-generation languages. The firstthrough fifth-generation language classification is chiefly a matter of the power of a typical instruction. A fifthgeneration logical instruction ought to do more than a third-generation instruction does-so the theory goes. Turbo Prolog has many instructions that PROLOG lacks, but these are all third-generation (or possibly, in the case of the graphics operations, fourth-generation) instructions.

To give a true picture of what LIPS measure as compared with non-logical IPS would require fairly detailed analysis of some large tasks, lifting out components that are and are not good candidates for backtracking and resolution. The picture would be complicated by subtle differences in the goals of the declarative and imperative modes of programming: How do you compare speed if you don't agree about what constitutes acceptable user input, for example?

What I'm doing here is much less than this; I'm providing the results of a typical benchmark for imperative programming with a rough bound on the number of logical instructions it requires in Turbo Prolog.

The results don't support Borland's extravagant claims. The benchmark I ran was a simple recursive version of the sieve of Eratosthenes. Generating all primes less than n should take on the order of n² operations or less: for primes less than 100, that's on the or-

der of 10,000 LIPS as a rough bound. The Turbo Prolog result, 0.5 second for all primes less than 100, should be compared with results for your favorite imperative language and for other PROLOG implementations. (I got a value of 19 seconds for another, particularly slow, interpreted implementation of PROLOG.) Turbo Prolog was fast, but nowhere near 10,000 times as fast as the slowest competitor I could find. Furthermore, because the Symbolics PROLOG machine is projected to run at 100,000 LIPS, I don't think that any claim of speed for Turbo Prolog comparable to speed for serious fifth-generation machines need be taken seriously.

Finally, Turbo Prolog lacks virtual memory, a feature of some other microcomputer implementations. I suspect that the fast benchmark results Borland alludes to are based on accesses to databases in RAM.

Turbo Prolog requires an IBM PC or compatible with PC-DOS or MS-DOS 2.0 or later and 384K RAM. I tested it with an AT&T 6300 with 640K RAM. I also brought it up on a MacCharlie Plus with 640K RAM as a 128K Switcher application on a 512K Hyperdrive Mac.

Borland's speed claims are perhaps extravagant, but Turbo Prolog certainly produces fast code, particularly when databases are small enough to reside in RAM.

Claim 4: Difficult

PROLOG is difficult to understand, learn, and use, and Turbo Prolog is in this respect an implementation of PROLOG.

This one is common among experienced programmers. I support Morein's law, passed by Robert Morein, the author of A.D.A. PROLOG, a year or so ago, which states the following: If it's hard in FORTRAN, it's easy in PROLOG. If it's hard in PROLOG, it's easy in FORTRAN.

I think, but will not try to defend this opinion, that PROLOG is no harder than FORTRAN. I find Turbo Prolog to be an excellent learning environment, although it's arguable just what the learner is learning when learning Turbo Prolog.

Turbo Prolog has an excellent user interface, with multiple windows for editing, tracing, output, and messages and pull-down menus for accessing DOS, configuring the system,

and selecting the destination for compilation (RAM, disk). It's a compiler with the interactive feel of an interpreter. It has the same editor Borland puts in all its products—fine if you like WordStar, but more to the point, instantly familiar to millions of people. This is the user interface Borland will put into the next version of Turbo Pascal, projected for release in the second quarter of next year.

The manual is a decent tool for learning Turbo Prolog or the beginnings of PROLOG. To go beyond, a book on the language is necessary. The manual contains abundant examples of code, both short illustrative segments and full programs. After developing the difficult topic of the cut operator, the manual gives practical, rule-of-thumb advice for its use. The manual's chief defects as a learning tool are an inadequate index, excessive errors, and the lack of adequate acknowledgment of deviations from Clocksin and Mellish core PROLOG. For that matter, I could find no references to Clocksin and Mellish or any other book on PROLOG. Nevertheless, it's generally good tutorial documentation and, if cleaned up for the next printing, should be useful to most people interested in getting started with PROLOG.

I conducted an informal test of ease of learning, teaching a novice the rudiments of Pascal and of PROLOG using the Turbo Pascal and Turbo Prolog manuals as texts. Although I have taught Pascal professionally and know it much better than I do PROLOG, I saw no difference in ease of acquiring the concepts.

Claim 5: Sorry Excuse for Code

Turbo Prolog is a "sorry excuse for coding" from "a couple of Danish folks."

PC Week made this claim in the May 27, 1986, issue under its house pseudonym Spencer F. Katt.

It's true that Turbo Prolog is a Danish product, as is Turbo Pascal; nearly all Borland products are European. Borland is oddly secretive about the fact that it is primarily in the business of software acquisition and distribution; Borland's Independent Contractor Nondisclosure Agreement (which I have not signed) defines as trade secret "all information concerning the identity or whereabouts of key devel-

MACRO ASSEMBLER/ MBP COBOL PROGRAMMERS:

THE BEST FULL-SCREEN FIELD-ORIENTED MAPPING SYSTEMS FOR ASSEMBLER AND COBOL:

\$49.95 . . . COMPLETE.

"PCFM is absolutely the best screen formatting facility available . . . "
John Hooper, President, Business Data Services, Inc.

PCFM Release 1.10 Features:

- Easy-to-use Map Development Language (like CICS/BMS®).
- $\bullet \ Unrestricted \ {\it Field-to-Field Forward/Backward Cursor Movement}.$
- Color and Monochrome Support.
- Comprehensive Field Options including: PROTECT/UNPROTECT/AUTOSKIP, NUMERIC EDITING, LOWER/UPPER CONVERSION, LEFT/RIGHT JUSTIFY, unrestricted PAD characters, etc.
- NEW---> Monitor Protection "Time-Out" Feature.
- NEW---> Valid Control Keys defined in Map Development Language.
- Field oriented INSERT, DELETE, and EOF.

PCFM is not copy protected, comes with complete documentation, and is royalty free. PCFM is written in $MACRO\ Assembler$ providing INSTANTANEOUS data-to-screen and screen-to-data transmission.

Your copy of PCFM includes the PCFM Technical Reference Manual, the Application Map (DSECT) Generator, the Map Load Module (.OBJ) Generator, and PCFM 1.10 internal software.

PCFM requires an IBM/PC, XT, or compatible computer with 128k RAM and PC/MS DOS 2.0 or better.

CICS/BMS is a trademark of IBM.

YES! My check or money order is	enclosed. Please se	nd PCFM 1.1	10 for:		
☐ MACRO Assembler (\$49.95) ☐ MBP COBOL (\$49.95)	NAME ADDRESS_				
SEND BOTH! (\$69.95)	CITY_				
SEND BROCHURE (\$7.95 for handling)	STATE		ZIP	_TEL	

Please make check payable to ISES, INC. and mail to:

(NJ residents please add 6% sales tax).

ISES, INC. Attn: Jim Weideli Suite 8, Foxhall Middlesex, NJ 08846

TURBO PROLOG

(continued from page 42)

opers of Company products, past or current." Reflex may be the one Borland product widely known to have been acquired.

It's not true, however, that Turbo Prolog is poorly written. This is a good piece of coding. It produces surprisingly fast compiled code. The user interface is better than Turbo Pascal's current interface for rapid development of small routines. And the links to DOS and other languages and the tools for optimization make

. . Software Developers . Develop your software to work with most of the desktop printers on the market?

Now, CARDINAL POINT INCORPORATED has published Volume II of the PROGRAMMERS' HANDBOOK OF COM-PUTER PRINTER COMMANDS II, for models as new as 1985. Volume II compliments (but does not replace) book one and adds more detailed ESCAPE and Control Codes sequences for more printers by the leading printer manufacturers. Each book is 5½" x 8½", spiral bond, and contains an easy to use table-format. Codes are listed in text form with hex and decimal equivalents and detailed function description.
These two volumes should be a part of your reference library

1. Volume I (models through 1984) 2. Volume II (models as new as 1985)

3. 2 book set (Vols. | & ||) (Indiana residents add 5% sales tax. Please include \$2.50 shpg/hdlg) TO ORDER CALL

1-800-628-2828 ext. 534 (24 Hrs)

Quantity Orders or Dealers may call the number below collect. For detailed information, call or write:





P.O. Box 596, Ellettsville, IN 47429 (812) 876-7811 (M-F, 9-5 EST) We accept MC, VISA, MO-same day shpg. COD — \$2 extra. CK's — Allow extra 14 days

VISA

Circle no. 246 on reader service card.



Over 90 volumes of public domain "C" software including:

- compilers
 - editors
- text formatters
- communications packages
- many UNIX-like tools

Write or call for more details

The C Users' Group

Post Office Box 97 McPherson, KS 67460 (316) 241-1065

Circle no. 181 on reader service card.

this product more than a toy.

The applications for which Turbo Prolog is most appropriate may be applications that are on the border of artificial intelligence rather than in the mainstream. As the manual suggests, it could serve as a good specification language. The speed of the compiled code and the fifth-generation richness of the instructions may make it a good database development language, whereas the lack of metalinguistic power may make it a poor candidate for abstract problem solving. In any case, it has the Turbo Pascal strengths for quick development and testing of small modules. The product has a place.

Claim 6: Half-Million Sales

Borland will sell half a million copies of Turbo Prolog in the next two

That's what Philippe Kahn claims. Well, actually he says there may be that many people using the product—not the same thing, quite.

It's possible. Logic programming is in vogue, and Borland has built a reputation with Turbo Pascal that could transfer to Turbo Prolog. Novice Turbo Pascal users didn't care about its deviations from the standard, and novice Turbo Prolog users will be even less sensitive to the less-constraining soft standard for PROLOG. Of course, Turbo Prolog is not the only PROLOG, nor this time has Borland got the cheapest product. But if any PROLOG is as successful as Kahn hopes his will be, it will be good news for all PROLOG developers.

Some companies are beginning to look upon Borland as the company that opens markets for them. On May 20, less than three weeks after Turbo Prolog became available, Arity announced its trade-in plan. Buy Arity's \$795 PROLOG development system, and the firm will give you \$50 for page 213 of your Turbo Prolog manual as proof of purchase (that's the page that explains that there is no simple way of interfacing Turbo Prolog modules with Turbo Pascal programs). The program is due to expire about the time you read this, but it presents one view, the view Arity would like you to have, of Turbo Prolog's position: a beginner's language for those who want to play with PRO-LOG syntax before deciding whether

to move up to a serious development system. It's the view Logitech would like you to have of Turbo Pascal vis-àvis Logitech's Modula-2, which is why it is selling a product that lets you translate your old Turbo Pascal programs to Modula-2.

There is undoubtedly some truth to this perception. It's quite possible that Turbo Prolog, with its inviting user interface, will open up a large market for PROLOG products.

Logic programming has been projected to be the dominant form of programming in the next century. The next century begins in 14 years and 4 months. That should be more than enough time to turn PROLOG into that "important new generation of programming languages and systems" Clocksin and Mellish envision, especially if Kahn's prediction of half a million new PROLOG programmers is even half right.

Bibliography

Byte (August 1985). Special section on declarative languages.

Clark, K. L., and McCabe, F. G. micro-PROLOG: Programming in Logic. Englewood Cliffs, N.J.: Prentice-Hall,

Clocksin, W. F., and Mellish, C. S. Programming in Prolog. Berlin: Springer-Verlag, 1984.

Cohen, Paul R., and Feigenbaum, Edward A. The Handbook of Artificial Intelligence, vol. 3. Stanford, Calif.: HeurisTech Press, 1982.

Communications of the ACM (September 1985). Special section on architectures for knowledge-based systems. de Saram, Hugh. Programming in micro-PROLOG. Chichester, England: Ellis Horwood Ltd., 1985.

Dr. Dobb's Journal (March 1985). Special PROLOG issue.

Ennals, Richard. Beginning micro-PROLOG. New York: Harper & Row,

DDJ

Vote for your favorite feature/article. Circle Reader Service No. 4.

C spoken here...

High C™

Do you want to use a C compiler that

- was chosen by Ashton-Tate for implementing dBASE III® Plus
- was well rated in Computer Language, Feb. 86 and Dr. Dobbs Journal, August 86
- "would have saved me three weeks of porting time had I had High C instead of Microsoft's new C'

Mike LeBlanc, compiler developer, Sky Computers

 "is the only C compiler for the IBM PC capable of compiling NYU's Ada/Ed compiler"

Dave Shields, research scientist, New York Univ.

- has a complete run-time library
- · has structure assignment, enum, void...
- supports nested functions as in Pascal
- supports pcc and full K&R C plus some latest, nifty extensions from the new ANSI-proposed C standard
- "saved 15% of code over five large modules of MultiMate relative to Lattice C"

David Beauchesne, Multimate International

Pascal spoken here...

Professional Pascal™

Do you want to use a Pascal compiler that

- · was chosen by Lifetree Software, Inc., for implementing Volkswriter DeluxeTh
- was well rated in Computer Language, May 86: "The clear choice for large-scale programming projects..."; and PC Tech Journal, July 86
- serves as a systems and applications language at CAD/CAM giant Daisy Systems Corporation
- has 8-, 16-, and 32-bit integers; sets up to 64K bits
- has varying-strings of up to 64K characters
- has a full-fledged C macro preprocessor
- has many run-time library additions: UNIX™-like I/O. multiple heaps, interrupts, . . .
- has all the bit-pushing operators of C
- has many more extensions, getting you half way to Ada® for a non-Ada price
- · is the "howitzer" of Pascals and "could well be the most powerful Pascal compiler ever implemented on a microcomputer" PC Magazine, Oct. 29, 1985, p. 144

Power Tools



Power Users

Each compiler • generates superb code, with optimizations such as common-subexpression elimination and cross-jumping • sports no less than five memory models for the 8086 (Small, Compact, Medium, Big, and Large) • supports a unique implementation of register variables • supports the 8087/80287 in native mode, or emulates • supplies three floating-point formats • generates special instructions for the 80186/286 • generates code that runs in 80286 protected mode • gives you hundreds of error and warning messages, helping you find those subtle bugs before you need a debugger's help • lets you overlay data as well as code (when used with PLINK86), for substantial space savings • lets you write interrupt routines directly in high-level language • lets you get "close to the machine" with built-in move/scan/compare operations • is supported by equivalent resident and cross compilers for the 80286 (UNIX V.2, Xenix, Concurrent DOS 286), 80386 (DOS, UNIX V.3), 68010/20/68881 (UNIX V & 4.2, GEM-DOS™), 32032 (UNIX 4.2), VAX (UNIX 4.2, VMS), IBM 370,... • contains a **multi**modular cross-referencer • produces ROM-able code for embedded applications • can talk to those other languages by those other vendors • gives you 64K run-time stack space that can be shared with the heap • is endowed with an amazing number of pragmas (compiler controls) for customization to your application • has a compiler start-up profile • supports direct access to MS-DOS; library supports DOS 3.X file-sharing • generates symbolic debugger information for use with all known MS-DOS debuggers • allows exec-ing subprocesses • was designed for professional software developers, not hobbyists • comes with great technical support by a company that specializes in compilers • comes with extensive typeset documentation • and more... call or write for your information packet today...

Not recommended for casual use, but for applications needing industrial-strength tools, contact



(408) 429-6382 (429-META), TELEX: 4930879

Abroad:

ABC Software, The Netherlands Microsoftware, Tokyo Grey Matter. United Kingdom Buchdata. Frankfurt

Professional Tools Since 1979

High C V1.3: \$495 -on any MS/PC-DOS system-Professional Pascal V2.6: \$595

Contact us about porting our professional compilers to your systems. OEMs: TWS:

Professional Compiler Developers and competitors, ask about our Translator Writing System compiler toolbox; see the review in Computer Language, December, 1985.

DOS Helper™: Need UNIX-like utilities to enhance MS-DOS? Ask about our powerful tools for \$49.95—included free with MetaWare compilers: FIND, TAIL, MV, LS, CAT, UNIQ, FGREP, and WC.

 MetaWare, High C, Professional Pascal, and DOS Helper are trademarks of MetaWare Incorporated
 Other trademarks and their owners are: UNIX— AT&T, dBASE III—Ashton-Tate, Volkswriter Deluxe—Lifetree Software, GEM-DOS—Digital Research, Ada-DoD. © 1986 MetaWare.

High-Speed Thrills

A Review of Eight Turbo Boards for the IBM PC

ver the past few years, most of us switched from our old Z80 computers using the CP/M-80 operating system to IBM PCs (or clones) using PC(MS)-DOS. Then we experienced the big disappointment of learning that the new machines weren't quite as fast as the old ones were. After all, most of us, even programmers, have the great American dream: "More speed, faster is better, drag you for pink slips at the next stoplight!" Finding that your new computer isn't as fast as your old one can damage your ego more than learning your brand new, expensive, foreign sports car isn't as fast as your old jalopy.

When IBM announced the PC/AT, we envisioned the enhanced productivity and throughput the original PC had seemed to promise but had not produced. After all, we can rationalize that the most time-consuming part of program development is the endless debug-recompile-test process. If we have faster machines, we can shorten the software development process and we can save money. The AT rekindled the American dream: lightning fast compiles; the pleasure of being power users. Most of us, though, have invested too much time and money expanding our old PCs and PC/XTs with memory expansion boards, hard disks, and anything else we could stuff into them to really justify junking our old PCs and XTs to buy new ATs.

Early 1985 produced rumors of high-speed computer chips and

Mike Elkins and Steve King, 720 Flora Dr., Oceanside, CA 92056 by Mike Elkins and Steve King

We used six applications programs and five benchmark programs to test the boards.

boards that could speed up PCs to match the AT's performance—well, almost match the AT's performance. NEC V20 rumors promised to replace your old 8088, provide complete software compatibility, and give you an 85 percent increase in processing speed—still no match for the AT but not bad. In reality, the V20 provided what may be an 18 percent speed increase rather than the dreamed of 85 percent gain.

Last fall, we wandered through Comdex in Las Vegas and saw prototype accelerator boards that made PCs run not just as fast as ATs but even faster—the boards were software compatible with both machines. These boards are now becoming one of the most popular and desired PC and XT hardware enhancements. In this article, we'll review six of these so-called turbo boards and maybe rekindle your American dream.

The Benchmarks

Most turbo boards utilize on-board high-speed memory with a 16-bit interface, a high clock rate, and a more efficient CPU to produce the desired

increase in throughput. The boards we tested for this article produced processing speeds ranging from one and a half times the speed of a standard PC to well beyond the speed of a standard AT—even beyond the speed of an AT with a higher clock speed.

Our test machine was an IBM PC containing:

- 256K RAM on the motherboard
- AST Six Pac with 384K RAM
- · two floppies
- 10-megabyte internal drive
- 10-megabyte IOMEGA Bernoulli Box
- STB Graphics Plus and Color Monitor
- Mitsuba Expansion Unit

We used the following programs to test the turbo boards' PC compatibility: BASICA, Brief Programmer's Editor, dBASE III, Framework II, Microsoft C 3.0, and Microsoft Link. We've noted where any didn't function properly.

We used the following benchmark programs compiled with the Microsoft C 3.0 compiler:

- Compile/Link: Compile and link a 425-line C program with a RAM disk for the TMP work area.
- Sieve * 10: Ten loops through the Eratosthenes Sieve prime-number program (Listing One, page 88).
- \bullet Sieve * 100: 100 loops through the Sieve program.
- Dhrystone: The Dhrystone benchmark program (Listing Two, page 88).
- The Sysinfo utility included in Norton's Utilities, Version 3.1.

The public-domain utility TIMEIT, written by Jack Means, timed the first

three benchmarks. Table 1, below, contains a summary of our results.

Reinhold P. Weicker originally developed the Dhrystone program using the Ada programming language. A careful C conversion preserves the Ada likeness at the expense of C format and at the same time demonstrates the versatility of C. The program does nothing useful but is a well-rounded benchmark program containing dynamic memory allocation and manipulation, along with some number crunching.

The Boards

We'll now give a brief description of each of the boards we used in our benchmark tests and some brief comments on their performance. See the list of companies and addresses on page 49.

QuadSprint

Quadram's QuadSprint contains an 8086 microprocessor running at 9.54 MHz. This board takes up one full-size slot and replaces the 8088 with a jumper-type ribbon cable. Because you remove the 8088 from the PC, you have to de-install the board in order to return to native mode. Quad Sprint needs no software drivers or special programs for operation.

The QuadSprint board has 4K RAM, high-speed cache memory that is

software switchable with a small BA-SIC program, which is listed in the manual. The program uses an *OUT* command to send a value to the specified port (on or off). The board was software and hardware compatible with all our tests. QuadSprint uses the existing PC memory via the 8-bit PC system bus, which is probably why the speed increase was not as high as that of some of the other 8086 boards.

PC Turbocharger

PC Turbocharger from Univation uses an 8086 microprocessor running at 10 MHz. The board takes up a full slot and replaces the 8088 with a ribbon cable. The company provides an 8087 noise suppressor to plug into the 8087 socket on the motherboard. You must replace two chips on the board if you have the PC Model 2 with a 256K motherboard. Failure to read the documentation prior to installation to ensure the proper chips are in place may scramble the data on your hard disk!

The PC Turbocharger board doesn't require that you reboot the system to change speeds, as is the case with some of the other boards.

Univation provides several utilities with the PC Turbocharger, including a RAM disk, spooler, and cache—all have user-definable sizes. The company also includes a memory tester

and a program that copies ROM to high-speed RAM for fast execution of programs that make BIOS calls, such as BASICA. Because this board contains its own memory, we neutralized the AST Six Pac memory by setting its memory jumpers to 0.

SpeedPac 286

SpeedPac 286 from Victor Technology contains an 80286 microprocessor running at 7.2 MHz. The board takes up one half-size slot and replaces the 8088 with a jumper-type ribbon cable. You can't switch back to standard mode, and you must set jumpers to indicate available memory. Because the board has no memory, only PC memory is used. The board does, however, contain a highspeed 8K cache buffer and resident caching software. No software drivers or special programs are necessary. The SpeedPac 286 has a socket for an 80287 math coprocessor.

Victor Technology provides special instructions for installing dBASE III. Because you can't switch back to PC mode, many types of protected software may require that you remove the board temporarily when installing the software on your hard disk. This is a minor inconvenience in exchange for the added performance you receive for this board's low price. The board is compatible with IBM's

	Comp/Link index seconds	Sieve*10 index seconds	Sieve*100 index seconds	Dhrystone index loops/sec	Sysinfo index
IBM PC	1.00 231.95	1.00 12.30	1.00 107.60	1.00 333	102
IBM PC/AT	N/A	N/A	N/A	3.13 1041	5.60
PC Turbo 286	<u>3.35</u> 69.15	3.44 3.57	<u>4.55</u> 23.62	<u>5</u> 1666	8.40
PC Turbocharger	1.83 110.48	1.90 6.45	<u>2.39</u> 44.99	<u>2.63</u> 877	2.20
Pfaster 286	3.30 70.19	3.79 3.24	<u>5.33</u> 20.16	<u>5.17</u> 1724	8.40
QuadSprint	1.51 153.41	1.62 7.58	<u>1.92</u> 56.08	1.97 657	2
SpeedPac 286	<u>2.08</u> 111.45	2.37 5.17	3.43 31.36	3.41 1136	6.60
286 Speed Pack	N/A	<u>2.28</u> 5.39	3.28 32.80	3.84 1282	7

Table 1: Benchmark summary

HIGH SPEED THRILLS (continued from page 47)

Enhanced Graphics Adapter.

We found that the 8088 replacement cable was too short to reach over an existing board in the first slot. We had to insert the SpeedPac 286 board in the slot closest to the 8088 socket, which is not a disadvantage in the XT where the half slot is seldom used. This board performed very well considering that it was using existing 200-ns PC memory and an 8-bit interface. Victor Technology also offers a 60-day money-back guarantee. This is a real plus!

286 Speed Pack

Classic Technology Corp.'s 286 Speed Pack contains an 80286 microprocessor; its speed is not documented. The board takes up one full-size slot and replaces the 8088 with a jumper-type ribbon cable. You plug the PC's 8088 into a socket on the board and change back to standard mode with a switch on the back of the board. Then you must reboot. The socket is positioned

so that the 8088's label reads in the opposite way from the labels for the rest of the chips on the board; this could cause confusion, even though it is well documented.

You must set a jumper on the 286 Speed Pack board to indicate motherboard type: Model 1, 2, or XT. The board has a socket for an 80287 math coprocessor and has its own RAM, which may be expanded to 4 megabytes. This board is designed primarily for the XT and, if you have an internal hard disk, requires a 130-watt power supply. Because our test computer had only a 60-watt power supply and an internal hard disk, we couldn't run the PC with the hard disk installed. We also didn't run the compile/link benchmark. When installed in an XT, 286 Speed Pack uses the first 64K RAM on the motherboard to hold DOS; all other applications run in the high-speed memory located on the board itself.

The 286 Speed Pack board's benchmark times were inconsistent, as was the case with most of the boards; we used the "best case" values. Classic

Technology Corp. also provides network boards that allow multiple workstations to be attached to a PC/XT containing 286 Speed Pack. This setup gives you an XT file server with the power and speed of an AT server.

Pfaster 286

Pfaster 286 from Phoenix Computer Products Corp. uses an 80286 microprocessor running at 8 MHz. The board takes up a full slot and is the easiest of all the boards to install. It uses no ribbon cables, and you leave the 8088 in place. Software and easily installed device drivers activate it. You switch to the standard PC mode with a program called PSLOW and back to the 80286 mode with PFAST. Our test board came with 2-megabyte RAM, but it is also available with only 1 megabyte. The board also contains an 80287 math coprocessor.

Pfaster 286 supports the Lotus/Intel/Microsoft (LIM) Extended Memory Specification (EMS) and comes with a RAM disk that utilizes the extra megabyte of memory for non-EMS use.

The Pfaster 286 board was the fastest in many of the tests, but the screen I/O seemed jumpy and especially slow with programs such as Framework II that write directly to the video memory. The Norton Sysinfo results were inconsistent, ranging from 6.1 to 8.4 in the PFAST mode.

In the PFAST mode, Pfaster 286 uses motherboard memory for caching, allowing the compile/link benchmark to outperform an 8-MHz IBM PC/AT containing a high-speed hard disk. The compile time was much better (51.74 seconds) when a 1-megabyte RAM disk was used to hold all the necessary files. CHKDSK revealed that 704K RAM was available after the 1-megabyte RAM disk was defined and the 8088 memory was set aside for caching.

We couldn't convince the Brief editor to run in the high-speed mode—the cursor disappeared and characters were lost or duplicated. We recommend this board, which seems well implemented and versatile despite the I/O problem, but it's expensive

PC Turbo 286

Orchid Technology's PC Turbo 286 uses an 80286 microprocessor run-

HELP



is at hand

HELP/Control[™] - an online help subsystem for the IBM-PC. Increase product marketability. Reduce product development time.

HELP/Control is **fast**. Screens - up to full display size - appear almost instantaneously because the runtime system is written in assembler and accesses the screen memory directly. Smaller screens appear as windows. Once they've helped, the original display is restored just as quickly.

HELP for the programmer. A few simple subroutine calls add a full-featured online help subsystem to your application because HELP/Control is a runtime system linked or loaded with that application. HELP/Control has been fully tested with Microsoft C, Lattice C, Turbo Pascal, IBM BASIC (Interpreter and Compiler), Microsoft FORTRAN, IBM COBOL and assembler. It is distributed with sample programs in each language.

HELP for the documentation writer. Build screens. Define captions. Associate each caption with a screen. HELP/Control includes a screen generation language, HELPGEN, that reads your sources, creates a runtime file, and lets you use your favorite editor. Our HELP/Control reads that file and displays help screens when the user activates the help function.

HELP for the end user. Use the cursor control keys to select a caption. Press return. That's it. Each screen has a number of highlighted captions which indicate other screens with information on that subject. Lotus 1-2-3 users will feel right at home. We've even made the entire **HELP/Control** manual available as a set of screens so you can browse without ever cracking a book.

HELP/Control comes complete with a detailed manual, both online and printed, with information for the programmer and documentation writer. It also includes instructions for the end user which may be incorporated into the application documentation.

PC-DOS 2.0 or greater required for developing **HELP/Control** applications. Applications using **HELP/Control** will run under PC-DOS 1.0 or greater. The runtime system requires approximately 9K for code and buffers for full size help screens.

The complete HELP/Control package (software, both manuals, demo programs) is \$125.00. A demonstration diskette, including the online manual, is available for \$15.00. To order or for more information, contact MDS, Inc. at (207) 772-5436. MasterCard and VISA accepted.

MDS, INC., P.O. BOX 1237, PORTLAND, MAINE 04104



Circle no. 285 on reader service card

ning at 8 MHz with no wait states. The board takes up a full slot but requires no extra cables or chip removal. You activate this board with software device drivers that are easy to install and customize. The installation software carefully changes your existing AUTOEXEC.BAT file and doesn't disturb any commands, paths, or prompt commands. We found the software installation procedures to be very professional; they prompted for parameters and always explained the available options. The test board came with 1-megabyte RAM, but it is available with an additional 1 megabyte on a daughterboard. It fully supports the LIM EMS.

PC Turbo 286's benchmark times were very consistent, and all test software performed quite well. Screen I/O was extremely fast, and there were no noticeable differences when we used the Turbo mode. An installation option allows an increased screen I/O speed for nonflicker graphics boards—for example, our test PC's STB board. With the software installed for the flicker option, we

found the resulting screen I/O was a little slower and somewhat jumpy, but PC Turbo 286 performed much better than did Pfaster 286.

Fixed-disk caching (floppies, too, with a command-line option) takes advantage of the memory on the motherboard while the board is operating in the Turbo mode. RAM disks and spoolers in the standard PC memory are also accessible in the Turbo mode.

PC Turbo 286 supports the 80287 math coprocessor, but our evaluation unit didn't have one. The board performed flawlessly with all hardware in the test machine.

Orchid Technology's unit can also run in the PC/AT as a true dual processor. Two PC Turbo boards in a PC or XT can provide the same effect. The software to provide access to the other boards was in development and not available (but was documented) for our tests, however.

Orchid Technology's documentation is complete and helpful, which is surprising because we had a beta version of the board. The documentation covers jumper settings to change I/O addresses and interrupt request lines to minimize chances of unresolved hardware conflicts.

Try It, You'll Like It

Using these boards, we found microprocessor speed increases from two to more than eight times the speed of the 8088 in a stock PC but at best about a five times' increase in actual throughput. Standard I/O devices provide the primary bottleneck. Because of software enhancements, such as cache and RAM-disk programs that come with most of the boards, you can achieve the actual throughput of an IBM PC/AT and greatly surpass the standard PC. We see these turbo boards as serious alternatives to an AT because they provide the desired performance increase and save money-it's much cheaper to upgrade your old PC or XT with one of these boards than to buy an AT, even one of the new, cheap AT clones.

We tested two categories of boards—Intel 8086-based (or NEC V30 compatible) and Intel 80286-based. The first group benchmarked very closely, and choosing a winner was difficult.

All the installed 80286 boards performed consistently faster than a stock IBM PC/AT. For raw performance and overall throughput and compatibility, Orchid Technology's PC Turbo 286 was a clear winner, far surpassing the standard IBM PC/AT's performance. It has lightning-fast screen I/O and a reasonable price for an AT alternative, and it fully supports EMS. If price is the primary consideration, look at Victor Technology's SpeedPac 286. It can attain the speed of the AT without expensive memory replacement-its perfor-With public-domain cache and RAMdisk software, this board could provide the throughput you're looking for.

DDJ

(Listings begin on page 88.)

Vote for your favorite feature/article. Circle Reader Service No. 5.

PC Turbo 286

Orchid Technology 47790 Westinghouse Dr. Fremont, CA 94539 (415) 490-8586 Price: \$1,195 (1 megabyte) \$1,480 (2 megabytes) Reader Service Number 45

PC Turbocharger

Univation Inc.
1037 N. Fair Oaks Ave.
Sunnyvale, CA 94089
(408) 745-0180
Price: \$595 (128K)
\$795 (640K)
Reader Service Number 46

Pfaster 286

Phoenix Computer Products Corp. 320 Norwood Park South Norwood, MA 02062 (617) 762-5030

Price: \$1,495 (1 megabyte) \$1,895 (2-megabyte unit evaluated) \$2,395 (2 megabytes w/ViaNet LAN software) Reader Service Number 47

QuadSprint

Quadram 4355 International Blvd. Norcross, GA 30093 (404) 923-6666 Price: \$645 Reader Service Number 48

SpeedPac 286

Victor Technology 980 El Pueblo Rd. Scotts Valley, CA 95066 (408) 438-6680 Price: \$595 Reader Service Number 49

286 Speed Pack

Classic Technology Corp. 2090 Concourse Dr. San Jose, CA 95131 (408) 434-9333 Price: \$995 Reader Service Number 50

FORTH AT SEA

Liet	ing One	(continued from July)		
LIJI	FDB HERE-6	Link to HERE	LDA SPO,X	
NOT3	LDX SP		INCX STA LOAD+2	
	LDA SPO,X		INCX	drop high data byte
	STA SPO, X		IDA SPO,X INCX	and move low byte
	INCX LDA SPO,X		STX SP	Substitution of the substi
	COMA		CLRX JSR LOAD	
	STA SPO,X JMP NEXT		JMP NEXT	
*	FCB 2	1+	FCB 1	
	FCC '1+ '		FCC ', 'FDB CSTO-6	link to C!
ONEP	FD NOT3-6	Link to NOT	COMA LDA DP	move DP to Load
ONLL	INCX	point to low byte	STA LOAD+1 LDA DP+1	THE RESERVE OF THE PARTY OF THE
	LDA SPO,X ADD #1		STA LOAD+2	move data to DP
	STA SPO, X	now the high byte	LDX SP LDA SPO,X	high byte
	LDX SP LDA SPO,X	now the high 2700	INCX	公司。 医医疗 医骶骨髓 医肾髓 医
	ADC #0		STX SP CLRX	Company of the balance of the latest
	STA SPO,X JMP NEXT		JSR LOAD LDX SP	low byte
*	FCB 3	HID	LDA SPO, X	
	FCC 'HLD'		INCX STX SP	
HLD3	FDB ONEP-6 LDA #HLD	link to 1+ (fall through to DOUSE)	LDX #1	
*		Does the common part of the	JSR LOAD LDA #2	
DOUS	E ADD #USER LDX SP	execution of a user variable	INCDP ADD DP+1	bump DP
	DECX		STA DP+1 LDA DP	
	STA SPO,X CLRA		ADC #0 STA DP	
300	DECX STA SPO,X		JMP NEXT	
	STX SP		* FCB 2	c,
*	JMP NEXT		FCC 'C, '	
	FCB 5	STATE	FDB COMA-6 CCOMA LDA DP	
	FCC 'STA' FDB HLD3-6	link to HLD	STA LOAD+1 LDA DP+1	
STAS	IDA #STATE		STA LOAD+2	data to DB
*	BRA DOUSE		LDX SP INCX	move data to DP drop high byte
	FCB 7 FCC 'CON'	CONTEXT	LDA SPO,X	get low byte
	FDB STA5-6	link to STATE	INCX STX SP	
CON	7 LDA #CONTEXT BRA DOUSE		CLRX JSR LOAD	
*		CURRENT	LDA #1	bump DP by 1
	FCB 7 FCC 'CUR'		BRA INCDP	
CUR	FDB CON7-6 7 LDA #CURRENT	link to CONTEXT	FCB 3 FCC 'DUP'	DUP
	BRA DOUSE		FDB CCOMA-6	link to C,
*	FCB 5	FORTH	DUP3 LDX SP LDA SPO,X	get high byte
	FCC 'FOR' FDB CUR7-6	link to CURRENT	DECX	and bump SP to point to new location
FOR	5 LDA #FORTH		DECX STA SPO,X	then store it
*	BRA DOUSE		LDX SP	get low byte
	FCB 1 FCC '!	Let my a thorac (Lavis Oc. 1977).	INCX LDA SPO,X	
	FDB FOR5-6	link to FORTH	DECX	bump SP for it too
STO	LDA SPO,X	move addr to Load	STA SPO, X	and store it update SP
	INCX		DECX STX SP	update or
	STA LOAD+1 LDA SPO,X		JMP NEXT	
	INCX STA LOAD+2		FCB 2	+!
	LDA SPO,X	now move data to addr	FCC '+! ' FDB DUP3-6	link to DUP
	INCX STX SP	high byte first	PLSTO IDX SP IDA SPO,X	move Addr to Load and Get
	CLRX JSR LOAD		INCX	
	LDX SP	and the loss but o	STA LOAD+1 STA GET+1	
	LDA SPO,X INCX	now the low byte	LDA SPO, X	
	STX SP		INCX STA LOAD+2	
	LDX #1 JSR LOAD		STA GET+2 STX SP	
*	JMP NEXT		IDX #1	get low byte of addr data
	FCB 2	C!	JSR GET LDX SP	get low byte of number
	FCC 'C! 'FDB STO-6	link to !	INCX	
CS	STO LDX SP LDA SPO, X	move addr to Load	ADD SPO,X IDX #1	
	INCX		JSR LOAD	and save it back (continued on page 52)
	STA LOAD+1			(continued on page 52)

WIZARO C

The new **Wizard C version 3.0** sets new records for all out speed! It leaves other C compilers in the dust! When your project depends on that last ounce of speed, choose Wizard.



The following SIEVE benchmark was run without register variable declarations on an IBM/PC with 640K memory and an 8087.

Wizard C 3.0 Microsoft	Exec Time : 6.8	Code Size 130	EXE Size 7,766
	:11.5	186	7,018
Lattice	:11.8	164	20,068

Fast executable code, with multiple levels of optimization.

Six memory Models, supporting up to 1 megabytye of code and data, plus mixed model programming.

Effective error diagnosis, including multiple source file cross-checking of function calls.

A comprehensive runtime library, including fully portable C functions, MSDOS and 8086 functions.

8086, 8087, 80186 and 80286 hardware support.

Full Library Source Code included with package.

ROM based application support, including a ROM development package available to create Intel Hex files.

Fully ANSI compatible language features.

"...The compiler's performance makes it very useful in serious software development."

> PC Tech Journal January, 1986

"We found that the support team at Wizard offered by far the best technical assistance....Wizard's got the highest marks for support."

"The Wizard Compiler had excellent diagnostics; it would be easier writing portable code with it than with any other compiler we tested."

Dr. Dobb's Journal August, 1985

"...written by someone who has been in the business a while. This especially shows in the documentation."

> Computer Language February, 1985

For debugging, the compiler emits full Intel debugging information including local symbol and type information.

For stand-alone applications, we supply a ROM development package that carries your program all the way to Intel Hex files ready for a PROM burner.

Wizard C	\$450.00
ROM Development Package	\$350.00
Combined	\$750.00
Automatic Upgrade Program	
(annual fee)	\$100.00
Make	\$150.00
Math 87 Library	\$ 50.00



11 Willow Court, Arlington, MA 02174

(617) 641-2379

FORTH AT SEA

Listing One				
Listing One (1			DR OTMM	
CLRX JSR GET	The same for the high byte		DB QIMM DB NOT3	
IDX SP			DB ZBRAN	
ADC SPO, X			DB \$0010 DB STA5	
CLRX JSR LOAD		F	DB FTCH	
INC SP	update SP		DB ZBRAN DB \$0008	
INC SP JMP NEXT		F	DB COMA	
*			DB BRAN DB \$FFE6	
FCB 6	LATEST		DB EXE7	
FCC 'LAT' FDB PLSTO-6	link to +!		DB BRAN	
LAT6 JMP DOCOL			DB \$FFE0 DB HERE	
FDB CUR7 FDB FTCH		F	DB NUM8	
FDB FTCH			DB ZBRAN DB \$0014	
* FDB EXIT		F	TDB STA5	
FCB 5	ALLOT		TDB FTCH FDB ZBRAN	
FCC 'ALL' FDB LAT6-6	link to LATEST		FDB \$FFD0	
ALL5 JMP DOCOL	11111 00		TDB COMP TDB LIT3	
FDB DP2			FDB COMA	
FDB PLSTO FDB EXIT			FDB BRAN	
*	1.70		FDB \$FFC6 FDB QUES	
FCB 3 FCC 'LIT'	LIT		FDB BRAN	
FDB ALL5-6		*	FDB \$FFBA	
LIT3 LDA IP	move IP to Get	*	POWER ON	RESET ROUTINE
STA GET+1 LDA IP+1		*	FCB 4	COLD
STA GET+2	move low byte to stack		FCC 'COL'	
LDX #1 JSR GET	Move tow byce to seask	*	FDB LIT3-6	link to LIT
LDX SP			BSET3 \$05	
DECX STA SPO,X			BSET3 PUT	Move the default RAM data
STX SP		TAGS	LDX #\$3F LDA ROM, X	Move the deladic last data
CLRX	and then the high byte	SDAT	STA O, X	
JSR GET LDX SP			DECX CPX #\$20	
DECX			BNE SDAT	15 modified no godo
STA SPO,X STX SP		COURT	LDX #\$80	Move the self-modifying code to its executable location
LDA #2	now bump IP	SREPT	LDA ROM, X STA O, X	(done in two steps to avoid the
ADD IP+1 STA IP+1			INCX	CPUs stack: 40-7F)
CLRA			BNE SREPT CLRX	
ADC IP STA IP		SREP2	IDA ROM+\$100,X	(moving 200 HEX bytes)
JMP NEXT			STA \$100,X DECX	
* QIMM LDX SP	Tests for IMMEDIATE	*	BNE SREP2	
INCX	using count byte	*	Calculate the HIG	H and LOW BYTES of OUTER
LDA SPO,X TSTA	from <find></find>	*	EQU OUTER/\$100*\$1	
BMI QID		HO	EQU OUTER-HO	
CLRA BRA QSKIP		HO1	EQU OUTER/\$100	
QID LDA #SFF		*	LDA #LO	Load the default
QSKIP STA SPO,X			STA START+1	Outer Interpreter into START
DECX STA SPO,X			LDA #HO1 STA START	THÍC STULT
JMP NEXT		*		THE TON DYTES OF Intest entry
*		*	Calculate the HIC	GH and LOW BYTES of Latest entry
MESS FCB 67		HCR	EQU LATEST/\$100*\$	\$100
FCC 'RAFOS '		LCR	EQU LATEST-HCR EQU LATEST/\$100	
FCC 'V1.0'		# HICK	PÃO INTERIVATOO	TOPMI
* FCB CR			LDA #H1CR STA USER+FORTH	Initialize FORTH
FCB LF	SSRY PRODUCTION'		LDA #LCR	
* FCC A TEAM ROS	SSBY PRODUCTION'		STA USER+FORTH+1	
FCB CR		*		
FCB LF FCC '(C) EVERI	ETT CARTER 1986'	*	Calculate the HI	GH and LOW BYTES of MESS
*		* H	EQU MESS/\$100*\$1	00
OK FCC 'OK'	The FORTH prompt	L	EQU MESS-H	
*		H1 *	EQU MESS/\$100	
* DEFAULT OUTER	INTERPRETER		CLRX	Push start up message
*			LDA #L DECX	
OUTER FDB COUS			STA SPO, X	
FDB TYPE			LDA #H1 DECX	
FDB INLINE			STA SPO, X	
FDB DFND FDB ZBRAN FDB \$001E			STX SP	Initialize Stack Pointer (continued on page 54)

A MEGABYTE FOR DOS!

MicroWay is the world's leading retailer of 8087s and high performance PC upgrades. We stock a complete selection of 8087s that run from 5 to 12 MHz. All of our coprocessors are shipped with a diagnostic disk and the best warranty in the business – one year! We also offer daughterboards for socketless computers (NEC PC) and 287Turbo which increases the clock speed of the 80287 from 4 to 10 MHz. Our NUMBER SMASHER/ECM™ runs at 12 MHz with a megabyte of RAM and achieves a throughput of .1 megaflops with 87BASIC/INLINE, Intel For-

tran, or Microsoft Fortran. Software reviewers consistently cite MicroWay software and 8087 expertise as the best in the industry! Our customers frequently write to thank us for recommending the correct software and hardware to meet their specific needs. They also thank us for our same-day shipping! In addition to our own products which support the 8087 and 80287, we stock the largest supply of specialized software available. For more information call us at

617-746-7341

NUMBER SMASHER/ECM™ THE FASTEST ACCELERATOR CARD AVAILABLE

gives you 12 MHz speed in two modes: 704K or one megabyte of "Extended Conventional Memory." MEGASWITCH MMU and MegaDOS software make it possible to run DOS applications with up to 1015K using PC compilers, Auto-CAD and Lotus 1-2-3. Does not require EMS software. Totally compatible. Priced from \$599 with 512K to \$1199 for complete package. Optional 8087-12...\$295



Micro Way® 8087 Support

For the IBM PC, PC XT, PC AT and Compatibles.

A2D-160[™] MicroWay's Data Acquisition Board performs 160,000 12 bit Analog to Digital conversions per second! Includes software drivers. The fastest 12 bit A to D board available. For the IBM PC XT and compatibles. \$1295

875FL™ MicroWay's Scientific Function Library contains 170 scientific and engineering functions Callable from most 8087 compatible compilers . . . First Language \$250; Additional \$100.

87FFT™ Written in assembly language, performs Forward and Inverse FFTs on real and complex arrays which occupy up to 512 Kbytes of RAM. Also does convolutions, auto correlations, hamming, complex vector multiplication, and complex to radial conversions. Callable from most 8087 compatible compilers......\$200

87FFT-2™ performs two-dimensional FFTs Ideal for image processing Requires 87FFT **\$100**

Microsoft Fortran V 3.31	\$200
IBM Professional Fortran	\$565
Hyan-McFarland Fortran V 20	\$300
NAG FORTAN LIDIARY	\$300
Graffiatic for Fortran or Pascal	CIOE
MUITING Graphics (1 Janguage)	6100
LABIECH NOTEBOOK	\$745
UnkelScope	\$540
INTEL ABOVE BOARD	CALL
JRAM, AST, MAYNARD	CALL
	CALL

MICTO P.O. Box 79
Kingston, Mass.
02364 USA
(617) 746-7341

MegaPage™ The only Intel-Lotus EMS board which comes with two megabytes of cool-running, low power drain CMOS RAM installed. Includes RAM disk, print spooler, disk cache, and EMS drivers. For the IBM PC, XT & compatibles \$549

MegaPage AT/ECC™ EMS card for the PC AT and compatibles includes Error Correction Circuitry. With ECC, 11 RAM chips cover 256K so the user never encounters RAM errors. With 1 megabyte CMOS \$799; with 3 megabytes CMOS \$1295. Optional serial/parallel daughterboard....\$95.

DFixer™ Our disk utility which thoroughly checks PC or AT hard disks for bad sectors and updates the MS DOS file allocation table accordingly. Solves the AT hard disk problem! ...\$149

DOptimizer™ Optimizes the way your hard disk or floppy stores its files. Speeds up accesses by recombining fragmented files.\$49

87MACRO/DEBUG™ Contains all the pieces needed for writing 8087/80287 assembly code & MicroWay's 87DEBUG debugger. \$199

OBJ→ASM™ A multipass object module translator and disassembler. Produces assembly language listings which include public symbols, external symbols and labels commented with cross references. Ideal for patching object modules for which source is not available. \$200

87BASIC™ includes patches to the IBM BASIC or MS Quick BASIC Compiler for USER TRANS-PARENT 8087 support. Provides super fast performance for all numeric operations including trigonometrics, transcendentals, addition, subtraction, multiplication, and division..... each \$150

87BASIC/INLINE™ converts the output of the IBM BASIC Compiler into optimized 8087 inline code which executes up to seven times faster than 87BASIC. Supports separately compiled inline subroutines which are located in their own segments and can contain up to 64 Kbytes of code. This allows programs greater than 128KI. Requires the IBM BASIC Compiler Version 1 and a Macro Assembler. Includes 87BASIC ... \$200

MICROWAY UDI runs RTOS or RMX compilers under DOS\$300

8087 UPGRADES

All MicroWay 8087s include a one year warranty, complete MicroWay Test Program and accurate installation instructions.

1	motanation motructions.	
	8087 5 MHz	\$109
	For the IBM PC, XT and compatibles. 8087-2 8 MHz. For Wang, AT&T, DeskPro, NEC, Leadi	4.00
	8087-2 8 MHz	\$149
	For Wang, AT&T, DeskPro, NEC, Leadi	ng Edge.
	80287-3.5 MHz	Q170
	For the IBM PC AT and 286 compatible	les.
	80287-6 6 MHz	\$229
	FOR 8 MHz AT compatibles.	
	80287-8 8 MHz	\$295
	For the 8 MHz 80286 accelerator card	de
	NEC V20, V30\$1	16, \$30
	64K RAM Set 150ns	\$10
	256K RAM Set 150ns	\$29
	256K RAM Set 120ns	\$39
	128K RAM Set PC AT	\$49
	287Turbo™ 10 MHz If you own Deskpro 286 or AT compatible, this is the	vn an AT,
	lieed to del reasonable numeric perfor	rmanaa It
	plugo ilito your ouzo/ socket and inclin	ac a cno
	cially driven 10 MHz 80287. The card three configurations. The IBM AT version	
	a nardware RESET button	\$450
	287Turbo 8 MHz	\$369
	87/88Turbo™ is a stubby card which a clock calendar and a speed control	includes
	Changes the speed of vour motherhoard	from 177
	10 7.4 MIDZ Its use requires your PC t	o have a
	socketed 8284. Typical speed increase 2.0. The card overcomes slow hardware	by olove
	II IQ UD ONIV When such devices are acce	seed and
	running at full speed otherwise Optional 8087-2	\$149 \$149
	286TurboCooho™ Ti	4.40

286TurboCache™ This new MicroWay accelerator uses 8K of cache memory and 80/286/

FORTH AT SEA

sting One (listing		* PUTC	STA CHAR		
RM LDA #\$80 Init: STA TIB+\$7E	ialize input terminators	OUTCHAR	EQU PUTC STA ATEM	P	
STA TIB+\$7F	A DANGUETON -1-1-	100	STX XTEM		
CLR USER+STATE Put CLR USER+STATE+1	system in EXECUTION state		LDA #9 STA COUN	Т	
CLR RP Init	tialize Return Stack pointer		CLRX		
JSR CRLF LDA START Load	d the IP		CLC SEI		
STA IP		PUTC5	BRA PUTC ROR CHAR		
IDA START+1 STA IP+1		PUTC2	BCC PUTC	3	
JMP NEXT GO.			BSET3 PU BRA PUTC		
FCB 4 SI	WAP	PUTC3	BCLR3 PU	T	
FCC 'SWA'		PUTC4	BRA PUTC		
FDB COLD-6 1. AP LDX SP	ink to COLD		DEC COUN BNE PUTC		
LDA SPO,X		50 P. S.	BSET2 PU	T	
INCX STA PH			BSET3 PU CLI	T	
LDA SPO,X INCX			BSR DELA		
STA PL			LDX XTEM		
LDA SPO, X INCX		*	RTS		
STA QH		*			
LDA SPO,X STA QL		* 7	AIT PF	AND X ARE	Y ZERO AT EXIT.
IDA PL STA SPO,X		*			ADJUST FOR FIRST TIME
LDA PH		DELAY	EQU WAIT		ADOUGH FOR PIROT TIPE
DECX STA SPO,X			AND #!11 TAX		
LDA QL			LDX DELA		
DECX STA SPO, X		DEL3	ADD #\$08		
LDA QH		DEL2	DECA		
DECX STA SPO,X			BNE DEL	4	
JMP NEXT			BSET1 P	UT	
FCB 3 FCC 'SP!'	EP!		BNE DEL	3	
FDB SWAP-6	ink to SWAP		LDA #0 RTS		
STO CLR SP JMP NEXT		*		0	300 BAID
		DELAYS	FCB \$0	8	300 BAUD 1200 BAUD
SERIAL I/O RO	TTINES	*	FCB \$0	1	9600 BAUD
SEKIND 1/0 KO		*	TD3 #67		
		CRLF	LDA #CF JSR OUT		
GETCHAR/GETC GET A	CHARACTER FROM THE TERMINAL		LDA #LF JSR OUT		
A GETS THE CHARACTER T	YPED, X IS UNCHANGED		RTS		
ETC STX XTEMP		*	FCB 2		CR
ETCHAR EQU GETC			FCC 'CR ' FDB SPSTO-	-6	link to SP!
LDA #8 STA COUNT		CR2	BSR CRLF		
ETC4 CLI SEI		*	JMP NEXT		
BRSET2 PUT, GETC4			FCB 6		CREATE
IDA PUT AND #!11			FCC 'CRE' FDB CR2-6		link to CR
TAX	load Baud delay	CRE6	JMP DOCOL FDB BL2		
LDX DELAYS, X ETC3 LDA #4	TOAU DAUG GETAY		FDB WORD		
ETC2 DECA BNE GETC2			FDB LIT3 FDB #04		
TSTA			FDB ALL5		
DECX BNE GETC3			FDB LAT6 FDB COMA		
BRSET2 PUT, GETC4			FDB CUR7 FDB FTCH		
TST ,X TST ,X			FDB STO		
BSR DELAY BRCLR2 PUT, GETC6		*	FDB EXIT		
GETC6 TST ,X		*			
ROR CHAR DEC COUNT		*	++++++++	******	*********
BNE GETC7		*****	******		
CLI BSR DELAY		*	INTERRUPT	VECTORS	
LDA CHAR AND #\$7F	Mask the eighth bit.		ORG	MEMSIZ-10	START OF VECTORS
LDX XTEMP		*	FDB	WTIME	TIMER IRQ VECTOR FROM WAIT STAT
RTS			FDB	WTIME+3	ALTERNATE TIMER VECTOR IRQ VECTOR.
*			FDB FDB	WTIME+6 WARM	SWI TO FORTH INITIALIZATION POI
* OUTCHAR/PUTC PRIN	T A ON THE TERMINAL	*	FDB	COLD	POWER ON VECTOR
*			END		End Listi

The Peak of Performance



OF PRODUCTIVITY

Sure, you've proven that in your hands a computer is a productive tool. But if you haven't teamed up with a SemiDisk you have heights yet to climb!

IT'S NO MERE RAMDISK

SemiDisk has been leading the way for Disk Emulators since their inception. If you've seen RAMdisks you know what it's like to load programs in an

SEMIDISK

SemiDisk Systems, Inc. P.O. Box GG, Beaverton, Oregon 97075 503-626-3104

instant, and read or write files without delay. Unlike alternatives, the SemiDisk offers up to 8 megabytes of instant-access storage while leaving your computer's main memory free for what it does best - computing!

KEEP A GRIP ON DATA

Go ahead, turn off your computer. Take a vacation. With the battery backup option, your valuable data will be there in the morning even if you aren't. You'll sleep better knowing not even a 5 hour blackout will sabotage your files.

NEW LOWER SEMIDISK PRICES THAT WON'T SNOW YOU UNDER

	512K	2Mbyte
IBM PC, XT, AT	\$495	\$995
Epson QX-10	\$595	\$995
S-100, SemiDisk II	\$799	\$1295
S-100, SemiDisk I	\$595	
TRS-80 II, 12, 16	\$695	\$1295
Battery		
Backup Unit	\$130	\$130
Software drivers avail	able for CD	A4 00

Software drivers available for CP/M 80, MS-DOS, ZDOS, TurboDOS, and VALDOCS 2.

LETTERS

Listing One (Text begins on page 10.)

```
Program Squareroot:
  Squareroot algorithm & testprogram; DDJ March 1986, p.122
  Features: - sqrt routine in 68000 machine language;
- long integer loopcount;
}
               { Iteration count for test loop }
NNR = 6E4: { real, for printing of statistics }
NNS = '60000'; { string, for assignment to long integer }
const
              long - record
type
                                 low, high : integer;
                              end:
               ( --- ROUTINES FOR LONG (32-BIT) INTEGER SUPPORT --- )
procedure lg clr(var 1:long); external;
{ Clears long integer 1 }
procedure lg_asn_DU(s:string; var l:long); external;
{ Assigns the unsigned decimal string s to the long integer 1 }
  procedure lg_incl(var 1:long); external; Increments long integer 1 by 1 )
procedure lg_grt(a,b:long; var flag:boolean); external;
{ Compares long integers a and b and assign result to flag }
 ( --- SQUAREROOT ROUTINE --- }
procedure sqrt(number:long; var result:integer); external;
{ Calculates square root of 'number' and returns it in 'result' }
   sqrrto :- 100;
    lg_clr(number); { number := 0 }
lg_asn_DU(NNS,limit); {limit := NNS }
finished := false;
    write('Start...');
time(t1,t2); time1 := t2; { get start time }
    while not finished do ( calculate sqrt(number) )
          sqrt (number, sqrrt):
         if sqrrt <> sqrrto
    then begin
    write ('Number = ',number.high:6,' | ',number.low:6);
    writeln(' --- Sqrt = ',sqrrt:4);
    sqrrto := sqrrt;
       !
lq incl(number); { number := number + 1 }
lq_grt(number,limit,finished); { finished := (number > limit) }
end;
       time(t1,t2); time2 := t2: { get end time }
       writeln('finished !'); writeln;
writeln('Time: ',(time2-time1)/60,' seconds')
```

End Listing One

Listing Two

```
* Squareroot algorithm; DDJ March 1986, p.122
* 68000 assembly language version
6 * Features: - equivalent to compiler-generated code:
9 * procedure sqrt(nt)
10 * Calculates integ
12 *
13 * Register usage:
   * procedure sqrt(number:long; var result:integer);
    * Calculates integer square root of 'number' and returns it in 'result';
 15
16 *
17 * D0 : word register
18 * D1 : number
19 * D2 : guess1
20 * D3 : guess2
                                        A0 : parameter stack pointer
A1 : scratch register
18 * D1 : number

19 * D2 : guess1

20 * D3 : guess2

21 * D4 : error

22 *

23 proc

24 *
                         sqrt,2 ;2 words of parameters
     * Get parameters from stack
               move.1 (sp)+,a0 ;get return address
move.w 2(sp),a1 ;get ^number
move.1 (a1),d1 ;get number
                                                         ;get number
 30
 31 * bra Q15 ;--- for timing only 32 *
                                                            ;if number=0, skip
              beq Q8
 33 Deq 34 * 35 * Set initial values 36 * 37 Q7 moveq $1,d2 move.1 d1,d3
                                                            ; guess1 := 1
    ; guess2 := number
  39 *
40 * Do shifts until guess1 ~ guess2
```

```
41 *
42 Q9
43
44
45
46
47
48
                                                                                                        ; guess1 to work register
; guess1 * 2
                          move.1
                          asl.l
cmp.l
bge
asl.l
asr.l
bra
                                                                                                        ;quess1 * 2
;compare with guess2
;branch if guess1 * 2 >= guess2
;guess1 := guess1 * 2
;quess2 := guess2 / 2
                                                     #1,d0
d3,d0
                                                    Q11
#1,d2
#1,d3
Q9
 49 *
50 * Now do divisions
 51 *
51 *
52 Q11
53 Q13
54
55
56
57
                                                                                                        ;guess := quess1 + guess2
;guess1 := (guess1+guess2)/2
;number to work reqister
;number / guess1
;guess2 := number/guess1
;extend to 32 bits
;guess1 to work register
;guess1-guess2
;error := quess1-guess2
;if error <= 0
;loop back if error > 0
;result := guess1
                                                     d3, d2
#1, d2
d1, d0
d2, d0
d0, d3
                           add.1
                          asr.l
move.l
divs
move.w
                            ext.1
                                                     d3
                                                     d2, d0
                           move.1
 60
                            sub.1
                                                     d3, d0
 61
62
63
64 Q14
                            move.1
                                                     d0. d4
                           ble
bra
move.1
                                                     Q14
Q13
d2,d0
Q15
 65 bra Q15
66 Q8 moveq #0,d0
67 % Set result & return to caller
69 *
                                                                                                         result := 0
                                                                           ;get ^result
                          movea.w (sp)+,al
move.w d0,(al)
  70 Q15
  70 Q1
71
72 *
73
74
75 *
76
                                                                                                          :store result
                                                                                                         drop 'number; return to caller
                            addq.1
                            qmt
                            .nolist
```

End Listing Two

Listing Three

```
* Squareroot algorithm: DDJ March 1986, p.122
      * 68000 assembly language version
      * Features: - hand-optimized machine code;
      * procedure sgrt (number:integer: var result:integer);
       * Calculates square root of 'number' and returns it in 'result';
  18 * D1 : number A1 : 19 * D2 : quessl,result 20 * D3 : quess2 21 * D4 : temporary storage for return address 22 *
                                                                    ;2 words of parameters
                                sgrt, 2
       * Get parameters from stack
                                                                    :result := 0 --- remove for timing
                  moveq #0, d2
   29 *
move.1 (sp)+,d4 ;get return address (sp)+,a0 ;get ^result move.w (sp)+,a1 ;get ^num ove.l (al),d1 ;get numb
                                                                    :if number-0, then result-0
                                                                     :guess1 := 1
                                                 d1, d3
                                                                                     ; guess2 := number
   42 move.1 d1,d3
43 * 44 * Do shifts until guess1 ~ guess2
45 *
   44 * Do
45 *
46 Q9
47
48
49
50
51 *
52 Q11
53 *
                                                                     :quess1 := quess1 * 2
;compare with guess2
;branch if quess1 * 2 >= quess2
;quess2 := quess2 / 2
                   asl.l
                    cmp.l
bge
asr.l
bra
                                     d3.d2
                                    011
                                    #1, d3
                                    #1,d2
                                                                     ;adjust guess1
    54 * Now do divisions
55 *
                                                                      ;quess1 := quess1 + quess2
;quess1 := (quess1+quess2)/2
;quess2 := number
;quess2 := number / quess1
;extend quess2 to 32 bits
;quess1 to work reqister
;error := quess1 - quess2
;loop back if error > 0
                    add.1
    56 013
                                     #1,d2
d1,d3
d2,d3
                    asr.1
    58
59
60
                    move.l
divs
ext.l
                                     d3
                                     d2, d0
    61
                    move.1
    61 move.1 d2,d0
62 sub.1 d3,d0
63 bqt Q13
64 *
65 * Store result and return to caller
66 *
67 Q15 move.w d2,(a0)
68 *
movea.1 d4.a0
                                                                      :store result
                    movea.1
                                                                      ;move return address to adr-reg; return to caller
     69
70
                    .nolist
                                                                                  End Listing Three
```

(continued on page 58)



Western Computer 286 Turbo™

Standard Features

- IBM PC/AT Compatible with 512K RAM
- Up to 1 MB of system memory on the main board
- Switch selectable 8 or 10 MHz operation with one wait state on memory access (80286-10)
- One parallel port/one serial port and Clock/ Calendar on main board
- Optional Serial Port on board
- Mass storage options from 20 to 140 MB Hard Disk Drives and 20 to 60 MB tape backup systems
- EGA video options available for CAD/CAM, word processing, etc....
- One year factory warranty

Western Computer has high quality computers at very competitive quantity pricing.

Western Computer


17781 MITCHELL STREET, IRVINE, CA 92714 U.S.A. PHONE (714) 553-1611

Customer Service Only (714) 553-1705

TELEX 7566731 - Answer Back WESTERN COMP FAX (714) 553-0236

Western Computer XT Turbo™ Standard Features

- IBM PC/XT compatible with 640K RAM on main board
- 4.77 or 8 MHz operation (CPU board made in U.S.A.)
- Two 360K Floppy Disk Drives
- Hercules compatible monochrome graphics controller (720×350) or IBM compatible color graphics adapter (320 x 200 - four colors or



640 x 200 - two colors) and parallel printer port Monochrome monitor (Composite or TTL input)

- IBM PC/AT style keyboard
- Various hard disk drive and tape backup options available
- One Year Factory Warranty

Western Computer Australiasia Limited
4-82 ABBOT STREET
ASCOT BRISBA
QUEENSLAND, AUSTRALIA
4007 - #(07) 268-6589
Telex: AA144746
FAX: #(07) 2685256
Answer Back MCGUIR



"For High Technology and Performance"

European Head Office

BELECTRONIC SA, RUE CENTRALE 43 CH-1880-BEX, SWITZERLAND PHONE (025) 631250 TELEX 456 168 Answer Back BELE CH.

LETTERS

Listing Four

(Listing continued, text begins on page 10.)

```
Squareroot algorithm; DDJ November 1985, p.88
     68000 assembly language
    * procedure sqrt (number:long; var result:integer);
Calculates the integer squareroot of 'number' and returns it in 'result'
                                                   :2 words of parameters
                                     ; get ^numbe
                                                   ;get number into d0
                          #16-1,d4 ;set loopcount,16*2 - 32 bits
#0,d1 ;clear error term
#0,d2 ;clear estimate
                                      ;estimate * 2
                                                   ;branch if error term <- corrector
;otherwise, add low bit to estimate
                                                   ; and calculate new error term
                          d4, sqrtl ; do all 16 bit-pairs
 50 *
51 exit
52
53
54
55
56 *
                          (sp)+,a0 ;get return address
(sp)+,a1 ;get *result
d2,(ai) ;store integer result
#2,sp ;drop *number
(a0) ;return to caller
              move.1
              .nolist
```

End Listing Four

Listing Five


djnz:		(accordance) d0	* 10 djnz e * d0 < distance
		(pseudopc)+,d0	* dec b
	subq.b	#1, regb (regs) dinz2	* loop count expired
	ext.w	d0	* to word
	ext.l	d0	* to long
			* add distance
djnz2:	add.1	d0, pseudopc	- add distance
d Jhzz:	NEXT		
400	NEXI		* 18 jr e
jr:		(manudama) dO	* d0 < distance
	move.b	(pseudopc) +, d0	
	ext.w	d0	* to word
	ext.l	d0	* to long
	add.l	d0, pseudopc	* add distance
	NEXT		
jrnz:			* 20 jr nz,e
	move.b	(pseudopc)+,d0	* d0 < distance
	btst	#6, regf	* if Z bit set
	bne	jrnz2	* then no branch
	ext.w	d0	* to word
	ext.l	d0	* to long
	add.l	d0, pseudopc	* add distance
jrnz2:			
	NEXT		
jrz:			* 28 jr z,e
	move.b		* d0 < distance
	btst	#6,regf	* if Z bit reset
	beq	jrz2	* then no branch
	ext.w	d0	* to word
	ext.l	d0	* to long
	add.l	d0, pseudopc	* add distance
jrz2:			
	NEXT		
jrnc:			* 30 jr nc,e
	move.b	(pseudopc)+,d0	* d0 < distance
	btst	#0,regf	* if C bit set
	bne	jrnc2	* then no branch
	ext.w	d0	* to word
	ext.l	d0	* to long
	add.l	d0, pseudopc	* add distance
			(continued on page 6)

(continued on page 60)

Relocating Macro Assemblers

• Z80 • NSC800 • 8085 • HD64180

What is your turnaround time? Eliminate this dilemma with the fastest most powerful assemblers on the market.



- math on externals
- T-states in listing
- local labels
- full drive/user support

Requires: Z80 W/40 K TPA, CP/M 2.2 or greater



- M80 Macros
- M80 Pseudo-ops
- tables overflow to disk
- recommend JR over JP

\$195



1622 N. Main St., Butler, PA 16001 (800) 833-3061 (412) 282-0864

Circle no. 78 on reader service card.



Power Tools for system builders™

Call today for our free catalog of design aids, compilers, libraries, debuggers, and support tools for Apple and IBM micro computers. The Power Tools catalog includes product descriptions, warranty and license terms, and all the information you need to make an intelligent purchase decision.

TSF offers technical support, competitive pricing, free UPS shipping on orders over \$100, and a reasonable return policy. Visa, MasterCard, and American Express accepted without surcharge. TSF helps you get your job done.

Sample Prices:

MS Quick Basic \$49.00 Periscope II \$129.00 DS Backup \$64.95 10 Diskette Mailers \$4.95 Gimpel PC Lint \$139.00 PCMacBasic \$100.00 Call Toll Free 24 hrs a day/7 days a week

Ask For Operator 2053

800-543-6277

Calif: 800-368-7600



TSF • Dept. C-2 • 649 Mission Street • San Francisco • CA 94105 • (415) 957-0111 The Software FamilyTM

Circle no. 230 on reader service card.



For over six years VEDIT has been the choice of professionals who demand the most powerful editing software available. CompuView has once again enhanced this power with the latest VEDIT PLUS - you can now open windows to simultaneously edit several files, access editing functions with pop-up menus, use keystroke macros to speed editing and run other programs within VEDIT PLUS.

Whether your needs are program development, technical writing or word processing, VEDIT PLUS is your answer. VEDIT PLUS is simple enough to learn for the novice, yet has the speed, flexibility and power to satisfy the most demanding computer professional. Its powerful macro programming language helps you eliminate repetitive editing tasks.

If you take your editing seriously, you need VEDIT PLUS. With over 40,000 users, you can depend on VEDIT PLUS to perform consistently and reliably. As have GE, EDS, U.S. Navy, GM, Sperry and many others. Available for MS-DOS, PCDOS, CP/M-86 and CP/M-80. List price \$185.

'To sum things up, VEDIT PLUS is a small, fast, sophisticated editor with a wealth of features and a good macro language. It offers many rewards for the dedicated programmer.'

Computer Language, Chris Wolf, Scott Lewis, Mark Gayman 6/86

'VEDIT PLUS is a wholly remarkable program: blindingly fast, extremely powerful, and highly flexible.'

Profiles Magazine, Robert Lavenda 4/86

VEDIT PLUS FEATURES

- Simultaneously edit up to 37 files of unlimited size.
- Split the screen into variable sized windows.
- 'Virtual' disk buffering simplifies editing of large files.
- Memory management supports up to 640K.
- Execute DOS commands or other programs.
- MS-DOS pathname and CP/M user number support.
- · Horizontal scrolling edit long lines.
- Flexible 'cut and paste' with 36 text registers.
- Customization determine your own keyboard layout, create your own editing functions, support any screen size, any CRT.
- Optimized for IBM PC/XT/AT. Also 132 column & up to 70 lines.

EASY TO USE

- Interactive on-line help is user changeable and expandable.
- On-line integer calculator (also algebraic expressions).
- Single key search and global or selective replace.
- Pop-up menus for easy access to many editing functions.
- Keystroke macros speed editing, 'hot keys' for menu functions.

FOR PROGRAMMERS

- Automatic Indent/Undent for 'C', PL/I or PASCAL.
- Match/check nested parentheses, i.e. '{' and '}' for 'C'
- Automatic conversion to upper case for assembly language labels, opcodes, operands with comments unchanged.
- Optional 8080 to 8086 source code translator.

FOR WRITERS

- Word Wrap and paragraph formatting at adjustable margins.
- Right margin justification.
- Support foreign, graphic and special characters.
- Convert WordStar and mainframe files.
- Print any portion of file; separate printer margins.

MACRO PROGRAMMING LANGUAGE

- 'If-then-else', looping, testing, branching, user prompts keyboard input, 17 bit algebraic expressions, variables.
- CRT emulation within windows, Forms entry.
- Simplifies complex text processing, formatting, conversions and translations.
- Complete TECO capability.
- Free macros: Full screen file compare/merge Sort mailing lists
- Print Formatter Main menu

CompuView

VEDIT and CompuView are registered trademarks of CompuView Products, Inc. MS-DOS is a registered trademark of Microsoft. CP/M is a registered trademark of Digital Research. WordStar is a registered trademark of MicroPro.

LETTERS

Listing Five (Listing continued, text begins on page 10.)

```
NEXT
                                                  * 38 jr c,e
irc:
                                                  * d0 <-- distance
                    (pseudopc) +, d0
         move.b
                                                  * if C bit reset
                    #0, regf
         btst
         beq
                    jrc2
                                                  * then no branch
                                                 * to word
          ext.w
                    dO
          ext.l
                                                  * to long
                    dO
                                                  * add distance
                   d0, pseudopc
         add.l
irc2:
         NEXT
```

End Listing Five

Listing Six

```
/* c_draw.c */
                            /* jnm 5-27-86 rev.1
 /* line drawing routine using Bresenham's algorithm. */
  c_draw (x1, y1, x2, y2, color)
  int x1, y1, x2, y2, color;
10 int incl, inc2, inc3, xend, yend;
11 int d, x, y, dx, dy;
12
13 dx = abs (x2 - x1);
14 dy = abs (y2 - y1);
15 if (dy <= dx)
16
      if (x1 > x2)
          x = x2;
19
          y = y2;
20
          xend = x1;
21
22
          dy = y1 - y2;
23
```

68020 and 68881

Development today

Just plugs into or clips onto any 68000

68020 and 68881 Take full advantage of the 68020. The new 128K ROMs from Apple and our 68020 board will give you a complete 68020 work station.

Macintosh

20 Megabyte

SCSI Hard Drive.

(800) 826-5178

(602) 884 - 7402

SPECTRA P.O.Box 41795, Tucson, AZ.85717

Circle no. 106 on reader service card.

```
x = x1
26
            y = y1;
27
            xend = x2;
            dy = y2 - y1;
30
       inc1 = dy << 1;
inc2 = (dy - dx) << 1;
31
32
       inc3 = (dy + dx) << 1;

d = (dy >= 0) ? inc1 - dx:inc1 + dx;
33
       while (x < xend)
             pcvwd (y, x, color); /* or whatever point plotting */
37
                                            /* function you have handy... */
38
             x++:
             if (d >= 0)
39
                if (dy \ll 0)
                    d += incl;
42
                else
43
                    y++;
                   d += inc2;
47
48
49
             else
51
                if (dy >= 0)
52
                    d += incl:
53
                else
54
                    d += inc3;
57
58
59
60
 61 else
 63
        if (y1 > y2)
64
             y = y2;

x = x2;
 65
 66
             yend = y1;
             dx = x1 - x2;
 69
 70
       else
 71
             y = y1;
x = x1;
 73
 74
             yend = y2
             dx = x2 - x1;
 75
 77
        inc1 = dx << 1;
        inc2 = (dx - dy) << 1;
inc3 = (dx + dy) << 1;
d = (dx >= 0) ? inc1 - dy:inc1 + dy;
 79
 80
        while (y < yend)
 83
             pcvwd (y, x, color);
             y++; if (d >= 0)
 84
 85
 86
                 if (dx \le 0)
                    d += incl;
 89
                 else
 90
 91
 92
                     d += inc2;
 94
 95
              el se
 96
                  if (dx >= 0)
                   d += incl;
                  else
  99
  101
                     x--;
d += inc3;
  102
  103
  105
  106
  107 pcvwd (y, x, color);
  108
  109
```

End Listings

C Bricklin Run

A Primer for Modern Times, or How to Use C-scape to Turn Dan Bricklin's Demo Screens into C Code.

Jane writes software. Dick is Jane's client. Dick wants his software yesterday. Jane uses Dan Bricklin's Demo Program to prototype Dick's software. That makes Dick and Jane happy.

Now Dick wants the real thing. Jane uses C-scape's demo2c utility to turn Bricklin's screens into C code with text, menus, input fields, and colors. Next Jane links with C-scape's library to add scrolling and type support.

Jane's program runs. Dick changes specs. Jane fixes the code easily with C-scape. See Dick smile. Dick is one happy client.

Look at **C-scape**. C Bricklin run. See productivity soar.

That's right. Compilable C code created directly from each and every screen you produce using Dan Bricklin's Demo Program. And the procedure is as simple as Dick and Jane. Make **C-scape** your primer.

- scrolling
- colors
- full type support
- completely definable kevs
- fully definable validation
- ☐ full screen I/O support
- fields, menus, prompts, and text
- flexible, easy to learn and use
- Lotus-like and pull-down menus
- source code included

30-day guarantee: Try C-scape for 30 days and see how it simplifies your development process. Following registration you'll get full source code and support. No run-time license, no royalties. We're developers, too. We know your needs.

> \$149.00 C-scape (Lattice 3.0/Microsoft 3.0; others call) \$219.00 C-scape with Dan Bricklin's Demo Program

Please add \$3.00 for shipping. Massachusetts orders please include 5% sales tax.

Another Key to Freedom, from

Oakland Group, Inc.



675 Massachusetts Avenue, Cambridge, MA 02139



For orders and information, call: 617-491-7311 or 800-233-3733

Circle no. 227 on reader service card.

QGLISP

THE CLOSEST THING TO COMMON LISP AVAILABLE FOR YOUR PC

RICH SET OF DATA TYPES

Bignums, for high precision arithmetic 8087 support, for fast floating point Arrays, for multidimensional data Streams, for device-independent i/o Packages, for partitioning large systems Characters, strings, bit-arrays

FULL SET OF CONTROL PRIMITIVES

flet, labels, macrolet, for local functions if, when, unless, case, cond, for conditionals Keyword parameters, for flexibility Multiple-valued functions, for clarity Flavors, for object-oriented programming Stacks, for coroutining Closures, for encapsulation

LARGE COMPLEMENT OF FUNCTIONS

Mappers, for functional programming format, for output control sort, for user-specified predicates Transcendental floating point functions String handling functions Over 400 functions altogether

APPLICATION SUPPORT

Save and restore full environments User-specified initializations Assembly language interface

HARDWARE REQUIREMENTS

8088 or 8086 CPU, MSDOS Operating System 390K RAM or more

IOCLISP

51/4" diskettes and manual

\$300.00

Foreign orders add \$30.00 for airmail. U.S. Shipping included for prepaid orders.

q Integral Quality P.O. Box 31970 Seattle, Washington 98103 (206) 527-2918

Washington State residents add sales tax. VISA and MASTERCARD accepted.

EXTENDABILITY

defstruct, to add data types Macros, to add control constructs Read macros, to extend the input syntax Extendable arithmetic system Customizable window system

DEBUGGING SUPPORT

step, for single-stepping trace, for monitoring break, for probing inspect, for exploring Flexible error recovery Customizable pretty-printer

MSDOS INTERFACE

Random access files Hierarchical directory access MSDOS calls

DOCUMENTATION

On-line documentation of functions apropos 300-page indexed reference manual

C CHEST

Listing One (Text begins on page 14.)

```
Listing 1 -- dtree.c
1 #include <stdio.h>
   #include <ctype.h>
                                  /* needed by spawn()
/* needed by dir()
/* needed by signal()
   #include <process.h>
4 #include <mydir.h>
5 #include <signal.h>
     * WHEREIS and DTREE
    * A general-purpose directory traversal program. If invoked with name
* "whereis" it searches for a file in the directory system. If invoked
* with "dtree" it does the above and can also print the directory tree or
* executes a program in each directory. See usage() and wusage() below
11
12
13
14
15
     * for more details about the command-line syntax.
                                   (C) 1986 Allen I. Holub. All rights reserved.
16
    */
                                   *mk_dir( int );
del_dir( DIRECTORY* );
dir( char*, DIRECTORY* );
*strrchr( char*, int );
19 extern DIRECTORY
20 extern void
21 extern void
22 extern char
24 /* -
     * These IBM graphics (box drawing) characters are used only if the
25
    * output stream is stdout and isatty() is true (it will be false if * stdout is redirected).
28
                                                                           (dash) -----
                            T RIGHT
                                                        VERT
30
     * \300 +----
                            \303
                                                        \263
                                                                          \304
33
                         *Graph_chars[] = { "\263", "\300\304\304\304\304\304\304\
                                                              "\303\304\304\304\304\304\304"
35
36
                         *Norm chars[] = { "|", "+----", "+---
**Cset = Norm chars;
38 static char
    #define ELL
                         Cset[1]
 42 #define T RIGHT Cset [2]
 46 #define DSIZE 255
                        47 static char
 48 static char
                         **Args = NULL; /* Thing to execute, pass to spawnv */
Short_pname = 0; /* Use short pathnames
Draw = 0; /* Draw directory tree */
*Findfile = NULL; /* File for which we're searching */
 52 static char
 53 static int
54 static int
 55 static char
 58
      * bitmap routines:
                                              Evaluates TRUE if bit x is set.
                          testbit (x)
 59
                          setbut (x,val) Set bit x if val is TRUE, else clear it.
      */
 61
     #define testbit(x) ( Map(x >> 3) & (1 << (x & 0x07)) )</pre>
 64
  65 static setbit(c, val)
  66 int
               c, val;
  67 (
                          Map[c >> 3] |= 1 << (c & 0x07);
  69
  70
                          Map[c >> 3] 6 = ~(1 << (c & 0x07));
  72 1
  76 pline( depth, terminate ) 77 {
                          Print all the spaces and vertical bars in a graphic representation of a tree. Does nothing if Draw if FALSE.
  78
  79
80
  81
  82
                 int
                           i:
                 if ( !Draw )
   84
   85
                           return;
                 ":"
                                                                              ", VERT );
   88
   89
90
91
                 92 1
   93
   95
   96 pname ( dname )
   97
                 *dnar
  98 (
                            Print a directory name with or without the full path
  100
                            spec (depending on whether Short pname is set.
  101
                  * /
  102
  103
                 char
  104
                 if(!Short_pname || (dname[0] == '/' && !dname[1]) )
  105
  106
                            name = dname:
```

```
else if ( name = strrchr(dname, '/') )
109
                         name++;
112
113
               printf( "%s\n", name );
114 }
115
117
118 execute ( dname )
120 {
                         Execute the command specified on the command line from
121
                         the directory we're now visiting. This routine changes the current directory but doesn't put it back.
123
124
                         The Args vector must point at the command array.
126
127
               if ( Args )
                         chdir( dname );
129
                         if( spawnvp(P_WAIT, *Args, Args) == -1 )
    perror(*Args);
130
132
133 }
134
135 /* -
137 find ( dname )
138 char
                *dname:
               /* Look for the Findfile file in dname. If it's there, print
* the full path and file names and return 1, else return 0.
140
141
143
                                    pathname[DSIZE];
**vects;
144
                static char
                char
145
146
                int
                                    count;
                                    rval;
                DIRECTORY
149
                sprintf( pathname, "%s/%s", dname, Findfile );
 150
151
                if( !(dp = mk dir( 64 )) )
 152
                          printf("dtree: Out of memory\n");
 155
                          return 0;
 157
                do->files = 1;
                dp->sort = 1;
dp->path = 1;
                                                         /* sort the list
                                                         /* and include the full path name */
 160
                dir( pathname, dp );
                                                         /* Fill the DIRECTORY structure
 161
                vects = (char **) dp->dirv;
count = rval = dp->nfiles;
while( --count >= 0 )
                                                         /* ... and print it.
 164
 165
                         printf( "%s\n", *vects++ );
 166
 167
 168
                del dir ( dp );
                return rval;
 170 }
 171
 172 /*
 173
 174 static prnt ( dname, others )
 175 char
 176 int
                others;
 177 {
178
                 /* Does a recursive traversal of the directory tree rooted at
* dname. "others" is true if the calling routine has more
  179
  180
                  * subdirectories to print.
  181
  182
  183
184
                 DIRECTORY
                                     *dp;
                                     **vects;
                 char
                                     count;
depth = -1;
  185
                 int
                  static int
  187
  188
                 if ( ++depth && Draw )
                           pline( depth, 0 );
printf("%s", others ? T_RIGHT : ELL );
  190
  191
  193
                                                                 /* If -f was set don't
/* execute a -e command
/* unless we've found the
                 if ( Findfile )
  194
  195
                            if( find( dname ))
                                      execute ( dname );
  197
                  else
   200
                                                                 /* else print the directory */
/* name and execute the cmd */
   201
                            pname
                                    ( dname );
                            execute ( dname );
   203
   204
   205
                  if( ! (dp = mk_dir( 32 )) )
                            printf("dtree: Out of memory\n");
   207
   208
                            return;
   210
                                                       /* Get subdirectories
   211
                  dp->dirs = 1;
   212
                  dp->sort = 1;
dp->exp = 1;
                                                       /* and sort them.
                                                        /* expand subdirectories rather than */
                                                        /* printing their names.
   214
                                                                (continued on page 66)
```



puters. We're your best one-stop source for the professional PC/MS-DOS and XENIX programming tools you need.

Since we're an independent dealer, we'll look out for your best interest. Our courteous, knowledgeable, noncommissioned sales staff is always ready to assist you. If you aren't sure about your needs, you can talk to our experienced, professional technical staff for sound, unbiased advice. They can compare products, answer technical questions and send you detailed product information that's tailored to your needs.

Our product line consists of hundreds of high quality software development tools specifically for IBM Personal Computers and compatibles. We don't carry everything ever written for programmers — only those products that meet our very high standards for quality and value.

The products we carry are the latest version and they all come with the same manufacturer's technical support as if buying direct. Unlike other dealers who participate in the software gray market, we're authorized to sell every product we carry.

We discount all software products — even special order items. We don't try to fool you by discounting some products and charging full list price for others. Every product in our price list is shown with its discounted and retail price. We want you to know exactly how much you'll save on every product.

Other dealers add extra rush charges for shipping via express services. We'll express your order to you with no special handling charges. We only charge you what the shipping carrier charges. And if you have your order shipped via standard UPS, shipping is FREE.

efficient service. If we don't have a product in stock, we'll get it for you fast. Again -

no extra charge.

Some dealers charge your credit card at the time they take your order. This means you could be left waiting in vain for your order for weeks or months while they use your money interest free. We never charge your credit card until we actually ship your order.

Quite simply, the discount prices you see on the next two pages are all you pay. There are no hidden charges. We don't charge extra for standard UPS shipping, credit cards, COD orders, purchase orders or special handling (except orders outside the U.S. and Canada are charged \$5 for customs form preparation).

Our goal is customer satisfaction and that's why we offer 30 day no-risk return guarantees and 30 day evaluation periods on most of our products. Note that some items, especially those with source code, are restricted by the manufacturers from this quarantee. Please call for specific details.

Our customers keep coming back because we consistently provide high quality service and low discount prices. So make the connection today and see how convenient one-stop service can be.

CALL TOLL FREE US: 800-336-1166 CANADA: 800-225-1166

OHIO AND OVERSEAS: 216-877-3781 Hours: 8:30 AM to 8:00 PM Eastern Time, Mon.-Fri. Customer Service: 216-877-1110



Call or write for our FREE comprehensive price guide. Turn the page for our latest advertised price list.

PROGRAMMER DEVELOPMENT TOOLS FOR THE IBM-PC/XT/AT

anllanguage	LIST	OLIDE	and comp	atib	les.
APL*PLUS/PC System by STSC	595	OURS 449			
APL*PLUS/PC Tools Vol 1 by STSC	295	239	c interpreters		
APL*PLUS/PC Tools Vol 2 by STSC	150 195	129 159	C-terp by Gimpel Software Specify compiler interface	300 500	239 379
APL*PLUS/UNX System For AT Xenix by STSC	995	795	Instant C by Rational Systems	125	105
Btrieve ISAM File Mgr with No Royalties by SoftCraft	250	195	Run/C by Age of Reason	150	99
Financial/Statistical Library by STSC	275 95	219 79	Run/C Professional by Age of Reason	250	184
STATGRAPHICS Statistical Graphics System by STSC	795	619	c utilities		
arity products			Also refer to Blaise, Lattice, Microsoft, Phoenix, Polytror SoftCraft and Xenix System V sections.	,	
Arity Expert System Development Package New	295	279	APT Application Programmer's Toolkit by Shaw American	395	339
Arity File Interchange Toolkit New Arity Prolog Compiler & Interpreter New	50 795	48 739	Basic C Library by C Source	175 100	135 85
Arity Prolog Interpreter	350	329	C to dBase ISAM Manager by Computer Innovations	150	139
Arity SQL Development Package New	295 50	279 48	c-tree ISAM File Manager with source by FairCom	395 185	329 139
Arity Screen Design Toolkit New Arity Standard Prolog New	95	89	C Utility Library by Essential Software	100	89
artificial intelligence			C Wings by Syscom	50	45
ExpertEDGE by Human Edge	795	659	CI Probe Source Level Debugger Limited Quantity Sale CI RomPac for C-86 by Computer Innovations	225 195	159 149
Experteach II Complete System by Intelligenceware	475 395	CALL 339	dBx dBase to C Translator by Desktop Al New	350	329
EXSYS Expert System Development Software by EXSYS First Class by Human Edge	500	419	dbQUERY by Raima	CALL 195	CALL 159
GCLISP Golden Common LISP by Gold Hill	495	CALL	dbVISTA Single-User DBMS by Raima	495	429
GCLISP 286 Developer LM Interpreter & LM Compiler	1190 95	CALL 75	dbVISTA Multi-User DBMS by Raima	495	429
Insight 2+ by Level Five Research	485	389	with Source Code Entelekon Combo Package All 3 items below	990	849 175
Logic-Line Series All varieties by Thunderstone New	CALL	CALL	C Function Library	130	115
Microsoft LISP Common LISP PLA microProlog by Programming Logic Associates	250 250	189 219	C Windows	130	115 45
with APES	450	399	Superfonts for C Essential Graphics No Royalties by Essential Software	50 250	219
PLA Professional microProlog by Programming Logic	395	349 599	Flash-up Windows by Software Bottling of NY	75	69
with APES	695 375	359	GraphiC Mono version 2.2 by Scientific Endeavors	280 350	219 299
Turbo Prolog Compiler by Borland International	100	79	GraphiC Color version 3.0 by Scientific Endeavors The Greenleaf Functions by Greenleaf Software	185	135
assembly language			Greenleaf Comm Library by Greenleaf Software	185	135
8088 Assembler w/Z-80 Translator by 2500 AD	100	89	The HAMMER by OES Systems	195 185	175 139
ASMLIB Function Library by BC Associates New Cross Assemblers Over 25 Varieties from 2500 AD	149 CALL	129 CALL	MetaWINDOWS by Metagraphics	235	199
Microsoft Macro Assembler with utilities	150	99	Multi-Halo with Royalties by Media Cybernetics	300	219
Turbo EDITASM Fast Assembler by Speedware	99 80	84 65	On-line Help from Opt-Tech Data Processing PANEL by Roundhill Library Source Also Available	149 295	119 229
Visible Computer: 8088 by Software Masters	00	05	PC Lint by Gimpel Software	139	109
basic language BetterBASIC by Summit Software	200	165	Scientific Subroutine Library for C by Peerless	175 150	139 139
8087 Math Support	99	85	Vitamin C by Creative Programming VC Screen Interactive Forms Designer	99	85
Btrieve Interface	99	85	Zview with Free Updates by Data Mgmt Consultants	245	199
C Interface	CALL 250	CALL 225	cobol language		
Microsoft QuickBASIC Compiler New version 2.0	99	79	Micro Focus COBOL Workbench	4000	3599 CALL
Professional BASIC by Morgan Computing	99 50	79 47	Micro Focus Level II COBOL	1500 250	219
8087 Math Support	150	105	COMATH	200	169
Run-time Module	500	435	FORMS-2Level II Animator	300 900	269 CALL
blaise products			Level II SOURCEWRITER	2000	CALL
ASYNCH MANAGER Specify for C or Pascal	175 175	136 149	Micro Focus Level II COBOL For Novell NetWare	2000	1799
C TOOLS / TOOLS 2 Combination Package	125	105	Micro Focus Micro/SPF	175	159 2395
C TOOLS 2	100	84	Multi-user Runtime for PC Network	500	449
C TOOLS PLUS for Lattice C 3+ and Microsoft C 3+ New EXEC Program Chainer	175 95	139 79	Microsoft COBOL See Microsoft Section OPT-Tech Sort Also Sorts Btrieve Files	700 149	495 119
PASCAL TOOLS/TOOLS 2 Combination Package	175	139	Realia COBOL	995	839
PASCAL TOOLS	125 100	105 84	RM/COBOL by Ryan-McFarland	950	675
PASCAL TOOLS 2	50	47	RM/COBOL 8X ANSI 85 COBOL by Ryan-McFarland	1250	995
TURBO ASYNCH PLUS for Turbo Pascal New Version	100	84	debuggers & profilers	175	120
TURBO POWER TOOLS PLUS for Turbo Pascal New Version VIEW MANAGER with Source Specify for C or Pascal	100 275	84 209	Advanced Trace-86 with ASM Interpreter by Morgan CI Probe Source Level Debugger Limited Quantity Sale	175 225	139 159
borland products	215	203	Codesifter Execution Profiler by David Smith New	119	99
REFLEX Data Base System	150	119	Codesmith-86 Debugger by Visual Age	145 295	109 249
REFLEX Workshop New	70	59	Periscope II w/NMI Breakout Switch Only	145	115
REFLEX and REFLEX Workshop Combo Package New Turbo DATABASE TOOLBOX	200 70	159 54	Periscope II-X Software only Special Price thru August	115	85
Turbo EDITOR TOOLBOX	70	54	forth language		
Turbo GAMEWORKS TOOLBOX	70 70	54 54	CFORTH Native Code Application Compiler by LMI	300 750	239 599
Turbo GRAPHIX TOOLBOX		75	PC/Forth by Laboratory Microsystems	150	119
Turbo PASCAL with 8087 and BCD	100	69	PC/Forth+ by Laboratory Microsystems	250	209
Turbo Prolog Compiler	100 40		fortran language	405	400
Word Wizard New	70	59	ACS Time Series by Alpha Computer Service	495 250	429 195
Word Wizard and Turbo Lightning Combo Package New	150	129	50 MORE: FORTRAN by Peerless Engineering	125	99
ccompilers		000	For-Winds by Alpha Computer Service	90 70	79 55
C-86 Optimizing Compiler Datalight C Compiler Small Memory Model	395 60		Forlib-Plus by Alpha Computer Service FORTRAN Addenda by Impulse Engineering New	95	89
Datalight Developer's Kit with Large Memory Model	99	79	FORTRAN Addendum by Impulse Engineering New	165	149
DeSmet C with Source Debugger			Grafmatic or Plotmatic by Microcompatibles New Grafmatic and Plotmatic by Microcompatibles New	135 240	119 219
Desiriet C with Depugger & Large Case Option New				240	
Eco-C Complete Development System by Ecosoft	209 125	89	Microsoft Fortran	350	215
Eco-C Complete Development System by Ecosoft	209 125 500	89 299	Microsoft Fortran	300	219
Eco-C Complete Development System by Ecosoft Lattice C Compiler from Lattice Let's C Compiler by Mark Williams	209 125 500 75	89 299 59	Microsoft Fortran Multi-Halo with Royalties by Media Cybernetics PANEL Screen Designer by Roundhill RM/Fortran by Ryan-McFarland		219 229
Eco-C Complete Development System by Ecosoft Lattice C Compiler from Lattice See Lattice Section Let's C Compiler by Mark Williams with csd Source Level Debugger Microsoft C Compiler with CodeView New version 4.0	209 125 500 75 150 450	89 299 59 118 299	Microsoft Fortran Multi-Halo with Royalties by Media Cybernetics PANEL Screen Designer by Roundhill RM/Fortran by Ryan-McFarland Scientific Subroutine Library by Peerless	300 295 595 175	219 229 394 139
Eco-C Complete Development System by Ecosoft Lattice C Compiler from Lattice See Lattice Section Let's C Compiler by Mark Williams with csd Source Level Debugger	209 125 500 75 150 450 495	89 299 59 118 299 299	Microsoft Fortran Multi-Halo with Royalties by Media Cybernetics PANEL Screen Designer by Roundhill RM/Fortran by Ryan-McFarland	300 295 595	219 229 394 139

lattice products		OURS
Lattice C Compiler from Lattice	500 900	299 549
C Cross Reference Generator	50 200	39 159
C-Food Smorgasbord Function Library	150	99
with Source Code	300 175	195 139
Curses Screen Manager	125	98
with Source Code	250 250	194 194
with Source Code	500	388
LMK Make Facility	195 750	149 635
SecretDisk File Encryption Utility	120	95
SideTalk Resident Communications. Text Mgmt Utilities (GREP,DIFF,ED,WC,Extract,Build).	120 120	95 95
TopView Toolbasket Function Library. with Source Code	250	194 388
Z-80 C Cross Compiler	500 500	388
with Library Source Code	1000	789
logitech products Logimouse	99	89
Logimouse+ New	119	105
Logimouse+ with Paint New MODULA-2/86 Compiler	169	149 64
with 8087	129	104
with 512K	189	148 49
MODULA-2 Runtime Debugger MODULA-2 Source Package	69	59
MODULA-2 Translator TurboPascal to MODULA- 2 New	179 49	155 45
MODULA-2 Utilities Package	49	45 45
:	73	75
Microsoft BASIC Interpreter for Xenix	350	279
Microsoft C Compiler with CodeView New version 4.0 Microsoft COBOL Compiler	450	299
for Xenix	700 995	495 795
Microsoft COBOL Tools with COBOL Source Debugger for Xenix	350 450	209
Microsoft Fortran Compiler	350	359 215
for Xenix Microsoft LISP Common LISP	695 250	CALL 189
Microsoft Macro Assembler with utilities. Microsoft Mouse Bus Version	150	99
MICROSOft Mouse Serial Version	175 195	149 159
Microsoft muMath Includes muSIMP Microsoft Pascal Compiler	300	195
for Xenix	300 695	195 CALL
Microsoft QuickBASIC Compiler New version 2.0 Microsoft Sort	99 195	79 149
Microsoft Windows	99	74
	500	395
other languages CCS MUMPS Single-User version by MGlobal New	60	55
CCS MUMPS Multi-User version by MGlobal New Janus/ADA C Pack by R&R Software	450	379
Janus/ADA D Pack by R&R Software	95 900	89 795
Methods Smalltalk by Digitalk Smalltalk/V by Digitalk New	79 99	69
SNOBOL4+ by Catspaw New	95	89 84
other products		
Dan Bricklin's Demo Program by Software Garden	75	65
Interactive EASYFLOW by Haventree Software	179 150	159 129
Quilt Computing Combo Package Both Items Below. New QMake Program Rebuild Utility. New	199 99	169 84
SRMS Software Revision Mamt System	125	109
Source Print by Aldebaran Laboratories. Taskview by Sunny Hill Software New	139	119 59
phoenix products		-
Pfantasy Pac (Pfinish,Pfix+,Plink+,Pmaker,Pmate,Ptel)	1295	949
Plix-86 Plus Symbolic Debugger	395 395	259 259
Plink-86 Overlay Linker	395	289
Plink-86 Plus Enhanced Overlay Linker	395 495	259 359
Pmate Macro Text Editor	195 295	149 195
Ptel Binary File Transfer Program	195	149
polytron products		
Polytron C Beautifier	49 99	45 79
Polytron PowerCom Communications	179	139
PolyLibrarian Library Manager	99	79

		9/86
PolyLibrarian II Library Manager	149	119
PolyMake UNIX-like Make Facility	99	79
PolyOverlay Overlay Optimizer	99	79
PolyWindows Products All Varieties.	CALL	CALI
PolyXREF Complete Cross Reference Utility	219	179
PolyXREF Support for one language only	129	109
PVČS Polytron Version Control System PVMFM Polytron Virtual Memory File Manager	395	329
	199	149
softcraft products		
Btrieve ISAM File Manager with No Royalties	250	19
Xtrieve Query Utility for Btrieve	195	16
Rtrieve Report Generator for Xtrieve	85	7
Btrieve/N for Networks	595	46
Xtrieve/N Query Utility for Btrieve/N	395	299
Rtrieve/N Report Generator for Xtrieve/N	175	159
text editors		
Brief from Solution Systems	195	CALL
Epsilon Multi-tasking Emacs-like editor by Lugaru	195	165
FirsTime for Turbo by Spruce Technology	75	69
KEDIT Xedit-like editor by Mansfield Software Group	125	109
PC/VI by Custom Software Systems New	149	129
Personal REXX by Mansfield Software Group New	125	109
SPF/PC by Command Technology Corp	195	165
Vedit by CompuView	150	115
XTC Text Editor with source by Wendin	225	180
	99	84
turbo pascal utilities		
Also refer to Blaise, Borland and SoftCraft sections. ALICE Turbo Pascal Interpreter by Software Channels	OF	
FirsTime for Turbo by Spruce Technology	95	69
Flash-up Windows by Software Bottling of NY	75 75	69
Multi-Halo with Royalties by Media Cybernetics	CALL	CALL
On-line Help from Opt-Tech Data Processing.	149	119
Screen Sculptor by Software Bottling of NY	125	95
Turbo EXTENDER by TurboPower Software	85	69
Turbo Professional by Sunny Hill Software	70	49
TurboPower Utilities by TurboPower Software	95	84
TurboWINDOW by MetaGraphics	80	69
wendin products		
Operating System Toolbox Build your own OS	99	84
PCUNIX Operating System	99	84
PCVIMS Operating System Similar to VAX/VMS	99	84
XTC Text Editor with Pascal Source Code	99	84
xenix system v		
Complete Xenix System by SCO All 3 items below.	1295	1099
Xenix Development System	595	529
Aeriix Operating System Specify XT or AT	595	529
Xeriix Text Processing Package	195	169
xenix languages and utilitie	es	
APL*PLUS/UNX System For AT Xenix by STSC	995	795
Birleve ISAM File Manager by SoftCraft	595	465
C-tree ISAM File Manager with Source by FairCom	395	329
UDX UDase to C Translator w/source by Deskton Al New	550	499
dbVISTA Single and Multi User versions by Raima	CALL	CALL
Informix by Relational Database Systems	995	839
Informix4GL by Relational Database Systems New	CALL	CALL
InformixSQL by Relational Database Systems New Lyrix by SCO	995	839
Lyrix by SCO Micro Focus Level II Compact COBOL For AT	595	489
1 011113-2	1000	899 359
Level II ANIMATOR	600	539
MICROSOft Languages See Microsoft Section	000	303
Networks for XENIX by SCO	595	529
PANEL Screen Designer for AT Xenix by Roundhill	695	CALL
RM/COBOL by Ryan-McFarland	1250	995
KM/FORTRAN by Ryan-McFarland	750	599
SCO Professional Complete Lotus clone by SCO	795	695
Prices are subject to change without notice.		
VICA TICES WE Subject to change without notice.		

VISA

Prices are subject to change without notice. Ohio customers please add 5% state sales tax.



Hours: 8:30 AM to 8:00 PM EST, Monday through Friday.



1-800-336-1166 1-800-225-1166 1-216-877-3781



FTL Modula-II \$49.95!



Your next computer language. The successor to Pascal, Modula is powerful. Why? Once a routine is written, it need never be recompiled. Programs work everywhere from Z80 through VAX.

FTL Modula-II is a full Z80 CP/M compiler (MSDOS version soon)! It's **fast** -- 18K source compiles in 7 seconds! The built-in split screen editor is worth \$60 alone. Some standard features: full recursion, 15 digit reals, CP/M calls, coprocesses, assembler and linker. The one-pass compiler makes true Z80.COM, ROMable code, too. Get the language you've waited for now. Only \$49.95!

FTL Editor Toolkit

Full source to our split-screen programming editor. Curious? Want to customize to your tastes? Want sample Modula-II code? This is perfect for you. Comes with all you need for your personal editor or terminal installer.

WORKMAN & ASSOCIATES

1925 East Mountain St. Pasadena, CA 91104 (818) 791-7979

We have over 200 formats in stock! Please specify your format when ordering. Add \$2.50 per order for shipping. We welcome COD orders!

Circle no. 244 on reader service card.

Maximum Performance Debugging

DSD86, The PC-DOS Debugger	69.95
DSD87, The PC-DOS Debugger with 8087 Support.	
DSD80. The CP/M Debugger	125.00



P.O. Box 49473 • Austin, Texas 78765 • (512) 478-4763 1-800-232-8088

Circle no. 83 on reader service card.

C CHEST

Listing One

(Listing continued, text begins on page 14.)

```
do-Snath = 1:
                                                          /* and include the full path name. */
217
                 vects = (char **) dp->dirv;
218
                                                                   /* pointer to list of subdirs */
                 count = dp->ndirs;
                                                                   /* number of subdirs.
220
221
                 while ( --count >= 0 )
                                                                           /* visit the subdirs, one */
                                                                          /* at a time. the setbit
/* call is used for
                            setbit( depth, count );
prnt( *vects++, count );
223
224
                                                                          /* printing the tree.
226
                                                                          /* If there aren't any */
/* subdirs in the parent, */
/* output a blank line */
                 if (!others)
                            pline ( depth, 1 );
228
229
                 del_dir(dp);
231
                 --depth;
232 }
233
234 /*
236 char
                  dodot ( str )
237 char
                 *str:
                 /* If str has no dots in it, return str, else get the pathname
239
                  * refered to by str (ie. whatever name is indicated by
*.or..or../.. etc.) and return a pointer to that string.
240
242
243
244
245
246
                 static char root_name[ DSIZE ];
                 if( !strchr( str. '.' ) )
247
                 if ( chdir(str) || !getcwd(root_name, DSIZE) )
250
                             fprintf(stderr, "Can't find %s, aborting\n", str );
 252
 253
                             exit(1);
 255
                  for ( p = root_name; *p; p++)
                                                                           /* Map the name from DOS */
 256
                                                                           /* style to UNIX style by */-
/* mapping upper to lower */
/* case and changing \ to */
 257
                             if( *p == '\\' )
 258
                                        *p = '/';
 260
                                        *p = tolower( *p );
 261
 263
                                                                           /* Restore the original
/* working directory
 264
                  chdir( Startdir ):
                  return root name ;
 266 1
 267
 270 doargs ( argc, argv )
271 char **argv;
                  /* Does several things. First, it shifts all the arguments down one notch, overwriting the original argv[0]. Next, it puts a NULL into argv[argc-1], finally it processes are removes from argv) all command line switches. Switch processing stops after a -e is encountered (but the compression continues).
 273
 276
 277
                    * Argc, decremented to reflect all this stuff, is returned.
  279
                    * We can't use getargs() in the program because -e is * position dependant.
  282
                   register int nargc;
register char **nargv;
  285
  287 #ifdef DEBUG
                   char **v = argv;
  288
  290 tendif
  291
                   nargc = 0;
for( nargv = argv++; --argc > 0; argv++ )
  292
  293
  294
                              if( **argv != '-' || Args )
   296
                                          *nargv++ = *argv ;
  297
  298
                                          nargc++;
                               else
   300
   301
302
303
                                           switch( argv[0][1] )
                                           case 'e':
   304
                                                           Args = nargv ;
^nargv++ = *++argv ;
nargc ++;
putenv("CMDLINE=") ;
   305
306
                                                           Args
   307
   308
                                                           break;
                                           case 'f': Findfile = &argv[0][2];
case 's': Short_pname = 1;
case 'd': Draw = 1;
default : usage();
                                                                                                    break:
                                                                                                    break;
    313
   314
    316
    317
                                                                         (continued on page 68)
```

NOW AT THE SBC MART **COMPUTING SALE-A-THON**

1.2MB Floppy on your PC or XT


Now you can have a 1.2MB-and-360K AT-compatible floppy disk drive on your IBM (or compatible) PC or XT. Our 1.2MB controller replaces your floppy disk controller. The controller is \$149, a TEAC 1.2MB/360K disk drive is \$135, the driver is \$36. The controller combined with clock/calendar, serial and parallel ports, and able to control 3.5" and 8" floppy disk drives is only \$189.

SPECIAL BONUS Norton Utilities Ver 3.0 Reg \$99 only \$60 w/purchase of any disk drive. IBM PC-DOS 3.2 (the real thing) Reg \$95 only \$70, w/purchase of motherboard.

ADD-ON CARDS

- multifunction card 384K, clk/cal w/battey, serial, parallel, and game ports, with 0K save \$50 Model MFC-4 \$89
- monochrome graphics card runs 1-2-3 graphics, w/printer port, 720x348, MGC-1 now \$99 (Hercules equiv.)
- floppy controller for 1-4 48tpi or 96tpi drives, w/cable save 125 Model FDC-2 now only \$59
- · color adapter w/light pen port, RGB and composite outputs Reg \$140 Model CC-1 now just \$79
- * better than the Super 7: floppy disk controller, clk/calendar, serial, parallel & game ports, spooler & RAMDISK s/w Sale \$99 ideal mate for 640K motherboards
- clock/calendar card Reg \$58, CL-1 \$49
- ★ 808K ON A SINGLE FLOPPY, TEAC 96tpi 80-track disk drive kit, complete, nothing else to buy now \$169

CASES




- high quality IBM PC look alike w/sideswitch, flip-flop top or side chassis
- any-combo disk drive brackets
- heavy steel 5- and 8-cutout style
- Model CA-8 Reg \$95, now \$69

SBC PLEDGE

- * service after sale
- * technical support
- ★ low prices
- * one year warranty

MOTHERBOARDS



- full IBM PC/XT compatibility
- 8 I/O slots - runs IBM's PC-
- DOS 3.1 & 3.2 BASIC inter-
- preter available great foundation for business or
- personal system 1 year warranty
- ★ Model MB-2 640K Turbo motherboard 4.77 & true 8MHz clock (switchable from keyboard or by software) with 256K RAM Reg \$349 now \$239
- Model MB-3 640K motherboard with OK Reg \$199 now \$159
- TURBO Program see below, right.

ABOUT OUR MOTHERBOARDS

- the most IBM PC compatible 'motherboards available
- each runs all commercially available software
- each works with all commercially available add-on cards

These FOUNDATION motherboards are the most compatible you can buy. All work with V20 chips, have parity checked memory, an 8087 socket, 8 adapter slots. four empty ROM sockets. Super manual includes complete data on how to put together a complete PC system. It even includes schematics.

HARD DISKS



- complete 20 MB kit
- special only \$479
- complete internal 1/2-high 20MB kit, incl. controller and cables, special \$479
- complete 30 MB kit with 1/2-high drive, uses new Adaptec 2070-A controller.
- * OMTI hard disk controller card (this card is super fast) Reg \$220, Model HDC-1 now \$175, w/cables
- ★ Generalized hard-disk controller works with almost any drive. Just tell the controller your drive specs. Fast OMTI 5510-7 hard disk controller with cables and OMTIDISK utilities HDC-4 only \$189
- "Assembling an IBM PC/XT Compatible Computer System" A novice can put an IBM PC compatible together with this new detailed manual. \$19
- Microsoft's new QuickBASIC full MS BASIC compiler, Reg \$99, only \$89

POWER SUPPLY

- 135 Watts
- side switch
- top quality
- one year warranty
- standard cables for 4 disk drives
- Model PS-135 power supply Reg \$129.

now only \$75 **TURBO PROGRAM**

* This program will set virtually all turbo motherboards to the turbo, or high-speed, mode. Can be called from the keyboard or

from your AUTOTEXEC file only \$19

BEST DOS MANUAL

★Microsoft Press' "Running MS DOS". For the less experienced and the most knowledgeable MS/PC DOS user. 423 pages. We regularly get calls from our customers telling us how great this book \$21.95


Shipping and handling: drives/motherboards/cases/power supplies \$4.50 ea., cards \$2 ea., software \$2.50 ea., keyboards/modems \$4 ea., speedup kits \$2 ea., memory \$1/set, COMPUTERFACTS \$3 first set then \$1/set. CA residents add 6% sales tax.



Visa/MC/AmEx ORDERS:(619) 375-5744 The SBC MART, P.O. BOX 1296, Ridgecrest, CA 93555



The SBC Mart is part of Computing Technology, 247 Balsam Street, Ridgecrest, CA 93555



the dBx™ translator

- dBx produces quality C direct from dBASE II or III programs.
- Move dBASE programs to UNIX or other machines.
- Improve program speed and reliability.
- Support multi-user/network applications.
- With power guidebook of conversion hints.
- Includes full screen handler and uses your current C database manager.
- May be used to move existing programs or help dBASE programmers learn C easily.
- For MSDOS, PCDOS, UNIX, XENIX, Macintosh, AMIGA.
 (Uses ANSI.SYS driver on MSDOS, CURSES under UNIX)
- Priced from \$350, also available from distributors.

dBx is a trademark of Desktop Ai

1720 Post Road E., Westport, CT 06880 MCIMAIL • DESKTOPAI Phone • 203•255•3400 Telex • 6502972226MCI



Transform Your Programs with CPP—C Preprocessor Plus

Includes ALL features of the standard C preprocessor.

- Define arbitrarily complex macros with #define command.
- Include and nest files to any depth with #include command.
- Include lines with #if, #ifdef and #ifndef commands.
- Define multiple constants with #enum command.
- Optional extra feature: Imbed formatting or other commands in your source code. (Lines starting with . or * are ignored.)

Fast and flexible

- 30 times faster than the Preprocessor published in Dr. Dobb's Journal.
- Can be used for any language, including assembler.
- Can be used as a stand-alone macro/include processor.
- Code can be used as the lexical analyzer for parsers or assemblers.

Complete

- You get complete SOURCE CODE in standard C.
- You get everything you need to use CPP immediately.
- CPP is unconditionally guaranteed. If for any reason you are not satisfied with CPP, your money will be refunded promptly.

Price: \$95.

Enteleki, Inc. 210 N. Bassett St., Room 101 Madison, WI 53703 Tele. (608) 258-7078

TO ORDER: Specify both the operating system (MS-DOS, CP/M 80 or CPM 68K) and the disk format (8 inch CP/M or the exact type of 5½ inch disk). Send a check or money order for 595 (\$105 for foreign orders). Foreign checks must be denominated in U.S. dollars drawn on a U.S. bank. Sorry, I do NOT accept phone, credit card or COD orders. Please do NOT send purchase orders unless a check is included.

C CHEST

Listing One

(Listing continued, text begins on page 14.)

```
*argv = NULL ; /* Add a NULL as the last entry */
321 #ifdef DEBUG
                printf("New argv is:\n");
322
323
                for( c = nargc; --c >= 0 ; v++)
printf("<%s> 0x*x\n", *v, *v );
324
326
                327
329 #endif
330
                return nargo ;
331
332 1
334 /*
335
 336 #define E(x) fprintf(stderr, "%s\n", x)
337 usage ()
338 (
            339
340
341
            E("-fFind file called called cnames" );E("-s Use short path names" );E("-d Draw directory tree" );E("\nEach switch must be in its own argument (-sd is illegal,");E("you must say -s -d). If -f and -e are both specified, the command");E("is only executed if the indicated file is found.");
 342
343
344
 346
 348 }
 349
 350 wusage ()
 351 (
           E( "\nUsage is: whereis <filename>\n"); 
E( "Only one file name is permitted, though wildcards are recognized"); 
E( "by whereis itself, so you must escape these from the shell as in:"); 
E( "\twhereis \\".c\" or whereis \\\.c\" );
 352
 353
 355
 356
           exit (1):
 357 }
 358
 359 /* -
 361 onintr()
 362 1
                                                /* Called when a ^C is encountered:
                                                /* Get back to starting directory /* before exiting.
                 chdir ( Startdir );
 364
 365
                 exit(0):
 367
 368 /*
369
 370 main (argc, argv)
 371 ch
372 (
                           If the program is invoked under the name "whereis" it
 373
                            treats the command line: whereis <fname>
as if you had said: dtree / -f<fname>
 375
  376
  377
378
                 reargy( &argc, &argv ); /* Redo arg list if running under shell */
  379
                  if (!strcmp(*argv, "whereis"))
  381
                           if ( argc != 2 || argv[1][0] == '-' )
  382
                                      wusage();
  384
                                                           /* Search for a file.
/* Force search to begin at /
  385
                            Findfile = argv[1]:
  387
                  else
  389
                            argc = doargs( argc, argv );
  390
                                                                      /* argv[0] [1] [2] ... */
/* pathname cmd args ... */
                            if ( Args && argc < 2 )
  392
  393
                                       usage();
   395
   396
                  Cset = isatty(fileno(stdout)) ? Graph_chars : Norm_chars ;
   397
   398
                  if ( !getcwd (Startdir, DSIZE) )
   400
                             fprintf(stderr, "Can't save current directory, aborting\n");
   401
   402
                             exit(1);
   403
   405
406
407
                  signal( SIGINT, onintr );
prnt( (argc < 1 || argv == Args) ? "/" : dodot(argv[0]), 0 );
chdir( Startdir );</pre>
   408
                  exit(0):
                                                                            End Listing One
```

Listing Two

Listing 2 -- fix.c

1 finclude <stdio.h>

#include <fcntl.h>
#include <types.h>
#include <stat.h>
6 extern char *strrchr();

(continued on page 70)

DIGITAL RESEARCH COMPUTERS

(214) 225-2309

S100 EPROM PROGRAMMER

OUR NEWEST DESIGN. FOR FAST EFFICIENT PROGRAMMING OF THE OUR NEWEST DESIGN, FOR FAST EFFICIENT PROGRAMMING OF THE MOST POPULAR EPROM'S ON YOUR S100 MACHINE. COMES WITH MENU DRIVEN SOFTWARE THAT RUNS UNDER CP/M 2.2 (8 INCH), PC BOARD SET CONSISTS OF (S100) MAIN LOGIC BOARD REMOTE PROGRAMMING CARD AND SIX PERSONALITY MINI BOARDS FOR 2716, 2532, 2732, 2732A, 2764, AND 27128. SOLD AS BARE PC BOARD SET ONLY WITH FULL DOC. SOFTWARE FEATURES "FAST" PROGRAMMING ALGORITHM. FOR Z80 BASED SYSTEMS.



PC BOARD SET, FULL **DOCUMENTATION, 8 IN.** DISKETTE WITH SOFTWARE.

NEW! \$6995

128K S100 STATIC RAM/EPROM BOARD

JUST OUT! USES POPULAR 8K X 8 STATIC RAMS (6264) OR 2764 EPROMS. FOR 8 OR 16 BIT DATA TRANSFERS! IEEE 696 STANDARD. LOW POWER. KITS ARE FULLY SOCKETED. FULL DOC AND SCHEMATICS INCLUDED. 24 BIT ADDRESSING.

NEW!

\$5995


BARE PC BOARD

\$21900 128K RAM KIT

\$13900 128 EPROM KIT

256K S-100 SOLID STATE DISK SIMULATOR! WE CALL THIS BOARD THE "LIGHT-SPEED-100" BECAUSE IT OFFERS AN ASTOUNDING INCREASE IN YOUR COMPUTER'S PERFORMANCE WHEN COMPARED TO A MECHANICAL FLOPPY DISK DRIVE.

PRICE CUT!



BLANK PCB

(WITH CP/M° 2.2

PATCHES AND INSTALL PROGRAM ON DISKETTE)

\$4995

(8203-1 INTEL \$29.95)

FEATURES:

- 256K on board, using + 5V 64K DRAMS.
- Uses new Intel 8203-1 LSI Memory Controller.
- Requires only 4 Dip Switch Selectable
- Runs on 8080 or Z80 S100 machines. Up to 8 LS-100 boards can be run together for 2 Meg. of On Line Solid State Disk Storage.
- State Disk Storage.
 Provisions for Battery back-up.
 Software to mate the LS-100 to your
 CP/M* 2.2 DOS is supplied.
 The LS-100 provides an increase in
 speed of up to 7 to 10 times on Disk
- Intensive Software
- Compare our price! You could pay up to 3 times as much for similar boards.

(ADD \$50 FOR A&T)

(FULL 256K KIT)

ZRT-80

CRT TERMINAL BOARD!

A LOW COST Z-80 BASED SINGLE BOARD THAT ONLY NEEDS AN ASCII KEYBOARD, POWER SUPPLY, AND VIDEO MONITOR TO MAKE A COMPLETE CRT TERMINAL. USE AS A COMPUTER CONSOLE, OR WITH A MODEM FOR USE WITH ANY OF THE PHONE-LINE COMPUTER SERVICE. SERVICES.

FEATURES:

- Uses a Z80A and 6845 CRT Controller for powerful video capabilities
- RS232 at 16 BAUD Rates from 75
- 24 x 80 standard format (60 Hz). Optional formats from 24 x 80 (50 Hz) to 64 lines x 96 characters
- (60 Hz) to 64 lines x 96 characters (60 Hz). Higher density formats require up to 3 additional 2K x 8 6116 RAMS. Uses N.S. INS 8250 BAUD Rate Gen. and USART combo IC. 3 Terminal Emulation Modes which
- are Dip Switch selectable. These include the LSI-ADM3A, the Heath H-19, and the Beehive.
 Composite or Split Video.
 Any polarity of video or sync.
 Inverse Video Capability.
 Small Size: 6.5 x 9 inches.

- Upper & lower case with descenders.
 7 x 9 Character Matrix.
- Requires Par. ASCII keyboard. FOR 8 IN. SOURCE DISK (CP/M COMPATIBLE)

ADD \$10

#ZRT-80

A&T ADD \$50

(COMPLETE KIT, 2K VIDEO RAM)

BLANK PCB WITH 2716 CHAR. ROM. 2732 MON. ROM

\$4995

SOURCE DISKETTE - ADD \$10 SET OF 2 CRYSTALS - ADD \$7.50

Digital Research Computers

P.O. BOX 381450 • DUNCANVILLE, TX 75138 • (214) 225-2309

64K S100 STATIC RAM \$9900

LOW POWER!

150 NS ADD \$10

BLANK PC BOARD WITH DOCUMENTATION \$49.95

SUPPORT ICs + CAPS \$17.50

FULL SOCKET SET \$14.50

FULLY SUPPORTS THE NEW IEEE 696 S100 STANDARD (AS PROPOSED)

ASSEMBLED AND TESTED ADD \$50

PRICE CUT! **FEATURES:**

- Uses new 2K x 8 (TMM 2016 or HM 6116) RAMs. Fully supports IEEE 696 24 BIT Extended Addressing.

- Addressing. 64K draws only approximately 500 MA. 200 NS RAMs are standard. (TOSHIBA makes TMM 2016s as fast as 100 NS. FOR YOUR HIGH SPEED APPLICATIONS.) SUPPORTS PHANTOM (BOTH LOWER 32K AND ENTIRE BOARD). 2716 EPROMS may be installed in any of top 48K. Any of the top 8K (E000 H AND ABOVE) may be disabled to provide windows to eliminate any possible conflicts with your system monitor, disk controller, etc. Perfect for small systems since BOTH RAM and EPROM may co-exist on the same board.
- EPROM may co-exist on the same board.

 * BOARD may be partially populated as 56K.

PANASONIC

Green Screen - Video Monitors 25 MHZ. TYPICAL BANDWIDTH!!!

Brand New In The Box! 9-Inch Screen #K-904B1 (Chassis #Y08A) Open Frame Style

GROUP SPECIAL:

900 WITH DATA & SCHEMATIC

(USA SHIPPING: \$3. PER UNIT. CANADA: \$7. PER UNIT)

COMPUTER MANUFACTURER'S EXCESS. STILL IN ORIGINAL PANASONIC BOXES. THE CRT TUBE ALONE WOULD COST MORE THAN OUR PRICE FOR THE COMPLETE UNIT. FOR SPLIT VIDEO (TTL INPUTS) OPERATION, NOT COMPOSITE VIDEO. OPERATES FROM 12VDC AT 1 AMP. VERTICAL INPUT IS 49 TO 61 HZ. HORIZONTAL INPUT: 15,750 HZ \pm 500 HZ. RESOLUTION IS 800 LINES AT CENTER 650 LINES AT CORNERS.

THE NEW 65/9028 VT **ANSI VIDEO TERMINAL BOARD!** * FROM LINGER ENTERPRISES *

A second generation, low cost, high performance, mini sized, single board for making your own RS232 Video Terminal. Use as a computer console or with a MODEM for hook up to any of the telephone-line computer services.

- Uses the new SMC 9028 Video Controller Chip coupled with a 6502A CPU.
- RS-232 at 16 Baud Rates from 50 to 19,200
- to 19,200 On board printer port! 24 X 80 format (50/60 Hz). For 15,750 Hz (Horiz.) monitors. 3 Terminal Modes: H-19, ADM3A, and ANSI X 3.64-1979
- Wide and thin-line graphics.
 White characters on black back-
- Ground or reversed.
 Character Attributes: De-Inten,
 Inverse, Underline and Blank.
 Low Power: 5VDC @ .7A, ± 12VDC
- @ 20MA.
 Mini size: 6.5 X 5 inches.
 Composite or split video.
 5 X 8 Dot Matrix characters

- (U/L case) with descenders.
 Answer back capability.
 Battery backed up status memory.
 For ASCII parallel keyboard.

MICRO SIZE!



(Full Kit)

ADD \$40 FOR A&T

SOURCE DISKETTE: PC/XT FORMAT 51/4 IN. \$15

OPTIONAL EPROM FOR PC/XT STYLE SERIAL KEYBOARD: \$15

TERMS: Add \$3.00 postage. Orders under \$15 add 75¢ handling. No C.O.D. We accept Visa and MasterCharge. Tex. Res. add 5-1/8% Tax. Foreign orders (except Canada) add 20% P & H. Orders over \$50 add 85¢ for insurance

HOW WOULD IT FEEL TO HAVE THE POWER OF TWO VAX 11/780s ON YOUR DESK?

With the Consulair™ Professional Development Workstation, Now You Can!

he programmers' dream system takes an ordinary Macintosh™ and adds the Levco Prodigy 4, a 32 bit 68020 with a 68881 floating point coprocessor accelerated to 16 MHz, 4 megabytes of high speed memory, and SCSI interface. You get MacUser Magazine's Best Development Language of the Year, Consulair Mac C/ Mac C Toolkit with Direct Access™ compiler support for the 68020 and 68881. Together, the system runs almost 1/2 million Whetstones per second and the Sieve benchmark in 0.68 seconds. As a special introductory offer you can upgrade your own Macintosh or Mac Plus for \$6495, including the complete software and hardware development system. An internal SCSI 20 Mbyte hard disk is available for an additional \$995.

If you want to move in smaller steps, we have a complete range of development systems to suit your needs. Leap into your future today with the Consulair Professional Development Workstation.

Call our Order and Information Hotline Today at **415-851-3272**.

Consulair

140 Campo Drive

Portola Valley, CA 94025


Circle no. 94 on reader service card.

C CHEST

Listing TWO (Listing continued, text begins on page 14.)

```
9 #define BSIZE
10 #define CTL_Z
11 #define SMODE
                    (10 * 1024)
                                                                    /* Buffer size
                   /* EOF marker
                                                             read & write modes */
12 #define DMODE
17 char
           *name;
18 (
           20
21
           static char buf[128], *p;
23
24
           strncpy ( buf, name, 128-5 );
           if ( p = strrchr (buf, '.')
26
                    strcpy( p+1, "bak" );
                    strcat ( buf, ".bak" );
29
           return buf;
31
32 )
34 /*-
35
36 usage()
37 (
            fprintf(stderr, "Usage: fix file [file...]\n\n");
fprintf(stderr, "Removes trailing ^2's from files.\n");
40
41 }
43 /*
 45 main (argc, argv)
46 char **argv;
            static char
static char
                             buf[BSIZE];
*srcname;
 49
             char
                              *p;
                                             /* # bytes got from read
             register int
                             src, dest;
 52
            register int
 53
54
55
                                                 /* Fix ^C Interrupt handling */
/* Remake argv from CMDLINE */
            reargy ( &argc, &argv );
             if( argc < 2 || argv[1][0] == '-')
 58
                     usage();
 59
60
             for ( ++argv, --argc; --argc >= 0; ++argv )
 61
                     62
 64
65
66
                     printf("Fixing %-20s (creating %s)\n", *argv, srcname );
 67
68
69
                     if( (src = open(srcname, SMODE)) == -1 )
 70
71
72
                              perror ( srcname );
                              continue;
                     if( (dest = open( *argv, DMODE, S_IWRITE | S_IREAD)) == -1 )
 73
74
75
76
77
78
                              perror ( *argv );
                              continue;
                     while ( got = read(src, buf, BSIZE) )
                               if ( got == -1 )
  81
82
                                       perror ( srcname );
  83
                                       break:
  86
                               for ( p = buf; --got >= 0 && *p != CTL_Z ; p++ )
  89
                               got = p - buf; /* got = distance to ^Z */
  90
  92
                               if ( write (dest, buf, got) != got )
  93
94
95
96
97
98
99
                               if( *p == CTL_Z )
                                       break;
 100
 101
                      close( src );
close( dest );
  103
 104
              exit(0);
```

End Listings



QNX: With any other OS, your personal computer is asleep at the switch.

If real-time performance is the key to the next generation of small systems, task-switching is the key to real-time performance.

QNX task-switching has been measured using standard Intel benchmarks. Here are the results:

os	Computer	Processor	Switches/ Sec	
QNX TM	IBM AT	8Mhz 80286	2800	
QNX TM	IBM PC	5Mhz 8088	787	
XENIX TM	Intel-286	5Mhz 80286	203	
UNIX TM	CODATA	8Mhz 68000	187	
XENIX TM	ALTOS	5Mhz 8086	96	
UNIX TM	FORTUNE	6Mhz 68000	95	

The margin by which QNX outperforms UNIX-based systems is not accidental. QNX architecture is unique among multi-tasking small computer operating systems because it is modular, not monolithic. On the PC, this distinction is decisive: UNIX system overhead and processing demands sap any computer smaller than an AT.

Because QNX was developed specifically for smaller computers, not "kluged" from an OS written for larger computers, its structural advantages are apparent. QNX was the first multi-tasking, multi-user OS for the IBM PC (1982), the first again for the AT (1984) and the first networking OS for the PC and the AT (1984). For the forseeable future,

QNX will remain the only real-time multi-user, multi-tasking OS for the PC, the AT and compatibles.

As a networking OS, only QNX provides integrated performance at the fundamental level of intertask communications. The tasks need not be on the same machine: the messaging is network-wide.

A task responsible for handling an A/D converter on one machine can provide data and accept requests from tasks on any other machine. For this reason only QNX can

implement true distributed processing, distributed file systems and distributed devices, with no need for a central file server.

Since QNX is modular, programmers can easily adapt and enhance the OS itself by adding their own system task. PC-DOS 2.1 or 3.1 [™] can run as one of QNX's many tasks.

With over 20,000 QNX systems installed worldwide, QNX is the undisputed standard for real-time microprocessor applications.

Multi-User	10 serial terminals per PC, AT.	C Compiler	Standard Kernighan and Ritchie.
Multi-Tasking	40 (64) tasks per PC (AT).	Flexibility	Single PC, networked PC's,
Networking	2.5 Megabit token ring. 255 PC's and/or AT's per network. 10,000 tasks per network. thousands of users per network.		Single PC with terminals, Networked PC's with terminals. No central servers. Full sharing of disks, devices and CPU's.
RealTime	2800 task switches/sec (AT).	PC-DOS	PC-DOS runs as a QNX task.
Message Passing	Fast intertask communication between tasks on any machine.	Cost	From US \$450. Runtime pricing available.

For further information or a free demonstration diskette, please telephone (613) 726-1893.

The only multi-user, multi-tasking networking operating system for the IBM PC, AT and compatibles. By Quantum.

XENIX is a registered trademark of the Microsoft Corporation. Unix is a registered trademark of AT&T Bell Labs. IBM PC, AT, XT and PC DOS are trademarks of IBM Corp.

Quantum Software Systems Ltd., Moodie Drive High Tech Park, 215 Stafford Road, Unit 104, Ottawa, Ontario, Canada K2H 9C1

CUBIC SPLINES

Listing One (Text begins on page 24.)

```
/* SPLINE.C - Interpolate Smooth Curve
 * Version 2.00
                             December 25th, 1985
  Modifications:
     V1 00 (85/11/01)
                        - beta test release
     V2.00 (85/12/25)
                         - general revision
                          Ian Ashdown
 * Copyright 1985:
                          byHeart Software
                          620 Ballantree Road
                          West Vancouver, B.C.
                          Canada V7S 1W3
  This program may be copied for personal, non-commercial use only, provided that the above copyright notice is included in
   all copies of the source code. Copying for any other use
   without previously obtaining the written permission of the
   author is prohibited.
   Synopsis:
                SPLINE [option] ...
   Description: SPLINE takes pairs of numbers from the standard
                  input as abscissae and ordinates of a function.
                  (A minimum of four pairs is required.) It
                 produces a similar set, which is approximately equally spaced and includes the input set, on the
                  standard output. The cubic spline output (R.W.
                  Hamming, "Numerical Methods for Scientists and
                  Engineers", 2nd ed. 349ff) has two continuous
                  derivatives and sufficiently many points to look
                  smooth when plotted.
                  The following options are recognized, each as a
                  separate argument:
                  -a Supply abscissae automatically (they are
                      missing from the input); spacing is given by
                      the next argument or is assumed to be 1 if
                      next argument is not a number.
                  -k The constant "k" is used in the boundary
                      value computation
                           y'' = ky'', y'' = ky''
                       is set by the next argument. By default,
                       k = 0. A value of k = 0.5 often results in a
                       smoother curve at the endpoints than the
                       default value. Negative values for k are not
                       allowed. Cannot be used with -p option.
                  -n Next argument (which must be an integer)
                       specifies the number of intervals that are to
                       occur between the lower and upper "x" limits.
                       If -n option is not given, default spacing is
                       100 intervals.
                  -p Make output periodic, i.e. match derivatives
                       at ends. First and last input values must
                       agree. Cannot be used with -k option.
                   -x Next 1 (or 2) arguments are lower (and upper)
                       "x" limits. Normally these limits are calculated from the data. Automatic abscissae
                       start at lower limit (default 0). If either
                       argument is outside of the range of
                       abscissae, it is ignored.
     Diagnostics: When data is not strictly monotone in "x", SPLINE
                   reproduces the input without interpolating extra
                   points.
                   A limit of 1000 input points is silently
     Bugs:
                   enforced.
                   The -n option has not been implemented in
```

accordance with the "UNIX Programmer's Manual" specification. This was done to avoid ambiguities


argument.

when the -n option follows the -x option with one

At certain negative values for the -k option (for example, k equals -4.0), the curve becomes discontinuous. The -k option value has thus been

```
arbitrarily constrained to be greater than or
                 equal to zero.
                 The above description is a reworded and expanded
  Credits:
                 version of that appearing in the "UNIX Programmer's
                 Manual", copyright 1979, 1983 Bell Laboratories.
/*** Definitions ***/
#define FALSE
#define TRUE
#define MAX SIZE 1000 /* Input point array limit */
                      0 /* Error codes */
#define ILL ARG
#define ILL CMB
#define ILL KVL
#define ILL NVL
#define ILL OPT
#define ILL XVL
#define INS INP
#define MIS KVL
#define MIS NVL
#define MIS_XVL
#define MIS YVL
                     10
#define NMT ORD
#define SQUARE(a) a*a
#define CUBE(a) a*a*a
/*** Typedefs ***/
typedef int BOOL:
                          /* Boolean flag */
/*** Include Files ***/
#include <stdio.h>
#include <ctype.h>
#include <math.h>
/*** Main Body of Program ***/
int main (argc, argv)
int argc;
 char **argv;
  int n = 0.
       1.
       n \text{ val} = 0,
       atoi();
   float x[MAX_SIZE],
        y[MAX_SIZE];
   double a val = 1.0,
        k \, val = 0.0,
          x1_{val} = 0.0,

x2_{val} = 0.0,
          x intvl.
          ix,
          iy,
          d2y[MAX SIZE],
          h,
          atof().
          fabs ()
          spl int();
   char buffer[257],
         *temp,
         *gets();
   BOOL aflag = FALSE,
kflag = FALSE,
                          /* Command-line option flags */
        pflag = FALSE,
         x1flag = FALSE,
         x2flag = FALSE,
   is_float();
void spl coeff(),
         pspl coeff().
   /* Parse the command line for user-selected options */
   while (--argc)
      temp = *++argv;
if(*temp != '-')
                           /* Check for legal option flag */
       error (ILL_OPT, *argv);
        switch (toupper (*++temp))
                                              (continued on page 81)
```



Inside:

Dr. Dobb's Bound Volumes
Dr. Dobb's Listings on Disk
Dr. Dobb's Z80 Toolbook
A Complete C Toolbox
A NEW Version of the
Unix-like Shell &
Utility Package
for MS-DOS

The Toolbook of FORTH

This comprehensive collection of useful Forth programs and tutorials contains exanded and revised versions of DDJ's best Forth articles, along with new Forth material. In addition to the practical code and tutorials, you'll glean important insights about the potential of this increasingly popular language from the many in-depth discussion of advanced Forth topics.

You'll find sections on:

Forth—the Language, including "The Forth Philosophy," "Teaching Forth as a First Language" and "Forth-83 and Vocabularies"

Mathematics in FORTH including "Series Expansion in Forth," "FORTH Floating-Point Package," "Signed Integer Division"

Modifications/
Extensions, including "A
Proposal for Strings in
Forth," "NonDeterministic Control
Words," "Some Forth
Coding Standards,"
"Towards a More
Writable Forth Syntax"

Implementing FORTH, including "Forth and the Motorola 68000," "A 68000 Forth Assembler," "A Forth Assembler for the 6502," "Z8000 Forth"

Forth Programs, including "GO in Forth," "Elements of a Forth Data-Base Design," "The Forth Sort," "SEND & RECV," "Interface for a Mouse," "Relocating Loader in Forth," "Forth Decompiler," "Screen-Oriented Editor Revisited," "Evolution of a Video Editor," "H-19 Screen Editor" and "The Conference Tree"

You'll also find Appendices that will help you convert fig-Forth to Forth-83, and tell you how to stay up-to-date on the latest developments and refinements of this popular language.

The screens in this book are also available on disk as Ascii files. Receive *Dr. Dobb's Toolbook of Forth*, along with the software on disk, together for only \$39.95.

Dr. Dobb's Toolbook of Forth
Item #030 \$22.95
Toolbook with Disk
Item #031 \$39.95
Please specify MS/PC
DOS, Apple II,
Macintosh, or CP/M. For
CP/M disks, specify
Osborne or 8" SS/SD.

To Order:

To order any of Dr. Dobb's products, return the order form at the end of this catalog, or

CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions,



Programs by the Pound

Dr. Dobb's **Bound Volumes**

Announcing: Dr. Dobb's Bound Volume 9

Over 1000 pages of listings and text. The entire 1984 editorial contents of Dr. Dobb's Journal of Software Tools.

Bound Volume 9: 1984 Item #020B

Shaping things to come. In 1984 new Editor-in-chief Mike Swaine brought his interests in advanced technology to Dr. Dobb's Journal. We presented the concepts behind Prolog and published an expert system for weather prediction. We learned Modula-2, and taught Forth to talk to a 68000, to MS DOS, and to the people of China. We examined a new language implementa-

tion called Turbo Pascal and extended implementations of C with a preprocessor, a library, Tony Skjellum's tricks, and Allen Holub's Grep. We published two powerful encryption systems, telefloating-point benchmark results, and an issue devoted to the internals of Unix. And Ray Duncan, Bob Blum, and Dave Cortesi were on hand with their fascinating columns.

communications protocols,

Bound Volume 1: 1976

Item #013

The working notes of a technological revolution. Programmers from Defense laboratory systems analysts to kitchen-table entrepreneurs worked for the intrinsic rewards to put development software on the brand-new invention, the microcomputer. Before there was an Apple, Dr. Dobb's Journal of Tiny Basic Calisthenics and Orthodontia (subtitle: Running Light without Overbyte) was founded to put a programming language on the machine, and became both chronicler and instrument of the revolution. In this first-year volume: Tiny Basic, the first word on CP/M, notes on building an IMSAI, floating-point and timer routines.

Bound Volume 2: 1977

Item #014

Running light without overbyte. By year two, Dr. Dobb's formula was concocted: tough questions and serious technical issues handled with enthusiasm, and wit, scant reverence for the accepted answers. Source code. Tools for programmers. Respect for tight programming. Dr. Dobb's Journal readers shared insights on warping the Intel 8080 into a computer CPU, and Dr. Dobb's published a complete operating system for the chip. A motley crop of computers and software products were popping up, and Dr. Dobb's investigated: the Heath H-8, the KIM-1, the Alpha Micro, MITS Basic, Poly Basic,

and Lawrence Livermore Labs Basic. Dr. Dobb's introduced Pilot for microcomputers and published tips on doing string handling, high-speed I/O, and turtle graphics in limited memory.

Bound Volume 3: 1978 Item #015

The roots of the Silicon Valley growth. In 1978 Steve Wozniak and other programmers were publishing in Dr. Dobb's Journal code that would help them grow multi-million-dollar computer companies. The proposed S-100 bus standard was hashed out in Dr. Dobb's pages. Dr. Dobb's contributors began to speak more in terms of technique than of specific implementations as the industry began to diversify. Languages covered in depth included SAM76, Pilot, Pascal, and Lisp.

To Order:


To order any of Dr. Dobb's products, return the order form at the end of this catalog, or

CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions,







Bound Volume 4: 1979 Item #016

In the midst of the Gold Rush. Three years before IBM would release its PC, a thriving, rough-andtumble personal computer industry existed. Fortunes had been made and lost, the effective power of the machine multiplied a hundredfold. By 1979 some stability had even emerged; one could speak of the processors that had proven longevity as micro-computer CPUs; the 8080, the **Z**80, the 6800, and the 6502. Dr. Dobb's Journal focused on the best ways to use these processors, with algorithms, tips, and code for 8- to 16-bit conversion, pseudo-random number generation, micro-tomainframe connections, telecommunications, and networking. And lots of useful code.

Bound Volume 5: 1980 Item #017

The preeminence of CP/M and the rise of C. More than any other magazine, Dr. Dobb's Journal was

responsible for the spread of CP/M and C on microcomputers. Both of those movements began in 1980. Dr. Dobb's all-CP/M issue, including Gary Kildall's history of CP/M, sold out within weeks of publication. This was the vear of Ron Cain's original Small C complier, of a CP/M-oriented Cinterpreter, CP/M-to-UCSD Pascal file conversion techniques, ans a greater concern in Dr. Dobb's with software portability.

Bound Volume 6: 1981 Item #018

The first of Forth. 1981 saw Dr. Dobb's first all-Forth issue (now sold out), along with an emphasis on CP/M, C, telecommunications, and new languages, David Cortesi began "Dr. Dobb's Clinic," one of the magazine's most popular features. Highlights included information on PCNET, the Conference Tree, the Electronic Phone Book, Tiny Basic for the 6809, writing your own compiler, and a systems programming language.

Dr. Dobb's Bound Volumes

Bound Volume 7: 1982

Item #019

Legitimacy. By 1982 IBM had become a player in the personal computer game and was changing the rules. New microprocessors arrived, the first designed speicifcally to serve as personal computer CPUs. In Dr. Dobb's Journal Dave Cortesi published the first serious comparison of MS DOS and CP/M-86. Dr. Dobb's started two new columns: the CP/M Exchange, as a rearguard maneuver to ensure that good tools for CP/M programmers would continue to be developed and circulated, and the 16-Bit Software Toolbox to investigate the 8088/86 and other new microprocessors. We published code for the 68000 and Z8000 processors, and looked ahead. in a provocative essay, to fifth-generation computers.

Bound Volume 8: 1983 Item #020

Power Tools. Personal computers were proving themselves to be true professional software development tools by 1983, the year in which Jim Hendrix completed his "canonical" version of Small C in *Dr. Dobb's* Journal. Dr. Dobb's published more 68000 and 8088 code, and as the memory limitations relaxed, the magazine's commitment to tight code let it shoehorn impossibly large systems into memory. Small C was just one of the major software products published in their entirety in Dr. Dobb's pages that year; there were Ed Ream's RED screen editor and a version of the Ada language called Augusta.

Buy the complete set and save 15%

If you buy all nine volumes, covering the entire editorial content of *Dr. Dobb's Journal of Software Tools* from the first issue in 1976 through 1984, you pay just \$225. That's a 15% discount and over \$40 off the combined individual prices. To order the complete set of Bound Volumes 1 through 9, ask for item #020C.

Vol. 1	Item #013	\$27.75
Vol. 2	Item #014	\$27.75
Vol. 3	Item #015	\$27.75
Vol. 4	Item #016	\$27.75
Vol. 5	Item #017	\$27.75
Vol. 6	Item #018	\$27.75
Vol. 7	Item #019	\$30.75
Vol. 8	Item #020	\$31.75
Vol. 9	Item #020B	\$35.75

All 9 volumes Item #020C \$225.00


To Order:


To order any of Dr. Dobb's products, return the order form at the end of this catalog, or CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions, CALL M&T PUBLISHING, INC. 415-366-3600 EXT. 216



A collection of powerful tools for C software developers, including books, software on disk, and reference materials from the publisher of Dr. Dobb's Journal Of Software Tools





From M&T Publishing and Brady Communications...

Dr. Dobb's Toolbook of C Item #005

The **Toolbook** contains over 700 pages of C material, including articles by such C experts as Kernighan and Ritchie, Cain and Hendrix, Skjellum and Holub. The level is sophisticated and pragmatic, appropriate for professional C programmers.

The most valuable part of the **Toolbook** to many will be the hundreds of pages of useful C source code, including a complete compiler, an assembler, and text-processing utilities. The accompanying text explains, in the programmers' own words, why they did what they did

Dr. Dobb's Journal of Software Tools introduced a generation of personal computer programmers to the C programming language, and all the best C articles and code published in Dr. Dobb's over the years is included and updated in the Toolbook, in

cluding Ron Cain's original Small C article and articles from sold-out issues. But the **Toolbook** also includes material never before published, including Jim Hendrix's complete macro assembler in C.

Dr Dobb's offers the Toolbook in a special hardbound edition for just \$29.95. You'll find: Jim Hendrix's famous Small C Compiler and New Library for Small C (both also available on disk). NEW: Hendrix's Small Mac: An Assembler for Small Cand Small Tools: Programs for Text Processing (both also available on disk), All of Tony Skjellum's C Programmer's Notebook columns distilled by Tony into one thoughtprovoking chapter.

Dr. Dobb's C Software Tools on Disk

To complement the Toolbook, Dr. Dobb's also offers the following programs on disk. Full C source code and documentation is included. Except where indicated, both CP/M and MS/PC DOS versions are available.

Also from M&T Publishing and Brady Communications...

The Small C Handbook

Item #006 or #006A
Jim Hendrix's Small-C
Handbook is the reference
book on his Small-C compiler. In addition to describing the operation of
the compiler, the book
contains complete source
listings to the compiler and
its library of arithmetic
and logical routines.

Hendrix has ported the compiler to the MS/PC DOS environment since the Handbook was printed, and the Handbook plus his MS/PC DOS Handbook Addendum, Item #006A, is \$22.95.

A perfect companion to the Hendrix Small-C compiler offered by Dr. Dobb's on disk, the Handbook even tells how to use the compiler to generate a new version of itself.

While both the Handbook and the Toolbook provide documentation for the Small-C compiler, the Handbook contains a more detailed discussion and is available with an addendum for the MS/PC DOS version.

The **Handbook**, Item #006, is just \$17.95. Jim

Small-C Compiler Item #007

Jim Hendrix's Small-C Compiler is the most popular piece of software ever published in *Dr. dobb's* 10year history. Like a homestudy course in compiler design, the **Small-C Compiler** and **Small-C Handbook** provide everything you need but the computer for learning how compilers are constructed, and for learning C at its most fundamental level.

While both the Handbook and the Toolbook provide documentation for the Small-C compiler, the Handbook contains a more detailed discussion and is available with an addendum for the MS/PC DOS version. The MC/PC DOS Small-C Handbook Addendum is recommened in addition to the Handbook for MS DOS or PC DOS users.

The Small-C compiler is available for \$19.95 in either the CP/M or the MS/PC DOS version



To Order:

To order any of Dr. Dobb's products, return the order form at the end of this catalog, or

CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions,



Dr. Dobb's Complete C Toolbox

Small-Mac: An Assembler for Small-C Item #012A

Small-Mac is an assembler designed to stress simplicity, portability, adaptability, and educational value. The package features a simplified macro facility, Clanguage expression operators, object file visibility, descriptive error messages, and an externallydefined machine instruction table. You get the macro assembler, linkage editor, load-and-go loader, library manager, CPU configuration utility, and a utility to dump relocatable

Small-Mac is available with documentation for \$29.95. For CP/M systems only.

Small-Tools: Programs for Text Processing Item #010A

A package of programs performing specific, modular operations on text files, including: editing; formatting; sorting; merging; listing; printing; searching; changing; transliterating; copying; concatenating; encrypting and decrypting; replacing spaces with tabs and tabs with spaces; counting characters, words, or lines; and selecting printer fonts. Supplied in source code form so you can select and adapt these tools to your own purposes.

Small-Tools is available with documentation for \$29.95. For CP/M or MS/PC DOS systems.

Special Packages— 20% Off

Now for almost 20% off the combined individual

product prices, you can order a complete set of *Dr. Dobb's* C programming tools for your CP/M or MS/PC DOS system.

C Package for CP/M

Item #005A Ordered individually, these items would cost about \$120. If you order the CP/MC package, you'll get Dr. Dobb's Toolbook, the Small-C Hand-book, the Small-C Compiler on disk, the Small-Mac assembler on disk with documentation in the Small-Mac Manual, the Small-Tools text-processing programs on disk with documentation in the Small-Tools Manual, all for just \$99.95.

C Package for MS/PC DOS

Item #005B

These items would cost over \$100 if purchased individually. If you order the MS/PC DOS C package, you'll get *Dr. Dobb's Toolbook*, the Small-C Handbook with the MS/PC DOS Addendum, the Small-C Compiler on disk, the Small-Tools text-processing programs on disk with documentation in the Small-Tools Manual, all for just \$82.95.

Dr. Dobb's Sourcebook: A Reference Guide to the C Programming Language Item #004

Products and services for C programmers are appearing at so rapid a rate that it's all but impossible to keep up with them. Dr. Dobb's presents this handy

guide to the who, what, when, where, and why of C. A comprehensive reference manual to new information, products, and services, the **Sourcebook** contains:

- A bibliography of over 300 articles and books on the C language;
- A descriptive list of products for C programmers: compilers, editors, interpreters, and utilities;
- A list of C-related services: classes, seminars, and on-line services.


The Sourcebook is just \$7.95. Dr. Dobb's Sourcebook: A Reference Guide to the C Programming Language
Item #004 \$ 7.95

Dr. Dobb's Toolbook for C Item #005 \$29.95

The Small-C Handbook Item #006 \$17.95

The Small-C Handbook and MS/PC-DOS Addendum Item #006A \$22.95

Small-C Compiler disk Item #007 \$19.95



Small Tools: Programs for Text Processing disk & manual Item #010A \$29.95

Small Mac: An Assembler for Small-C disk (For CP/M only) & manual. Item #012A \$29.95

CP/M C Package Item #005A \$99.95

MS/PC DOS C Package Item #005B \$82.95

For CP/M disks, please specify one of the following formats: Apple, Osborne, Kaypro, Zenith Z-100 DS/DD, 8" SS/SD.

To Order:

To order any of Dr. Dobb's products, return the order form at the end of this catalog, or

CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions,

CALL M&T PUBLISHING, INC. 415-366-3600 EXT. 216



Dr. Dobb's Journal, September 1986

Dr. Dobb's Z80 Toolbook



David E. Cortesi longtime Dr. Dobb's columnist and author of Inside CP/M brings you —

Dr. Dobb's Z80 Toolbook

Here's all you need to write your own Z80 assembly language programs for only \$25!

Do you use CP/M? Do you feel as if the only part of the computer industry that has not abandoned you is your own Z80 computer? It keeps on working, but when you need programs for it, you have to write them yourself. When you do, you quickly find that while Pascal or BASIC is okay for some things, there is often no substitute for the speed, small size, and flexibility of an assembly language program.

Dr. Dobb's Z80 Toolbook puts the power of assembly language in the hands of anyone who's done a little programming. You'll find:

**A method of designing programs and coding them in assembly language. Cortesi will take you on a walk through the initial specifications, designing an algorithm and writing the code. He demonstrates this method in the construction of several complete, useful programs.

ng lem in rtesi cifica-orithm

kit of subroutines for arithmetic, for string-handling, an for total control of the CP/M file system. They bring the ease and power of a compiler's runtime library to your assembly language work, without a compiler's size and sluggish code. Best of all, every line of the toolkit's source code is there for you to read, and every module's operation is explained with the clarity and good humor for which Dave Cortesi's writing is known.

**A complete, integrated tool-

Order the Z80 Software on Disk! Save Yourself the Frustration of File Entry

All the software in **Dr. Dobb's Z80 Toolbook**—the programs

plus the entire toolkit, both as source code and as object modules for both CP/M 2.2 and CP/M Plus—is yours on disk. (A Z80 microprocessor and a Digital Research International RMAC assembler or equivalent are required.)

Receive *Dr. Dobb's Toolbook* for Z80, along with the software on disk, together for only \$40!

Dr. Dobb's Toolbook for Z80 Item #022 \$25

Dr. Dobb's Toolbook for Z80. together with software on disk. Please specify one of the following formats: 8" SS/SD; Apple; Osborne: Kaypro.

Item #022A

\$40

Most of the programs are included in the book; however, the disk is necessary for complete listings


To Order:

To order any of Dr. Dobb's products, return the order form at the end of this catalog, or

CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions,





Dr. Dobb's Catalog A UNIX-like Shell and Utility Package for MS-DOS

A UNIX-like Shell for MS-DOS, V.2 and A **UNIX-like Utility** Package for MS-DOS by Dr. Dobb's C-Chest Columnist, Allen Holub Only \$29.95 each! If you are a registered user or have already purchased version 1 of The Shell from DDJ. vou can receive the upgrade for only \$6!

THE SHELL Version 2.0

An MS-DOS implementation of the most often used parts of the UNIX C Shell. This package includes an executable version of the shell, along with the complete C source code and full documentation. Supported features are: **Editing** Command-line editing with the cursors is supported. The line is visible as you edit it. Aliases Can be used to change the names of commands or as very fast, memory-resident, batch files. Nested aliases are supported in version 2. History You can execute previous commands. The command can be edited before being executed. Version 2 supports embedded history requests (bar; !!>foo).

Redirection and Pipes

Pipe temporary files can be put on a RAM disk.

Unix-like Command Syntax: / can be used to separate directory names (\can now be used as well).

A 2048-byte command line is supported. Commandline wild card expansion. Multiple commands on a

DOS-compatible prompt support \$d \$t \$ - \$e \$h \$n \$q\$\$\$%

C-Shell Based Shell Scripts (batch files) Shell Variables are macros that can be used on the command line. Version 2 supports arithmetic manipulation of shell variables using the @ command. The following C operators are supported: () + -★/ % <= >= < > == ! && || =

A batch file can call another batch file like a subroutine. Control is passed to the second file and then back to the first when the second is finished. Batch files can return values to the calling file using the exit and \$status mechanisms.

A powerful, interpretive, programming language, based on the UNIX C Shell, is now supported. including:

if/then/else while foreach switch/case break continue All commands can be nested.

A UNIX-like Utility Package for MS-DOS This collection of utility programs for MS-DOS includes updates of the highly acclaimed Dr. Dobb's articles Grep: A UNIX-Like Generalized Regular Expression Processor Ls from Dr. Dobb's C Chest column,



and Getargs from DDJ's C Chest.

Source code is included and all programs (and most of the utility subroutines) are fully documented in a UNIXstyle manual. You'll find executable versions of: cat A file concatenation and viewing program cp A file copy utility date Prints the current time and date du Prints amount of space available and used on disk echo Echoes its arguments to standard output grep Searches for a pattern defined by a regular expression Ls Gets a sorted directory mkdir Creates a directory mv Renames a file or

directory. Moves files to another directory p Prints a file, one page at a

pause Prints a message and waits for a response printenv Prints all the environment variables rm Deletes one or more

rmdir Deletes one or more directories

sub Text substitution utility. Replaces all matches of a regular expression with another string.

chmod change all file attributes (write permission, hidden, system, archive bit).

ORDER THE SHELL AND /UTIL TOGETHER FOR ONLY \$50! SAVE OVER 15%

The Shell runs on IBM PC's and compatibles

The Shell Item #160 \$29.95 Shell Upgrade Disk for owner of the Shell v.1 Item #160A \$ 6.00 /util Item #161 \$29.95 Shell/util Package Item #162 \$50.00

To Order:

To order any of Dr. Dobb's products, return the order form at the end of this catalog, or

CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions,



Dr. Dobb's Listings On Disk and Back Issues



Dr. Dobb's Listings

You can save time entering Dr. Dobb's valuable code listings! Selected listings from this August 1986 issue, along with listings from all previous 1986 DDJ issues, are yours on disk! Now, as a useful adjunct to the magazine, DDJ offers the additional value and convenience of selected listings from each 1986 issue, on disk. The first two of three Dr. Dobb's 1986 Listings disks, featuring a collection of listings from the DDJ January 1986 issue through this August 1986 issue, are now available.

And, in case you missed a single valuable issue of Dr. Dobb's Journal of Software Tools, while the supply lasts you can also receive any available 1986 back issue for only \$2.50 each when you purchase a DDJ Listings disk. That's a savings of 50% off the regular back issues price!

Dr. Dobb's Listings Disk #1/86 January— April 1986 You'll find listings from the following articles, among others:

From issue #111 January 1986 ** A Simple OS for I

**A Simple OS for Realtime Applications; 68000 assembly language techniques for an operating system kernel by DDJ editor Nick Turner

**Exec calls and Fortran;
a technique allowing
execution of a user or
system task from a user
program from DDJ's 16Bit Software Toolbox, by
Robert Sypek

**32-bit Square Roots; An 8086 assemblylanguage routine for 32bit square roots by Michael Barr (Sorry, back issue #111 is sold out)

From Issue #112 February 1986

**Fast Integer Powers for Pascal; An implementation of the fastest-known algorithm for the computation of integer powers by Dennis E. Hamilton **Data Absrtaction with

Modula-2; Construction of a priority queue in Modula-2 by Bill Walker and Stephen Alexander **Learning Ada on a

**Learning Ada on a Micro; A draw poker program in Ada by Do-While Jones

**Fast IBM PC graphics routines from DDJ's 16-Bit Software Toolbox, by Dan Rollins (Sorry, back issue #112 is

sold out)

From Issue #113 March 1986

**Recursive Bose-Nelson Sort; An alternative to Joe Celko's September 1985 sort routine by R.J.

Wissbaum
**A Variable-Metric
Minimizer; A C program
for minimizing arbitrary
functions by Joe Marasco
**Concurrancy and
Turbo Pascal; An
approach to implementing

coroutine in Pascal by
Ernest Bergmann
**Speeding MS DOS
Disk Access; Programs to
test disk-access speed by
Greg Weissman
**Square Roots on the
NS32000; Comparable
square root routines in C
and assembly language
for National
Semiconductor's 32000
family by Richard
Campbell

From Issue #114 April 1986

**Boca Raton Inference Engine; Lisp, Prolog, and Expert-2 techniques and code by Robert Brown

Dr. Dobb's Listings Disk #2/86 May— August 1986 You'll find listings from the following articles, among others.

From Issue #115 May 1986

**Simple plots with the Enhanced Graphics Adapter by Nabajyoti Barkakati **The Cryptographer's Toolbox by Fred A. Scacchitti

From Issue #116 June 1986

**Structured
Programming:
Overloading Procedures,
Exporting Opaque Types,
Data Hiding by Namir

Shammas
**Compuserve B Protocol
by Steve Wilhite

From Issue #117 July 1986

**Structured
Programming: Tiny
Tools, Array-Defining
Words by Michael Ham

From Issue #118 August 1986

**Structured
Programming: Generic
Routines in Ada and
Modula-2, Extended for
Loop by Namir Shammas

Dr. Dobb's Listings Disk #1/86 Item #170 \$14.95 Dr. Dobb's Listings Disk #2/86

Item #171 \$14.95

Please specify MS/DOS, Macintosh, or CP/M. For CP/M disks, please specify one of the following formats: Apple, Osborne, Kaypro, Zenith Z-100 DS/DD, 8" SS/ SD.

To order any DDJ 1986 back issue at the discounted price of only \$2.50 each with your Dr. Dobb's Listings Disk, please specify the issue date and number on the order form. January Issue #111 and February Issue #112 are sold out.

To Order:

To order any of Dr. Dobb's products, return the order form at the end of this catalog, or

CALL TOLL FREE 1-800-528-6050 EXT. 4001

and refer to product item number, title, and disk format. For customer service questions,



Order Form

ORDER NOW

NAME (Please use street add	, DO D		-	on Credit Ca	
ADDRESS	ress, not P.O. Box)				OLL FREE
					528-6050
CITY		STATE	ZIP		
DAY PHONE				Ext. 400	7
DITT THOUGH				Please Refer : When Orderir	
For disk and an ar	1				
Special formats a	lease indicate format. vailable for additiona	Refer to ad for standard format availability for	each product.	Self-Mailing C	is Postage Paid,
MS/DOS	Macintosh	CP/M	Ochorna	And Return To	
	Apple II	Zenith Z-100 DS/DI	Osborne Kaypro	M&T PUBLISHIN	IG INC
		——— Apple	8" SS/SD	501 GALVESTO REDWOOD CIT	ON DRIVE
QUANTITY	ITEM #	DESCRIPTION		UNIT PRICE	TOTAL PRICE
					1
,					
	2				
			-		
ě.					
				SUB-TOTAL	
A residents must	add applicable sale ta	on merchandise total %		SALES TAX	
CA residents must	add sales tax EXCE	T Dr. Dobb's Sourcehook #004)			
nipping must be ir	ncluded with order. Se	rates below.		SHIPPING	
U.S. For Bound V	olumes, add \$2.25 per	book. Add \$8.75 for special C Packages. For ot	hon has been all the court of the court	TOTAL ORDER	
utside U.S. For Bo	ound Volumes, add \$5	25 per book surface mail. Add \$18 surface ma	il for Special C Packages. For		
ner books and disi	ks, add \$3.25 per item	surface mail. Foreign airmail rates available or	request.		
VISA		NAME ON CARD			
MASTERCAR	D.				
		ACCOUNT NO.			
AMERICAN F	EXPRESS	EXPIRATION DATE			
CHECK		SIGNATURE			2
ake checks payabl M&T Publishing					



Dr.Dobb's Catalog Order Please Rush!

Please fold along fold-line and staple or tape closed.



BUSINESS REPLY MAIL

First Class Permit No. 790 Redwood City, CA

Postage Will Be Paid By Addressee

Dr. Dobb's Catalog

501 Galveston Dr. Redwood City, CA 94063 No Postage Necessary If Mailed In The United States



Please fold along fold-line and staple or tape closed.

CUBIC SPLINES

Listing One (Listing continued, text begins on page 24.)

```
/* "-a" option */
          aflag = TRUE;
          if (argc > 1 && is_float (* (argv+1)))
          argc--:
          argv++;
          if((a_val = atof(*argv)) <= 0.00)
            error (ILL_ARG, *argv);
        break:
                       /* "-k" option */
      case 'K':
        if (pflag == TRUE)
           error (ILL CMB, NULL);
        kflag = TRUE;
        if(argc > 1 && is_float(*(argv+1)))
          argc--;
           k val = atof(*argv):
          if(k \ val < 0.00)
            error (ILL KVL, *argv):
        else
          error (MIS_KVL, NULL);
        ase 'N': /* "-n" option */
if (argc > 1)
      case 'N':
          argc--:
           argv++;
           if((n_val = atoi(*argv)) < 1)
            error (ILL_NVL, *argv);
           else
            break;
          error (MIS_NVL, NULL);
      case 'P': /*
if (kflag == TRUE)
                      /* "-p" option */
           error (ILL_CMB, NULL);
        pflag = TRUE;
        break:
                      /* "-x" option */
      case 'X':
        xlflag = TRUE;
        if (argc > 1 && is_float(*(argv+1)))
          argc--;
          argv++;
          x1 val = atof(*argv);
          error (MIS XVL, NULL);
        if (argc > 1 && is_float (*(argv+1)))
          x2flag = TRUE;
          argc--;
          argv++;
          x2_val = atof(*argv);
          if(x2_val <= x1_val)
            error(ILL_XVL,x2_val);
        break:
      default:
                      /* "-n" option */
        error (ILL OPT, *argv):
if (n val == 0)
                       /* Set "n_val" if not given */
  n val = 100;
/* Get the input data */
while (1)
                       /* ... while there is more input data */
  if(aflag == TRUE) /* Automatic abscissae were called for */
    if(n == 0)
      x[0] = x1_val;
      x[n] = x[n-1] + a_{val};
  else
                      /* Abscissae supplied with input data */
    if (gets (buffer))
     x[n] = atof(buffer);
   else
      break:
 if (gets (buffer))
                      /* Read in the corresponding ordinate */
   y[n] = atof(buffer):
```

```
if (aflag == TRUE)
        break;
         error (MIS_YVL, NULL);
    if(++n == MAX_SIZE) /* Maximum amount of input data? */
      break;
  if(n < 4)
                          /* Check for insufficient input data */
    error (INS INP, NULL);
  /* Check for non-monotonic abscissae. Output input data set
   * without interpolation if true.
  h = x[1] - x[0];
for(i = 1; i < n-1; i++)
    if(fabs(x[i+1] - x[i] - h) > 0.0)
      for (i = 0; i < n; i++)
        printf("%g\n%g\n",x[i],y[i]);
      exit():
  /* Calculate abscissa interval. Use "-x" option values if
   * they were given unless they fall outside the range of
   * given (or calculated) abscissae.
  if(xlflag == FALSE || xl_val < x[0])
  xl_val = x[0];</pre>
  if (x2flag == FALSE || x2_val > x[n-1])
x2_val = x[n-1];
  x_{intvl} = (x2 val - x1 val)/n val;
  /* Find the coefficients */
  if (pflag == FALSE)
    spl_coeff(y,d2y,h,n,k val);
    pspl_coeff(y,d2y,h,n);
  /* Interpolate and output results */
  ix = x1_val;
  for(j = 0; j <= n_val; j++)
    while (ix >= x[i] && i < n - 1)
      1++;
    iy = spl_int(ix,x,y,d2y,h,i);
   printf("%g\n%g\n",ix,iy);
    ix += x intvl;
/*** Functions ***/
typical form:
                       0 | | y1" | = m * | y2 - 2*y1 + y0 |
0 | | y2" | | y3 - 2*y2 + y1 |
0 | | y3" | | y4 - 2*y3 + y2 |
         1 4+k 1
                    0
               4
                    1
            0
                    4
                                              | y5 - 2*y4 + y3 |
          0
                0
                         4+k | | y4"
                  where k = k_val, m = 6.0/(h*h) and yn is the
                  second derivative of the interpolated function at the "nth" abscissa, y0" = k * y1" and
                  y5" = k * y4".
void spl_coeff(y,d2y,h,n,k_val)
float y[];
double d2y[],
       k val;
         a[MAX_SIZE-1];
 int i:
  /* Set up the (symmetric tridiagonal) matrix, where the only
                                         (continued on next page)
```

CUBIC SPLINES

Listing One (Listing continued, text begins on page 24.)

```
elements of interest are those on the diagonal. These are
    stored in array "a[]". Array "d2y[]" initially holds the constants vector, then is overlaid with the calculated
  * variables vector.
m = 6.0/(h*h):
for(i = 1; i < n-1; i++)
   d2y[i] = m * (y[i+1] - 2.0 * y[i] + y[i-1]);
a[1] = 4.0 + k_val;
 /* Reduce the matrix to upper triangular form */
 for (i = 2; i < n-2; i++)
   a[i] = 4.0 - 1.0/a[i-1];
   d2y[i] = d2y[i-1]/a[i-1];
 a[n-2] = 4.0 + k val - 1.0/a[n-3];
 d2y[n-2] = d2y[n-3]/a[n-3];
 d2y[n-2] /= a[n-2];
 /* Solve using back substitution */
 for (i = n-3; i > 0; i--)
    d2y[i] = (d2y[i] - d2y[i+1])/a[i];
 /* Solve for end conditions */
 d2y[n-1] = d2y[n-2] * k_val;
 d2y[0] = d2y[1] * k_val;
/* PSPL_COEFF() - Calculate periodic spline coefficients and
                      return in vector "d2y[]". Matrix to be solved
                      has the typical form:
          | 4 1 0 0 1 | | y1" | = m * | y2 - 2*y1 + y0
                                              | y3 - 2*y2 + y1
| y4 - 2*y3 + y2
| y5 - 2*y4 + y3
                        0 0 | | 1 1 12" |
          1 1 4
                    1
                    4 1 0 | | y3" |
1 4 1 | | y4" |
               0
          10
                                                   | y1 - y0 - y5 + y4 |
                    0
                       1
                            4 | | y5" |
               0
                      where m = 6.0/(h*h) and yn" is the second
                      derivative of the interpolated function at the "nth" abscissa and y0" = y5".
void pspl coeff (y, d2y, h, n)
float y[];
double d2y[],
        h:
int n:
   double c,
              fabs ():
   static double a[MAX_SIZE-1],
                   b[MAX_SIZE];
   int i;
   /* Check for matching end ordinates */
   if(fabs(y[n-1] - y[0]) > 0.0)
      error (NMT_ORD, NULL);
   /* Set up the matrix, where array "a[]" holds the diagonal
    * elements, "b[]" holds those elements of column "n-1", and
* "c" holds the current element of interest of row "n-1".
* Array "d2y[]" initially holds the constants vector, then is
     * overlaid with the calculated variables vector.
   m = 6.0/(h*h):
    \begin{array}{lll} m & = 0.57 & \text{(ii)}, \\ \text{for (i = 1; i < n-1; i++)} \\ & \text{d2y[i]} & = m * (y[i+1] - 2.0 * y[i] + y[i-1]); \\ \text{d2y[n-1]} & = m * (y[1] - y[0] - y[n-1] + y[n-2]); \\ \end{array} 
   a[1] = 4.0;

b[1] = 1.0;
   b[n-2] = 1.0;

b[n-1] = 4.0;
    /* Reduce the matrix to upper triangular form */
    for (i = 2; i < n-1; i++)
      m = 1/a[i-1]:
```

```
b[i] -= b[i-1] * m;
   d2y[i] -= d2y[i-1] * m;
b[n-1] -= c * m * b[i-1];
    d2y[n-1] -= c * m * d2y[i-1];
   c = -c * m;
 c += 1.0;
 b[n-1] -= c * b[n-2]/a[n-2];
 d2y[n-1] = c * d2y[n-2]/a[n-2];
  /* Solve using back substitution */
 d2y[0] = d2y[n-1] /= b[n-1];
 d2y[n-2] = (d2y[n-2] - b[n-2] * d2y[n-1])/a[n-2];
  for (i = n-3; i > 0; i--)
    d2y[i] = (d2y[i] - b[i] * d2y[n-1] - d2y[i+1])/a[i];
/* SPL INT - Interpolate points using spline function */
double spl_int(ix,x,y,d2y,h,i)
     y[];
double ix.
      d2y[],
       h;
int i;
  double iv.
         t1,
  t1 = (ix - x[i-1])/h;
  t2 = (x[i] - ix)/h;

iy = y[i-1] * t2 + y[i] * t1 - SQUARE(h) * (d2y[i-1] * (t2 - i)
      CUBE(t2)) + d2y[i] * (t1 - CUBE(t1)))/6.0;
  return iy;
/* IS_FLOAT() - Check that character string is in correct floating
                 point format. Return TRUE if correct, FALSE
                 otherwise. The algorithm used is a deterministic
                 finite state machine. Using the regular
                 expression terminology of Unix's "lex", the
                 character string must be of the form;
                          -?d*.?d*(e|E(\+|-)?d+)?
                 where d = 0|1|2|3|4|5|6|7|8|9
 BOOL is float (str)
 char *str:
                          /* Next FSM input character */
                          /* Current FSM state */
        state = 0;
    while(c = *str++)
      switch (state)
                           /* FSM State 0 */
        case 0:
          switch(c)
            case '-':
              state = 1;
              break;
            case '.':
             state = 3;
              break;
             default:
              if (isdigit (c))
                 state = 2;
               else
                return FALSE;
               break:
           break:
                           /* FSM State 1 */
        case 1:
           switch(c)
             case '.':
               state = 2;
               break;
             default:
               if (isdigit (c))
                 state = 2;
```

```
return FALSE;
                break:
       break:
     case 2:
                        /* FSM State 2 */
       switch(c)
            state = 4;
           break;
         case 'e':
         case 'E':
           state = 5;
           break;
         default:
           if (isdigit (c))
             state = 2:
             return FALSE:
           break:
     case 3:
                       /* FSM State 3 */
       if (isdigit (c))
         state = 4;
       else
         return FALSE;
       break;
     case 4:
                       /* FSM State 4 */
       switch(c)
         case 'e':
         case 'E':
           state = 5;
           break:
           default:
             if (isdigit (c))
               state = 4;
             else
              return FALSE;
             break:
        break:
       case 5:
                        /* FSM State 5 */
         switch(c)
          case '+':
          case '-':
            break;
          default:
            if (isdigit (c))
              state = 7;
             else
              return FALSE;
            break;
        break:
      case 6:
                         /* FSM State 6 */
        if (isdigit (c))
          state = 7;
        else
          return FALSE:
        break;
      case 7:
                         /* FSM State 7 */
        if (isdigit (c))
          state = 7;
        else
          return FALSE:
        break;
    }
  return TRUE:
/* ERROR() - Error reporting. Returns an exit status of 2 to the
            parent process.
void error (n, str)
char *str:
  fprintf(stderr,"\007\n*** ERROR - ");
    case ILL ARG:
      fprintf(stderr, "Argument must be greater than zero: %s",
         str);
     break;
    case ILL CMB:
      fprintf(stderr, "Cannot use -k option with -p option");
    case II.I. KVI.:
      fprintf(stderr, "Illegal value for -k option: %s", str);
```

```
fprintf(stderr, "Illegal value for -n option: %s", str);
      break;
    case ILL OPT:
      fprintf(stderr, "Illegal command line option: %s", str);
      break:
    case ILL XVL:
      fprintf(stderr, "Illegal value for -x option: %s", str);
      break:
    case INS INP:
      fprintf(stderr, "Insufficient input data");
      break:
    case MIS KVL:
      fprintf(stderr, "Missing value for -k option");
     break;
    case MIS NVL:
      fprintf(stderr, "Missing value for -n option");
      break;
      fprintf(stderr, "Missing value for -x option");
      break:
    case MIS YVI.
      fprintf(stderr, "Missing ordinate value");
    case NMT ORD:
      fprintf(stderr, "End ordinates do not match");
      break:
   default:
     break:
  fprintf(stderr, " ***\n\nUsage: spline [-aknpx]\n");
  exit (2);
/*** End of SPLINE.C ***/
```

End Listing

LEARN C ON TV

with the video training course A Programmer's Introduction to C by Ray Swartz

Topics Covered: Data Types • Operators • Expressions • Loops • Conditionals • Input and Output Character Handling • Interactive Control • Arrays • Pointers • Switch

Reviewers' Comments:

"The tapes cover the major features of C and are aimed at professionals with a background in another computer language. The key to the package is that Swartz knows his subject and how to teach it."

Dr. Lance Leventhal

"If you're looking for a way to learn C quickly and easily, this course is something you'll want to consider."

Doug Topham


Price: \$400 includes two video tapes (3½ hours) and 106 page manual.

ASK ABOUT OUR FREE 15 DAY REVIEW


TO ORDER CALL (408) 458-0500

Circle no. 202 on reader service card.

SOFTSTRIP® NOW OFFERS YOU SOMETHING IN NEVER BEFORE AVAILABLE...



CONVENTIONAL DATA HANDLING



THE SOFTSTRIP SYSTEM

A CHOICE.

Until now you were stuck with disks.

No more. Install our unique STRIPPER™ software on your personal computer today and discover the many benefits of the fastest, easiest, least expensive way to handle information.

STRIPPER lets you print – ON PAPER – your own machine readable Softstrip data strips using your dot matrix printer. The Softstrip System Reader reads that information into a computer rapidly. With STRIPPER and the reader, your PC and printer become part of the most versatile information handling system available.

With this system you can do anything you wish with any data you have in your PC - ON PAPER.

DATA ENTRY: Why use keystrokes when you can eliminate them with data strips? Whatever the document - invoices, packing slips, memos, letters, sales reports, the list is endless — simply print a data strip right on the same printed page. Now you have a document that is both human readable and machine readable. A typical document can be entered in only 15 seconds using data strips. And, it ends keystroke errors forever.

DATA DISTRIBUTION: Why copy disks? It's time consuming and expensive. Softstrip data strips will end all that. Simply photocopy as many data strips as you like and send them by mail. Data strips ignore folding, coffee stains, ink marks and, by the way.

magnetic fields. And if you're using telecommunications, you can stop making the phone company rich.

DATA STORAGE AND RETRIEVAL: Why have a file of disks and a file of paper? Eliminate one with Softstrip data strips. File the data strip with the document. Better still, print the strip right on the document. Then put it in a file or binder.


Retrieval is simple. To find existing data, pull the document and its related data strip from the file. They've been stored together. Then use the reader to enter the data. No more hassle trying to match documents with the right disk — if you can find it.

DATA TRANSFER: Why bother with cables, modems and phone lines to move files between computers? A Softstrip data strip generated by an IBM PC can be read into another PC, or compatible, an Apple or even a Macintosh. If you work at home on a Macintosh, make a data strip on your printer, take it into the office and read it into your IBM PC. Simple. And we've created the utilities to let you do that easily. (See Application Notes on opposite page.)

Fascinating, isn't it? Anything you can do with disks can be done with the Softstrip data strip system — faster, easier and at lower cost — ON PAPER.

All you need is STRIPPER software at \$19.95 and the Softstrip System Reader at \$199.95.

DATA HANDLING



SEPTEMBER CASE HISTORY



Nick Turner, editor of Dr. Dobbs Journal, has been making his own data strips to back up and store articles, listings and other important materials. Turner notes that the STRIPPER™ software "creates compact, machine readable archives that are immune to dust, dirt and magnetic fields". Strips that Turner prints on his printer are filed in a loose leaf binder, along with the appropriate article. This permits him to pull the strip from the binder and read it back into his computer quickly using the reader. The method saves

disk file space, since once an article has been printed, maintaining it on a disk for revision isn't required.

The STRIPPER system has solved another problem for the busy editor, intermachine file compatibility. Using the Softstrip® System, Turner can transfer files between his PC-clone and his Macintosh "with a minimum of fuss".

"It's about time we had a way to store files on paper in machine readable form," Turner comments. Mr. Turner's comments are his own and do not reflect the opinion of the publication.

APPLICATION NOTES |

On the other side of this ad we said you can move data between different programs - on paper.

Using Softstrip data strips you can!

For instance move data between AppleWorks and Excel and back. Or Lotus 1-2-3 to and from AppleWorks.

We've created a series of several dozen Application Notes on Softstrip data strips. These lead you through simple steps to make the file transfer as easy as possible. Here are just a few examples:

- AppleWriter to or from MacWrite.
- dBASE to or from Appleworks.
- WordStar to or from AppleWriter.
- WordStar to or from MacWrite.
- Framework to PageMaker.

And more are coming.

ACT NOW!! Don't delay. See your local SOFTSTRIP dealer or call us at 1-800-533-7323. In Connecticut: 203-573-0150.

Users' Groups: Call for special User Group deals.

Circle no. 226 on reader service card.

These strips contain "The IRA Calculator," a worksheet for calculating returns with either Lotus or Excel. To receive the complete Application Note, call 1-800-533-7323, or write to Cauzin.

CAUZIN

835 South Main Street Waterbury, CT 06706 (203) 573-0150

IBM is a registered trademark of International Business Machines Corporation.
Framework is a trademark and dBASE is a registered trademark of Ashton-Tate.
PageMaker is a registered trademark of Aldus Corporation.
Cauzin and Softstrip are registered trademarks and STRIPPER is a trademark of Cauzin Systems Inc.
WordStar is a registered trademark of MicroPro International Corporation.
Lotus and 1-2-3 are registered trademarks of Lotus Development Corporation.
MacWrite, AppleWriter and AppleWorks are trademarks and Apple is a registered trademark of Apple Computer.
Excel is a product of Microsoft Corporation.
Dr. Dobbs Journal of Software Tools is published by M&T Publishing, Inc. under license from People's Computer Company.

Computer Company.

Macintosh is a registered trademark of McIntosh Laboratories licensed to Apple Computer Inc.

Softstrip

SORTING ALGORITHM

Listing One (Text begins on page 32.)

```
/* Listing one */
/*Radix sort listing*/
/* These includes are necessary to get the proper declarations for some of
  the Macintosh routines */
#include event.h
#include quickdraw.h
         typedef struct (
         char sortdat[KEYSIZ];
         sortrec;
char *lmalloc():
main()
         sortrec *begin, *first, *start, *temp;
         int i, j, recno;
         long tick;
         unsigned char dat;
                                             /*Get maximum size application heap*/
         MaxApplZone();
         begin = (sortrec *) lmalloc(0x40000); /*Allocate 256K for sortrecs*/
        /*Check if allocation was successful and exit if not*/
        if (!begin) {
                  printf("\nNot enough memory in heap");
                   _exit();
}
                                              /*Point to first record*/
          first = begin;
          printf("How many recs to sort\n");
          scanf ("%d", &recno);
          for (i=0; i<recno; ++i) {
                           first->ptr = first+1;
                   for (j=0; j< KEYSIZ; ++j)
                                   /*Point to next sort key record*/
                   ++first;
                                              /*All records allocated and filled*/
                                              /*Terminate the linked list*/
          first->ptr = 0;
                                              /*Get the current time*/
          tick = TickCount();
          start = sort(KEYSIZ, begin); /*Sort the list*/
          printf("\nTickcount=%ld",TickCount()-tick); /*Print elapsed time*/
                  /*number of bytes in the sort key*/
 sortrec *sort (a, b)
                   /*Pointer to head of linked list to be sorted*/
 sortrec *b;
           /*First and last are pointers to follow two linked lists whose
            heads are start and start2. Temp follows the full-length
             original or partly sorted list*/
  sortrec *first, *last, *start, *temp, *start2;
           static char mask[8] = { 1,2,4,8,16,32,64,128};/*Individual bit masks*/
           register i, j;
                                               /*point to original unsorted list*/
           start = b;
           for (i = a-1; i >= 0; --i) { /*Loop for all bytes of the sort key*/
                    for (j = 0; j < 8; ++j) ( /*Loop for all bits of each byte*/
                             first = last = start2 = 0; /*Set up working ptrs*/
                              /*Loop for each key in the list*/
                             for (temp = start; temp; temp = temp->ptr) {
    if (temp->sortdat[i]&mask[j])
           /*Value of the bit was 1. If last list is empty, initialize it*/
                                               if (last==0) start2 = temp;
                                                /*else add this item to the list*/
                                                else last->ptr = temp;
                                                last = temp;
           /*Value was 0. If first list empty, initialize it*/
                                                if (first==0) start = temp;
                                                /*else add this item to the list*/
                                                else first->ptr = temp;
                                                first = temp;
                                       } /*End of list*/
                              /*If last list not empty, terminate it*/
                              if (last) last->ptr = 0;
                              /*if first list empty, use last only*/
                              if (first == 0) start = start2;
                              /*Else add last list to first list*/
else first->ptr = start2;
                               } /*All bits this byte examined*/
                               } /*all bytes examined*/
                     return start;
                                                                                                      End Listing One
```

Listing Two

```
/* Listing two */
  /*Shell sort listing*/
  /*Includes for certain Macintosh routines*/
  #include quickdraw.h
  #include event.h
  typedef struct (
                     /*This structure consists only of KEYSIZ bytes*/
           char sortdat [KEYSIZ];
           } sortrec;
 char *lmalloc();
 main()
           int i, j, recno;
           long tick;
           sortrec *array, *base;
           unsigned char dat;
           MaxAppl Zone ();
                             /*Get heap space, allocate 256K for sort keys*/
           array = base = (sortrec *) lmalloc(0x40000);
           printf("How many recs to sort\n");
           scanf ("%d", &recno);
           if (!array) (
                     printf("\nNot enough memory in heap");
                     exit();
 /*Fill the area with random data. Use array as a pointer to all records*/
           for (i=0; i<recno; ++i) {
                     for (j=0; j<KEYSIZ; ++j) {
                               dat = (Random() &0x7fff) %256;
                               array->sortdat[j] = dat;
                     ++array;
           tick = TickCount();
                                                  /*Get the current time*/
           sort (KEYSIZ, base, comp, swap, recno);
           printf("\nTickcount=%ld", TickCount()-tick); /*Print elapsed time*/
 sortrec *sort (size, start, comp, swap, n)
 int size, n;
 sortrec *start;
 long (*comp) (), (*swap) ();
 /*This is essentially identical to that in the Kernighan and Ritchie text.
  The call includes size (the number of records), start (a pointer to the
   first record), comp and swap (routines for comparing and swapping byte
  strings, given pointers to them, and the number of bytes contained therein,
   and n (the number of bytes in the sort key) */
          int gap, i, j;
          for (gap = n/2; gap > 0; gap /= 2)
                    for (i=gap; i<n; i++)
                              for (j=i-gap; j>=0; j-=gap) (
                                       if ((*comp) (start+j, start+j+gap, size) <= 0) break;</pre>
                                       (*swap) (start+j, start+j+gap, size);
comp (val1, val2, n)
char *val1, *val2;
int n;
          register i;
          for (i=0; i<n; ++i) {
                    if (*(val1+i) < *(val2+i)) return (-1);
                    else if (*(vall+i) > *(val2+i)) return(1);
          return 0;
swap (val1, val2, n)
char *val1, *val2;
int n:
         register i, temp;
         for (i=0; i<n; ++i) {
    temp = *val1;
    *val1++ = *val2;
                   *val2++ = temp;
```

End Listings


PROMPT DELIVERY!!! SAME DAY SHIPPING (USUALLY) OUANTITY ONE PRICES SHOWN for JULY 21, 1986

2	OUTSIDE	OKLAHOM	IA: NO SAI	LES TAX	
\$74.32 stra			IC RAM		00
50: \$74 Vectra	200-1-1	1000Kx1	100 ns	\$70.00	0.0
50. Ve	256K	64Kx4	150 ns	4.00	\$ 14 (
h d	256K	256Kx1	100 ns	5.50	
Zenith 150: Plus; hp Vec	256K	256Kx1	120 ns	3.34	Mhz
100000	256K	256Kx1	150 ns	2.74	8 8
RD KITS: Portable &	128K	128Kx1	150 ns	4.25	0 m
KITS: able 8	64K	64Kx1	150 ns	1.29	V20/V30 80287-8
35 pr		EPR			20/
AP q P	27512	64Kx8	250 ns	\$23.00	> ∞
HERBOA Compaq	27C256	32Kx8	250 ns	6.65	
E P	27256	32Kx8	250 ns	5.20	88
F 7.	27128	16Kx8	250 ns	3.65	75.
te MOT PC/XT.	27C64	8Kx8	200 ns	4.55	8.5
640 Kbyte MOTHERBOARD IBM PC/XT. Compaq Port	2764	8Kx8	250 ns	3.40	လုတ္
Kby		STATIC			8087- 8087-
40	43256L-12		120 ns	\$35.00	88
တ်	6264LP-15	8Kx8	150 ns	2.94	
OPEN 61/4 DAYS: WE CAN SHIP VIA FED-EX ON SAT					

SUNDAYS & HOLIDAYS: SHIPMENT OR DELIVERY, VIA U.S. EXPRESS MAIL SAT DELIVERY

MasterCard/VISA or UPS CASH COD Factory New, Prime Parts 11P00 MICROPROCESSOR UNLIMITED, INC. Th: Std Air \$6/4 lbs Fr: P-One \$13/2 lbs BEGGS, OK. 74421 (918) 267-4961

Circle no. 105 on reader service card



TRANSFER DATA BETWEEN OVER 500 DIFFERENT COMPUTER SYSTEMS

WORD PROCESSORS TOO

QUICK TURN-AROUND

PRICES FROM \$9 PER DISK CALL OR WRITE FOR YOUR

FREE CATALOG

PORT-A-SOFT

555 S. STATE ST., SUITE #12 P.O. BOX 1685, OREM, UT 84057 (801) 226-6704

Circle no. 229 on reader service card.

MEGABYTE S100 BOARD

Available as an upgrade to your present 256K LS-100 Solid State Disk Simulator (sold by Digital Research Computers of Texas) for only \$27500.

Also available new, fully assembled & tested for \$49500.

Runs as if you plugged 3 more boards into your system. Up to 8 megabytes, warm boot with CP/M 2.2. North Star DOS patches for either board.

We also repair and stock most circuit boards for Dynabyte, North Star, and Ithaca systems.

SYNC Studios

42 Pondview Drive Southington, CT 06489 (203) 621-6839

Shipping free with all pre-paid orders. Call for details.

Circle no. 166 on reader service card.

HIGH SPEED THRILLS

Listing One (Text begins on page 46.)

These listing are available for downloading from co-author Mike Elkins Fido BBS at (619)722-8724 which operates at 300 and 1200 baud, 8-bits, no partity, 1 stop-bit.

```
Erathosthenes Sieve Prime Number Program in C
#define TRUE 1
#define FALSE 0
#define SIZE 8190
#define SIZEP1 8191
char flags[SIZEP1];
main()
 int i, prime, j, count, loops;
 loops = 1;
 while (loops <= 10) /* Changed to 100 for second benchmark */
  i = 0:
  while (i <= SIZE)
   flags[i] = TRUE;
  i = 0;
  while (i <= SIZE)
   if (flags[i])
    prime = i + i + 3;
     j = i + prime;
while(j <= SIZE)</pre>
      flags[j] = FALSE;
      j = j + prime;
     count++;
    i++;
   loops++;
  printf("%d primes, %d loops\n", count, loops);
  return;
```

End Listing One

Listing Two

- LISTING 2 ---

"DHRYSTONE" Benchmark Program

cl dry.c (Microsoft 3.0) Compile: Defines are provided for old C compiler's Defines:

which don't have enums, and can't assign structures. The time(2) function is library dependant; One is provided for CI-C86. Your compiler may be different. This is not required for Microsoft 3.0 which supports all of the standard calls and will compile asis.

MACHINE	OPERATING	COMPILER	DHRYSTONES
TYPE	SYSTEM		/SEC
IEM PC IEM PC/AT \$ IEM PC/AT \$ ATT 3B2/300 \$ IEM PC/AT \$ Sun2/120	PCDOS 3.1 PCDOS 3.1 PCDOS 3.0 UNIX 5.2 VENIX/86 2.1 Sun 4.2BSD	Microsoft C 3.0 Microsoft C 3.0 CI-C86 2.1 cc cc	333 1041 684 806 1000 1219

The entries with \$ supplied by Rick Richardson, who origanally converted the program from ADA.

The rest are provided by Mike's "C" Board 619-722-8724.

The rest are provided by Mike's "C" Board 619-722-8724.

The following program contains statements of a high-level programming language (C) in a distribution considered representative:

assignments 328 control statements procedure, function calls

100 statements are dynamically executed. The program is balanced with respect to the three aspects:
- statement type


- operand type (for simple data types)

- operand access

```
operand global, local, parameter, or constant.
          The combination of these three aspects is balanced only approximately.
          The program does not compute anything meaningfull, but it is
          syntactically and semantically correct.
  /* Compiler dependent options */
                                    /* Define if compiler has no enum's */
/* Define if compiler can't assign structures */
  #undef
         NOENUM
  #undef
          NOSTRUCTASSIGN
  #undef
         NOTIME
                                    /* Define if no time() function in library */
  #ifdef NOSTRUCTASSIGN
 #define structassign(d, s)
                                    memcpy (& (d), & (s), sizeof (d))
  #else
  #define structassign(d, s)
 #endif
  #ifdef NOENUM
 #define Ident1
#define Ident2
  #define Ident3
 #define Ident4
 #define Ident5
 typedef int
                  Enumeration:
 #else
 typedef enum
#endif
                  {Ident1, Ident2, Ident3, Ident4, Ident5} Enumeration;
 typedef int
                   OneToThirty;
 typedef int
                  OneToFifty;
 typedef char
                  CapitalLetter;
 typedef char
                  String30[31];
 typedef int
                  ArraylDim[51];
 typedef int
                  Array2Dim[51][51];
 struct Record
          struct Record
                                    *PtrComp;
          Enumeration
                                    Discr;
         Enumeration
                                    EnumComo:
         OneToFifty
                                    IntComp;
         String30
                                    StringComp;
 typedef struct Record
                          RecordType;
 typedef RecordType *
                           RecordPtr;
 typedef int
                           boolean;
 #define NULL
 #define TRUE
 #define FALSE
 #ifndef REG
#define REG
#endif
extern Enumeration
                          Func1():
extern boolean
                          Func2();
main()
         Proc0();
   Package 1
int
                 IntGlob;
boolean
                 BoolGlob;
char
                 CharlGlob;
                 Char2Glob:
Array1Dim
                 ArraylGlob;
Arrav2Dim
                 Array2Glob;
RecordPtr
                 PtrGlob:
RecordPtr
                 PtrGlobNext:
Proc0()
        OneToFifty
                                  Int Loc1:
        REG OneToFifty
                                  IntLoc2:
        OneToFifty
                                  IntLoc3;
        REG char
                                  CharLoc;
        REG char
                                  CharIndex;
        REG Enumeration
                                  EnumLoc;
        String30
                                  StringlLoc;
        String30
                                  String2Loc;
#define LOOPS
                         50000
                         time();
```

(continued on next page)

Byte Magazine called it.



The SBI80 Computer/Controller

Featured on the cover of Byte, Sept. 1985, the SB180 lets CP/M users upgrade to a fast, 4" x 7½" single board system.

• 6MHz 64180 CPU

(Z80 instruction superset), 256K RAM, 8K Monitor ROM with device test, disk

format, read/write.

• Mini/Micro Floppy Controller
(1-4 drives, Single/Double Density,
1-2 sided, 40/77/80 track 3½", 5½"

and 8" drives).

• Measures 4" x 7%", with mounting holes

One Centronics Printer Port Two RS232C Serial Ports

(75-19,200 baud with console port auto-baud rate select).

Power Supply Requirements
 +5V +/-5% @500 mA
 +12V +/- 20% @40mA
 ZCPR3 (CP/M 2.2/3 compatible)

Multiple disk formats supported Menu-based system customization

SB180 computer board w/256K bytes RAM and ROM monitor\$369.00

SB180-1-20

same as above w/ZCPR3, ZRDOS and BIOS source.....\$499.00

-Quantity discounts available-

NEW

COMM180-M-S

optional peripheral board adds 1200 bps modem and SCSI hard disk interface.

TO ORDER CALL TOLL FREE 1-800-635-3355

TELEX 643331

For technical assistance or to request a data sheet, call: 1-203-871-6170



Micromint, Inc. 25 Terrace Drive Vernon, CT 06066

FORTH APPLICATION AND RESEARCH

Volume 4 Subscriptions

Corporate/Institutional 100. Individual 40.

Outside N.A. add airmail 20.

Send checks or money order to: JFAR P.O. Box 27686 Rochester, NY 14627

Incredible SwyftWare! TM

It is not possible in an ad to really explain this Apple II (e or c) product which outperforms all other software in speed and simplicity. It does no-frills word processing, information retrieval, telecommunications and many other tasks. Reviewers call it "foolproof and frustration free" and "blindingly fast." It appeals to beginners and experts. Jef Raskin, who invented the Macintosh and who later created SwyftWare, has written up the hows and whys of this product. Please write for a copy. No charge. Or order SwyftWare and see for yourself. At \$89.95 and with a 30-day refund policy, there's no risk.

US 800/982-5600 CA 800/562-7400

Information Appliance 1014 Hamilton Ct., Menlo Park, CA 94025

Dr. Dobb's Journal

Subscription Problems? No Problem!



Give us a call and we'll straighten it out. Today.

Outside California
CALL TOLL FREE: 800-321-3333

Inside California CALL: 619-485-6535 or 6536

HIGH SPEED THRILLS

Listing TWO (Listing continued, text begins on page 46.)

```
starttime;
                                 bencht ime:
long
                                 nulltime;
long
register unsigned int
starttime = time(0);
for (i = 0; i < LOOPS; ++i);
nulltime = time(0) - starttime;
           PtrGlobNext = (RecordPtr) malloc(sizeof(RecordType));
PtrGlob = (RecordPtr) malloc(sizeof(RecordType));
PtrGlob->PtrComp = PtrGlobNext;
PtrGlob->Discr = Ident;
           PtrGlob->EnumComp = Ident3;
PtrGlob->IntComp = 40;
strcpy(PtrGlob->StringComp, "DHRYSTONE PROGRAM, SOME STRING");
-- Start Timer --
starttime = time(0);
for (i = 0; i < LOOPS; ++i)
            Proc5():
            Proc4();
            IntLoc1 = 2;
IntLoc2 = 3;
            stropy (String2Loc, "DHRYSTONE PROGRAM, 2'ND STRING");
            EnumLoc = Ident2;
BoolGlob = ! Func2(String1Loc, String2Loc);
            while (IntLoc1 < IntLoc2)
                       IntLoc3 = 5 * IntLoc1 - IntLoc2;
Proc7(IntLoc1, IntLoc2, &IntLoc3);
                        ++IntLoc1;
            Proc8 (ArraylGlob, Array2Glob, IntLoc1, IntLoc3);
             Proc( (Rraylob); Proc( (Rraylob); ++CharIndex (CharIndex = 'A'; CharIndex <= Char2Glob; ++CharIndex)
                       if (EnumLoc = Funcl(CharIndex, 'C'))
                                   Proc6(Ident1, &EnumLoc);
             IntLoc3 = IntLoc2 * IntLoc1;
IntLoc2 = IntLoc3 / IntLoc1;
IntLoc2 = 7 * (IntLoc3 - IntLoc2) - IntLoc1;
             Proc2(&IntLoc1);
    ******
  -- Stop Timer --
  benchtime = time(0) - starttime - nulltime;
printf("Dhrystone time for %ld passes = %ld\n", (long) LOOPS, benchtime);
printf("This machine benchmarks at %ld dhrystones/second\n",
              ((long) LOOPS) / benchtime);
   Proc1 (PtrParIn)
                        PtrParIn;
   REG RecordPtr
                                     (* (PtrParIn->PtrComp))
   #define NextRecord
              structassign (NextRecord, *PtrGlob);
              PtrParIn->IntComp = 5;
NextRecord.IntComp = PtrParIn->IntComp;
NextRecord.PtrComp = PtrParIn->PtrComp;
              Proc3 (NextRecord .PtrComp);
               if (NextRecord.Discr == Ident1)
                          NextRecord.IntComp = 6;
Proc6(PtrParIn->EnumComp, &NextRecord.EnumComp);
                          NextRecord.PtrComp = PtrGlob->PtrComp;
                          Proc7 (NextRecord.IntComp, 10, &NextRecord.IntComp);
               else
                          structassign (*PtrParIn, NextRecord);
    #undef NextRecord
    Proc2 (IntParIO)
                         *IntParIO;
    OneToFifty
                                                 IntLoc:
               REG OneToFifty
               REG Enumeration
                                                 EnumLoc;
               IntLoc = *IntParIO + 10;
               for(;;)
                           if (CharlGlob == 'A')
```

```
-- IntLoc:
                                *IntParIO = IntLoc - IntGlob:
                                EnumLoc = Ident1;
                      if (EnumLoc == Ident1)
   Proc3 (PtrParOut)
   RecordPtr
                      *PtrParOut;
            if (PtrGlob != NULL)
                      *PtrParOut = PtrGlob->PtrComp;
                      IntGlob = 100;
            Proc7(10, IntGlob, &PtrGlob->IntComp);
  Proc4()
            REG boolean
                               BoolLoc:
            BoolLoc = CharlGlob == 'A';
BoolLoc |= BoolGlob;
Char2Glob = 'B';
  Proc5()
           CharlGlob = 'A';
BoolGlob = FALSE;
  extern boolean Func3();
  Proc6 (EnumParIn, EnumParOut)
  REG Enumeration EnumParIn;
  REG Enumeration *EnumParOut;
            *EnumParOut = EnumParIn;
           if (! Func3 (EnumParIn) )

*EnumParOut = Ident4;
           switch (EnumParIn)
           case Ident1:
                               *EnumParOut = Ident1; break;
           case Ident2:
                               if (IntGlob > 100) *EnumParOut = Ident1;
                               else *EnumParOut = Ident4;
                               break:
           case Ident3:
                               *EnumParOut = Ident2; break;
           case Ident4:
                              break:
           case Ident5:
                               *EnumParOut = Ident3;
 Proc7(IntParI1, IntParI2, IntParOut)
 OneToFifty
                     IntParI1:
 OneToFifty
                    IntParT2:
 OneToFifty
                     *IntParOut;
           REG OneToFifty IntLoc;
          IntLoc = IntParI1 + 2;
           *IntParOut = IntParI2 + IntLoc;
 Proc8 (ArraylPar, Array2Par, IntParI1, IntParI2)
 Array1Dim
                    ArraylPar;
 Array2Dim
                    Array2Par;
 OneToFifty
                   IntParI1;
 OneToFifty
                   IntParI2;
          REG OneToFifty IntLoc;
REG OneToFifty IntIndex;
         IntLoc = IntParI1 + 5;
ArraylPar[IntLoc] = IntParI2;
ArraylPar[IntLoc+1] = ArraylPar[IntLoc];
ArraylPar[IntLoc+30] = IntLoc;
          for (IntIndex = IntLoc; IntIndex <= (IntLoc+1); ++IntIndex)</pre>
                   Array2Par[IntLoc][IntIndex] = IntLoc;
         ++Array2Par[IntLoc][IntLoc-1];
Array2Par[IntLoc+20][IntLoc] = Array1Par[IntLoc];
IntGlob = 5;
Enumeration Func1 (CharPar1, CharPar2)
Capitalletter
                   CharPar1:
Capitalletter
                  CharPar2:
         REG CapitalLetter
                                      Charloc1:
         REG CapitalLetter
                                      CharLoc2;
```

(continued on next page)



Perfect Windows, Powerful Data Entry, <u>FULLY Integrated</u>, For Effortless Data Entry Windows!

- · Complete input formatting
- · Unlimited Validation
- · Full attribute control
- · Field sensitive application help system
- · Multiple virtual windows
- Fully automatic, collision proof overlay and restore
- · Print to & scroll background windows
- · Animated window "zoom"
- Move, grow, shrink, hide, or show any window
- "Loop function" allows processing while awaiting input

and much much more!

Designed to increase your productivity and help you produce superior applications in dramatically less time! Includes 100% source, tutorial, reference manual, examples, and sample programs.

Specify Microsoft, Lattice, Computer Innovations, Aztec,

\$149.95

or Mark Williams. Ask about Unix.

NOW... VCScreen!

Our new interactive screen "painter" actually lets you draw your data entry windows! Define fields, text, boxes & borders. Move them around. Change attributes. Then the touch of a button generates C source code calls to the Vitamin C routines! Now, your screen designs will be faster and more pleasing when they are created with VCScreen!

Requires Vitamin C lib- \$99.95 rary above. For IBM & compatibles.

For Orders Or Information,

(214)245-6090

Creative Programming Consultants
Box 112097 Carrollton, TX 75011-2097
Include \$3 ground, \$6 air, \$15 overnight
shipping, \$25 if outside USA. Texans add
6% tax. All funds must be in U.S. dollars
drawn on a U.S. bank.

HIGH SPEED THRILLS

Listing TWO (Listing continued, text begins on page 46.)

```
CharLoc1 = CharParl;
CharLoc2 = CharLoc1;
         if (CharLoc2 != CharPar2)
    return (Ident1);
         else
                   return (Ident2);
boolean Func2 (StrParI1, StrParI2)
                   StrParI1;
String30
String30
                   StrParI2:
         REG OneToThirty
         REG CapitalLetter
                                      CharLoc;
         IntLoc = 1;
while (IntLoc <= 1)</pre>
                   if (Funcl(StrParI1[IntLoc], StrParI2[IntLoc+1]) == Ident1)
                             CharLoc = 'A';
                             ++IntLoc;
         if (Charloc >= 'W' && Charloc <= 'Z')
         IntLoc = 7;
if (CharLoc == 'X')
                   return (TRUE);
          else
                    if (strcmp(StrParI1, StrParI2) > 0)
                             IntLoc += 7:
                             return (TRUE);
                    else
                             return (FALSE);
```

ENTION

C-PROGRAMMERS

File System Utility Libraries

All products are written entirely in K&R C. Source code included, No Royalties, Powerful & Portable.

BTree Library

- High speed random and sequential access Multiple keys per data file with up to 16 million records per file
 - Duplicate keys, variable length data records

ISAM Driver

4000

- Greatly speeds application development.
- Combines ease of use of database manager with flexibility of program-
- ming language. Supports multi key files and dynamic index definition.
- Very easy to use

Make

- Patterned after the UNIX utility
- Works for programs written in every language Full macros, File name expansion and built in rules.
- Full Documentation and Example Programs Included.

ALL THREE PRODUCTS FOR

Credit cards accepted

1343 Stanbury Drive Oakville, Ontario, Canada L6L 2J5 (416) 825-0903 Dealer inquiries invited

Circle no. 259 on reader service card.

C CODE FOR THE PC

-

source code, of course

QC88 C Compiler	\$90
Concurrent C	\$45
Coder's Prolog in C	\$45
LEX	\$25
YACC & PREP	\$25
Small-C compiler for 8088	\$20
tiny-c interpreter & shell	\$20
Xlisp 1.5a & tiny-Prolog	\$20
C Tools	\$15
[사용자] [1885] [1886] [1885] [1885] [1886] [1886] [1886] [1886] [1886] [1886] [1886] [1886] [1886] [1886] [1886]	

The Austin Code Works 11100 Leafwood Lane Austin, Texas 78750-3409 (512) 258-0785

Free shipping on prepaid orders

No credit cards

Circle no. 250 on reader service card.

```
colean Func3 (EnumParIn)
REG Enumeration EnumParIn:
          REG Enumeration Enumloc:
          EnumLoc = EnumParIn;
          if (EnumLoc == Ident3) return (TRUE);
          return (FALSE);
#ifdef NOSTRUCTASSIGN
memcpy(d, s, l)
register char *d;
register char
          while (1--) *d++ = *s++;
#endif
          Library function for compilers with no time (2) function in the
#ifdef
         NOTIME
long
         time (p)
long
                   /* CI-C86 time function - don't use around midnight */
         struct regval (unsigned int ax,bx,cx,dx,si,di,ds,es; ) regs;
         regs.ax = 0x2c00;
         regs.ax = 0x2c00;

sysint21(sregs, &regs);

t = ((regs.cx>>8)*60L + (regs.cx & 0xff))*60L + (regs.dx>>8);

if (p) *p = t;

return t;
endif
```

End Listings

PLOTDEV ADDS GRAPHICS TO \$39 PC-DOS

MicroPlot, innovator of creative PC software programs is excited to announce PlotDev, the alternative to virtual device drivers and graphics tool kits for PC-DOS graphics programs.

- Installable PC-DOS device driver adds graphics command capabilities to any program language
- Allows full screen PC-DOS command editing by unsticking the cursor
- Supports most popular graphics boards and provides a built-in graphics screen dump for printers
- Non-interfering with memory resident or application programs
- Provides user with all the intelligent alpha terminal commands of a DEC VT-100
- Provides user with the graphics commands of the Tektronix 4010/4014 and 4027 graphics terminals
- And much more ...

Site license and educational discounts available.

For a detailed PlotDev brochure or for ordering information call toll free 1-800-338-0333, in Ohio call 1-800-242-0333. Use touch-tone to enter I.D. code 766-8501, or wait for operator assistance. Visa or MasterCard welcome.



659-H Park Meadow Road Westerville, Ohio 43081

(614) 882-4786

Circle no. 84 on reader service card.

the Dtest

Professional Test/Format Program For Hard Drives in PC/XT/AT

- Setup interleave, step rate, etc.
- Surface analysis to flag bad tracks
- Load/save setup and bad track files
- Now supports AUTOCONFIG!
- Menu driven, with help windows
- Free PARK program included!
- Order HDTEST today for only \$99!

Proto PC inc. 612-644-4660

2424 Territorial Road, St. Paul, MN 55114 Telex 910-380-7623

Circle no. 295 on reader service card.

QPARSER^M

Translator Writing System

THE PRODUCTIVITY TOOL FOR SOFTWARE DEVELOPERS

QPARSER assists you in writing:

* Compilers * Translators * Interpreters *
* Prototypes * Simulators * Syntax Checkers *
* Data Converters * Assemblers *

QPARSER is a unique LALR(1) parser generator:

Generates complete source code for your application in C, Pascal, or another language of your choice; Extensive examples include a Pascal subset compiler, assembler, and simulator;

The widely used college text, Compiler Construction:
Theory & Practice, from SRA Associates, was
written by the author of QPARSER

Lauded by both industrial and university users
Available for: IBM PC,XT,AT; DEC VAX; HP 9816; MACINTOSH
(PC System \$400; Demo \$10; Educational/Site Licenses available)

"LEADERS IN SOFTWARE TOOLS"



1164 Hyde Ave., San Jose CA 95129 Toll-free Orders: (800) 538-9787; In CA: (408) 727-6671

Circle no. 117 on reader service card.

THE PROGRAMMER'S SHOP

helps save time, money and cut frustrations. Compare, evaluate, and find products.

RECENT DISCOVERY

BreakOut - Manipulate and capture asynch data communications on COM1 or COM2 ports or IBM PC. Keystoke macros, windows, ASCII. Determine protocol, test, and control RS232 asynch devices. PC \$ 125

AI-Expert System Dev't

Arity System - incorporate with C programs, rule & inheritance PC \$ 295 Experteach - Powerful, no limit on memory size. Samples PC \$ 399 EXSYS - Improved. Debug, file & external program access. MS \$ 339 Insight 2 + - dB2, language. MS \$ 879 Others: APES (\$359), Advisor (\$949), ES Construction (\$100), ESP (\$845), Expert Choice (\$449)

Al-Lisp

BYSO - Common, MacLISP compatible.

250 + functions, fast PC \$ 150
GC LISP Interpreter - "Common",
rich. Interactive tutorial Call
Microsoft MuLisp 85 \$ 199
PC Scheme LISP - by TI PC \$ 95
TLC LISP - classes, compiler. MS \$ 225
TransLISP - learn fast MS \$ 75
WALTZLISP - "FRANZLISP" - like,
big nums, debug, CPM-80 MS \$ 149
Others: IQ LISP (\$155), UNX LISP (\$59),
IQC LISP (\$269)

Al-Prolog

ARITY Standard - full, 4 Meg Interpreter - debug, C, ASM PC \$ 350 COMPILER/Interpreter-EXE PC \$ 795 With Exp Sys, Screen - KIT PC \$1250 MacProlog by Programming Logic MS \$ 295 MS \$ 229 MAC Systems MicroProlog - enhanced Prof. MicroProlog-full memory MS \$ 359 Prolog-86 - Learn Fast, Standard, MS \$ tutorials, samples Prolog-86 Plus - Develop MS \$ 250 TURBO PROLOG by Borland PC \$ 79 Others: Prolog-I (\$365), Prolog-2 (\$1795)

Al-Other

METHODS - SMALLTALK has objects, windows PC \$ 69 with graphics PC \$ 89 Methods by Digitalk PC \$ 209 Q'NIAL - Combines APL with LISP. Source or binary. PC \$ 359

FEATURES

Quick Basic v2.0 - New user interface. Editor, source level error detection, built-in debugger, in-memory compilation, build and link user libraries. BASICA, GW-BASIC compatible. BLOAD, BSAVE

700 + Programmer's Products

The Programmer's Shop carries every programmer's software product for MSDOS, PCDOS, CPM, Macintosh, Atari, and Amiga systems. We help you choose the best tools for you. Most popular products are in stock, available for quick delivery. We will gladly special order a product for you at no charge—just allow a few extra days for delivery. Need Cross Compilers, Translators, or the right Fortran compiler? Ask us.

Our Services:

Programmer's Referral List
 Compare Products
 Help find a Publisher
 Evaluation Literature FREE
 BBS - 7 PM to 7 AM 617-826-4086
 National Accounts Center

Basic

ACTIVE TRACE Debugger -BASICA, MBASIC, well liked MS \$ 79 APC MegaBASIC - powerful PC \$ 339 Basic Development System - for BASICA; Adds Renum, more. PC \$ 105 PC \$ 95 Basic Windows by Syscom BetterBASIC - all RAM, modules \$ 169 Structure. Full BASICA PC \$ 89 8087 Math Support PC \$ 235 Run-time Module Better Tools - for Better Basic PC \$ CADSAM FILE SYSTEM - full MS \$ 75 ISAM in MBASIC source. \$ 95 PC GoodBas - maintain code LPI Basic - MS compatible UNIX \$1100 \$ Prof. Basic - Interactive, debug PC \$ 47 8087 Math Support PC \$ 119 TRUE Basic - ANSI PC \$ 459 Run-time Module

Cobol

UNIX \$1200 LPI Cobol - ANSI '74 \$ 459 Macintosh COBOL - full MAC MS \$ 885 MBP - Lev. II, native MicroFocus Professional - full PC Call Microsoft Cobol Tools - xref, debugger w/source support. Xenix \$359 PC \$ 239 Microsoft Version II - upgraded. MS \$ 479 Full Lev. II, native, screens. MS \$ 839 Realia - very fast MS \$ 699 Ryan McFarland COBOL COBOL-8X MS \$1049

Editors for Programming

BRIEF Programmer's Editor - undo, PC Call windows, reconfigure 80/86 \$ 75 C Screen Editor - w/source EMACS by UniPress - powerful, Source:\$949 \$299 multifile, windows Epsilon - like EMACS, full PC \$169 C-like language for macros. PC \$109 Kedit - like XEDIT Lattice Screen Editor - multiwindow Amiga \$100 MS \$109 multitasking PMATE - power, multitask 80/86 \$149 PC \$ 85 XTC - multitasking

Atari ST & Amiga

We carry full lines of Manx,
Lattice, & Metacomco.
Amiga - LINT by Gimpel Amiga \$ 79
Cambridge LISP Amiga \$ 200
Lattice C ST, Amiga \$ 139
Lattice Text Utilities Amiga \$ 75
Megamax - tight, full ST \$ 200

RECENT DISCOVERY

TurboHALO Graphics for Turbo
PASCAL - respected, mature, full.
150 HALO routines, up to 16 colors,
medium or high resolution, multiple
fonts. IBM CGA and EGA, Hercules,
AT&T DEB, more.
PC \$ 99

C Language-Compilers

AZTEC C86 - Commercial	PC	\$499
AZTEC C65 - Personal App	le II	\$199
C86 by CI - 8087, reliable	MS	\$299
Lattice C - from Lifeboat		\$289
Lattice C - from Lattice		\$339
Mark Williams - w/debugger	MS	\$399
Microsoft C 3.0	MS	\$259
Q/C 88 by Code Works - Compile	r	
source, decent code, native	MS	\$125
Wizard C - Lattice C compatible, full sys. III, lint, fast.	MS	\$389

C Language-Interpreters

		A STATE OF THE PARTY OF
C-terp by Gimpel - full K & R	MS	\$249
INSTANT C - Source debug, Edit to Run-3 seconds	MS	\$389
Interactive C by IMPACC Assoc. Interpreter, editor, source, debug Introducing C - self paced tutorial	. PC	\$225 \$109
Run/C Professional - Run/C plus create add-in libraries, more Run/C Lite - improved		\$189 \$109

C Libraries-General

		100	-
Blackstar C Function Library	PC		
Blaise C Tools 1 (\$109), C Too	ols 2	\$	89
C Essentials - 200 functions	PC	5	85
C Food by Lattice-ask for source	MS	\$	109
C Utilities by Essential - Compre	hensi	ve	
screen graphics, strings, source	e. PC	3	139
C Worthy Library - Complete, m	achin	ie	
independent	MS	3.	
Entelekon C Function Library			119
Entelekon Superfonts for C			45
Greenleaf Functions - portable,	ASM	\$	139
PforCe by Phoenix - objects	PC	\$	299

C Libraries-Communications

Asynch by Blaise	PC \$149
Greenleaf - full, fast	PC \$139
Software Horizons - pack 3	PC \$119

C Libraries-Files

FILES: C Index by Trio - full B +		
Tree, vary length field, multi cor	npiler	
/File is object only	MS	\$ 89
/Plus is full source	MS	\$349
C to dBase - with source	MS	\$139
CBTREE - sequential, source, no	0	
royalties	MS	\$ 99
CTree by Faircom - no royalties		\$339
dbVISTA - full indexing, plus of	otiona	1
record types, pointers, Network	K.	
Object only - MS C, LAT,	C86	\$159
Source - Single user	MS	\$429
Source - Multiuser	MS	\$849
dBASE Tools for C	PC	\$ 79
dbc Isam by Lattice	MS	\$199

We support MSDOS (not just compatibles), PCDOS, Xenix-86, CPM-80, Macintosh, Atari ST, and Amiga.

THE PROGRAMMER'S SHOP

provides complete information, advice, guarantees and every product for Microcomputer Programming.

GREENLEAF BARGAINS ORDER TODAY

Order before 9/31/86 and mention this ad for the special prices to the right:

The HAMMER by OES Systems PC \$179

PC LINT - Checker. Amiga \$89 MS \$119 SECURITY LIB - add encrypt to MS C, C86 programs. Source \$250 PC \$125 C-Screens. Windows. Graphics

C Power Windows by Entelekon PC \$119

PC \$139

MS \$600

MS \$ 95

MS \$105

PC \$ 79

PC \$109

PC \$219

PC \$219

PC \$139

PC \$159

PC \$239

PC \$149

PC \$109

PC \$139

MS \$ 95

PC \$269

PC \$129

PC \$249

\$199

PC \$209

PC \$319

C Support-Systems

Basic-C Library by C Source

C ToolSet - DIFF, xref, source

Lattice Text Utilities

dBASE Graphics for C

ESSENTIAL GRAPHICS - fast,

Topview Toolbasket by Lattice

View Manager for C by Blaise

Windows for Data - validation

Advanced Trace-86 by Morgan Modify ASM code on fly.

CODESMITH - visual, modify and rewrite Assembler

Periscope I - own 16K Periscope II - symbolic, "Reset

Pfix-86 Plus Symbolic Debugger

single step, 2 screen, log file. MS \$115

Smalltalk-80 - "Official" Xerox licensed version. Compatible with Smalltalk-80 v2 running on other systems. Compiler, complete graphics interface, debugger, windows, text and graphics editor, source. Protected mode, RAM access. Requires

C SPRITE - data structures

DSD87 - windowing, 8087

by Phoenix - windows

Software Source by Atron -Lattice, MS C, Pascal, Windows

GraphiC - new color version

Curses by Lattice

fonts, no royalties

Vitamin C - screen I/O

Windows for C - fast

Debuggers

Box," 2 Screen

w/Breakswitch

FEATURE

C Sharp - well supported. Source, realtime, tasks, state system

Greenleaf Functions - 200 + functions in C for printer, formatting. With source. Covers all bases including screen, graphics, & DOS interface. Good doc. Specify compiler.

Greenleaf Comm Library - Full ASYNCH

• support with source. Xmodem, CRC, polling. Specify compiler.

	LIST	Before	After
프랑아 보고 하는 지근 가장 나를 먹었다.		9/30	9/30
Greenleaf Functions	185	119	139
Greenleaf Communications	185	119	139

Fortran & Supporting

ACS Time Series	MS	\$449
Forlib + by Alpha - graphics an	d	
file routines, comm.	MS	\$ 59
MACFortran by Microsoft	MAC	\$229
MS Fortran link to C		\$219
No Limit - Fortran Scientific	PC	\$119
PolyFortran - xref, pp. screen		\$149
Prospero - '66, reentrant		\$349
RM/Fortran - enhanced "IBM		4017
Professional Fortran"	MS	\$395
Scientific Subroutines - Matrix	MS	\$149
Statistician by Alpha	MS	\$269
Strings and Things - register, she	ell PC	\$ 59

Multilanguage Support

BTRIEVE ISAM	MS	\$199
BTRIEVE/N-multiuser		\$469
CODESIFTER - Profiler.	MS	\$109
HALO Graphics - 115 + devices		4.07
Animation, engineering, busine	SS.	
Any MS language, Lattice, C86	PC	\$229
PANEL - Create screen with editor		7
generates code. Full data validation	on.	
no royalties. Xenix \$539.	MS	\$239
Pfinish Performance Analyzer	PC	\$249
PLINK 86-program-independent	MS	\$249
PLINK-86 PLUS - incremental	MS	\$369
PolyLibrarian by Polytron		\$ 85
PVCS Version Control		\$329
Rtrieve - Btrieve front end	MS	\$ 79
Screen Sculptor - slick, thorough,		
fast, BASIC, PASCAL.		\$ 99
Xtrieve - organize database	MS	\$169

Pascal and Supporting

ZView - screen generator

ZAP Communications - VT 100,

TEK 4010 emulation, file xfer.

PC \$ 95

MS \$219

r ascaratia supporting		
Alice - learn Pascal. Turbo		
compatible, interpreter	PC	\$ 85
MetaWINDOW - graphics toolkit	PC	\$119
Microsoft PASCAL - faster	MS	\$109
MICROTEC PASCAL - 5 memor	ry mo	dels,
"Iterators", 65 bit 8087 strings	MS	\$665
Pascal Tools - strings, screen	PC	\$109
Pascal Tools 2 - by Blaise	MS	\$ 85
Pfas - Portable Isam	MS	\$185
Prospero Pascal - full ISO +	MS	\$349
USCD Pascal - native code	MS	\$ 69
	Section Street	THE RESERVED

RECENT DISCOVERY

Lattice RPG II Compiler - Run RPG II programs developed for the System III or system 32/34/36 with little or no change in source code. Screen gen, ISAM, & direct files. No royalties. PC \$639

Other Languages

APL*PLUS/PC			469
Artek ADA Compiler - DODs	tandar	d	
minus multitasking	PC	\$	895
CLIPPER-dBASE Compiler	MS	\$	449
ED/ASM - 86 by Oliver	PC	\$	85
	MAC		99
MasterForth - Forth '83 MAC	or PC	\$	125
	MS		109
Modula 2 by Volition Systems	MS	\$	250
Modula-2/86 Compiler by Log	itech		
w/8087 (\$105), 512K (\$149)	. PC	\$	65
Pasm - by Phoenix	MS	\$	219
RPG II by Lattice	PC	\$	639
SNOBOL4 + - great for strings	MS	\$	85
Turbo Edit/ASM - by Speedware	PC	\$	85

Xenix-86 & Supporting

		0.75
Basic - by Microsoft	\$	279
Cobol - by Microsoft	\$	795
Fortran - by Microsoft		399
Xenix Complete Development S	System,\$	1149

Other Products

Other Products			
BSW Make - like UNIX make	MS	\$	85
Dan Bricklin's Demo Program	n PC	\$	65
dBrief - Customize BRIEF for	dBAS	F	
development. with BRIEF \$27.	5. PC	\$	95
H Test/H Format - XT Fix	PC	\$	89
Interactive Easyflow-HavenTre	e PC	\$	139
Link & Locate - MSDOS tools	to wo	rk v	with
Intel and Tektronix projects.	MS	\$	329
LMK - like UNIX make	PC	\$	149
Microsoft Windows	PC	\$	75
Microsoft Windows Software			
Development Kit	PC	\$	399
Opt Tech Sort - sort, merge	MS	\$	119
PMaker - by Phoenix	PC	\$	139
Polymake by Polytron	MS	\$	79
PolyWindows Dev. Kit	PC	\$	149
PS MAKE	MS	\$	129
SECRET DISK by Lattice	PC	\$	99
SET:SCIL - manage revisions	PC	\$	299
Shrink/Shrinkem - put more file	S		
on disk	PC	\$	150
SoftEst - Manage projects.	MS	\$	350
Source Print	PC	\$	89
Synergy-Create user interfaces	MS	\$	375
Texsys - control source	MS	\$	89
Visible Computer: 8088 - Simul	ates		
demos or any .exe. com, Debu	gger.		
350 pg. tutorial, unprotected	PC	\$	69
Notes All			

Note: All prices subject to change without notice.

Mention this ad. Some prices are specials. Ask about
COD and POs. All formats available.

UPS surface shipping add \$3/item.

Call for a catalog, literature, advice and service you can trust

HOURS 8:30 AM - 8:00 PM EST. 800-421-8006

THE PROGRAMMER'S SHOP™
128-DRockland Street, Hanover, MA 02339
Mass: 800-442-8070 or 617-826-7531 7/86

"You've got everything I've heard of, and much I haven't! . . . Normally, I expect my money to be "fan letter" enough, but you people are SUPER!"

Shel Hall Artell Corp.

COMBINE THE **RAW POWER OF FORTH** WITH THE CONVENIENCE OF CONVENTIONAL LANGUAGES

Why HS/FORTH? Not for speed alone, although it is twice as fast as other full memory Forths, with near assembly language performance when optimized. Not even because it gives MANY more functions per byte than any other Forth. Not because you can run all DOS commands plus COM and EXE programs from within HS/FORTH. Not because you can single step, trace, decompile & dissassemble. Not for the complete syntax checking 8086/ 8087/80186 assembler & optimizer. Nor for the fast 9 digit software floating point or lightning 18 digit 8087 math pack. Not for the half megabyte LINEAR address space for quick access arrays. Not for complete music, sound effects & graphics support. Nor the efficient string functions. Not for unrivaled disk flexibility — including traditional Forth screens (sectored or in files) or free format files, all with full screen editors. Not even because I/O is as easy, but far more powerful, than even Basic. Just redirect the character input and/ or output stream anywhere - display, keyboard, printer or com port, file, or even a memory buffer. You could even transfer control of your entire computer to a terminal thousands of miles away with a simple >COM <COM pair. Even though a few of these reasons might be sufficient, the real reason is that we don't avoid the objections to Forth — WE ELIMINATE THEM!

Public domain products may be cheap; but your time isn't. Don't shortchange yourself. Use the best. Use it now!

HS/FORTH, complete system: \$395. with "FORTH: A Text & Reference" by Kelly and Spies, Prentice-Hall and "The HS/FORTH Supplement" by Kelly and Callahan



Visa

Mastercard Mastercard



HARVARD SOFTWORKS

PO BOX 69 SPRINGBORO, OH 45066 (513) 748-0390

16-BIT

Listing One (Text begins on page 108.)

Listing 1.

- 1) copy masm.exe masm.sav (to make a backup)
- 2) ren masm.exe masm.fix (debug.com can't write EXE files)

```
3) debug masm.fix
3a) D 72B8 L 22 (should see 34 bytes of 00)
3b) E 72B8
           enter these bytes:
           8B 1E D6 09 C6 06 C0 01 00 E9 75 02 C4 57 06 FE 06 C0 01 E9 74 02 80 7C FF 1A 74 03 39 9D 02 4E
           EB F4
    3c) U 7535 L 1 (should see "MOV BX,[09D6]" ) 3d) E 7535
    enter these bytes: E9 80 FD
3e) U 753F L 1 (should see "LES DX, [BX+06]")
3f) E 753F
```

- bytes: E9 82 FD (should see "CMP BYTE PTR [SI-01],1A") enter these bytes:
- 3g) U 756D L 1 (should see "CMP enter these bytes: E9 5E FD (to write changes to masm.fix)
- 3i) O (to exit debug.com)

4) ren masm.fix masm.exe

5) Test masm. exe to make sure changes have been made correctly. If not, copy masm.sav to masm.exe and try again.

End Listing One

:::

Listing Two

```
Listing Two
Basic I/O functions using handle packing.
                                             ;;;;
     hpkio
::::
                                             ;;;;
;;;;
                                             ::::
                  Paul M. Adams
Route 4 Box 23
          Written By
                                             ;;;;
::::
                  Shelbyville, KY 40065
;;;;
                                              ;;;;
;;;;
....
     include model.h
     include prologue.h
```

```
hcreate (dsn, attr)
:::
                                            /* Data Set Name
                                *dsn;
          unsigned char
                                           /* file attribute byte */
                                attr;
;;;
          int
                                                                                                  ;;;
:::
                                                                                                  ;;;
          hold handle = psp handle[19]
psp handle[19] = FF
call dos to create file
;;;
;;;
           if error
:::
                                                                                                  ;;;
                      retval = -1
:::
                      retval = psp_handle[dos_handle]
psp_handle[dos_handle] = FF
                                                                                                  ;;;
:::
;;;
           psp handle[19] = hold_handle
;;;
```

return (retval) - real dos handle ;;; hcreate proc public hcreate push es push bp

NOV bp, sp sp, 2 sub equ [bp + dsn equ [bp + 8] hold handle equ [bp - 2] mov ah, 62h 21h int es, bx

Product Information

Free!

U	G.	9	1	7	ı

nfori	natio	on

Product

Free!

Dr. Dobb's Journal of Software Tools

September 1986 #119 **Expiration Date:** December 31, 1986 Name Title Company _ Phone Address

Please circle one letter in each category:

I. My work is performed:

City/State/Zip_

- A. for in-house use only.
- B. for other companies. C. for end users/retailers.
- D. in none of the above areas.

II. My primary job function:

- A. Software Project Mgmt/Spvr
- B. Hardware Project Mgmt/Spvr
- C. Computer Consultant D. Corporate Management
- E. Other

III. My company department performs:

- A. software development. B. computer system integration.
- C. computer manufacturing.
- D. computer consulting.
- E. computer research
- F. none of the above.
- IV. This inquiry is for:

- A. a purchase within 1 month.

 B. a purchase within 1 to 6 months.
- C. product information only.

V. Corporate Purchase Authority:

- A. Final Decision-maker
- B. Approve/Recommend
- C. No Influence

VI. Personal Computer Users at my Jobsite:

- A. 10,000 or more
- B. 500 to 9,999 C. 100 to 499
- D. 10 to 99
- E. less than 10
- VII. On average, I advise others about computers:
- A. more than once per day.
- B. once per day.
- C. once per week
- D. less than once per week.
- VIII. In my job function, I:

A. design software and/or write code.

- B. design software. C. write code.
- D. don't design software or write code.

A Reader Service number appears on each advertisement. Circle the corresponding numbers below for more info.

the price of \$29.97

Thank You! Dr. Dobb's greatly appreciates your responses to questions I through VIII.



First Class Permit #217, Clinton, Iowa

POSTAGE WILL BE PAID BY ADDRESSEE

Dr. Dobb's Journal of

հենահվահվանհանհանհենանվել

P.O. Box 2157 Clinton, Iowa 52735-2157

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES



BUSINESS REPLY MAIL

First Class Permit #217, Clinton, Iowa

POSTAGE WILL BE PAID BY ADDRESSEE

Dr. Dobb's Journal of

P.O. Box 2157 Clinton, Iowa 52735-2157

IF MAILED IN THE UNITED STATES

NO POSTAGE NECESSARY

Product Information

Free!

Thank You! Dr. Dobb's greatly appreciates your

responses to questions I through VIII.

հեկակվայել հունական հունական հեկական և

Postage Paid!

A Reader Service number appears on each advertisement. Circle the corresponding

num	bers b	elow	for m	ore ir	iro.			
001	002	003	004	005	006	007	008	009
010	011	012	013	014	015	016	017	018
019	020	021	022	023	024	025	026	027
028	029	030	031	032	033	034	035	036
037	038	039	040	041	042	043	044	045
046	047	048	049	050	051	052	053	054
055	056	057	058	059	060	061	062	063
064	065	066	067	068	069	070	071	072
073	074	075	076	077	078	079	080	081
082	083	084	085	086	087	088	089	090
091	092	093	094	095	096	097	098	099
100	101	102	103	104	105	106	107	108
109	110	111	112	113	114	115	116	117
118	119	120	121	122	123	124	125	126
127	128	129	130	131	132	133	134	135
136	137	138	139	140	141	142	143	144
145	146	147	148	149	150	151	152	153
154	155	156	157	158	159	160	161	162
163	164	165	166	167	168	169	170	171
172	173	174	175	176	177	178	179	180
181	182	183	184	185	186	187	188	189
190	191	192	193	194	195	196	197	198
199	200	201	202	203	204	205	206	207
208	209	210	211	212	213	214	215	216
217	218	219	220	221	222	223	224	225
226	227	228	229	230	231	232	233	234
235	236	237	238	239	240	241	242	243
244	245	246	247	248	249	250	251	252
253	254	255	256	257	258	259		261
262	263	264	265	266	267	268		
271	272	273	274	275	276	277		
280	281	282	283	284	285	286		
289	290	291	292	293	294	295	296	297

Circle 999 to start a 12 month subscription at the price of \$29.97

Dr. Dobb's Journal of Software Tools

September 1986 #119	Expiration Date:	December 31, 1700
Vame	Title	
Company	Phone _	
Address	* * * *	
City/State/Zip		
Please circle one letter in e	each category:	

I. My work is performed:

- A. for in-house use only. B. for other companies.
- C. for end users/retailers. D. in none of the above areas.
- II. My primary job function:
 - A. Software Project Mgmt/Spvr B. Hardware Project Mgmt/Spvr
 - C. Computer Consultant D. Corporate Management
- E. Other
- III. My company department performs: A. software development.
 - B. computer system integration.
 - C. computer manufacturing.
 - D. computer consulting. E. computer research. F. none of the above.
- IV. This inquiry is for:
 - A. a purchase within 1 month. B. a purchase within 1 to 6 months.
 - C. product information only.

V. Corporate Purchase Authority:

- A. Final Decision-maker B. Approve/Recommend
- C. No Influence

VI. Personal Computer Users at my Jobsite:

- A. 10,000 or more
- B. 500 to 9,999
- C. 100 to 499
- D. 10 to 99 E. less than 10

VII. On average, I advise others about

- computers:
- A more than once per day.
- B. once per day.
- C. once per week D. less than once per week

VIII. In my job function, I:

- A. design software and/or write code.
 B. design software.
- C. write code.
- D. don't design software or write code.

Product Information

Free!

```
mov
                 al, byte ptr es:[18h + 19]
         xor
                 ah, ah
         mov
                 hold handle, ax
         mov
                 byte ptr es: [18h + 19], Offh
         mov
                 ah, 3ch
         mov
                 dx, dsn
         mov
                    attr
         int
                 21h
                 hcreate_error
         jc
         mov
                bx, ax
al, byte ptr es:[bx + 18h]
         mov
         xor
                 ah, ah
                 byte ptr es:[bx + 18h], Offh
         mov
                 hcreate done
         gmt
 hcreate_error:
        mov
                 ax, Offffh
 hcreate done:
        push
                 ax, hold handle
        mov
                 byte ptr es:[18h + 19], al
        DOD
 hcreate exit:
        mov
                 sp, bp
        pop
                 bp
        pop
                 es
hcreate endo
 ;;;
 ;;;
         hopen (dsn, mode)
                        *dsn;
 :::
        unsigned char
                                 /* Data Set Name
                                                                        ;;;
 ;;;
                        mode;
                                 /* DOS open mode
                                                                        ;;;
;;;
        hold handle = psp handle[19]
psp handle[19] = FF
call dos to open file
                                                                        ;;;
 ;;;
                                                                        ;;;
        if error
 :::
                retval = -1
 ;;;
        else
                                                                        ;;;
                retval = psp_handle[dos_handle]
psp_handle[dos_handle] = FF
;;;
;;;
                                                                        ;;;
                                                                        ;;;
;;;
        psp_handle[19] = hold_handle
                                                                        ;;;
        return (retval) - real dos handle
hopen
        proc
        public
                hopen
        push
                es
        push
                bp
        mov
dsn
            equ [bp + 6]
                [bp + 8]
            equ
hold_handle equ [bp - 2]
        mov
                ah. 62h
        int
                21h
        mov
                es, bx
        mov
                al, byte ptr es:[18h + 19]
                   ah
        xor
                hold handle, ax
        mov
        mov
                byte ptr es: [18h + 19], Offh
        mov
                ax, mode
        mov
                ah, 3dh
        mov
                dx, dsn
        int
                21h
                hopen_error
        to
        mov
                bx, ax
        mov
                al, byte ptr es:[bx + 18h]
       xor
                ah, ah
        mov
                byte ptr es: [bx + 18h], Offh
        Jmp
                hopen_done
hopen error:
                ax, Offffh
       mov
hopen done:
       push
       mov
                ax, hold_handle
       mov
                byte ptr es:[18h + 19], al
       pop
hopen_exit:
```

(continued on next page)



Performance beyond BASICA.

- Quickly compiles BASICA Interpreter programs into native code.
- Can compile entirely in memory for even faster compilation. New!
- Programs execute up to ten times faster.
- Can call high speed assembly routines.
- Network file sharing with record locking. Graphics (incl. EGA), sound and music.
- Numeric arrays, each up to 64K bytes, can use up to available memory. New!
- Programs can be distributed without source and runtime fees.

Complete development environment.

- Built-in editor and debugger to write programs and locate and fix errors. New!
- Execution tracing at source level. New!
- Menu-driven interface that supports either keyboard or optional mouse. New!

Structured & modular programs.

- Update and maintain programs effortlessly.
- Multi-line IF/THEN/ELSE statements.
- Alphanumeric labels line labels are optional — for easy to read programs.
- Subprograms that use local and global variables.
- Programs use up to available memory by compiling and linking individual modules.
- Includes a library of routines to access DOS and BIOS interrupts. New! Send one dollar and we'll send you a Microsoft QuickBASIC demonstration diskette.

US 800-336-1166

CANADA 800-225-1166 Ohio & Overseas 216-877-3781

programmer's connection 136 SUNNYSIDE ST. HARTVILLE, OHIO

Circle no. 86 on reader service card.

16-BIT

Listing TWO (Listing continued, text begins on page 108.)

```
sp, bp
bp
es
       mov
       pop
hopen
       endo
;;;
       hclose (handle)
                                     /* File handle from hopen */
                      handle;
                                                                   ;;;
       int
                                                                   ;;;
;;;
;;;
;;;
;;;
                                                                   ;;;
       hold handle = psp handle[19]
psp_handle[19] = handle
                                                                   ;;;
       call dos to close handle
                                                                   ;;;
;;;
       if error
               retval = -1
                                                                   ;;;
               retval = 0
;;;
       psp_handle[19] = hold_handle
                                                                    ;;;
;;;
        return (retval)
hclose proc
        public hclose
        push
               es
        push
mov
               bp
               bp, sp
sp, 2
        sub
               sp,
handle equ [bp + 6]
hold_handle equ [bp - 2]
               ah, 62h
21h
        int
               es, bx
        mov
               al, byte ptr es:[18h + 19]
        mov
               ah, ah
hold handle, ax
ax, handle
        xor
        mov
        mov
               byte ptr es:[18h + 19], al
bx, 19
ah, 3eh
        mov
        mov
        mov
         int
                hclose_error
         jc
        xor
                hclose_done
         qmt
 hclose_error:
                ax, Offffh
        mov
 hclose_done:
         push
                ax
                ax, hold_handle
         mov
                byte ptr es:[18h + 19], al
         mov
         DOD
 hclose_exit:
                sp, bp
         mov
         pop
                bp
es
         pop
  hclose endp
  ;;;
         hget (handle, ioarea, len)
int handle;
unsigned char *ioarea;
  ;;;
                                       /* File handle from hopen */
                                       /* Input Buffer */
/* Number of bytes to read */
                                                                     ;;;
  ;;;
         unsigned char
                                                                     ;;;
         hold handle = psp handle[19]
psp_handle[19] = handle
  ;;;
                                                                     ;;;
  ;;;
          call dos to read file
                                                                     ;;;
         if error
                 retval = -1
  ;;;
                 retval = number of bytes read
  ;;;
          psp_handle[19] = hold_handle
                                                                      ;;;
          return (retval)
```

```
hget
         public
                haet
         push
         push
                 bo
         mov
                 bp, sp
         sub
                 sp,
 handle
              equ [bp
get_area
get_len
             equ
                 [bp + 8]
[bp + 10]
             eau
 hold handle equ [bp - 2]
                 ah. 62h
         mov
         int
                 21h
         mov
                 es. bx
         mov
                 al, byte ptr es:[18h + 19]
         xor
                 ah, ah
         mov
                 hold handle, ax
         mov
                 ax, handle
         mov
                 byte ptr es: [18h + 19], al
                 dx, get_area cx, get_len bx, 19
         mov
         mov
         mov
                 ah, 3fh
21h
         mov
         int
         to
                 hget_error
         amt
                 hget done
hget error:
                 ax, Offffh
        mov
hget done:
        push
        mov
                 ax, hold_handle
        mov
                 byte ptr es: [18h + 19], al
        pop
hget exit:
        mov
                 sp, bp
        pop
        DOD
hget
        endp
;;;
        hput (handle, ioarea, len)
;;;
                         handle;
                                          /* File handle from hopen
                                                                            ;;;
        unsigned char
                         *ioarea;
                                          /* Output buffer
;;;
                         len:
                                          /* Number of bytes to write*/
;;;
        hold handle = psp handle[19]
psp handle[19] = handle
;;;
        call dos to write file
;;;
        if error
                                                                            ;;;
                 retval = -1
;;;
        else
                                                                           ;;;
                retval = number of bytes written
                                                                            :::
;;;
        psp_handle[19] = hold_handle
                                                                           ;;;
        return (retval)
                                                                           ;;;
hput
        proc
        public
                hout
        push
        push
                gd
        mov
                bp, sp
sp, 2
handle
            equ [bp + 6]
put_area equ [bp + 8]
put_len equ [bp + 10]
hold_handle equ [bp - 2]
                ah. 62h
        int
                21h
        mov
                es, bx
        mov
                al, byte ptr es:[18h + 19]
        xor
                    ah
                hold handle, ax
        mov
        mov
                 ax, handle
                byte ptr es:[18h + 19], al
dx, put_area
        mov
        mov
                cx, put len
bx, 19
        mov
        mov
                ah, 40h
        mov
        int
                21h
                hput error
        jc
        qmt
```

(continued on next page)



The professional C compiler.

- Library routines implement most of UNIX System V and proposed ANSI C libraries.
- Implements register variables.
- Generates very fast and optimized code.
- Five memory models with new huge and compact.
- Mixed models using near, far and huge pointers
- Support for huge programs up to one MB.
- Separate module compilation.
- Math coprocessor and emulation support.
- IEEE single- and double-precision reals.
- Network file sharing with record locking.
- Support for pathnames and I/O redirection. Support for mixed language programming.
- Source and object compatible with XENIX.
- Support for huge arrays (>64K)
- Start-up source helps create ROMable
- code.
- Microsoft Windows support.
- Includes LINK, LIB, MAKE, EXEPACK. EXEMOD.

CodeView source-level debugger.

- Multi-window display.
- Debug using source code, disassembly or both intermingled.
- Can display values of local and global variables and expressions as you debug.
- Set conditional breakpoints on variables or memory, trace and single step.
- Displays CPU registers and flags.
- Easily debug graphics-oriented programs
- Accepts familiar SYMDEB or DEBUG commands
- On-line help and drop-down menus.
- Keyboard or optional mouse support.

Send one dollar and we'll send you a Microsoft C/CodeView demonstration diskette

US 800-336-1166 CANADA 800-225-1166 Ohio & Overseas 216-877-3781

programmer's connection 136 SUNNYSIDE ST. HARTVILLE, OHIO 44632

Circle no. 98 on reader service card.

16-BIT

Listing TWO (Listing continued, text begins on page 108.)

```
hput error:
                  ax, Offffh
         mov
hput done:
         push
                  ax ax, hold handle
         mov
                  byte ptr es:[18h + 19], al
         mov
         pop
hput exit:
         mov
                  sp, bp
                  bp
es
         DOD
         pop
         ret
hput
;;;
         long int hseek (handle, rba, method)
;;;
                                              /* File handle from hopen
/* Relative Byte address
                            handle;
;;;
                                                                                    ;;;
;;;
         long int
                            rba:
                            method;
                                               /* Seek method
;;;
         int
         hold handle = psp handle[19]
psp_handle[19] = handle
                                                                                    ;;;
;;;
;;;
;;;
          call dos to seek to rba
                                                                                    ;;;
;;;
         if error
                   retval = -1
                                                                                     ;;;
                  retval = seek address
;;;
                                                                                     ;;;
                                                                                    ;;;
;;;
          psp_handle[19] = hold_handle
return (retval)
;;;
;;;
hseek
          proc
          public hseek
          push
                   es
          push
                   bp
          mov
                   bp, sp
sp, 2
 handle equ [bp + 6]
rba_low equ [bp + 8]
rba_high equ [bp + 10]
seek method equ [bp + 12]
hold_handle equ [bp - 2]
 handle
                    ah, 62h
          mov
           int
                    21h
          mov
                    es, bx
                    al, byte ptr es: [18h + 19]
           mov
           xor
                    ah, ah
hold handle, ax
           mov
                    noid handle, ax
ax, handle
byte ptr es:[18h + 19], al
dx, rba_low
cx, rba_high
ax, seek_method
ah, 42h
bx, 19
           mov
           mov
           mov
           mov
           mov
           mov
           mov
           int
                    21h
                     hseek error
           jc
jmp
                    hseek_done
  hseek error:
                     ax, Offffh
                     dx, ax
           mov
  hseek done:
           push
                     ax
                     ax, hold handle
byte ptr es:[18h + 19], al
           mov
           pop
  hseek exit:
           mov
                     sp, bp
                     bp
es
           pop
            pop
            ret
  hseek
            endp
            include epilogue.h
```

End Listing Two

Listing Three

```
Listing Three
#include <stdio.h>
#define MAXF 256
                   scs, sss, sds, ses; } sreg; ax, bx, cx, dx, si, di, ds, es; }
struct
          { int
struct { int
                                                                dreg;
main (argc, argv)
int
                    argc;
unsigned char
                    *argv;
          int
                    fid[MAXF]:
          int
          int
                    j;
          int
                   c;
          long
                   1:
                   lastfile;
          int
         char
                   dsn[30];
         char
                   line[80];
         long int
                             hseek();
         segread(&sreg);
dreg.ax = 0x6200;
sysint21(&dreg, &dreg);
         printf("\nCreate files");
         c = hcreate(dsn, 0);
fid[i] = c;
printf("\nCreate dsn = %s, handle = %3d", dsn, c);
                   if (c == -1) {
                            break
         lastfile = i;
         printf("\n");
         printf("\nWrite files");
         for (i = 0; i < lastfile; i++ ) {
             printf("\nWriting file number %02d", i);
             for(j = 0; j < 10; j++ ) {
    sprintf(line, "out file no %03d line no %02d\n\r", i, j);
    c = hput(fid[i], line, 28);</pre>
        printf("\nClose files");
        for (i = 0; i < lastfile; i++ ) {
                 c = hclose(fid[i]);
printf("\nreturn from close %3d = %3d", i, c);
       printf("\nOpen files");
       for (1 = 0; 1 < lastfile; 1++ )
                 sprintf(dsn, "\\test\\bt%d.dat", i);
                 c = hopen(dsn, 0);
fid[i] = c;
                 printf("\nOpen dsn = %s, handle = %3d", dsn, c);
      printf("\nRead files");
      for (i = 0; i < lastfile; i++ ) {
    l = 28 * (i % 10);
    l = hseek(fid[i], 1, 0);
    c = hget(fid[i], line, 28);
    line[26] = 0;
    printf("\nseek return = %3D, get return = %3d, line = %s", 1, c, line);</pre>
      printf("\nClose files");
      printf("\nreturn from close %3d = %3d", i, c);
```

End Listings



List Price \$150 Our Price \$99

World's fastest MS-DOS assembler.

- 3 times faster than prior release.
- 100% compatible with IBM macro assembler.
- Relaxed typing of statements
- Supports 8088, 80186, 80286, 8087, and 80287 opcodes and pseudo opcodes.
- Optional case sensitivity.
- Macros.
- Conditional assembly.
- Linkable with Microsoft BASIC, C, COBOL, FORTRAN and Pascal programs.

SYMDEB symbolic debugger.

- Supports source level debugging of Microsoft C, FORTRAN and Pascal programs.
- Screen swapping for visual applications.
- Disassemble, display, trace, single-step and set tracepoints.
- Display and modify variables by name.
- I/O redirection.
- Shell escapes for executing DOS commands

Plus these other useful utilities.

- LINK object code overlay linker.
- LIB library manager.
- CREF cross-reference utility
- MAKE program maintenance utility.
- EXEPACK file compression utility.
- EXEMOD file header utility.

Please refer to our main ad for more information.

US 800-336-1166 CANADA 800-225-1166 Ohio & Overseas 216-877-3781

programmer's connection

136 SUNNYSIDE ST. HARTVILLE, OHIO 44632

Circle no. 103 on reader service card.

RIGHT TO ASSEMBLE

Listing One (Text begins on page 114.)

```
* Author: Jan W. Steinman, 2002 Parkside Ct., West Linn, OR 97068.
                               The Worm memory test has three parts. Init sets up the registers for the
                              Worm. The Display Manager interacts with the Worm each pass and periodically Displays the Worm's progress. The Worm itself Worms itself through memory, from high to low, checking memory against a copy of itself. The Droppings form a pattern through memory when the test is complete.
                                                                                                           System dependent code
                               This version runs on the Tektronix 4404 under Uniflex.
                               is mostly segregated to the Init, Display, Disable and Enable routines. instructions in the Worm routine are system dependent, for enabling and
                               disabling interrupts.
                               Register usage:
                                    DO
                                                 scratch register.
                                                 scratch register.
                                    D1
                                                 scratch register.
                                    D2
                                    D3
                                                 scratch register.
                                                  address mask for determining if time to show progress.
                                    D5
                                                 base of memory area under test.
length of Worm in long words.
                                     D<sub>6</sub>
                                                  scratch register.
                                                  scratch register.
                                     A1
                                                  scratch register.
                                     A2
                                                  pointer to Display manager for position independent access. pointer to permanent Worm image for comparison. pointer to crawling Worm image.
                                     A3
                                     A4
                                     A5
                                     A6
                                     A7
                                                  stack pointer.
                             * These included files contain system definitions and interrupt (signal) * numbers for the Uniflex operating system. Don't bother to list these.
                                                                        (This makes all labels global for debug.)
                                         DEFINE
                              * Set D_MASK with the bits that are zero at each progress report.
                                                                       Report each boundary passed.
                                                    $00003FC
                                         EQU
         0000 03FC
                             D MASK
                                                                       Relocation is four bytes at a time.
                             REL_SIZ
MEM SIZ
         0000 0004
                                         EQU
                                                    $2000*REL SIZ Test a 32K chunk.

Trap number for Disable routine.

Trap number for Enable routine.
                                         EQU
         0000 8000
         0000 0002
                              DISABLE
                                         EQU
         0000 0003
                             ENABLE
                                         EQU
EQU
                                                                        Carriage return.
         0000 0000
                              CR
                                                                       Line feed.
                                                    $0A
         0000 000A
                              * Uniflex will not allow intersection math, so put all the code in the DATA
                              * section, and don't use TEXT or BSS at all!
                                                                       Assemble into writable data section.
000000
                                          DATA
                             MemBea
         0000 0000
                                         EOU
                              **** hexadecimalize
                              * hexadecimalize converts a long word to eight ASCII hexadecimal characters.
* This routine is machine and OS independent. It uses a simple table look-up
                                to generate the hexadecimal string.
                                                   d0 -- Long word to be converted to hex. a0 -- Pointer to buffer where hex characters will go.
                                      Entry:
                                                   d2 -- -1. (Just in case someone cares!)
d0 -- unchanged.
                                      Exit:
                                                   -8(a0) -- points to eight ASCII characters.
                                                   d3 -- nybble mask: constant $0F.
                                      Uses:
                                                   d2 -- nybble counter.
                                                   dl -- current nybble to convert is LSN.
                                                      '0123456789ABCDEF' Where we keep our hex characters.
 000000 3031 3233 3435 CharTab DC.B
                              hexadecimalize
                                                                        Bytes to make - 1.
 000010 7407
                                          move.1
                                                                        Nybble mask.

Shift the next nybble into the LSN,

make a copy for masking,

mask out all but least significant nybble,
                                                     #$0F,d3
#4,d0
 000012 760F
                                          move.1
 000014 E998
000016 2200
                              HexLoop rol.1
                                          move.1
                                                       d0, d1
                                          and.1
                                                       d3, d1
 000018 C283
                                                                              index into char table and store result.
                                                       CharTab(pc,dl), (a0)+
d2, HexLoop Repeat until done, and when done,
hit the road, Jack. -->
 00001A 10FB 10E4
00001E 51CA FFF4
                                          move.b
                                           dbra
 000022 4E75
                                           rts
                               **** Manager
                               * Manager checks the Worm's progress, and periodically reports to the Display.

* This routine is also entered if an error is encountered.
                                                   d0 -- W LONGS complement of pass count if error, else -1.
                                                    al -- test address pass/fail value.
                                                   via direct jump to Worm at (A5).
```

```
Uses:
                                            d3, d2, d1, d0, a7, a1, a0
                                 Stack:
                                            one level, plus needs of Display.
000024 0D57 6F72 6D20 ErrMsg
                                    DC.B
                                             CR, 'Worm reports memory error at '
                         ErrAddrMsg
DC.B
000042 3030 3030 3030
                                              '00000000 on pass '
000053
                         ErrCountMsg
DC.B
        3030 3030 3030
000053
                                              '00000000.',CR
        0000 0039
                                             *-ErrMsg
CR,'Worm tested memory from
                            SIZ
                                    EOU
00005D 0D57 6F72 6D20 DoneMsg
                                    DC.B
000076
                          DoneBegAddrMsg
000076 3030 3030 3030
                                    DC B
                                              '00000000 through '
                          DoneEndAddrMso
000087
        3030 3030 3030
                                    DC.B
                                              '00000000 successfully.', CR
        0000 0041
                          D SIZ
                                    EOU
00009E 3030 3030 3030 ProgMsg
                                    DC.B
                                              '00000000', CR
        0000 0009
                          P_SIZ
                                    EQU
                                              *-ProgMsg
0000A8 00
                                    EVEN
                                                              (Stay on legal instruction boundary.) Was loop exited by error, or countdown?
0000A8 4A40
                                    tst.w
                          Manager
                                              dO
0000AA 6A30
                                             GetErrMsg
                                    bol.s
                                                                  Error, go report it.
0000AC BC8D
0000AE 6708
                                    cmp.1
                                              a5.d6
                                                                  Countdown, so are we done yet?
Yes. Go finish up. -----
                                    beg.s
                                             GetDoneMsg
0000B0
        200D
                                    move.1
                                              a5, d0
                                                                    No, put the new source where we can
0000B2 C085
                                    and.1
                                              d5, d0
                                                                      look at the bottom bits: on boundary?
0000B4 674A
                                    beq.s
                                              Report
                                                                         Yes, set up for progress report.
0000B6 4ED5
                                    amt
                                                                              Keep on Crawlin'...
                                                                         No.
                                                                Finish up.
                                                                            Get the pointer to start addr.
0000B8 41Fa FFBC
                          GetDoneMsg lea
                                              DoneBegAddrMsg (pc), a0
0000BC 2009
                                    move.1
                                              a1.d0
                                                                 and the value to plug in, which gets converted, likewise, get
0000BE 6100 FF50
                                    bsr
                                             hexadecimalize
0000C2 41FA FFC3
                                    lea
                                              DoneEndAddrMsg (pc), a0
0000C6 203C 0000
0000CC 6100 FF42
                                             #MEM_SIZ,d0
hexadecimalize
                                    move.1
                                                                 the end address and its value,
                                              nexadecimalize also converted to hexAscii.

DoneMsg (pc), a0 Get pointer to complete done message,
0000D0 41FA FF8B
                                    lea
0000D4 7641
                                    move.1
                                             #D SIZ,d3
                                                                 length of the done message,
0000D6 487A 0050
                                              Exit (pc)
                                                                 push a return pointer,
                                    pea
0000DA 6034
                                    bra.s
                                             Display
                                                                 and go display the message.
                                                             Make an error report.
                                                                                          Get message ptr.
0000DC 41FA FF75
                         GetErrMsg lea
                                              ErrCountMsg (pc), a0
0000E0 0400 0007
                                    sub.b
                                                                 convert worm count to a pass count,
                                             #W LONGS-1, dO
0000E4 6100 FF2A
                                             hexadecimalize
                                                                 make it hex for Display.
                                                             Get addr of ASCII error addr,
0000E8 41FA FF58
                                              ErrAddrMsg (pc), a0
                                    lea
                                                                                                                   11
```

(continued on next page)



THE C JOURNAL

Trademarks – IBM PC: IBM Corp.; UNIX: AT&T Bell Labs; Macintosh: Apple Computer Corp.;
CP/M: Digital Research Inc.; The C Journal: InfoPro Systems.

Circle no. 194 on reader service card.

Up To Your Ears In Alligators?

If that sounds familiar, you need Write-Hand-Man™, the multifunction pop-up desktop organizer that works neatly with existing software for CP/M™ 2.2 and 3.0 systems. Write-Hand-Man eliminates that swamped feeling with tools that will get you organized. Write-Hand-Man comes with a 4-function, floating-point, 14 digit Calculator – Notepad – Two-week Appointment

Book, File and Directory viewing – Phonebook with dialing – Cut and Paste – Key Redefinition – ASC II table. Even add your own applications.

> Clear the swamp from your desktop. Order Write-Hand-Man today. \$49.95

CA residents add 6.5% tax. Sorry, no credit cards or purchase orders. Specify: 8" or which 5" format CP/M 2.2 or 3.0 format

30 day guarantee

™ Write-Hand-Man – Poor Person Software ™ CP/M – Digital Research Poor Person Software

Dept. 203 3721 Starr King Circle Palo Alto, CA 94306 (415) 493-3735

Circle no. 169 on reader service card.

RIGHT TO ASSEMBLE

Listing One (Listing continued, text begins on page 114.)

```
get bad long addr to display,
less four to account for postincrement,
                                             move.1 #-4,d0
 0000EE D089
                                             add.1
                                                          a1,d0
                                                              Mon Mar 24 02:15:36 1986 page 4
The Worm Memory Test
 0000F0 6100 FF1E
0000F4 41FA FF2E
0000F8 7639
                                                         hexadecimalize
                                                                                  make it hex for Display. <-->
                                             bsr
                                                                                 Get pointer to whole err msg,
the size for the write,
                                                          ErrMsg (pc), a0
                                              lea
                                              move.1
                                                         #E SIZ,d3
                                                                                  push a return pointer,
 0000FA 487A 002C
                                              pea
                                                          Exit (pc)
                                                                                  and Display the message.
                                                        Display
 0000FF 6010
                                              bra.s
                                                                               Progress report. Get message ptr,
 000100 41FA FF9C
                                 Report
                                             lea
                                                          ProgMsg (pc), a0
                                                                                  load the checked address,
 000104 200D
                                              move.1
                                                          a5, d0
                                                         hexadecimalize
                                                                                  make it hex for Display. <-->
 000106 6100 FF08
                                              bsr
                                              sub-1
                                                          #8,a0
                                                                               Regain pointer to the message,
 00010A 5188
00010C 7609
                                                                                  get the size for the write,
                                                         #P SIZ,d3
                                              move.1
                                                                                   push a return ptr to the new Worm,
 00010E 4855
                                              pea
                                                           (a5)
                                                                                  and drop through into Display.
                                                      **************
                                 **** Display
                                 Display is an implementation-dependent scheme for reporting the Worm's progress. Upon entry, AO contains a pointer to a string to Display, and D3 contains the length of the string to Display.
                                                       d3 -- number of bytes to display.
                                                       a0 -- address of a string to display.
                                                       d0 -- file descriptor of stdout.
                                          Uses:
                                                       al -- scratch register for pointing to SysCall param block.
                                                       as needed by system call.
                                          Stack:
                                 000110 2F03
  000112 2F08
  000114 3F3C 000D
  000118 204F
  00011A 7001
                                                                                   and write the message. <-->
 X00011C 0000 0001
                                              SYS
                                                          indx
                                                                              Remove the params from the stack, and return somewhere. -->
                                                         #10,a7
                                              add.1
  000120 DFFC 0000 000A
  000126 4E75
                                              rts
                                  * For lack of a better place to put it, the system- dependent exit code is here.
                                  _alt SYS
                                               SYS term Terminate this program. (System dependent.) E N D S Y S T E M - D E P E N D E N T C O D E ********
 X000128 0000 0005
                                   **** Disable, Enable
                                   * These routines provide the exclusion mechanism for the non-interruptible code
* in Worm at Crawl. These routines must execute in supervisor state, therefore
                                     they are executed via the TRAP exception instruction. Enable requires that
                                   * D1 be preserved from the preceding Disable.
                                                         SR -- interrupt mask is raised and lowered.
d2 -- scratch register for restoring original interrupt mask.
d1 -- scratch register storage place for old interrupt mask.
                                                                   SYSTEM-DEPENDENT
O Grab the status register,
                                                                                                                   CODE
                                   ******** BEGIN SY
Disable move sr,10
and.w #$0300,d1
   00012C 40F9 0000 000A Disable move
                                                                                    keep only the interrupt bits,
   000132 0241 0300
                                                                                     and disable all interrupts
                                                           #$0300,sr
                                                and
   000136 027C 0300
  +00013A 0000 0008 0000
                                                           cpint, SIGTRAP2, Disable <-->
                                                SYS
                                                                                     before entering critical code region. -->
   000146 4E77
                                                                               Regain the status register,
reset the previous interrupt level,
and enable the proper interrupts
                                                           sr,d2
                                   Enable move
   000148 4002
  000146 40C2
00014A 8441
00014C 46C2
+00014E 0000 0008 0000
                                                           d1, d2
                                                or.W
                                                move
                                                           d2.sr
                                                           cpint, SIGTRAP3, Enable <-->
                                                SYS
                                                 tr before exiting critical code region. -->
END SYSTEM-DEPENDENT CODE *********
                                   ****** P
   00015A 4E77
                                   * Worm is a self-modifying, self-relocating procedure which starts at some * location in high memory and works its way down to its end address,
                                      periodically reporting its progress.
                                      The loop at Crawl depends strongly on the 68000 prefetch mechanism. This
                                   * loop will not work on a 68020 machine (which has a 64 entry cache), nor on * most simulators (which often do not bother to simulate prefetch accurately). * This loop will also not work with the TRACE bit set, and must be protected * from all interrupts, including page faults in virtual memory systems.
                                    * When this loop moves the DBNE long word at Crawl+4, it overlays the MOVE.L * and the CMPM.L at Crawl. The CMPM.L is in the prefetch queue, so it gets * executed even though its memory image has just been clobbered. The DBNE is * fetched, and its execution flushes the prefetch queue as is the case with all * branches. Execution continues with the copy of the DBNE just moved, which * executes again, branching to Crawl-4, the new loop location. Note that the
```

```
loop count gets decremented twice in this scenario, removing the need for the
                                     usual predecrement before entering the loop.
                                                         d7 -- length of Worm in long words.
d6 -- base of memory area to test.
d5 -- address mask for display boundary.
                                           Entry:
                                                         a5 -- first long word address of Worm at present.
a4 -- first long word address of Worm's original image.
                                                             -- display manager's address.
                                                         d0 — \underline{W} LONGS complement of pass count if error. a5 — entry value less relocation, i.e.: next pass entry value. a1 — address pass/fail report value.
                                           Exit:
                                           Uses:
                                                         d0 -- decrementing Worm length.
                                                         a2 -- incrementing COMPARE address.
a1 -- incrementing TO address.
                                                         a0 -- incrementing FROM address.
                                          Unused:
                                                        d4, d3, a7, a6.
00015C 3007
00015E 204D
000160 244C
                                  Worm
                                               move.w
                                                             d7, d0
                                                                                Restore the Worm's length,
                                                 ove.l a4,a2 its starting point,
ove.l a4,a2 and its original address.
ea -4(a5),a1 Get the destination for this pass.
BEGIN SYSTEM-DEPENDENT CODE *******
END SYSTEM-DEPENDENT CODE ********
END SYSTEM-DEPENDENT CODE ********
ove.l (a0)+, (a1) Move a long word piece of Worm, <------+
                                               move.1
                                               move.1
000162 43ED FFFC
                                               lea
000166 4E42
                                              trap
E N D
                                                             (a0)+, (a1)
(a1)+, (a2)+
000168 2298
                                 Crawl
                                               move. 1
00016A B589
00016C 56C8 FFFA
                                               cmp.1
                                                                                     and check it against the original,
                                               dbne
                                                            d0, Crawl
                                                                  BEGIN
                                                          #ENABLE
000170 4E43
                                              trap
                                                          #ENABLE Allow interrupts -- critical section over. <-->
SYSTEM - DEPENDENT CODE ********
#REL_SIZ,a5 Update the new Worm address,
                                                 END
000172 598D
                                              sub.1
000174 4E71
000176 4ED3
                                               nop
                                                                                     keep the whole thing on long boundary,
                                               amt
                                                             (a3)
                                                                                     report to the Manager. -->
                                 * The following pattern (which is notoriously hard on 16-bit dynamic RAM
                                    memories) gets left in memory and can be checked later if desired.
```

(continued on next page)

DeSmet C

now with 32-Bit Pointer Option

C88...still \$109

The editors' choice for fast compilation and execution. The price/performance winner in all major C benchmarks since 1983. Includes Compiler, Assembler, Binder, Librarian, Execution Profiler and Full Screen Editor. Supports both disk and memory resident Overlays. Contains both 8087 and Software floating point support. Full STDIO library.

Large Case Option \$50

Makes a great C Compiler even better. Adds 32-Bit Pointers to C88 so you can utilize all of your PC. Groups scalar and static data for fast access. Supports the D88 debugger.

Gain most of the benefits of an interpreter while losing none of the run-time speed of the C88 compiler. Display C source and variable contents during execution. Set breakpoints by function name or line number. Examine and set variables by name using C expressions.

order direct from:

C Ware Corporation

505 W. Olive, Suite 767, Sunnyvale, CA 94086 U.S.A. (408) 720-9696 — Telex: 358185 We accept VISA, MasterCard & American Express

FORTRAN PROGRAMMERS

Looking for the right PC FORTRAN LANGUAGE SYSTEM? If you're serious about your FORTRAN programming then you should be using F77L- LAHEY FORTRAN.

Editor's Choice - PC Magazine

- Full FORTRAN 77 Standard (F77L is not a subset)
- Popular Extensions for easy porting of minicomputer and mainframe applications
- COMPLEX * 16, LOGICAL * 1 and INTEGER* 2
- Recursion allocates local variables on the stack
- IEEE Standard Floating Point Arithmetic
- IMPLICIT NONE
- Long variable names -31 characters

- Fast Compile Increase your productivity
- Source on Line Debugger (Advanced features without recompiling)
- Arrays and Common Blocks greater than 64K
- Clear and Precise English Diagnostics
- Compatibility with Popular 3rd Party Software (i.e. Lattice C)
- Easy to use manual
- Technical Support from LCS

• NEW FEATURE - NAMELIST

F77L - THE PROGRAMMER'S FORTRAN \$477.00 U.S.

System Requirements: MS-DOS or PC-DOS, 256K, math coprocessor (8087/80287)

FOR MORE INFORMATION: (702) 831-2500



Lahey Computer Systems Inc. P.O. Box 6091 Incline Village, NV 89450/U.S.A.

International Dealers:

England: Grev Matter Ltd... Tel: (0364) 53499 Denmark: Ravenholm Computing, Tel: (02) 887249 Australia: **Computer Transitions** Tel: (03) 537-2786 Microsoftware, Inc., Tel: (03) 813-8222

SERVING THE FORTRAN COMMUNITY SINCE 1967

Circle no. 186 on reader service card.


RIGHT TO ASSEMBLE

Listing One (Listing continued, text begins on page 114.)

```
Droppings DC.L
                                                                    Pattern to be left in RAM.
                                                  S5555AAAA
000178 5555 AAAA
                                        EOU
                                                                    Length of self-relocating code, in bytes
                                                  *-Worm
                            W STZ
        0000 0020
                                                  W SIZ/4
                                                                         and longs.
        0000 0008
                            W LONGS EQU
                            **** Init
                                                ***********
                            * Init performs system-dependent initialization and sets up registers for use
                              of Worm and Manager. Init then copies the Worm into the top of test memory
                              and starts the Worm crawling.
                                                not applicable
                                    Entry:
                                                a5 -- Worm's test image address at top of memory to be tested.
a4 -- Worm's permanent image address.
                                    Exit:
                                                a3 -- Manager routine pointer.
d7 -- length of Worm in long words.
                                                 d6 -- base of memory area to test
                                                 d5 -- address mask for testing display boundary.
                                                                    This area will be overlaid with the worm.
0000 017C Ovrly
00017C 576F 726D 206D LogMsg
000190 2448 6561 6465
                                        EOU
                                                  'Worm memory tester, 'SHeader: worm.a-v 1.2 86/03/24 01:44:36 jans Exp S'
                                        DC.B
                                                   CR, 'Memory checked down to location:', CR
                                        DC.B
0001C4 0D4D 656D 6F72
         0000 006A
                            L SIZ
                                        EOU
                                                   *-LoaMsa
                                        EVEN
0001E6 00
                                        GLOBAL Init
                             Init
0001E6
                             * First, perform some system-dependent initialization: set up the TRAPs needed
                               to protect the Worm from interrupts, protect the area to be tested from page
                             * faults, and write a welcome message.
                                                   IN SYSTEM-DEPENDENT CODE
cpint,SIGTRAP2,Disable Set up the exception
cpint,SIGTRAP3,Enable interrupt exclusion
                                           BEGIN
                                                                                     Set up the exception handlers for the interrupt exclusion routines.
Protect memory image from page faults.
                                        SYS
+0001E6 0000 0008 0000
                                         SYS
+0001F2 0000 0008 0000
                                                   memman, 1, MemBeg, MemEnd
                                         SYS
+0001FE 0000 0039 0000
                                                                                      Prepare and write a stdout
 00020E 7001
                                         move.1
                                                   #1,d0
                                          SYS write, LogMsg, L SIZ welco
E N D S Y S T E M - D E P E N D E N T
                             ******* SYS
                                                                                         welcome message.
+000210 0000 000D 0000
                                                                                                 CODE
                                Next, set up registers that will be used by the Worm and Manager.
                                                     D MASK,d5 Get the Display address boundary mask.

Ovrly(pc),a0 Load the lowest address to test
a0,d6 into a data register for comparison,
Manager(pc),a3 get the Display Manager's address,
the Manager saddress
                                                   #D MASK, d5
                                         move.1
 00021C 2A3C 0000 03FC
                                         lea
 000222 41FA FF58
 000226 2C08
                                         move.1
000226 2C08
000228 47FA FE7E
00022C 49FA FF2E
+000230 2A7C 0000 7FE0
000236 3E3C 0008
                                         lea
                                                                          the Worm's non-crawling image address,
                                                    Worm(pc), a4 the Worm's non-crawling image address and the high-mem Worm start address.
                                          lea
                                         move.1
                                                                     Get the Worm's length in longs.
                                         move.w #W LONGS, d7
                              * Finally, move the Worm to the top of memory to be tested.
                                                                      Get a copy of Worm's permanent image pointer,
its test image pointer,
and its length in longs.
                                                     a4, a0
 00023A 204C
                                          move.1
                                                     a5, a1
                                          move. !
  00023C 224D
                                                     d7, d0
                                          move.w
 00023E 3007
                                                    #1,d0
                                          sub.w
 000240 5340
                                                     (a0), (a1)
(a0)+, (a1)+
                                                                         Move, and compare <-
  000242 2290
                              MoveWorm move.1
                                                                           a long word of the Worm
                                          cmp.1
  000244 B388
                                                                           at a time.
  000246 56C8 FFFA
                                          dbne
                                                      d0, MoveWorm
                                                                      Exit loop by error, or countdown?
Error, go Report it. -->
Countdown. Start Crawling! -->
                                                      do
                                          tst.w
 00024A 4A40
00024C 6A00 FE5A
                                          bpl
                                                    Manager
                                          jmp
EQU
  000250 4ED5
                                                      (a5)
                                                     *-MemBeg
           0000 0252
                              C SIZ
                                                                       (Size of non-relocating code.)
                                                    MEM_SIZ-C_SIZ
  000252 0000 0000 0000
                                          DS.B
                              MemEnd
           0000 8000
                                          FOU
                                          ENDDEF
                                                                       (Set transfer address to the Init.)
                                                     Init
           0000 01E6
                                          END
 0 Errors detected.
 SEGMENT SIZES
TEXT SEGMENT = 000000
DATA SEGMENT = 008000
BSS SEGMENT = 000000
```

End Listing



catch

It's becoming an epidemic . . . everyone is switching to C! First there were a few hackers, then came the college students, next the major software houses, and now the rest of the programming world. Programmers everywhere are infected with the desire for SPEED, POWER, and PORTABILITY. It's time to face the inevitable. You're going to catch the fever too! When you do, give us a call. We've got the best cure — an illustrated guide to the C language, plus a complete program development system. Everything you need to master the C programming language.

to master the C programming language ... all at a price that's less than the cost of a book!

But don't let this price fool you. Our system is powerful; it compiles twice as fast as the others, is completely standard, and it's very easy to use. Most C compilers are designed for wizards. We have designed ours for you!

that supports all data types and the latest features like bit fields, enumerations, structure assignment, and passing/returning structures.

that loads separately compiled files, searches libraries, and builds an executable program.

(including the standard C functions and the computer specific functions that provide direct access to the operating system and BIOS).

your programs for minimal space or maximum speed.

Incredible Value

Money-Back Guarantee

Operators are standing by . . . Please use this Number for ORDERS ONLY!

For Technical Support Please call 1-214-783-6001

MIX Software, Inc. / 2116 E. Arapaho / Suite 363 / Richardson, Texas 75081

Or contact our Worldwide Distributors direct in:

Canada: Saraguay Software 1-416-923-1500 Switzerland: DMB Communication CH-1-825-53-29 Australia: Techflow 047-586924 France: Info/Tech 1-43-44-06-48

Split Screen Text Editor

Our high powered

editor is great for editing high level languages. It works just like Micropro's Wordstar, but macros allow you to create your own custom editor, and the split-screen feature lets you edit two files at the same time.

ONLY



The MSDOS/PCDOS version is loaded with special features:

- Execute any DOS command or RUN other programs from the editor.
- Quickly edit files as large as 300,000 characters
- Compile MIX C programs directly from memory. The editor automatically positions the cursor to the first error in your



Call assembly language routines MOX from your C programs. The ASM utility works with Microsoft's MASM or M80 assemblar Macrosoft's MASM or M80 assemblar Macrosoft's MASM or M80 assemblar Macrosoft and Macro works with Microsofts MASM or Mou assen bler. Macros make it easy! Works just as if you were calling a C function, and you can even call C functions from assembly lan-guage. Lots of useful assembly language functions are included as examples.

Buy both for an even greater Limited Time Only

ist Price!

Quantity PRICE

C Compiler & Text Editor

Total Order

Split-Screen Text Editor \$29 95 \$

C Compiler _ \$39.95 \$_ C and Text Editor (Special) _ \$54.95 \$_

Description

ASM Utility _ \$10.00 \$_

Texas Residents Add 6.125% Sales TAX Shipping Charges (See at Right)

TOTAL OF YOUR ORDER: \$

Please check method of payment:

ORDER FORM!

☐ Check☐ Money Order☐ MasterCard/VISA Your Card #:_

IN TEXAS, PLEASE

CALL TOLL FREE 1-800-622-4070

Expires _

Shipping Charges: (No charge for ASM

In the U.S.A.: Add \$5.00 per Order. In CANADA: Add \$10.00 per Order. OVERSEAS: Add \$10.00 per Text Editor. Add \$20.00 per C Compiler. Add \$30.00 for combined C Compiler and Text Editor.

Operating System: (Check one) ☐ CP/M Z80 ☐ MSDOS/PCDOS

Specify Your Computer Name ____

Specify Disk Format _____

NAME

Telephone A/C (_____)

Street

City__

State __ Country_ ZIP_

2116 East Arapaho Suite 363 Richardson, Texas, 75081

D

Ask about our Volume Discounts!

Call 1-214-783-6001

MS-DOS Books

In the May 1986 16-Bit Toolbox column, I briefly reviewed some books on MS-DOS assembly-language programming. Since I wrote that column, another interesting book has appeared:


Angermeyer, John, and Jaeger, Kevin. *MS-DOS Developer's Guide*. Indianapolis, Ind.: The Waite Group/Howard K. Sams and Co., 1986. 440 pages with index. \$24.95.

Compared to the previous published efforts on this topic, this is a remarkable book and is the first book on MS-DOS programming that I would actually characterize as being directed at advanced assembly-language programmers (that is, typical DDJ readers). Topics covered that have been neglected or ignored in nearly every other book published to date include detailed instructions on use of the advanced features of MASM (macros and conditional assembly), design and coding of memory-resident utilities and run-time libraries, memory management, installable device drivers, local-area networks, real-time programming under MS-DOS, disk-layout and file-recovery information, and the functional differences beteen MS-DOS versions.

The text of the book is well supplemented with assembly-language examples in the form of subroutines or complete working programs. The authors have included many tidbits of information and programming pearls (such as the method for removing a memory-resident program) that are obviously derived from extensive personal experience. I predict that nearly every reader of this column will find something new and useful

by Ray Duncan

in this book and that they will consider it money well invested.



The BIOS Done It

The short description of my problems with the PC/AT VDISK program in the April 1986 column drew a flurry of mail from readers. The first, and most caustic, reply came from George Scotten of Springfield, Vermont. Mr. Scotten wrote: "Ray Duncan's column is a classic case of RYFM (read your fact-filled manual)! . . . Although he claims that he and his coworkers spent a lot of time poring over the IBM tech ref manual, the time might have been better spent reading it.... Interrupts 0f1-0ffh are listed as reserved interrupts, and anyone using a reserved interrupt deserves what they get.... It only took this amateur 30 seconds to resolve his problem...."

Well, this letter from Mr. Scotten rattled me for a few minutes, I must admit. I leaped out of my chair and consulted my PC/XT and PC/AT technical reference manuals once again. No, I wasn't hallucinating: although the manuals clearly state that some interrupt ranges are "Reserved" (for example, 28h-3fh, 40h-5fh, and 80h-85h), the interrupts 0fth-0ffh are definitely tagged "Not Used" rather than "Reserved." (See PC/AT Technical Reference Manual, p. 5-6, and PC Technical Reference 2.02 Manual, p. 2-8.)

A considerably more helpful letter came from Thomas Thurston, of Intel Corp., who wrote: "... Actually, the problem is not in VDISK at all but in the PC/AT ROM BIOS function that VDISK uses to access extended memory (BIOS interrupt 15h, function 87h, pp. 5-150 to 5-155 of the PC/AT Techni-

cal Reference Manual). This BIOS function creates 80286 protected mode descriptor tables and then switches to protected mode so that it can access extended memory directly. As you noted in your column, to get out of protected mode, the BIOS sets a special value in the CMOS RAM, outputs a signal to cause a RESET, and then halts. In the power-up sequence after the RESET signal is received (pp. 5-33 to 5-35), the value from the CMOS RAM is checked. If it indicates that the RE-SET was caused by a shutdown, control is returned to the code that requested the shutdown.

"There are some side effects of going through the RESET sequence. The registers do not have the values they had before the shutdown. In particular, the stack registers (SS and SP) are lost. RESET initializes SS to 0 and leaves the value of SP undefined. The BIOS code recognizes this, but it handles it in a way that causes problems. After the power-up code recognizes that a shutdown has occurred, before transfering control back to the point that requested the shutdown, it initializes SS to 0030h and SP to 0100h (p. 5-34 and p. 5-29). This area of memory (absolute addresses 300h-400h) overlaps the end of the interrupt vector table. During system initialization, this isn't a problem. However, when the area is used as a stack during the RESET sequence to come out of protected mode, some of the entries in the interrupt vector table are trashed.

"When control is returned to the point in the BIOS code that requested the shutdown (p. 5-152), one of the first things it does is restore the user's stack (the values of SS and SP were saved previously). Before restoring SS and SP, however, the code actually does two procedure calls (which will cause two return addresses to be pushed on the stack). One of the procedures calls another procedure, which uses the stack to save the value of CX. In all, three words (6 bytes) of

stack space are used before the user stack registers are restored.

"With the Intel 8086 architecture, SP is decremented before pushing values onto the stack. Thus the last 6 bytes of the interrupt vector table are used as stack space and destroyed by this BIOS function. Each entry in the interrupt vector table uses 4 bytes. This means that the vectors for interrupts Ofeh and Offh are always lost (after a transition to protected mode and back again).

"It seems to me, however, that the problem is even more severe than this. When SS and SP are initialized by the RESET sequence (p. 5-34), the interrupts are turned off before and on again afterward. The reason for turning the interrupts off is to avoid the problem of an interrupt occurring while the stack is in an undefined state (after setting SS but before setting SP). However, it is not necessary to turn the interrupts off if SP is loaded during the very next instruction after loading SS because the 286 always inhibits interrupts until completing the next instruction after loading SS.

"In fact, turning the interrupts off and then on again causes problems because it leaves the interrupts on later, while the subsequent code (pp. 5-152 and 5-153) assumes that interrupts are off. In the first place, more than just the last entries in the interrupt vector table will be trashed if any interrupts occur before the user's stack is restored. Second, the code that restores the user's stack does not turn interrupts off when restoring SS and SP, and it executes an additional instruction after loading SS before loading SP. An interrupt at this point would trash arbitrary locations in the user's stack segment." [These might overlap and destroy locations in the user's code and data segments.—Ray]

Hans Pufal, Tom Roberts, and Bob Sharpe, among others, also sent de-

and al,0fh add al,90h daa add al,40h daa

Table 1: Pop quiz from Hans Pufal: What does this code do?

tailed explanations of the VDISK problem giving essentially the same information. Hans Pufal threw in a little conundrum for the amusement of DDJ readers (Table 1, below), and Bob Sharpe also added: "There is a block of interrupts specifically reserved for user programs (interrupts 60h-67h). The only 'problem' with using these interrupts is one of conflicting usage with other programs (for example, the Expanded Memory Manager for the Intel Above Board and other Lotus/Intel/Microsoft EMS implementations uses interrupt 67h). This need not be a problem for any application that can save the old interrupt vector, use the interrupt during execution, and finally restore the original interrupt.

"It might be noted that the original PC/AT BIOS has quite a collection of errors (for example, see the clever way the zero flag is set only a few lines later on p. 5-153 and followed by IRET). The newer 'infamous' BIOS that cripples the system to a 6-MHz clock rate includes fixes for nearly all the

BIOS problems we had located."

Microsoft Macro Assembler

In my May 1986 column, I noted a new problem that appeared in Version 4 of the Microsoft Macro Assembler such that end-of-file marks (1ah) don't seem to be recognized at the end of include files, resulting in confusing error messages if the text file was written with certain editors (such as WordStar in nondocument mode). The technical-support people at Microsoft have supplied a patch that will correct this problem (see Listing One, page 96).

With regard to another potential problem, David Gwillim of Los Angeles wrote: "If you are getting strange errors from your MASM, or strange results or even crashes from your assembled and linked programs, there is an insidious bug that may be responsible.

Versions of MASM other than the original IBM MASM 1.0 all expect to see a CR and an LF at the end of each line



Over 60 programs that perform tasks on machines like the IBM PC, XT, or AT with the ease that one would expect while working under UNIX. Designed especially for those developing software in a DOS environment, these utilities

awk — data transformation & report generation language prof — give a profile of the execution times of a command egrep — find a string using full regular expression patterns

diff — find the differences between two files cat chmod cmp comm date dd dev df du echo ed file find head help join lc line Is more mv nm od paste pwd rm sed sh size sort split strings tail time touch unia WC and more . .

The programs come with a shell and complete UNIX-style command-line file name expansion on 3 DSDD 5.25" floppies, load and run under DOS, and are not copyprotected. Phone support is available during business hours. Full documentation is

Price: \$139 from:

Mortice Kern Systems Inc.,

43 Bridgeport Rd. E., Waterloo, Ontario N2J 2J4 519-884-2251

For information or ordering call collect:

MasterCard & VISA orders accepted. OEM & dealer inquiries invited.

UNIX is a trademark of Bell Labs. MS-DOS is a trademark of Microsoft Corp.

STREAMLINE YOUR PROGRAMMING

Circle no. 249 on reader service card.

The Great

awk is now

in the MKS

Toolkit!

MULTI-TASKING!

UNO, DOS ... MULTI-DOS!



You can do this too. if you have Multi-DOS.

MultiDOS is the NEW Multi-Tasking Software that lets you run multiple programs on your PC all at the same time!

With Multi-DOS you can load all of your favorite programs (up to 32, limited by the size of individual programs and available memory) and switch from one program to another at a keystrokel

Compatible with most DOS software, including LOTUS, DBase, Wordstar, and others.

Multi-DOS

Software Professionals

there's Multi-DOS Plus. DEVELOP YOUR OWN MULTI-TASKING APPLI-CATIONS!

- inter task message communication
- suspend task for specified interval
- execute external and internal tasks lock/unlock semaphores
- change task priority (8 levels) commands for suspend, resume
- abort, etc.

 AND MORE!

Multi-DOS Plus

Specifications and Requirements:

• IBM-PC/XT (or clone) with DOS 2.0

or later operating system.

• Multi-DOS occupies 42 kb of memory (48 kb for Multi-DOS Plus) and 4 to 16 kb of memory per active task

ORDER NOW, call toll-free!

1-800-367-6707 VISA AND MASTERCARD ACCEPTED

send check or money order to:
Nanosoft,13 Westfield Rd Natick MA 01760

For Information or MA orders Call (617)651-0091 MA orders add 5% sales tax. Outside U.S.A. add \$7.95 S/H.

16-BIT (continued from page 109)

before they will recognize line termination. MASM 1.0 will work with either.

"The nonacceptance of a lone CR at the end of a line where there is a comment field (which is most lines in an ASM file) causes the next line simply to become part of the comment field of the previous line, effectively removing it from the assembler's view!

"In the case where no LFs are used at all, this will be immediately obvious, but if there are just a few CRonly lines, then you will have many strange occurrences—symbol-notdefined errors, crashes running a program that looks just fine in the source text, and so on.

"Because many text editors don't seem to care whether there is an LF accompanying each CR, the occasional omission of an LF can be hard to find. One simple way to locate these is to do a COPY FILENAME.ASM PRN, and the printer will print the lines that don't have an LF separating them on top of each other."

DOS File Handles

The discussions of the 20-handle limit in the December 1985 and May 1986 16-Bit Toolbox columns generated a great deal of interest and discussion among DDJ readers. A particularly unique work-around was contributed by Paul Adams of Shelbyville, Kentucky, who wrote: "The letter from Dan Daetwyler quoted in your December 1985 column was the first I had heard of MS-DOS' limit of 20 file handles per process. This came as an unpleasant shock to me because, like Dan, I was planning a database application that would certainly require more than 20 open files. Although, Dan's letter left the impression that this restriction is new with Version 3 of DOS, I have found that it applies to pos 2.0 as well.

"There is a way around. The clue was provided in the January 1986 PC Tech Journal. A Tech Notebook by Stan Mitchell describes the mechanism DOS uses to redirect file handles.

"A program segment prefix (PSP) contains a table of 20 bytes starting at offset 18h. When a file (or device) is opened, the handle returned by DOS is an offset into this table. The byte at

offset 18h + handle in the PSP will contain what I call the real handle. The real handle represents an entry in an internal DOS table. The default size of this table allows for eight real handles. This can be changed with the FILES command in CONFIG.SYS. If FILES = 255 is included in CONFIG.SYS, the real handle has a range of values from 0 to feh. A real handle of ffh always means the file is closed.

"The first three real handles are predefined by DOS as:

0-aux device

1-console

2-printer

"The result of this redirection is to allow child processes to inherit the open files of the parent process. The only use DOS seems able to make of this is to redirect standard input and

"By the way, as far as I can tell, a process is defined by a PSP. The currently active PSP can be determined by DOS function 62h. The only way I know to change the active PSP is to create a child process using DOS function 4bh. [See also Ross Nelson's explanation of MS-DOS process IDs in the May 86 column.—Ray)

"The way to open more than 20 files from a single process is to trick DOS into reusing one of the table entries in the PSP. I call this technique handle packing.

"To open or create a file using handle packing:

- 1. Open or create a file with the appropriate DOS handle function.
- 2. The dos_handle is the handle returned by DOS. The real_handle is the byte at offset 18h + dos_handle in the PSP. Save the real handle for use when performing I/O on the file.
- 3. Replace the byte at offset 18h+ dos_handle with ffh so the dos_handle can be reused.

"For all other file functions using handle packing:

- 1. Save the real_handle found at offset 18h + 19 so it can be restored later. (18h + 19), the last handle in the PSP table, was arbitrarily selected.)
- 2. Place the real_handle of the desired file at offset 18h + 19.
- 3. Move 19 to the bx register and exe-

THE PROGRAMMER'S SHO

31 Day RISK-FREE TRIAL on any product in this ad C Programmers:

8 Ways to Increase Productivity

Pascal to C Translation Easily and at Low Cost with The Translator (Pascal to C)

If you like Pascal's English-like syntax but want C's portability, speed, and control, or if you want to make a permanent switch to C at a very low cost, Milton Brown's

Pascal to C translator is for you. Take Jensen and Wirth standard Pascal and produce K&R standard C code. Any non-standard Pascal syntax is passed directly to the C program as in-line tokens. View the Pascal source code as the translator works. No file size limit; produces an approximately equal sized C file.

Includes meaningful, welldocumented sample applications, and a manual that helps you to complete the translation. Supports Lattice, Desmet, and C86.

MSDOS \$130

FAST, Easy-to-Use Graphics, Royalty-Free:

Essential Graphics

Draw fast dots, lines, circles, arcs, rectangles, and box fills. Draw a bar or exploded pie chart or a shaded line graph with one function call. Use the font and clip-art manipulation routines with the 10 fonts included (up to 8 simultaneously), or choose from over 500 other fonts and clip-art sets available.

Essential Graphics provides fast animation and graphic windowing using GET and PUT, and generates compact code. Demonstration programs and comprehensive manual

Supports IBM Color, EGA, and Hercules cards, Epson and Oki printers. Lattice, Aztec, C86, Desmet, MS C, others. No royalties.

PCDOS \$219

C DYNAMO! WINDOWING: Full C Source, No Royalties POWER WINDOWS AND C FUNCTION LIBRARY

Power Windows covers all the bases: overlays, borders, 1-2-3 style or popup menus/help windows, zap instantly on/off screen, status lines, horizontal/vertical scrolling, color control or highlighting, word-wrap, files to windows, keyboard to windows. Powerful, easy to use, integrated error messages, thorough documentation. Supports IBM monochrome or color.

MSDOS. Only \$119.
C Function Library - includes 325 fundamental functions with readable source and thorough documentation.

MSDOS. Only \$119.

No matter what you have, you need these Best value available. Highly recommended!

Always available, start debugging after a crash. Source lines, line numbers and symbol support help save

hours of frustrating work New version 2.1 enhancements include DOSEDIT-like command editing, definition of up to 4 DATA windows, increased 'monitor' breakpoint speed, and much more. Other features include: disassembly, customization by YOU, in-line assembly, full 8087/287, 286, 75 + breakpoints, EGA, and traceback. It also has source support for Lattice, MSC, C86, and MS Pascal, and symbol

Clean, Thorough Debugging

PERISCOPE I, II or IIx

suppport for Desmet and Aztec C. Even debug drivers and resident programs. Periscope I includes an independent,

memory-protected board and breakout switch; Periscope II has a break-out switch and software, Periscope IIx is software only

PCDOS, I \$269 II \$115 through 8/31/86 IIx \$95 through 8/31/86

Add Efficient Multitasking to Your C Programs with Multi-C

Create, manage, and communicate among tasks with little RAM and processor overhead. Handle multiple users, printers, communications, or just about anything else without complex polling schemes or lockups in your

Multi-C is designed for ease of use in production programming, and it cooperates with your operating system, so functions are reliable. 40+ functions use 32,000 priority levels, handle interrupts, control flags, and messages and control queues.

Multi-C is portable because it's written in C; use it for stand-alone systems, or make Multi-C the kernel of your own operating system.

Particularly good for applications in data acquisition, device control, and communications. MS C, Lattice, C86. Partial source. No royalties. Cytek **MSDOS \$149**

Even for Small Files: Convenient, Fast Access CBTRFF

Why spend time writing file management code when you can use consistent, flexible, documented, professional functions? Even multiuser record locking and variable-length records are supported.

Add, delete, and update without needing to reindex. Store keys and record locations in B + trees.

You can access any record or group of records by the value of a user specific key. Search your files from any point, forward or backward.

Full, balanced B-tree support includes use of multiple keys, unlimited number

Use this powerful ISAM, even if you've previously done without.

Learn how to write systems for managing large files by using CBTREE source as a guide. Modify it and transfer it to another operating environment without

MSDOS \$99

Flexible Screen Development with SECURITY CHECKING and HELP SCREENS: ZVIEW Screen Library

Use this field-sensitive tool to develop data entry screens and windows and provide run-time flexibility Security level settings restrict inquiry or update of fields; multiple screen help display is available at screen and field level. You can also cus-tomize ZVIEW's operation and make any field characteristic change during

ZVIEW gives you full control of attributes, colors, boxes, protected fields, scrolling, and more. Load screens from memory for fast response. Field support includes alpha, numeric, or alphanumeric data types, case conversion, range checking and field comparison, and ZVIEW provides automatic data conversion to and from ASCII screen format. For Microsoft C, Lattice 3.0, and Aztec 3.2e. Supports EGA, color, and monochrome displays

PCDOS \$219

Fastest C **Development on Earth:** Instant C version 2.0

Instant C's NEW version 2.0 gives you immediate (2 secs.) compilation and execution of large (5,000 + line) programs, and the ability to link in external (commercial or your own) libraries in an interactive, Lattice 3.0 or Microsoft 3.0 compatible. interpreter-like environment with an integrated full screen editor and source level debugger.
You'll get full K&R standard C,

fast (33 second sieve) execution speed, and debugging with source code animation, single-stepping, backtracing, and unlimited condi-

tional breakpoints.
Instant C now supports multiple screens and graphic devices, run-time checking of pointer and array references, and includes a new manual, expanded tutorial and reference sec-

tion, and complete library source.

MSDOS \$399 Systems, Inc.

Call for a catalog, literature, advice and service you can trust

HOURS

8:30 AM - 8:00 PM EST.

800-421-8006

THE PROGRAMMER'S SHOP™ 128-D Rockland Street, Hanover, MA 02339 Mass: 800-442-8070 or 617-826-7531 7/86

"We at Sunspot are thrilled to know that there is a store that can cut through all the "bull", and find us the products that most computer stores know nothing about. Keep up the good work

Arland Hensler Sunspot

Circle no 143 on reader contine

16-BIT (continued from page 110)

cute the desired DOS function.
4. Restore the *real_handle* that was saved in step 1.

"The functions in HPKIO.ASM [Listing Two, page 96] provide the basic handle-packing I/O system for use with the small-memory model of Version 2.1 of the Computer Innovations C86 compiler. The program HTEST.C [Listing Three, page 101] is used to demonstrate the functions. To try HTEST, create an empty \TEST directory. The number of files created by HTEST will be three less than the number of files specified in CONFIG.SYS.

"This solution is obviously something of a hack because the redirection scheme is not documented and thus may change in future releases of DOS.

"Considering current developments in mass-storage devices, the IBM PC family of machines could be used for some sizable applications. This arbitrary limit of 20 files, however, disqualifies these machines (under MS-DOS, at least) for serious database applications. I am surprised that there have not been more complaints. Is I/O redirection really worth cutting the file limit from 255 to 20?"

Resident Programs and File I/O

For those *DDJ* readers writing the next SideKick or Ready, Gary Cramblitt has got a question for you: "How can a resident MS-DOS program perform disk file I/O without trashing an existing program also doing disk I/O? An on-line notepad program, for example, allows the user to press a special key at any time, even while running some other program. A window opens up on the screen, the user enters his or her note, and the note is recorded in a notepad file on the disk.

"The problem is that MS-DOS is not reentrant. When the user presses a special key, the processor may be currently executing inside an MS-DOS file I/O routine. If the on-line notepad program calls MS-DOS disk I/O functions, the original program's

disk I/O will get trashed or the computer will hang.

"I've come up with several ideas on how to solve this problem, but so far, none of these solutions is ideal. One technique can be used if the target computer has a timer hardware interrupt. The MS-DOS Get Critical Flag Address function (interrupt 21h, function 52h) can be used to tell when the processor is not executing code inside MS-DOS. A timer interrupt routine could keep checking this flag. When DOS is no longer critical (and therefore is no longer inside an MS-DOS disk I/O routine), then the notepad program can safely request its disk I/O.

"There are three problems with this technique. First, it is hardwaredependent because you must have knowledge of (and capture) the particular computer's hardware timer interrupt. Second, the Get Critical Flag Address function is available only in MS-DOS, Version 2, and later. [Note: This function is not documented for PC-DOS systems, although it seems to work.—Ray] Third, a lot can happen between the time the user presses the special notepad activating key and the time MS-DOS is not in a critical section. For some applications, this won't be a big problem. However, I have in mind a program to dump the graphics screen of my computer (a Z-100) to a disk file. Too much can happen on the screen between the time the key to request the screen copy to disk is pressed and the time MS-DOS becomes noncritical.

"Another technique for solving the reentrancy problem would be to save the notes in memory—like a special RAM disk. The user must run a special program before shutting off his or her computer to copy the notes from the memory file to floppy disk. This solution suffers from two obvious deficiencies. First, it requires more memory. Second, if users forget to run the special program or if they lose power, their notes are lost forever.

"A third technique would be for the on-line notepad program to do its own file handling, reading and writing physical disk sectors directly. I think the problem with this approach is obvious."

(Listings begin on page 96.)

Vote for your favorite feature/article. Circle Reader Service **No. 6.**

How to tackle a 300 page monster.

Turn your PC into a typesetter.

If you're writing a long, serious document on your IBM PC, you want it to look professional. You want MicroT_EX. Designed especially for desktop publishers who require heavy duty typesetting, MicroT_EX is based on the T_EX standard, with tens of thousands of users worldwide. It easily handles documents from


smaller than 30 pages to 5000 pages or more. No other PC typesetting software gives you as many advanced capabilities as MicroT_FX.

So if you want typesetting software that's as serious as you are about your writing, get MicroT_EX. *Call toll free* 800-255-2550 to order or for more information.* Order with a 60-day money back guarantee.

MicroT_EX[™] from Addison-Wesley

Serious typesetting for serious desktop publishers.
*Dealers, call our Dealer Hot Line: 800-447-2226

(In MA, 800-446-3399), ext. 2643.




If you think you can't afford a UNIX system. we've got a \$160 surprise.

Turn your PC into a multi-user system.

Convert your IBM PC-AT (or compatible) into a multi-user/tasking UNIX work station—at absolutely the best price anywhere, any time. Based on the AT&T-certified UNIX System V/286, the MICROPORT SYSTEM V/AT is designed for use in virtually any computer environment, from office automation to software development.

 Dynamic disk buffer allocation provides RAM disk performance for systems with large memory configuration.

Runs on virtually all PC-AT clones.



Over 200 utilities come standard.

Grep, awk, sort, split, cut, paste, vi and ed (and many more) now let you search and modify files, make use of electronic mail, emulate terminals, calculate electronically, convert data and publish

SYSTEM V/AT is more than a look-alike. It was derived from AT&T's own UNIX System V release 2 iAPX286. It thereby contains standard System V features the competitors don't support, such as the powerful symbolic debugger, sdb, the shell-layering job-control facility and the F77 Fortran compiler, as well as programming tools such as ctrace, cflow, and bs. Also standard is File System Hardening which greatly reduces data loss in a power failure.

Want some more features?

- Console driver providing ANSI terminal interface for monochrome, CGA, Hercules and EGA cards
- Multiple Virtual consoles allow up to four virtual windows of operation.
- Record and File Locking
- Supports the 286's 16 megabyte virtual address space and fully utilizes its other advance features.
- Supports all standard IBM drive types and most non-standard hard-disk drives.
- Requires only one hard-disk partition, and allows DOS to reside on the same hard disk.
- Provides utilities to transfer files to-andfrom DOS file systems.

UNIX and DWB are trademarks of AT&T IBM and IBM PC-AT are trademarks of IBM CORPORATION. SYSTEM V/AT is a trademark of MICROPORT SYSTEMS, INC

Circle no. 154 on reader service card.

Super softwaredevelopment environment

We've provided everything: Make, yacc, lex, sccs, cflow, ctrace plus every standard System V software-development tool. The F77 Fortran compiler. And the AT&T Portable C compiler for the 286. Both C and Fortran compilers generate 287 instructions directly—for systems not containing 287 math coprocessors, a kernel-resident IEEE-compatible 287 emulator is provided. The large-model code produced by the compiler is among the densest and fastest currently available.

So, how do we do it?

MICROPORT offers SYSTEM V/AT at a fraction of the price of the competitors simply because we build on the generic System V/286 product from AT&T. This entire utility package from the certified release has been copied directly to SYSTEM V/AT—without so much as a recompile. Not only does this mean that MICROPORT can offer SYSTEM V/AT at a remarkable low price, it also guarantees a level of quality present in few (if any) other UNIX-system implementations. (And, since our staff was part of the group that implemented the standard System V/286 port for Intel, MICROPORT can offer comprehensive support for the system, as well.)

And a dollar change

The price is even better than you thought. Order right away and we'll return one silver dollar just as rapidly, with your product shipment. (If you'd like a little more time we'll apply that dollar to the cost of a brochure—which we'll send right away too.)

NOTE: Educational institutions—Call about our nominally-priced site licensing and source code

60 DAY MONEY-BACK GUARANTEE

Andadollar change.



To order: Complete the information below. Your attractively-packaged and fully-documented order will be shipped within two weeks.

MICROPORT SYSTEMS, INC.

4200 Scotts Valley Drive Scotts Valley, CA 95066 408/438-UNIX or 800/PC2-UNIX (outside CA)

CI	ST	CR	//	11	/ //	r
וט	O		VI	V	и	ı

- RUNTIME SYSTEM Includes the SYSTEM V/AT operation system and over 200 utilities, for two users.

 QUANT. \$160.00

 SOFTWARE DEVELOPMENT SYSTEM The complete Software Generation System for 286 development.

 QUANT. \$169.00

 TEXT PREPARATION SYSTEM Includes nroff, troff, spell and other programs.
- QUANT: \$169.00
- indicated above.

 QUANT: ______\$439.00


OPTIONAL three to eight-user upgrade.

QUANT: \$99.00

Subtotal: __

(CA residents add 6.5% tax per copy): _____ Shipping and handling charges (In the USA, \$14.00; in Canada, \$18.00; and in Europe, \$110 ____

TOTAL DUE:



THE RIGHT TO ASSEMBLE

The Worm Memory Test

o, this is not a method for quantifying the mental retentive powers of certain long, cylindrical invertebrates. It is a test that could help to diagnose certain types of computer memory errors. The Worm memory test (see Listing One, page 102) uses a dynamically executing program as the actual test data. Unlike previous memory test programs of this type, this worm has a special twist—it is able to overlay itself while it is executing, thanks to the MC68000's prefetch register.

Some Fetching Facts


Never heard of the prefetch register? To understand how the memory test works, it might help to review the way the MC68000 fetches and executes instructions. The MC68000 uses instruction pipelining in order to speed execution. There is, in effect, a 16-bit register between the data bus and the instruction decoding logic. When an instruction is executed, the opcode for that instruction is first loaded into the prefetch register (often while the previously fetched instruction is being executed), then the instruction is moved into the instruction decoding register, where it is executed. The net effect is that the processor usually has a handle on the next thing it is supposed to do.

Prefetch works fine most of the time, but it does slow things down during certain operations. If the instruction being executed causes a nonsequential instruction to be executed, execution may be either faster or slower. In the case of a conditional

by Jan W. Steinman

branch instruction, a branch taken is quite fast because the prefetch register already holds the displacement that must be added to the program

Jan W. Steinman, 2002 Parkside Ct., West Linn, OR 97068



counter in order to fetch the next nonsequential instruction. A branch not taken, however, will be a little faster if it is a short branch because the next instruction is already in the prefetch register and the two clocks needed to add a displacement to the program counter can be saved. The worst case happens when a branch is not taken and the branch displacement is 16 bits. In this case, the processor has useless information in the prefetch register and must flush that information before it can fetch the next instruction.

Other nonsequential instructions cause an immediate flush of the prefetch register and use an extra four clocks simply to restart the pipeline. One exception is the decrement-and-branch instruction, which like the taken branches benefits from having the branch displacement handy. (The MC68010, with its 32-bit prefetch register, actually executes many 16-bit instructions out of the prefetch register if they precede a decrement-and-branch instruction.)

How the Worm Crawls

Worm depends on these characteristics of pipelining in order to overlay itself while it is running, but it needs some management and control in order to be useful—a Worm on the loose would quickly destroy all memory! Besides Worm, a complete memory test requires two additional parts: an initialization sequence and a routine for controlling Worm and reporting its findings.

The initialization routine, *Init*, has some special characteristics and includes most of the system dependencies. It is executed only once—at the beginning—and is therefore throw-

away code. This is why it is placed last—Worm actually crawls right over its initialization code in this implementation. The registers are set up to the specifications of Worm, and several important system functions are performed. In particular, it is important that page faulting does not occur in systems that support virtual memory, and if special hocus-pocus is needed to turn off interrupts, it should be done here.

Manager exercises control over Worm and is responsible for communicating errors it discovers and displaying progress messages if desired. When Manager is entered upon completion of a Worm pass, it must decide if it has been entered because of an error or simply as a point of control. If there has been an error, Worm is no longer runnable, so Manager will have to report the error and terminate. If no error is detected, Manager must check the progress of Worm to keep it from consuming all memory. At this point, Manager can decide enough memory has been checked to warrant a progress report of some kind.

The real heart of the whole thing is, after all, Worm. Worm simply replicates itself, one long word lower in memory, while comparing the new copy of itself against the original, which never executes. Worm may be the heart of the memory test, but the three instructions starting at Crawl are where the magic happens. This loop starts at the beginning of Worm and copies the first long word down to Worm-4. It continues with each additional long word, until it gets to the long word at Crawl + 4, which is a dbne instruction with its 16-bit displacement. The preceding move.l and cmp.l have already been copied down.

At this point, it becomes a little difficult to keep track of what is data and what is code. When the *move.l* is in the instruction decode register,

ready to be executed, the following cmp.l is in the prefetch register, waiting its turn to be executed. When the move.l at Crawl executes, it moves the dbne instruction into the location it and the following cmp.l are currently occupying. The processor has no way of knowing it has just invalidated its prefetch register, so it continues—moving the cmp.l instruction into the instruction decode register and moving the following dbne into the prefetch register. The cmp.l executes, comparing the dbne just moved against the original while moving the branch displacement for the dbne into the prefetch register.

Assuming the compare was successful, the dbne executes, decrementing d0 and branching backward 4 bytes to where the move.l used to be. The prefetch register is flushed because of the branch, so the value at that location is loaded into the prefetch register and immediately into the instruction decode register. But what is loaded? A copy of the dbne, complete with the same negative displacement value. The condition codes have not changed, and the count register d0 should not be anywhere near 0, so the copy of the dbne gets executed identically to its predecessor, which still resides in the next long word. The dbne copy branches to the move.l copy, and the loop continues moving the code down 4 bytes. (See Table 1, above.)

When the count register d0 underflows, the dbne copy drops through, interrupts are enabled, Worm's dynamic image pointer a5 is adjusted to point to the new Worm copy, and Worm reports back to Manager. Note that none of the Worm code is ever executed before it has been compared and verified.

It is vitally important to disable interrupts when the *move.l* overlays itself and the following *cmp.l*. An interrupt at this point causes the prefetch to be flushed when the interrupt is serviced. Upon return from the interrupt, the displacement part of the *dbne* (hex fffa) will be fetched as an instruction. This will cause a "line 1111 emulator exception" unless your system has a coprocessor with an ID code of 7, but either way *Worm* will be broken and the memory test will fail. And of course, it is important that the length of *Worm*


remains a multiple of 4 if you decide to modify it!

But What Good Is It?

I originally developed the MC68000 Worm test for an embedded processor application that was having dynamic-RAM refresh problems. It was discovered that conventional RAM tests, which move smoothly up through consecutive addresses, were masking the problem by unintention-

	Before	After	
Crawl-4		move.l	(a0)+,(a1)
Crawl-2		cmp.l	(a1)+,(a2)+
Crawl move.l	(a0)+,(a1)	dbne	d06<+
Crawl+2 cmp.l	(a1)+,(a2)+		1
Crawl+4 dbne	d0, -6		·+

Table 1: The test in action



There's never been a better time to buy Lattice C. Professional programmers the world over have made Lattice C the standard compiler for serious MS-DOS programming. Our compiler features include: ANSI language constructs including, *unsigned* as a modifier, *void* data type, *enum* data type, structure assignments, structure arguments, structure returns, and argument type checking.

The library contains more than 200 new functions, including: ANSI/UNIX/XENIX compatibility; extended support for MS-DOS; extended support for networking including file sharing, file locking, and I/O redirection; and flexible error handling via user traps and exits. Plus the library has also been re-engineered to produce much smaller executables.

Try the new Lattice C Compiler. Because C-ing is believing.



Lattice, Incorporated P.O. Box 3072 Glen Ellyn, Illinois 60138 312/858-7950 TWX 910-291-2190

INTERNATIONAL SALES OFFICES:

Benelux: Ines Datacom (32) 2-720-51-61 Japan: Lifeboat Inc. (03)293-4711 England: Roundhill (0672)54675 France: SFL (1)46-66-11-55 Germany: (49)7841/4500 (49)8946/13290

Is LISP Right

for Your Expert System?

Find Out — FREE

You can explore LISP by examining a complete sample problem. Call and we will send you a free source listing of "SELECTWP".* It prompts users for criteria and helps them choose which



micro word processor to buy.

Look over the TransLISP syntax (COM-MON LISP compatible). Your application will probably have similar characteristics.

Power & Flexibility

Do you get flexibility in PASCAL and C? Of course, but examine the listing of SELECTWP to see how much more power and flexibility you get. The LISP advantages:

- forward references make program flow fit the problem
- manipulate data structures of varying sizes
- create your own language to fit the problem domain
- avoid mundane, busy work required with traditional procedural languages
- powerful function and macro building facilities provide better data abstraction

*SELECTWP includes 512 lines of LISP code and 335 lines of comments.

TransLISP gives You the Advantage

Using TransLISP for your expert system has several advantages over other AI tools. And you will see SELECTWP illustrate:

- * the ability to control how decisions are made
- * the freedom to assign weights and react to user choices
- * the complete control you have over how a problem is solved, and interaction with the

Nothing to lose

Examine LISP carefully by studying a practical program free.

Or buy TransLISP risk free. SELECTWP is just 1 of over 20 sample programs in the complete TransLISP system. The other sample programs include: an adverture game, a program to read dBASE SDF files, "Job Counselor" and more. Use the modular tutorial, the complete 300+ function LISP interpreter, and the online help, to get started in LISP in only a few hours.

Develop programs of up to 12000 lines on a 640K system or use TransLISP on a floppy only, 256K RAM machine. MSDOS.

Call 800-821-2492 for SELECTWP FREE. Or order the complete TransLISP system risk free for only \$95.

Solution

335 Washington St., Norwell, MA 02061 (617) 659-1571

Circle no. 148 on reader service card.

The C Programmer's Assistant

C TOOLSET

UNIX-like Utilities for Managing C Source Code

No C Programmer should be without their assistant – C ToolSet from Solution Systems. The package consists of several utilities designed to help make C programming tasks easier.

C ToolSet (formerly C Helper) includes:

DIFF – Compares text files on a line-by-line basis or use CMP for byte-by-byte – indispensable for showing changes among versions of a program under development. So "intelligent" it stays in synch even when you add 100 lines.

GREP – Regular expression searches – ideal for finding a procedural call or a variable definition amid a large number of header and source files.

FCHART – Traces the flow of control between the large modules of a program.

PP (C Beautifier) – Formats C program files so they are easier to read.

XREF (CCREF) – Cross references variables from a program.

Available For MS-DOS - \$95

ONLY \$95 Source Code Included



335 Washington St. Norwell, MA 02062 617-659-1571

800-821-2492

Circle no. 152 on reader service card.

RIGHT TO ASSEMBLE

(continued from page 115)

ally providing software refresh. The test is not long enough to cause a complete cycle of all a dynamic RAM's row-address-strobe (RAS) lines and was able to help diagnose the problem.

In the form presented, this implementation is useful primarily as an illustrative example of position-independent coding, modular design, and, of course, a unique use of the prefetch register. It could be put to practical use in several ways.

The best use of the memory test might be to have it running continuously, as a very-low-priority task. Manager would have to take some of the responsibility of Init by allocating test memory and restarting Worm when it has finished testing a buffer. The interrupt disabling code may be simpler on systems without virtual memory—on the Amiga it is a simple memory store.

Virtual-memory systems would also need to add code to branch around the interrupt disabling code on the copy of the first long word only, which would allow the memory test to generate page faults whenever it first crosses a page boundary. To make it practical in such systems, *Manager* would have to access the memory-management hardware in order to map faulty virtual locations to broken chips.

The Worm routine itself can hold much more code if desired. I originally had much of Manager's decision code in Worm, which did speed it up but at the expense of simplicity. In a message-based system, such as the Amiga, Manager could be totally deleted. Worm could contain all the task code, merrily crawling through any available RAM it could find and sending error reports through intertask messages—all with minimal impact on the user.

DDI

(Listing begins on page 102.)

Vote for your favorite feature/article. Circle Reader Service **No. 7**.

Now You Know Why BRIEF is BEST

"BRIEF, The Programmer's Editor, is simply the best text editor you can buy." John Dvorak, INFOWORLD 7/8/85

The Program Editor with the BEST

the **BEST** Features

Since its introduction. BRIEF has been sweeping programmers off their feet. Why? Because BRIEF offers the features MOST ASKED **FOR** by professional programmers. In fact, BRIEF has just about every feature you've ever seen or imagined. including the ability to configure windows. keyboard assignments, and commands to YOUR preference. One reviewer (David Irwin. DATA BASED ADVISOR) put it most aptly, "(BRIEF)...is quite simply the best code editor I have seen."

MACRO LANGUAGE

As Steve McMahon describes in Byte (3/85), "BRIEF is even more customizable than [another customizable editor] - not only may wholly new commands be created, but they may be assigned to any key, replacing even basic function keys like cursor control keys or the return key . . . String and integer [variable] types are available and may have either global or local scope . . . Arithmetic and logical primitives, type conversion, buffer and window control, search and translate, keyboard input, . . . are [also] available.

"Much of BRIEF was written in the BRIEF macro language, and the soruce of these macros is included with the editor. Using this source, it's possible to customize even sophisticated functions of the editor..."

No other editor has a more powerful macro language.

Every Feature You Can Imagine

Compare these features with your editor (or any other for that matter).

- FAST
- Full UNDO (N Times)
- Edit Multiple Large Files
- Compiler-specific support, like auto indent, syntax check, compile within BRIEF, and template editing
- Exit to DOS inside BRIEF
- Uses all Available Memory
- Tutorial
- Repeat Keystroke Sequences
- 15 Minute Learning Time
- Windows (Tiled and Pop-up)

- Unlimited File Size –(even 2 Meg!)
- Reconfigurable Keyboard
- Context Sensitive Help
- Search for "regular expressions"
- Mnemonic Key Assignments
- Horizontal Scrolling
- Comprehensive Error Recovery
- A Complete Compiled Programmable and Readable Macro Language
- EGA and Large Display Support
- Adjustable line length up to 512

Program Editing <u>YOUR</u> Way

A typical program editor requires you to adjust your style of programming to its particular requirements - NOT SO WITH BRIEF. You can easily customize BRIEF to your way of doing things, making it a natural extension of your mind. For example, you can create ANY command and assign it to ANY key even basic function keys such as cursor-control keys or the return key.

The Experts Agree

Reviewers at BYTE, INFOWORLD, DATA BASED ADVISOR, and DR. DOBB'S JOURNAL all came to the same conclusion – BRIEF IS BEST!

Further, of 20 top industry experts who were given BRIEF to test, 15 were so impressed they scrapped their existing editors!

NOT COPY PROTECTED


Solution Systems

MONEY-BACK GUARANTEE

Try BRIEF (\$195) for 30 days – If not satisfied get a full refund.

TO ORDER CALL (800-821-2492)

OF INTEREST



As artificial intelligence moves more into the real world and out of the laboratory, we are seeing more and more tools designed to help application developers use AI techniques in their programs. In particular, PROLOG and expert systems tools seem to be getting hot. Where it will lead is anybody's guess—we are still far from true "common sense" AI programs, and there are few products claiming to use AI that are much more than sophisticated database tools. What new developments are on the horizon? Will true AI finally become more than a complex toy? What about the poorly understood sister fields, pattern recognition and natural-language interfaces?

IntelligenceWare has announced a new expert systems tool, Experteach-II, a comprehensive guide including complete LISP and PROLOG interpreters for the IBM PC. The product includes on-line and written tutorials, plus tools and source code for expert systems based in LISP, PROLOG, dBASE II, or Pascal. It's priced at \$475. Reader Service No. 16. IntelligenceWare Inc. 9800 S. Sepulveda Blvd. Ste. 730 Los Angeles, CA 90045

PML Systems announces BEAGLE (Bionic Evolutionary Algorithm Generating Logical Expressions), a data

(213) 417-8896

analysis system that uses artificial intelligence to construct rules and inferences from a knowledge database. BEAGLE takes as input a database of examples and produces both a set of human-readable decision rules and a program (in FORTRAN, Pascal, BASIC, or C) that expresses the same rules. It's \$398 for the IBM PC or \$1,198 for the VAX. Reader Service No. 17. **PML Systems** 3139 East Almond Ave. Orange, CA 92669 (714) 771-7744

A new product line from Arity Corp. supports software development in PRO-LOG on the IBM PC. The line includes five products: the PROLOG Compiler and Interpreter for \$795, the Interpreter alone for \$350, the Expert Systems Development Package for \$295, the SQL Development Package for \$295, the Arity Screen DesignToolkit for \$49.95, and the Arity File Interchange Toolkit for \$49.95. The Combination Pack, which contains all five products, costs \$1,225. Reader Service No. 18. Arity Corp. 358 Baker Ave. Concord, MA 01742

For the Macintosh

(617) 371-1243

The WSM Group has released Hyper-C 68000 for the Macintosh computer. Hyper-C is a full K & R C compiler with extensions to allow a natural interface with the Macintosh ROM toolbox routines. Mac toolbox calls are generated inline, so there's no need for any special interfacing code. Pascal functions can be coded in-line, and assembly source code is produced as output. Full SANE (Standard Apple Numeric

Environment) support is provided. Hyper-C is priced at \$199.95 and has no licensing requirements. Reader Service No. 19. The WSM Group Inc. 1161 N. El Dorado Pl. Ste. 241 Tucson, AZ 85715 (602) 298-7910

Pascal Extender and C Extender from Invention Software Corp. are compiled libraries designed to simplify the task of programming the Macintosh interface and reduce development time. They support all standard toolbox commands plus add highand medium-level routines for creating and manipulating windows, menus, controls, scrollbars, dialogs, and alert boxes. The Extender handles graphics and text scrolling and window activation. It fully supports text editing, desk accessories, and graphics printing. Pascal Extender retails for \$69.95; C Extender retails for \$129.95. Reader Service No. 20. Invention Software Corp. P.O. Box 3168

For Atari ST

(313) 996-8108

Ann Arbor, MI 48106

The Pro Pascal language compiler from Prospero Software is available on the Atari ST. It includes strings, 7- and 16-digit precision floating point, separate compilation, and 4byte integers. Pro Pascal has full GEM AES and VDI bindings. It costs \$149. Reader Service No. 21. Prospero Software Ltd. 190 Castelnau London SW13 9DH England 011 441 741-8531

Let's Write is a new word processor for the Atari ST

from Mark Williams Co. It features advanced text processing, a spelling checker, and communications in one package. The editor gives the user up to 11 windows to view and change text from multiple files. The text formatter is similar to Unix's nroff. Let's Write costs \$79.95. Reader Service No. 22. Mark Williams Co. 1430 W. Wrightwood Ave. Chicago, IL 60614 (312) 472-6659

Hardware for the PC American Computer & Peripheral has introduced the American Abovefunction Card, a multifunction memory board for American IBM PC/XTs and compatibles with full support of Lotus, Intel, and Microsoft expanded-memory features. Supporting up to 2 megabytes of expanded memory, the Abovefunction Card also provides serial, parallel, and game ports and a real-time clock/calendar. It includes a utility disk that contains Expanded Memory Manager, RAM disk, print buffer, real-time clock/calendar program, and example CONFIG.SYS and AUTOEXEC .BAT files. The card has a suggested list price of \$380 with no RAM or \$820 with 2 megabytes RAM installed. Reader Service No. 23. American Computer &

Peripheral Inc. 2720 Croddy Way Santa Ana, CA 92704 (714) 545-2004

DigiBoard has announced DigiRam/3MB, a memory-expansion board for the IBM PC/AT that provides up to 3 megabytes of error-checked RAM on a single board. The board has split memory addressing, filling up to 640K and continuing

A NEW DIMENSION IN COMPUTER EDUCATION

"PC TechVideo provides an indepth overview of the installation of computer components. We use it to train all our technicians and assemblers."


John Atma, Chief Technician for Tech Personal Computers

"After viewing PC TechVideo, I now understand the basics of how my computer works and was even able to replace the 1.2M drive on my AT at work. PC TechVideo was definitely worth the money."

Brenda Hudson, Data entry and processor for Sark Enterprises

"PC TechVideo is great. With the help of PC TechVideo, I was able to install a 10MB hard disk on my XT without taking it to an expensive service center."

Gita Beant, Economics major at UC Irvine





1040 EAST CHAPMAN AVE. ORANGE, CALIFORNIA 92666

OUTSIDE CALIFORNIA IN CONTINENTAL U.S. - PUERTO RICO, HAWAII EXCLUDING ALASKA:

1-800-438-8877
CALIFORNIA RESIDENTS CALL:
(714) 771-3560

SPECIAL INTRODUCTORY OFFER \$89.95



PC TechVideo is an innovative set of two 2-hour instructional video tapes which form a complete guide to the IBM® and compatible personal computer systems. Designed for everyone, from the complete novice to the software expert. PC TechVideo provides the viewer invaluable first hand instruction in the installation and maintenance for IBM® and compatible systems.

Part I of PC TechVideo is a complete and comprehensive presentation of prominent features of the PC family including:

Motherboard architecture

Memory Configuration and Addressing Monitor Technology Floppy and Fixed Disk Technology Bus Architecture Serial and Parallel Ports

Part II of PC TechVideo shows the details involved in actually installing, configuring, and replacing:

Motherboards Power Supplies Floppy and Fixed Disks Drive Controllers Popular Expansion Boards

PC TechVideo provides instruction not found in books or magazines. It is an essential tool for anyone interested in understanding their PC. You can't afford not to have PC TechVideo

Dealers only circle **no. 245** on reader service card. Users only circle **no. 279** on reader service card.

OF INTEREST (continued from page 118)

at 1 megabyte and up. It is user-upgradable and available in any desired memory configuration. Reader Service No. 24. DigiBoard Inc. 6751 Oxford St. St. Louis Park, MN 55426

(612) 922-8055

Everex Systems has introduced an EGA video card that is compatible with the IBM Enhanced Graphics Adapter, includes a parallel printer port and 256K display memory on-board, and is supplied with the company's proprietary EG-MODE software. The Enhancer board provides 640×350-resolution graphics in 16 colors from a palette of 64 colors. It has a suggested retail price of \$425. Reader Service No. 25. Everex Systems Inc. 48431 Milmont Dr.

Pacific Data Products is offering the V68K line of intelligent graphics boards.

These high-resolution

Fremont, CA 94539

(415) 498-1111

graphics cards are full-size, IBM PC add-on cards that feature palette sizes of up to 16 million colors, a Motorola MC68010 video processor, and a capacity of up to 2 megabytes of video memory. Palettes can be reloaded every scan line with no screen performance degradation. The boards are compatible with the IBM PC, PC/ XT, PC/AT, and RT/PC. The MC68010 video processor can perform vector to raster conversion or other tasks. Reader Service No. 26. Pacific Data Products 8545 Arjons Dr., Ste. 1 San Diego, CA 92126 (619) 549-0136

Univation has announced a new multifunction accelerator card called the Dream Board for the IBM PC. It combines up to 2 megabytes RAM with a 200-400 percent increase in speed, serial and/or parallel ports, a clock/calendar, an optional 8087 math chip, and several utilities to speed disk I/O. The card retails for \$595-\$795 with 512K RAM, depending on options selected. Reader Service No. 27.

Univation 1231 California Cir. Milpitas, CA 95025 (408) 263-1200

Earth Computers' 287-Power-10 is a 10-MHz math coprocessor board for the IBM PC/AT that plugs into the existing 80286 socket. The product line also includes 5- and 8-MHz versions of the board. Prices range from \$249 for the 5-MHz version to \$695 for the 10-MHz version. Reader Service No. 28.

Earth Computers P.O. Box 8067 Fountain Valley, CA 92728 (714) 964-5784

Networking

ITT has introduced the Xtra XL, a high-performance supermicrocomputer running both DOS and Xenix. The system, based on the Intel 80286 processor, is designed to maximize the computing power available to users operating in local-area network and shared-processor environments and maintains existing industry standards. Xtra XL includes 8-MHz, zero-wait-state memory;

dynamic disk I/O caching; an average hard-disk access time of 28 milliseconds; and an optional 80287 math coprocessor. In addition, an 8-MHz 80186based communications coprocessor offers dramatic throughput speed in multiuser configurations. Models I and II are intended for use as local-area-network servers operating under ITT DOS 3.1. Model I, priced at \$5,299, includes 640K RAM, a 1.2-megabyte floppy disk, and a 40-megabyte hard disk. Model II, priced at \$7,299, includes 640K RAM, a 1.2-megabyte floppy disk, and a 72-megabyte hard disk. Reader Service No. 29.

ITT Information Systems 2350 Qume Dr. San Jose, CA 95131 (408) 945-8950

A local-area-network configuration for the AT&T 6300 series of microcomputers has been announced by **The Destek Group.** The new configuration uses industry-standard CSMA/CD media-access protocols with a network bus speed of 2

Tools For Programmers

\$250

CUTILITY LIBRARY

\$185



- Pascal
 Fortran
 C
- Fastest Library Available
- Powerful and Easy to Use
- Major Graphics Boards
- No Royalties

- 350 + C Functions. Source Included
- Pop-up Windows and Menus
- Fastest Screen Output Available
- · Strings, Files, Keyboard, Mice
- No Royalties

C ESSENTIALS

\$49



CESSENTIALS

the 200 most frequently used functions



ESSENTIAL SOFTWARE, INC. P.O. Box 1003 Maplewood, NJ 07040 914/762-6605

Circle no. 138 on reader service card.

Improve Program Quality Enhance Program Productivity

Design your programs around . .

ASE, the Aspen Systems Subroutine Editor you can call from your programs. With ASE you can easily:

★ Design you own screen layouts for Program Input

Color and/or highlight input fields

Define your own key functions

Convert and edit a wide variety of fields ★ Update in several windows simultaneously

ASE includes 2 major subroutines, many minor subroutines

and install and demonstration programs. Data & screen layouts described in a single map.

Price \$99

Available MSDOS1.2.3

Demo Disk \$5

ASP, the Aspen Systems Subroutine Package provides functions difficult or unavailable in some higher level languages, performs those available with greater speed/ease or smaller memory requirements.

The ASP Package includes:

★ 100 + subroutines

A 300 page manual packed with examples

★ Test, Demonstration and customization source

Price \$ 130

Available MSDOS1,2,3, CP/M

All subroutines are callable from assemblers and Microsoft Compilers, easily altered for other compilers, can be used in EXE or COM programs.

Prices are PPD (continental USA). Colorado Residents add 3%.

P. O. Box 1163 Grand Junction, CO 81502 (303) 245-3262 VISA/MasterCard accepted

CP/M and MS-DOS are trademarks of Digital Research and Microsoft, respectively.

Circle no. 277 on reader service card.

PC/VI

Full Screen Editor for MS-DOS (PC-DOS)

Looking for an Ultra-Powerful Full-Screen editor for your MS-DOS or PC-DOS system? Are you looking for an editor FULLY COMPATIBLE with the UNIX* VI editor. Are you looking for an editor which not only runs on IBM-PC's and compatibles, but ANY MS-DOS system? Are you looking for an editor which provides power and flexibility for both programming and text editing? If you are, then look no further because PC/VI IS HERE!

The following is only a hint of the power behind PC/VI: English-like syntax is command mode, mnemonic control sequences in visual mode; full undo capability; deletions, changes and cursor positioning on character, word, line, sentence, paragraph or global basis; editing of files larger than available memory; powerful pattern matching capability for searches and substitutions; location marking; joining multiple lines; auto-indentation; word abbreviations and MUCH, MUCH MORE!

The PC/VI editor is available for IBM-PC's and generic MS-DOS based systems for only \$149. For more information call or write:

The UNIX community has been using the VI editor for years. Now you can run an implementation of the same editor under MS-DOS. Don't miss out on the power of PC/VI!

*UNIX is a trademark of AT&T Bell Laboratories.

Circle no. 268 on reader service card

A REAL

Clocksin & Mellish Prolog for BOTH major microcomputing

operating systems with full cross-compatibility.

Complete with the predicates necessary for POWER AI programming: op () name () functor () clause () = .. ("Univ")

...And no constraining data typing.

Floating point

Step-by-step tutorial

■ Math functions ■ Integrated editor

PROLOG

Extensible overlay library, 8087 support, large memory model (up to 640K)

PROLOG

Complete Macintosh environment with extensive pull-down menus and dialogue boxes.

No Risk Offer: Examine the PROLOG/i or PROLOG/m documentation at our risk for 30 days. If not completely satisfied, return with disk still sealed for retund.

APPLICATIONS-Complete with SOURCE CODE

NFL X-pert

\$4,995

A true interactive expert system written by a professional knowledge engineer. A valuable learning tool for any Prolog programmer interested in using Prolog to develop expert systems.

TOOLBOX

More than 50 subroutines that speed and compress list handling, searches, sorts, and reversal algorithms. An inside look at the tricks of the professional Prolog programmer.

TOYBOX

Written by an academician to help his students understand Prolog, this collection of puzzles and mind-teasers will illustrate how the Prolog programmer creates programs that find the best solution to the problem. Turn your computer into a super reasoning machine!

System Requirements: Minimum 256K RAM (320K recommended) PC DOS/MS-DOS ANSI Standard Support

Minimum 512K Macintosh Macintosh-plus and HFS Compatible



5580 LA JOLLA BLVD. SUITE 126 D LA JOLLA, CA 92037 (619) 483-8513

SAVE 10% when you buy either PROLOG/i or PROLOG/m and all 3 applications.

20.00 Overseas Air

PHONE ORDERS: 1-800-621-0852 EXT 468

PAYMENT ENCLO	OSED \$dents add 6% sales tax		PROLOG/i PROLOG/m	\$99.95 99.95
☐ CHARGE MY:	☐ MasterCard	□ Visa	MS-DOS □	Mac □
Card No.	Exp. Dat	e	NFL X-pert TOOLBOX TOYBOX	49.95 29.95 29.95
Signature			Complete Pack	188.82
Mr./Mrs./Ms			SHIPPING:	100.02
Address	(please print full nam	e)	\$ 5.00 U.S. 7.50 Canad 10.00 Carribe	
City/State/Zip			Hawaii	

FROM THE DEVELOPERS OF THE

The programming handbook you've been waiting for.





Outlines the programming strengths of the 65816, 6502, and 65002.

 Includes a review of basic concepts, architecture, and logical operations.

Now available at your local bookstore or call toll free 1800/624-023 to order your copy roday. In New Jersey, call 1(800)624-0024



0-88303-789-3/288 p/\$22 95

Circle Reader Inquiry Number 219

PROGRAM WITH POWER ***

PC/POWER TM

Application Development and Management System

Runs on all 100% PC compatibles!

- Supports applications in a variety of languages

 Including C, PASCAL, BASIC and Assembler

 Even different languages in same application
 Screen painter language and program independent screens
 Allows programs to pop-up menu/selection windows
 Builds indexes of applications and programs for easy use
 Supplies EXEC function to pass control between programs

 One language can pass control to another

 One language can pass data to another

- - One language can even pass data to another Inter-language considerations handled by PC/POWER
- Run-time supports control of multiple applications with:
 Run-time start-up screen (customizable)

 - Pop-up application menu
- Integrates existing programs into an application Useful development applications included as samples

WITH RUNTIME MANAGER - NO ROYALTIES!

\$95.00 inc. Shipping and Handling

ORDERS & INQUIRIES (800) 628-2828 ext. 712

Beacon Street Software, Inc.



ORDER NOW!



OF INTEREST

(408) 737-7211

(continued from page 120)

megabits/second. It features increased buffer memory and circuitry. Prices vary according to configuration. Reader Service No. 30. The Destek Group 830 E. Evelyn Ave. Sunnyvale, CA 94086

Network-OS is a local-areanetwork operating system from CBIS designed to allow users of IBM PCs, PC/ XTs, PC/ATs, and compatibles to create microcomputer-based LANs. It is fully NetBIOS/DOS 3.1 compatible and can support all major LAN topologies including token ring. Network-OS also supports Novell file and record locking and can run virtually any thirdparty DOS 3.1 application. The retail list price of Network-OS is \$995 per 16 users. Reader Service No. 31. CBIS Inc.

2323 Cheshire Bridge Rd. Atlanta, GA 30324 (404) 634-3079

A simultaneous voice/data multiplexer for use on four-wire voice grade lines is available from Coherent Communications Systems Corp. The SVD-2400 overlays a full-duplex, 2.400-bps data channel to an existing leased line, allowing it to support both voice and data traffic. Reader Service No. 32.

Coherent Communications

Systems Corp. 60 Commerce Dr. Hauppauge, NY 11788 (516) 231-1550

A high-speed, 2,400-bps, stand-alone modem designed for personal computers and terminals is available from Prentice Corp. The P-224 is a full-duplex modem that meets

CCITT V.22 bus recommendations and Bell 212A and 103 standards and supports the Hayes AT command set. It features auto-answer and auto-dial operation and can be used with touch-tone or pulse-dial phones. Standard features also include automatic bit rate and parity selection and auto-speed recognition on answer. Reader Service No. 33.

Prentice Corp. 266 Caspian Dr. Sunnyvale, CA 94088-3544 (408) 734-9810

InterContinental Micro Systems has released Turbodos/PC, a package that runs on an IBM PC, a compatible, or any 8086-line microcomputer system that uses MS-DOS or PC-DOS, Versions 1.x, 2.x, or 3.0. Turbo-DOS/PC allows the PC to become a TurboDOS network client and to access the disk drives and printers belonging to the TurboDOS file and print servers in the network. The single-copy list price for TurboDOS/PC is \$100. Reader Service No. 34. InterContinental Micro

Systems 4015 Leaverton Ct. Anaheim, CA 92807 (714) 630-0964

Woolf Software Systems has announced Move-It, Version 4, a communications package for microcomputer users. The new version has automatic file compression, keyboard macros, scripting files, XMODEM protocol support, infilter and outfilter commands, and the ability to send and receive files automatically. Move-It, Version 4. retails for \$150. Reader Service No. 35.

Woolf Software Systems 6754 Eton Ave. Canoga Park, CA 91303 (818) 703-8112

Circle no. 267 on reader service card.

HIRE A PRO!

DDJ Announces a new service: Programmers' Opportunities

Dr. Dobb's Journal of Software Tools has a 10 year history of serving professional programmers with the most useful, technical information of any publication for the computer industry. Now, in our new Programmers' Opportunities section, we are offering our readers information to help them stay on top of the quickly

changing technical employment market.

We invite the top hardware, software, electronic, and instrument companies to list their computer-related career opportunities in Dr. Dobb's Journal. A limited number of companies will be given the chance to list jobs each month on a first come first served basis.

For more information on how your company can hire a pro, write or call Gary George, 893 Monroe Dr., Atlanta, GA 30308; (404) 897-1923.

Our first response is shown here as an example of what your listing will look like:

Position Title: Location: Company: Address: City/State/Zip: Phone:

Field Systems Engr. NY, DC, LA, and SF American Int'l Comm. 4760 Walnut St. Boulder, CO 80301 (303) 444-6675

A serial communications board that allows users to interconnect up to six IBM PCs, PC/XTs, PC/ATs, and compatibles using the Easy-LAN local-area network is available from Server Technology. The Com Port Board-6 is based on the RS-232 interface standard and works in conjunction with the DOS-supported COM1 and COM2 ports. By incorporating a Server Com Port Board-6 along with the DOS-supported COM1 and COM2, users can interconnect a total of eight PCs using EasyLAN. If desired, up to six PCs can be interconnected to the Com Port Board-6, with the COM1 and COM2 reserved for other serial devices. Three boards can be accommodated per PC, allowing up to 18 PCs to be interconected in an EasyLAN network. An Easy-LAN starter kit is priced at \$179.95. Reader Service No.

Server Technology Inc.

1095 E. Duane, Ste. 107 Sunnyvale, CA 94086 (408) 738-8377

Languages

Clarion from Barrington Systems is a structured programming language designed for commercial applications. Clarion runs on IBM PCs or compatibles, requires a hard-disk drive and a minimum of 320K. The utility programs are integrated; a single keystroke can terminate one utility, then load and execute the next. Screen and report layouts are designed interactively. The entire package sells for \$295. Reader Service No. 37. Barrington Systems Inc. 150 E. Sample Rd. Pompano Beach, FL 33064 (305) 785-4555

A new set of Forth example programs, the Forth Model Library (volumes 1-3), is now available from the Forth Interest

Group. The library includes application programs compatible with Forth-83 systems available from the most popular Forth vendors. The volumes are A Forth List Handler by Martin J. Tracy, A Forth Spreadsheet by Craig A. Lindley, and Automatic Structure Charts by Kim R. Harris. Each volume is available for \$40. Reader Service No. 38. Forth Interest Group P.O. Box 8231 San Jose, CA 95155 (408) 277-0668

Smalltalk-AT from Softsmarts includes the Xerox Smalltalk-80 source code, the Xerox image, and Softsmarts' ST-80 virtual machine. With Smalltalk-AT, users can run any application developed on a larger dedicated Smalltalk machine. It requres an IBM PC/ AT with 640K base memory, at least 512K expansion memory, a Mouse Systems'

three-button mouse, and the IBM Enhanced Graphics Adapter. The total package price is \$995. Reader Service No. 39. Softsmarts Inc. 4 Skyline Dr. Woodside, CA 94062

(415) 327-8100

Software Express has released Version 1.6 of Apgen, a fourth-generation language in the Unix marketplace. The new version features a set of training tutorials. It is compatible with all previous versions and sells for \$6,000. Reader Service No. 40. Software Express

2925 Briarpark Dr., 7th Floor Houston, TX 77042 (713) 974-2298

Star Value Software has announced four software development tools for Modula-2 programmers: Textio, a display and printer I/ O library; Graphix, an in-

OF INTEREST

(continued from page 123)

terface to the MetaWindow system from MetaGraphics; and Make and XRef, utilities for managing large-size development projects. These tools are designed to work in conjunction with the Logitech Modula-2/86 development system on IBM PCs or compatibles. All four products are sold separately and include complete documentation. Textio and Graphix

are \$79 each; Make and XRef are \$59 each. Reader Service No. 40. Star Value Software 12218 Scribe Dr. Austin, TX 78759 (512) 837-5498

Wordcraft's C: A Programming Workshop teaches the C programming language interactively. The workshop includes an integrated editor and standard compiler. The test module reports whether a program exercise gives correct results. Users can also develop C functions with no disk delay. The Workshop runs on IBM PCs and compatibles with 19K. It costs \$39.95 plus shipping and handling. Reader Service No. 41.

Wordcraft 3827 Penniman Ave. Oakland, CA 94619 (415) 534-2212

Version 1.5 of Mystic Pascal from Mystic Canyon Software features screen output, a complete on-line help library, and fast execution speed. It has a full-screen editor, multitasking operating system, ISO Pascal compiler, and interactive debugger mode. Users' programs can occupy up to 640K of storage for code and data, and users can run up to 100 program sections concurrently. Reader Service No. 42.

Mystic Canyon Software P.O. Box 1010 Pecos, NM 87552 (505) 757-6344

Graham Software Corp. has introduced Version 1.3 of Alice: The Personal Pascal. This version is compatible with industry-standard Pascal compilers and supports Borland International's Turbo Pascal. Alice: The Personal Pascal consists of four, integrated, computer language products: an IBM PC-compatible Pascal interpreter, a language intelligent editor, on-line help facilities, and a full-function debugging system. Version 1.3 has a suggested retail price of \$95 (U.S.) or \$129 (Canada). Reader Service No. 43.

Graham Software Corp. 4 Kingwood Pl. Kingwood, TX 77339 (713) 359-1024

QuickSilver Software has released memory-resident reference guides for popular compilers. These reference guides provide clear documentation on the procedural and syntactical elements of each language. The packages require 128K RAM, one disk drive, and PC-DOS 2.0 or later. Each guide costs \$16.95. Reader Service No. 44.

QuickSilver Software P.O. Box 880887 San Diego, CA 92108 (619) 543-9896

DDJ



Do you know where your bugs are?

This C programmer is finding his bugs the hard way...one at a time. That's why it's taking so long. But there's an easier way. Use

PC-Lint 2.00

PC-Lint analyzes your C programs (one or many modules) and uncovers glitches, bugs, quirks, and inconsistencies. It will catch subtle errors before they catch you. By examining multiple modules, PC-Lint enjoys a perspective your compiler does not have.

- NEW: ANSI C extensions (enum, prototypes, void, defined, pragma), Microsoft keywords, and many additional checks.
- Full K&R C
- Use PC-Lint to find: inconsistent declarations argument/parameter mismatches uninitialized variables unaccessed variables unreferenced variables suspicious macros indentation irregularities function inconsistencies unusual expressions ... MUCH MUCH MORE
- User-modifiable library-description files for most major compilers.
- All warning and informational messages may be turned off individually.
- Indirect files automate testing.

Amiga - Lint
Special Introductory Price
\$98.00

- Use it to check existing programs, novice programs, programs about to be exported or imported, as a preliminary to compilation, or prior to scaling up to a larger memory model.
- All one pass with an integrated pre-processor so it's very fast.
- Has numerous options and informational messages.
- PRICE: \$139.00 MC, VISA, COD (Includes shipping and handling within US) PA residents add 6% sales tax. Outside USA add \$15.00. Educational and quantity discounts available.
- Runs under MS-DOS 2.0 and up, with a minimum of 128Kb of memory. It will use all the memory available.
- Trademarks: PC-Lint(Gimpel Software), MS-DOS(Microsoft)

GIMPEL SOFTWARE

3207 Hogarth Lane • Collegeville, PA 19426 (215) 584-4261

Now there's a computer magazine that talks business. And only business.

Each month in BUSINESS SOFTWARE you'll read case studies of computer applications on everything from sales analysis to inventory control. Our monthly tutorials are invaluable in teaching programs that allow you to maximize the capabilities of your computer. You'll find honest, in-depth software evaluations by eminent experts . . . a guide to software decisions . . . even a steady flow of specific methods for improving your personal investment.

Every bit of advice comes from a staff of experts and outside consultants. Tried and proven. And every new software program is tested again and again before you're advised to buy it—or forget it.

BUSINESS SOFTWARE ... the no-nonsense magazine that shows you how to get the most for your business from your computer.

To subscribe, send filled out coupe	on to:
Business Softwar P.O. Box 27975, San Diego, CA 92128	'e,
Name	
Address	
City	
State Zi	0
Please start my 1 year subscription savings of 40% off the newsstand	n (12 issues) for \$19.97. A price.
\$19.97 Payment enclosed	Bill me later
Charge my VISA M/C] Am. Ex.
Card No	
Expiration date	
Signature	
Please allow 6-9 weeks for delivery of first is	sue 3060

Order our FULL C COMPILER For \$5995 and we'll give you a free CED Program Editor



The Ecosoft Eco-C88 compiler for the 8088 and MSDOS is going to set a new standard for price and performance. Consider the evidence:

Compiler	Eco-C88	Latice (1)	C86 (1)
Seive	12	11	13
Fib	43	58	46
Deref	14	13	40
Matrix	22	29	27
Price	\$59.95	\$500.00	*395.00

(1) Computer Language, Feb., 1985, pp. 73-102. Reprinted by permission.

Eco-C88 Rel. 3.0 on IBM PC with 2 floppy disks, 256K. Benchmarks from Feb., 1985, **Computer Language**. Eco-C88 includes:

- ★ All operators and data types (except bit fields)
- ★ Prototyping, structure passing and assignment, enum and void language enhancements.
- ★ Tiered error messages (gives you selectable levels of "lint" semantic checking)
- ★ memfiles (TM) for using memory outside the 128K limit as a file
- ★ Expanded library with over 200 functions (many of which are System V compatible) plus color and transcendentals
- ★ ASM or OBJ output; uses the MSDOS linker
- * 8087 support with 8087 sensed at runtime
- ★ cc and "mini-make" for easy compiles (with source code)
- * expanded user's manual

If ordered with the compiler, the C library source code (excluding transcendentals) is \$25.00 and the ISAM file handler (as published in the **C Programmer's Library**, Que Corp.) in OBJ format is an additional \$15.00. Please add \$4.00 for shipping and handling. To order, call or write:



Ecosoft, Inc. 6413 N. College Avenue Indianapolis, IN 46220 (317) 255-6476 • 8:30-4:30 1-800-952-0472 (orders only)







Circle no. 89 on reader service card.

Brand New From Peter Norton A PROGRAMMER'S EDITOR

\$50

that's *lightning fast* with the *hot* features programmers need


Direct from the man who gave you The Norton Utilities, Inside the IBM PC, and the Peter Norton Programmer's Guide.

EDITOR



"This is the programmer's editor that I wished I'd had when I wrote my Norton Utilities. You can program your way to glory with The Norton Editor."

Peter Nortan



Peter Norton Computing, Inc., 2210 Wilshire Boulevard, Santa Monica, CA 90403, 213-453-2361. Visa, Mastercard and phone orders welcome.

The Norton Editor™ is a trademark of Peter Norton Computing, Inc. © 1986 Peter Norton Computing.



Instant-C: The Fastest Interpreter for C

Runs your programs 50 to 500 times faster than any other C language interpreter.

Any C interpreter can save you compile and link time when developing your programs. But only *Instant-C* saves your time by running your program at compiled-code speed.

Fastest Development. A program that runs in one second when compiled with an optimizing compiler runs in two or three seconds with *Instant-C*. Other interpreters will run the same program in two minutes. Or even ten minutes. Don't trade slow compiling and linking for slow testing and debugging. Only Instant-C will let you edit, test, and debug at the fastest possible speeds.

Fastest Testing. Instant-C immediately executes any C expression, statement, or function call, and display the results. Learn C, or test your programs faster than ever before.

Fastest Debugging. Instant-C gives you the best source-level debugger for C. Single-step by source statement, or set any number of conditional breakpoints throughout your program. Errors always show the source statements involved. Once you find the problem, test the correction in seconds.

Fastest Programming. Instant-C can directly generate executable files, supports full K & R standard C, comes with complete library source, and works under PC-DOS, MS-DOS, or CP/M-86. Instant-C gives you working, well-tested programs faster than any other programming tool. Satisfaction guaranteed, or your money back in first 31 days. Instant-C is \$495.

Rational

Systems, Inc. P.O. Box 480 Natick, MA 01760 (617) 653-6194

ADVERTISER INDEX

Reade			Reader	•
Service		Page	Service	e Page
No.	Advertiser	No.	No.	Advertiser No.
92	Addison Wesley			Micro Way 53
277	Aspen Systems		*	Micromint 89
	Austin Codeworks			MicroPlot 93
250	Barrington Systems, Inc.	4-5	154	Microport Systems, Inc113
115	BC Associates	12	105	Microprocessors Unlimited 88
182	Beacon Street Software, Inc		126	Microsoft Press 21
267	Berkeley Decision/Systems, Inc.		*	Mix Software107
202	Blein Commuting	31	249	Mortice Kern Systems, Inc109
159	Blaise Computing Borland International	GA	*	Nanosoft Associates110
161	Brady Computer Books	122	243	Norton Utilities125
219	Given Computer Books	44	251	Nostradamus 2
181	C Users Groups	105	227	Oakland Group, Inc 61
	Cardinal Point		254	Oasys 18
246	Cardinal Point	122	76	Personal Tex 27
*	Career Opportunity	04 95	169	Poor Person Software103
226	Cauzin Systems	191	229	Port - A - Soft 88
150	Chalcedony Enterprises	121	129	Programmer's Connection 63,64,65
122	Compu View	59	98	Programmer's Connection101
237	CompuServe	C2	103	Programmer's Connection 99
94	Consulair Corporation	70	86	Programmer's Connection 97
•	Creative Programming	91	444 /422	Programmer's Shop 94-95
268	Custom Software Systems	121		Programmer's Shop111
203	Datalight	9	143	Programmer's Shop
*	Desktop A.I	68		Prospero Software 39
87	Digital Research Computers	69	160	Proto PC 93
0.00	DDJ Allen Holub-Shell	78	295	Quad Systems, Inc 93
	DDJ Bound Volumes	74-75	117	Quantum Systems 71
•	DDJ Code Listings	79	158	Raima Corporation 19
• •	DDJ C-Products	76-77	206	Rational Systems126
3.0	DDJ Toolbook of Forth	73	145	SAS Institute127
	DDJ Z80 Toolbook	80		SBC Mart 67
89	Ecosoft, Inc	125	183	Semi Disk Systems 55
	Edward K. Beam	68	85	SLR Systems 58
138	Essential Software	120	78	Soft Advances
93	Fair-Com	40	83	
	Gimpel Software	124	259	Softfocus
97	Greenleaf Software		147	Solution Systems
132	Harvard Softworks	96	148	Solution Systems
274	Hauppauge Computer Works	29	152	Spectra
233	Hawaiian Village Computers	35	106	Swyftware/Information Appliance 90
194	Info Pro Systems	103		Sync Studios
*.21	Integral Quality, Inc	61	166	5 Tech PC119
179	Intel Corporation			Tech PC
	Ises, Inc		108	lecware
	Journal of Forth	90	230	TSF 58
186	Lahey Computer Systems, Inc.	105	119	Turbo Tech Report DDJ Newsletter 17
101	Lattice, Inc	115	157	Vermont Creative Software 34
257	Logitech, Inc	13	112	Wendin
102	Mark Williams Company	1	211	Western Computer 57
285	MDS, Inc	48	116	Wizard Systems 51
95	MetaWare Incorporated	45		Wordtech Systems
			244	Workman & Associates 66

*This advertiser prefers to be contacted directly: see ad for phone number.

ADVERTISING SALES OFFICES

Midwest

Michele Beaty (317) 875-8093

Southeast

Gary George (404) 355-4128

Northern California/Northwest Lisa Boudreau (415) 366-3600

Southern California/AZ/NM/TX Michael Wiener (415) 366-3600

Advertising Director Robert Horton (415) 366-3600

SAS Institute Inc. Announces

Lattice C Compilers for Your IBM Mainframe

Two years ago...

SAS Institute launched an effort to develop a subset of the SAS® Software System for the IBM Personal Computer. After careful study, we agreed that C was the programming language of choice. And that the Lattice® C compiler offered the quality, speed, and efficiency we needed.

One year ago...

Development had progressed so well that we expanded our efforts to include the entire SAS System on a PC, written in C. And to insure that the language, syntax, and commands would be identical across all operating systems, we decided that all future versions of the SAS System—regardless of hardware—would be derived from the same source code written in C. That meant that we needed a C compiler for IBM 370 mainframes. And it had to be good, since all our software products would depend on it.

So we approached Lattice, Inc. and asked if we could implement a version of the Lattice C compiler for IBM mainframes. With Lattice, Inc.'s agreement, development began and progressed rapidly.

Today...

Our efforts are complete—we have a firstrate IBM 370 C compiler. And we are pleased to offer this development tool to you. Now you can write in a single language that is source code compatible with your IBM mainframe and your IBM PC. We have faithfully implemented not only the language, but also the supporting library and environment.

Features of the Lattice C compiler for the 370 include:

- Generation of reentrant object code.

 Reentrancy allows many users to share the same code. Reentrancy is not an easy feature to achieve on the 370, especially if you use non-constant external variables, but we did it.
- Optimization of the generated code. We know the 370 instruction set and the various 370 operating environments. We have over 100 staff years of assembler language systems experience on our development team.
- Generated code executable in both
 24-bit and 31-bit addressing modes. You
 can run compiled programs above the
 16 megabyte line in MVS/XA.
- Generated code identical for OS and CMS operating systems. You can move modules between MVS and CMS without even recompiling.
- Complete libraries. We have implemented all the library routines described by Kernighan and Ritchie (the informal C standard), and all the library

routines supported by Lattice (except operating system dependent routines), plus extensions for dealing with 370 operating environments directly. Especially significant is our byte-addressable Unix®-style I/O access method

■ Built-in functions. Many of the traditional string handling functions are available as built-in functions, generating in-line machine code rather than function calls. Your call to move a string can result in just one MVC instruction rather than a function call and a loop.

In addition to mainframe software development, you can also use our new cross-compiler to develop PC software on your IBM mainframe. With our cross-compiler, you can compile Lattice C programs on your mainframe and generate object code ready to download to your PC.

With the cross-compiler, we also offer PLINK86™ and PLIB86™ by Phoenix Software Associates Ltd. The Phoenix link-editor and library management facility can bind several compiled programs on the mainframe and download immediately executable modules to your PC.

Tomorrow...

We believe that the C language offers the SAS System the path to true portability and maintainability. And we believe that other companies will make similar strategic decisions about C. Already, C is taught in most college computer science curriculums, and is replacing older languages in many. And almost every computer introduced to the market now has a C compiler.

C, the language of choice...

C supports structured programming with superior control features for conditionals, iteration, and case selection. C is good for data structures, with its elegant implementation of structures and pointers. C is conducive to portable coding. It is simple to adjust for the size differences of data elements on different machines.

Continuous support...

At SAS Institute, we support all our products. You license them annually; we support them continuously. You get updates at no additional charge. We have a continuing commitment to make our compiler better and better. We have the ultimate incentive—all our software products depend on it.

For more information...

Complete and mail the coupon today. Because we've got the development tool for your tomorrow.

SAS.

SAS Institute Inc. SAS Circle, Box 8000 Cary, NC 27511-8000 Telephone (919) 467-8000 x 7000

☐ the C compiler for MVS☐ the C compiler for CMS☐ the cross-compiler with	software developers
todayso I'll be i	eady for tomorrow.
Please complete or attach y	our business card.
Name	
Title	
Company	
Address	
City	State ZIP
Telephone	그 하는 병사가 하는 것 같아. 하는 것 같아 하는 것 같아. 하는 것 같아 하는 것 같아. 그는 것 같아. 그는 것 같아. 그는 것
	Attn: CC, SAS Circle, Box 8000, Cary, NC, USA.
	DDJ 9.

SWAINE'S FLAMES

I 've noticed that all the best columnists make lists—lists of their favorite products, lists of announced but unreleased products, lists of their favorite announced but unreleased products. I think I ought to make some lists.

A list can be a sequence, and a sequence can be a puzzle, as in, What is the next item in this sequence?

- 1.
 00010100
 00010110

 00010001
 00000111

 00010110
 00000001

 00001111
- 2. STOA MACRO PAR
 IFC EQ,*PAR*A*
 SA6 PAR
 ENDIF
 ENDM
- 3. while remainder < > 0 do

 begin

 m:= n;

 n:= remainder;

 remainder:= m mod n


 end;
- 4. PLOT PIE
 HEADING 'PAGES OF SOURCE CODE'
 SHOW SLICE FOR 'DDJ' EXPLODED
 COMBINE SLICES LT 5 PERCENT
 END

Pencils down. Anyone who said . . .

omnipotent(X):-can(X,__,_).
 indestructible(X): not(can(_,destroy,X)).
 omnipotent(god).
 ?-can(god,create,X),
 indestructible(X).

gets to stay after class to clean erasers.

The sequence was, of course, first-through nth-generation language code. There is a clear progression, I think, in information density per statement as you go up the generations. The progression in readability is also clear, from the cryptic bitstream of first-generation binary to



the English-like code of fourth-generation RAMIS II.

When you get to the PROLOG code, though, the readability progression crumbles. PROLOG is about as readable as Pascal, and there are other reasons to question PROLOG's position in the sequence.

Given appropriate definitions of create and destroy, the PROLOG program above will answer the question, Can an omnipotent being create an indestructible object? You can actually go to your computer, load PRO-LOG, key in this program, and get an answer. Resolution of this classic antinomy would be an event in the history of logic, but I suspect that my four lines of code say more about PROLOG's failures as a logical language than about gods or logic. Clocksin and Mellish also seem to acknowledge that PROLOG may not be the language of fifth-generation programming by calling it "a potential basis for an important new generation of programming languages. . . . "

I really don't think we're there yet.

My cousin Corbett has been telling me lately that *DDJ* needs a new large software project. *DDJ*, he reminds me, gave the first micro programmers a language that would fit into their tiny memory spaces with Tiny BASIC in 1976. Four years later, the magazine published the first version of Small-C, again shoehorning a language into the limited memory space of micros.

But now microcomputers have megabytes of memory and validated

Ada implementations. Does this *DDJ* kind of minimization make sense any more? Corbett thinks so. Paradoxically, he holds that the key is to think big about thinking small. That's the principle behind his new software development project, for which he wants to solicit programmers through the pages of *DDJ*. There is, Corbett, maintains, only one possible next element in the sequence that began with Tiny BASIC and Small-C: Tiny Star Wars. Send to the usual address for your starter disk and security clearance.

But I don't seem to be getting the hang of this list thing. The most common kind of columnist list may be the classic bitch list. The tone can range from Andy Rooney-whiney to Ian Shoales-snarly. Here's my snarl.


I'm tired of waiting for Alan Kay's Dynabook, Ted Nelson's Xanadu and Hypertext, Adam Osborne's software pricing watershed, the home market, telecommunications software that doesn't push all the tough decisions off on me, hardware design that doesn't penalize me for being lefthanded. All the best programmers are left-handed. I was tired of "nearletter quality"; now I'm tired of "near-typeset quality." When will printers be good enough that their manufacturers don't have to apologize for their output? I'm tired of waiting for Americans to recognize the value of a dollar and of a vote, to stop spending both on trash, and to demand competence from industry and government. Either that or demand printer-style labeling: "near-Sony quality," "near-Gorbachev lucidity." And I'm tired of the lingering death of copy protection. Pull the plug on that baby.

I'm tired. I gotta go.

Michael Swans

Michael Swaine editor-in-chief

When you're hot, you're hot.



HOT C really is.

It's fast. It's powerful. It writes tighter, faster, more efficient code.

And it's cheap. So now just \$99 (suggested retail price) gets you cutting edge performance without the ragged edge problems.

HOT C is an optimizing single-pass compiler. It includes an assembler, linker, debugger, librarian and library source code. It supports large- and

small-memory models and all operators and types except bit fields, with outstanding error and type checking. And in performance, it meets or beats (sometimes dramatically) every other compiler we've come up against.

HOT C is a great power trip for novices, too. A comprehensive tutorial, an impressive text editor and totally revised documentation will have you speaking C like a native in no time flat.

So try HOT C today. Now you can have the steak *and* the sizzle.

For details, just drop a note to Word Tech Systems, Inc., P.O. Box 1747, Orinda, CA 94563.

Or call our HOTline at (415) 254-0900.




HOT $C^{\text{\tiny{IM}}}$ WordTech Systems, Inc. Other products trademarked by others © WordTech Systems, Inc. 1986.

Circle no. 208 on reader service card.

Borland's new Turbo Prolog is the powerful, completely natural introduction to Artificial Intelligence

Prolog is probably one of the most powerful computer programming languages ever conceived, which is why we've made it our second language—and "turbocharged" it to create Turbo Prolog."

Our new Turbo Prolog, the natural language of Artificial Intelligence. brings supercomputer power to your IBM® PC and introduces you step-bystep to the fascinating new world of Artificial Intelligence. And does all this for an astounding \$99.95.





Turbo Prolog is to Prolog what Turbo Pascal® is to Pascal!

Our Turbo Pascal astonished everyone who thought of Pascal as "just another language." We changed all that—and now Turbo Pascal is the de facto worldwide standard, with hundreds of

thousands of enthusiasts

and users in universities, research centers. schools. and with pro-

fessional programmers, students, and hobbyists.

You can expect at least the same impact from Turbo Prolog, because while Turbo Prolog is the most revolutionary and natural programming language, it is also a complete development environment—just like Turbo Pascal.

Turbo Prolog offers generally the fastest and most approachable implementation of Prolog.

Darryl Rubin, 99

Even if you've never programmed before, our free tutorial will

get you started right away

You'll get started right away because we have included a complete step-by-step tutorial as part of the 200-page Turbo Prolog Reference Manual. Our tutorial will take you by the hand and teach you everything you're likely to need to know about Turbo Prolog and artificial intelligence.

For example: once you've completed the tutorial, you'll be able to design your own expert systems utilizing Turbo Prolog's powerful problem-solving capabilities.

Think of Turbo Prolog as a high-speed electronic detective. First you feed it information and teach it rules. Then Turbo Prolog "thinks" the problem through and comes up with all the reasonable answers—almost instantly.

If you think that this is amazing, you just need to remember that Turbo Prolog is a 5th-generation language—and the kind of language that 21st century computers will use routinely. In fact, you can compare Turbo Prolog to

Turbo Pascal the way you could compare Turbo Pascal to machine language.



You get the complete Turbo Prolog programming system for only \$99.95

You get a complete Turbo Prolog development system including:

- The lightning-fast Turbo Prolog incremental compiler and the interactive Turbo Prolog editor. ■ The 200-page reference
- manual which includes the stepby-step Turbo Prolog tutorial. ■ The free GeoBase™ natural query language database including commented source code on disk—ready to compile. GeoBase is a complete database designed and developed around U.S. geography. It includes cities, mountains, rivers, and highways, and comes complete with natural query language. Use GeoBase immediately "as is," or modify it to fit your own interests.

So don't delay-don't waste a second—get Turbo Prolog now. \$99.95 is an amazingly small price to pay to become an immediate authority—an instant expert on artificial intelligence! The 21st century is only one phone call away.

Turbo Prolog 1.0 Technical Specifications Programming System Features

- Compiler: Incremental compiler generating native in-line code and linkable object modules. The linking format includes a linker and is compatible with the PC-DOS linker. Large memory model support. Compiles over 2500 lines per minute on a standard IBM PC
- Interactive Editor: The system includes a powerful interactive full-screen text editor. If the compiler detects an error, the editor automatically positions the cursor appropriately in the source code. At run-time, Turbo Prolog programs can call the editor, and view the running program's
- Type System: A flexible object-oriented type system is supported.
- Windowing Support: The system supports both graphic and text windows
- ✓ Input/Output: Full I/O facilities, including formatted I/O, streams, and random access files.
- ✓ Numeric Ranges: Integers: -32767 to 32767; Reals: 1E-307 to 1E+308
- Debugging: Complete built-in trace debugging capabilities allowing single stepping of programs.

To order by phone, or for a dealer nearest you,

Call (800) 255-8008

in (CA call	(800)	/42-1	133.		
Send me _	Turbo	Prolog a	t	\$ -		_
Outside US. CA and MA				tax \$.	_	
Amount end	:losed:			\$.		_
This pri	ce includ	es shipp	ing to a	II US c	ities	
Payment:	VISA	MC	Bank I	Draft	Ch	eck
Credit card	expiration	n date: _	_/_	-		
Card #						
ourd ii						
†You must he DOS 2.0 or My computer	later.			running	S	U11

NOT COPY PROTECTED 60-DAY MONEY-BACK GUARANTEE

Vame:		
Shipping Address:		
City:	-	
	Zip:	

CODs and purchase orders WILL NOT be accepted by Borland. Outside USA make payment by bank draft payable in US dollars drawn on a US bank.

*YES, if within 60 days of purchase this product does not perform in accordance with our claims, please call our customer service department and we will gladly arrange a refund.

†Minimum system requirements:



4585 SCOTTS VALLEY DRIVE SCOTTS VALLEY, CA 95066 (408) 438-8400 TELEX: 172373

Vive la différence

Borland products include Turbo Prolog: Turbo Pascal: Turbo Tutor: Turbo Editor Toolbox; Turbo Database Toolbox; Turbo Graphix Toolbox; Turbo GameWorks bolland process include intour intour failure reads intout failure value countedouts by discontinuous control failure values failure values failure values failure values valu

IBM, XT, AT, and PCjr are registered trademarks of International Business Machines Corp

